

CHAPTER 7 TOTAL MAXIMUM DAILY LOADS

TABLE OF CONTENTS

INTRODUCTION	1
TOTAL MAXIMUM DAILY LOAD FOR DIAZINON, CHOLLAS CREEK WATERSHED, SAN DIEGO COUNTY	2
<i>NECESSITY STANDARD [GOVERNMENT CODE SECTION 11353(B)]</i>	2
<i>CLEAN WATER ACT SECTION 303(D)</i>	2
<i>BENEFICIAL USE IMPAIRMENTS</i>	2
<i>WATER QUALITY OBJECTIVES</i>	2
<i>WATER QUALITY OBJECTIVE VIOLATIONS</i>	2
<i>SOURCES OF DIAZINON</i>	3
<i>CONCENTRATION-BASED TMDL</i>	3
<i>NUMERIC TARGETS</i>	3
<i>TOTAL MAXIMUM DAILY LOAD</i>	4
<i>LINKAGE ANALYSIS</i>	4
<i>WASTE LOAD AND LOAD ALLOCATIONS</i>	4
<i>DIAZINON LOAD REDUCTIONS NEEDED</i>	5
<i>SEASONAL VARIATIONS AND CRITICAL CONDITIONS</i>	5
<i>RESPONSIBLE PARTIES</i>	5
<i>TMDL IMPLEMENTATION PLAN</i>	6
TOTAL MAXIMUM DAILY LOAD FOR DISSOLVED COPPER, SHELTER ISLAND YACHT BASIN, SAN DIEGO BAY	10
<i>PROBLEM STATEMENT</i>	10
<i>NUMERIC TARGET</i>	10
<i>SOURCE ANALYSIS</i>	11
<i>TOTAL MAXIMUM DAILY LOAD</i>	11

<i>MARGIN OF SAFETY</i>	11
<i>ALLOCATIONS AND REDUCTIONS</i>	11
<i>RECALCULATIONS IF WATER QUALITY OBJECTIVES CHANGE</i>	12
<i>TMDL IMPLEMENTATION PLAN</i>	12
<i>COMPLIANCE SCHEDULE</i>	13
<i>METHOD FOR RECALCULATION OF THE TOTAL MAXIMUM DAILY LOAD FOR DISSOLVED COPPER IN THE SHELTER ISLAND YACHT BASIN, SAN DIEGO BAY</i>	14
TOTAL MAXIMUM DAILY LOADS (TMDLS) FOR TOTAL NITROGEN AND TOTAL PHOSPHORUS IN THE RAINBOW CREEK WATERSHED	16
<i>PROBLEM STATEMENT</i>	16
<i>NUMERIC TARGETS</i>	16
<i>SOURCE ASSESSMENT</i>	17
<i>TOTAL MAXIMUM DAILY LOADS OR LOADING CAPACITY</i>	17
<i>MARGIN OF SAFETY</i>	17
<i>LOAD ALLOCATIONS AND WASTELOAD ALLOCATIONS</i>	18
<i>RECALCULATIONS IF WATER QUALITY OBJECTIVES CHANGE</i>	19
<i>TMDL IMPLEMENTATION ACTION PLAN</i>	19
<i>TMDL IMPLEMENTATION MONITORING PLAN</i>	28
<i>AGRICULTURAL PROGRAM COSTS AND POTENTIAL SOURCES OF FINANCING</i>	34
<i>METHOD FOR RECALCULATION OF THE TOTAL MAXIMUM DAILY LOADS FOR NITROGEN AND PHOSPHORUS IN RAINBOW CREEK</i>	35
TOTAL MAXIMUM DAILY LOADS (TMDLS) FOR COPPER, LEAD, AND ZINC IN CHOLLAS CREEK	37
<i>PROBLEM STATEMENT</i>	37
<i>NUMERIC TARGETS</i>	37
<i>SOURCE ANALYSIS</i>	38
<i>TOTAL MAXIMUM DAILY LOADS</i>	38
<i>MARGIN OF SAFETY</i>	38
<i>ALLOCATIONS AND REDUCTIONS</i>	38
<i>TMDL IMPLEMENTATION PLAN</i>	38

IMPLEMENTATION MONITORING PLAN	39
SCHEDULE OF COMPLIANCE.....	40
TOTAL MAXIMUM DAILY LOADS FOR INDICATOR BACTERIA, BABY BEACH AND SHELTER ISLAND SHORELINE PARK SHORELINES.....	43
PROBLEM STATEMENT.....	43
NUMERIC TARGETS	43
SOURCE ANALYSIS.....	44
TOTAL MAXIMUM DAILY LOADS AND ALLOCATIONS	45
TMDL IMPLEMENTATION PLAN.....	49
REVISED TOTAL MAXIMUM DAILY LOADS FOR INDICATOR BACTERIA, PROJECT I – TWENTY BEACHES AND CREEKS IN THE SAN DIEGO REGION (INCLUDING TECOLOTE CREEK).....	62
PROBLEM STATEMENT.....	63
NUMERIC TARGET.....	63
SOURCE ANALYSIS.....	66
CRITICAL CONDITIONS.....	67
LINKAGE ANALYSIS.....	67
TOTAL MAXIMUM DAILY LOADS AND ALLOCATIONS	68
MARGIN OF SAFETY.....	72
TMDL IMPLEMENTATION PLAN.....	92
TMDL COMPLIANCE SCHEDULE.....	110
TMDL IMPLEMENTATION MILESTONES.....	121
TOTAL MAXIMUM DAILY LOADS FOR SEDIMENT IN LOS PEÑASQUITOS LAGOON	123
PROBLEM STATEMENT.....	123
NUMERIC TARGET.....	124
WATERSHED POINT AND NON-POINT SEDIMENT SOURCES.....	124
RESPONSIBLE PARTIES	125
LINKAGE ANALYSIS.....	125
TMDL, ALLOCATIONS, AND LOAD REDUCTIONS.....	126

<i>MARGIN OF SAFETY (MOS)</i>	126
<i>IMPLEMENTATION PLAN</i>	127
<i>MONITORING</i>	131
<i>COMPLIANCE SCHEDULE</i>	132

TABLES

TABLE 7-1. ADOPTED AND APPROVED TOTAL MAXIMUM DAILY LOADS IN THE SAN DIEGO REGION	1
TABLE 7-2. NUMERIC TARGETS FOR DIAZINON IN CHOLLAS CREEK	3
TABLE 7.3. TMDL (LOADING CAPACITY) FOR DIAZINON IN CHOLLAS CREEK.....	4
TABLE 7.4. WASTE LOAD AND LOAD ALLOCATIONS FOR DIAZINON IN CHOLLAS CREEK	4
TABLE 7.5 NEEDED LOAD REDUCTIONS IN CHOLLAS CREEK	5
TABLE 7.6. SCHEDULE OF IMPLEMENTATION	9
TABLE 7-7. TMDL NUMERIC TARGETS	10
TABLE 7-8. SUMMARY OF DISSOLVED COPPER SOURCES TO SIYB	11
TABLE 7-9. TMDL AND ALLOCATION SUMMARY	12
TABLE 7-10. INTERIM LOADING TARGETS FOR ATTAINMENT OF THE TMDL.....	13
TABLE 7-11. RAINBOW CREEK NITRATE, TOTAL NITROGEN, AND TOTAL PHOSPHORUS NUMERIC TARGETS	16
TABLE 7-12. SUMMARY OF TOTAL NITROGEN AND TOTAL PHOSPHORUS SOURCES TO RAINBOW CREEK	17
TABLE 7-13. ANNUAL NUTRIENT LOADING CAPACITY AND COMPLIANCE DATE	17
TABLE 7-14. ANNUAL TOTAL NITROGEN ALLOCATIONS FOR RAINBOW CREEK.....	18
TABLE 7-15. ANNUAL TOTAL PHOSPHORUS ALLOCATIONS FOR RAINBOW CREEK	19
TABLE 7-16. WASTELOADS FOR NITROGEN AND PHOSPHORUS.....	20
TABLE 7-17. REQUIRED MONITORING PARAMETERS.....	31
TABLE 7-18. TOTAL NITROGEN AND TOTAL PHOSPHORUS PHASED LOAD REDUCTION COMPLIANCE SCHEDULE	33
TABLE 7-19. COST OF IMPLEMENTING AGRICULTURAL WATER QUALITY CONTROL	34
TABLE 7-20. TOTAL NITROGEN AND PHOSPHORUS ALLOCATIONS FOR RAINBOW CREEK TMDL.....	36
TABLE 7-21A. WATER QUALITY CRITERIA /NUMERIC TARGETS FOR DISSOLVED METALS IN CHOLLAS CREEK (WET WEATHER ONLY).....	37
TABLE 7- 21B. SITE-SPECIFIC WERS FOR DISSOLVED METALS IN CHOLLAS CREEK (WET WEATHER ONLY)	37

TABLE 7-22. INTERIM GOALS FOR ACHIEVING WASTELOAD ALLOCATIONS	40
TABLE 7-23. COMPLIANCE SCHEDULE	41
TABLE 7-24. WET WEATHER NUMERIC TARGETS	43
TABLE 7-25. DRY WEATHER NUMERIC TARGETS	44
TABLE 7-26. REC-1 WET WEATHER TMDLS FOR TOTAL COLIFORM FOR BABY BEACH AND SHELTER ISLAND SHORELINE PARK SHORELINE SEGMENTS	46
TABLE 7-27. REC-1 WET WEATHER TMDLS FOR FECAL COLIFORM FOR BABY BEACH AND SHELTER ISLAND SHORELINE PARK SHORELINE SEGMENTS	46
TABLE 7-28. REC-1 WET WEATHER TMDLS FOR <i>ENTEROCOCCUS</i> FOR BABY BEACH AND SHELTER ISLAND SHORELINE PARK SHORELINE SEGMENTS	47
TABLE 7-29. REC-1 DRY WEATHER TMDLS FOR TOTAL COLIFORM FOR BABY BEACH AND SHELTER ISLAND SHORELINE PARK SHORELINE SEGMENTS	47
TABLE 7-30. REC-1 DRY WEATHER TMDLS FOR FECAL COLIFORM FOR BABY BEACH AND SHELTER ISLAND SHORELINE PARK SHORELINE SEGMENTS	48
TABLE 7-31. REC-1 DRY WEATHER TMDLS FOR <i>ENTEROCOCCUS</i> FOR BABY BEACH AND SHELTER ISLAND SHORELINE PARK SHORELINE SEGMENTS	48
TABLE 7-32. COMPLIANCE SCHEDULE FOR BABY BEACH TO ACHIEVE WET WEATHER TMDLS.....	58
TABLE 7-33. COMPLIANCE SCHEDULE FOR BABY BEACH TO ACHIEVE DRY WEATHER TMDLS.....	59
TABLE 7-34. COMPLIANCE SCHEDULE FOR SHELTER ISLAND SHORELINE PARK TO ACHIEVE WET WEATHER AND DRY WEATHER TMDLS	60
TABLE 7-35. TMDL IMPLEMENTATION MILESTONES.....	61
TABLE 7-36. BEACHES AND CREEKS ADDRESSED BY REVISED BACTERIA TMDLS PROJECT I	62
TABLE 7-37. WET WEATHER NUMERIC TARGETS	66
TABLE 7-38. DRY WEATHER NUMERIC TARGETS	66
TABLE 7-39. SUMMARY OF WET WEATHER EXISTING AND ALLOWABLE INDICATOR BACTERIA LOADS	74
TABLE 7-40. SUMMARY OF DRY WEATHER EXISTING AND ALLOWABLE INDICATOR BACTERIA LOADS	76
TABLE 7-41. WET WEATHER FECAL COLIFORM BACTERIA EXISTING LOADS, TMDLS, WLA, LAS EXPRESSED AS ANNUAL LOADS (BILLION MPN/YEAR).....	78
TABLE 7-42. WET WEATHER TOTAL COLIFORM BACTERIA EXISTING LOADS, TMDLS, WLA, LAS EXPRESSED AS ANNUAL LOADS (BILLION MPN/YEAR).....	80

TABLE 7-43. WET WEATHER ENTEROCOCCUS BACTERIA EXISTING LOADS, TMDLS, WLA, LAS EXPRESSED AS ANNUAL LOADS (BILLION MPN/YEAR).....	82
TABLE 7-44. ALTERNATIVE WET WEATHER ENTEROCOCCUS BACTERIA EXISTING LOADS, TMDLS, WLA, LAS EXPRESSED AS ANNUAL LOADS (BILLION MPN/YEAR).....	84
TABLE 7-45. DRY WEATHER FECAL COLIFORM BACTERIA EXISTING LOADS, TMDLS, WLA, LAS EXPRESSED AS MONTHLY LOADS (BILLION MPN/MONTH)	86
TABLE 7-46. DRY WEATHER TOTAL COLIFORM BACTERIA EXISTING LOADS, TMDLS, WLA, LAS EXPRESSED AS MONTHLY LOADS (BILLION MPN/MONTH)	88
TABLE 7-47. DRY WEATHER ENTEROCOCCUS BACTERIA EXISTING LOADS, TMDLS, WLA, LAS EXPRESSED AS MONTHLY LOADS (BILLION MPN/MONTH)	90
TABLE 7-48. RECEIVING WATER LIMITATIONS FOR BEACHES	105
TABLE 7-49. RECEIVING WATER LIMITATIONS FOR CREEKS.....	106
TABLE 7-50. MODELED ESTIMATE OF CRITICAL YEAR “EXISTING” WET WEATHER EXCEEDANCE FREQUENCIES BY WATERSHED.....	109
TABLE 7-51. RESPONSIBLE MUNICIPALITIES AND LEAD JURISDICTIONS†.....	111
TABLE 7-52. PRIORITIZED LIST OF IMPAIRED WATERS FOR TMDL IMPLEMENTATION.....	115
TABLE 7-53. DRY WEATHER COMPLIANCE SCHEDULE AND MILESTONES FOR EXCEEDANCE FREQUENCY REDUCTIONS	119
TABLE 7-54. WET WEATHER COMPLIANCE SCHEDULE AND MILESTONES FOR ACHIEVING EXCEEDANCE FREQUENCY REDUCTIONS	119
TABLE 7-55. ALTERNATIVE COMPLIANCE SCHEDULE CHOLLAS CREEK	120
TABLE 7-56. TMDL IMPLEMENTATION MILESTONES.....	121
TABLE 7-57. LOS PEÑASQUITOS LAGOON SEDIMENT TMDL IMPLEMENTATION COMPLIANCE SCHEDULE	132

PHOTOS

Chollas Creek at Federal Boulevard crossing. Photo by Linda Pardy	5
Chollas Creek streamside. Photo by Linda Pardy.....	5
Shelter Island Yacht Basin. Photo by David Barker	10
Rainbow Valley, California. Photo by John Phillips	16
Aliso Beach, Orange County. Photo by Christina Arias (2002).....	63

7. TOTAL MAXIMUM DAILY LOADS

INTRODUCTION

This chapter contains the Total Maximum Daily Loads (TMDLs) that have been adopted by the Regional Water Quality Control Board, San Diego Region (RWQCB), approved by the State Water Resources Control Board (SWRCB) and Office of Administrative Law (OAL), and/or adopted/approved by the United State Environmental Protection Agency (USEPA). Table 7-1 lists the adopted and approved TMDLs that have been incorporated into the Basin Plan.

Table 7-1. Adopted and Approved Total Maximum Daily Loads in the San Diego Region

Total Maximum Daily Load	RWQCB Adoption Date	SWRCB Approval Date	OAL Approval Date	USEPA Approval Date
Total Maximum Daily Load for Diazinon, Chollas Creek Watershed, San Diego County	8/14/02	7/16/03	9/11/03	11/3/03
Total Maximum Daily Load for Dissolved Copper, Shelter Island Yacht Basin, San Diego Bay	2/9/05	9/22/05	12/2/05	2/8/06
Total Maximum Daily Loads for Total Nitrogen and Total Phosphorus in the Rainbow Creek Watershed	2/9/05	11/16/05	2/1/06	3/22/06
Total Maximum Daily Loads for Copper, Lead, and Zinc in Chollas Creek	6/13/07	7/15/08	10/22/08	12/18/08
Total Maximum Daily Loads for Indicator Bacteria, Project I – Beaches and Creeks in the San Diego Region	12/17/07	-- ^a	--	--
Total Maximum Daily Loads for Indicator Bacteria, Baby Beach and Shelter Island Shoreline Park Shorelines	6/11/08	6/16/09	9/15/09	10/26/09
Revised Total Maximum Daily Loads for Indicator Bacteria, Project I – Twenty Beaches and Creeks in the San Diego Region (Including Tecolote Creek)	2/10/10	12/14/10	4/4/11	6/22/11
Total Maximum Daily Loads for Sediment in Los Peñasquitos Lagoon	6/13/12	1/21/14	7/14/14	10/30/14

^a Withdrawn by the RWQCB on December 18, 2008 from SWRCB consideration for revision. See Revised Total Maximum Daily Loads for Indicator Bacteria Project I – Twenty Beaches and Creeks in the San Diego Region (Including Tecolote Creek).

TOTAL MAXIMUM DAILY LOAD FOR DIAZINON, CHOLLAS CREEK WATERSHED, SAN DIEGO COUNTY

On August 14, 2002 the Regional Board adopted Resolution No. R9-2002-0123, Total Maximum Daily Load (TMDL) For Diazinon In Chollas Creek Watershed, San Diego County. The terms and conditions of Resolution No. R9-2002-0123 are incorporated into the Basin Plan. This amendment establishes the TMDL of diazinon which Chollas Creek can receive and still attain applicable water quality objectives and support beneficial uses. This TMDL is allocated to all contributing sources of diazinon in the watershed by establishing Waste Load Allocations for all point sources and Load Allocations for all nonpoint sources in the watershed. This TMDL includes a margin of safety. The TMDL Implementation Plan and Monitoring Plan are presented below.

NECESSITY STANDARD [GOVERNMENT CODE SECTION 11353(B)]

Amendment of the Basin Plan to establish and implement a Total Maximum Daily Load for Chollas Creek is necessary because water quality in Chollas Creek cannot satisfy applicable water quality objectives for "Toxicity" and "Pesticides" even with implementation of waste discharge requirements containing technology-based effluent limits or water quality-based effluent limits for discharges of pollutants to Chollas Creek and its tributaries. Clean Water Act section 303(d) requires the Regional Board to develop an implement a TMDL under the conditions that exist in Chollas Creek. This TMDL for diazinon is necessary to ensure attainment of applicable water quality objectives and restoration of beneficial uses designated for Chollas Creek.

CLEAN WATER ACT SECTION 303(D)

Chollas Creek is currently identified on the Clean Water Act section 303(d) list of impaired waters due to toxicity during storm events. Results from toxicity identification evaluations (TIEs) indicate that the insecticide diazinon in Chollas Creek has in part caused the toxicity during storm events.

BENEFICIAL USE IMPAIRMENTS

Chollas Creek supports several beneficial uses. The most sensitive beneficial uses are those designated for protection of aquatic life and aquatic dependent wildlife as described in the Basin Plan definition of the warm freshwater habitat (WARM) and wildlife habitat (WILD) beneficial uses. The WARM and WILD beneficial uses of Chollas Creek are adversely affected by toxicity due to diazinon.

WATER QUALITY OBJECTIVES

Diazinon levels in Chollas Creek cause toxicity during storm events. The Basin Plan does not contain a specific water quality objective for diazinon. The Basin Plan establishes narrative water quality objectives for "Toxicity" and "Pesticides" to ensure the protection of the WARM and WILD beneficial uses.

WATER QUALITY OBJECTIVE VIOLATIONS

Toxicity tests using the water flea *Ceriodaphnia dubia* indicate that Chollas Creek storm water flows are toxic. Toxicity Identification Evaluations (TIEs) show that diazinon is responsible for the toxicity to the water flea. Accordingly diazinon concentrations in Chollas Creek cause violations of the "Toxicity" and "Pesticide" water quality objectives during storm events. The average concentration of diazinon in Chollas Creek during storm events is 0.46 micrograms per liter ($\mu\text{g/L}$). Chollas Creek waters also contain metals that are responsible for toxicity to a marine invertebrate. A separate TMDL is under development to address metals in Chollas Creek.

SOURCES OF DIAZINON

Urban storm water flows represent the most significant source of diazinon to the Chollas Creek watershed.

CONCENTRATION-BASED TMDL

Because aquatic toxicity is the most significant adverse effect of diazinon and because aquatic toxicity is a function of water column concentrations, this TMDL is a concentration-based, rather than mass emission-based TMDL. The Numeric Targets, TMDL (Loading Capacity), and Waste Load and Load Allocations are all defined in terms of concentrations.

NUMERIC TARGETS

The TMDL Numeric Targets, which are derived from the water quality objectives, identify the specific water column, sediment, or tissue concentrations (or other endpoints) which equate to attainment of the Basin Plan water quality objectives and the protection of designated beneficial uses. Therefore, if the Numeric Targets are appropriately selected (for all causative pollutants), attainment of the Numeric Targets will result in attainment of the underlying water quality objectives and beneficial use protection.

The Numeric Targets for diazinon in Chollas Creek are set equal to the California Department of Fish and Game freshwater Water Quality Criteria for diazinon. The acute Water Quality Criterion of 0.08 µg/L diazinon protects aquatic life from short-term exposure to diazinon, while the chronic criterion of 0.05 µg/L diazinon protects aquatic life from long-term diazinon exposure.

Table 7-2. Numeric Targets for Diazinon in Chollas Creek ¹

Exposure Duration	Numeric Target	Averaging Period	Frequency of Allowed Exceedance
Acute	0.08 µg/L	One-hour average	Once every three years on the average
Chronic	0.05 µg/L	Four-day average	Once every three years on the average

¹ For the purpose of evaluating if the Numeric Targets have been attained, sample results shall be used as follows:

1. If only one sample is collected during the time period associated with the numeric target (e.g., one-hour average or four-day average), the single measurement shall be used to determine attainment of the numeric target for the entire time period.
2. The one-hour average shall be the moving arithmetic mean of grab samples over the specified one-hour period.
3. The four-day average shall apply to flow-weighted composite samples for the duration of the storm, or shall be the moving arithmetic mean of flow weighted 24-hour composite samples or grab samples.

TOTAL MAXIMUM DAILY LOAD

The term TMDL, or Loading Capacity, is defined as the maximum amount of a pollutant that a waterbody can receive and still attain water quality objectives and protection of designated beneficial uses. The concentration-based Loading Capacity for diazinon in Chollas Creek is set at exactly the same concentrations as the Numeric Targets.

Table 7.3. TMDL (Loading Capacity) for Diazinon in Chollas Creek

Exposure Duration	TMDL	Averaging Period
Acute	0.08 µg/L	One-hour average
Chronic	0.05 µg/L	Four-day average

LINKAGE ANALYSIS

The purpose of the linkage analysis is to confirm that the TMDL will result in the attainment of applicable water quality objectives and beneficial use protection. With respect to diazinon, this TMDL will result in the attainment of the "Toxicity" and "Pesticide" water quality objectives and the restoration of the WARM and WILD beneficial uses in the Chollas Creek watershed.¹ This is because the Numeric Targets are set equal to the diazinon Water Quality Criteria which are based on toxicity testing and are specifically established at levels to ensure the protection of aquatic life from acute and chronic exposure to diazinon. The Water Quality Criteria protect all aquatic life stages including the most sensitive stages.

WASTE LOAD AND LOAD ALLOCATIONS

The concentration-based Waste Load and Load allocations of this TMDL are applied equally to all diazinon discharge sources in the Chollas Creek watershed. All allocations are set at 90% of the Numeric Targets resulting in a diazinon allocation equal to 0.072 µg/L under acute exposure conditions and a diazinon allocation of 0.045 µg/L under chronic exposure conditions. These allocations include an explicit 10% margin of safety to account for uncertainties in the TMDL analysis. This concentration-based TMDL and its allocations apply year-round and will be protective during all flow conditions and seasons.

Table 7.4. Waste Load and Load Allocations for Diazinon in Chollas Creek

Exposure Duration	Numeric Targets	Margin of Safety	Waste Load and Load Allocations
Acute	0.08 µg/L	0.008 µg/L	0.072 µg/L
Chronic	0.05 µg/L	0.005 µg/L	0.045 µg/L

¹ MULTIPLE POLLUTANTS: The attainment of water quality standards is qualified with the words "with respect to diazinon" because there are multiple pollutants causing toxicity. Toxicity conditions in Chollas Creek are caused by metals and diazinon. Successful implementation of both the Chollas Creek diazinon TMDL and the Chollas Creek metals TMDL is expected to result in full attainment of the "Toxicity" water quality objectives, and of the WARM and WILD beneficial uses

DIAZINON LOAD REDUCTIONS NEEDED

The current average concentration of diazinon in Chollas Creek measured during storm events was 0.46 µg/L during the monitoring period 1998 through 2001. An 84% reduction of current diazinon concentration–based loads is needed to attain the acute diazinon allocations set forth in this TMDL. A 90% reduction of current diazinon concentration–based loads is needed to attain the chronic diazinon allocations set forth in this TMDL.

Table 7.5 Needed Load Reductions in Chollas Creek

Average Diazinon Concentration	Allocation		Reduction Needed	
	Chronic	Acute	Chronic	Acute
0.46 µg/L	0.045 µg/L	0.072 µg/L	90%	84%



Chollas Creek at Federal Boulevard crossing.



Chollas Creek streamside

SEASONAL VARIATIONS AND CRITICAL CONDITIONS

This concentration–based diazinon TMDL and allocations apply year round and will be protective during all flow conditions and seasons.

RESPONSIBLE PARTIES

As dischargers of diazinon in urban storm water flows to Chollas Creek, the City of San Diego, City of Lemon Grove, City of La Mesa, San Diego Unified Port District, County of San Diego, and the California Department of Transportation (Caltrans) are responsible for implementation of this TMDL. These entities are regulated as municipal Copermittees under the San Diego MS4 Permit or the statewide Caltrans MS4 Permit.

TMDL IMPLEMENTATION PLAN

The three most important mechanisms to implement the diazinon waste load reductions required by this TMDL are (1) USEPA's ongoing diazinon phase-out and elimination program; (2) modification of the San Diego Municipal Storm Water Permit (MS4 Permit)¹ as needed for consistency with this TMDL; and (3) activities by the municipal Copermittees in the Chollas Creek watershed to reduce diazinon discharges pursuant to the MS4 Permit and Water Code section 13267.

(1) USEPA's Diazinon Phase-Out and Elimination Program

The single most important action to implement this TMDL is USEPA's national ongoing Diazinon Phase-Out and Elimination Program. In January 2001, USEPA reached an agreement with registrants (manufacturers) of diazinon to phase-out most uses (USEPA 2002). Under the agreement, all indoor uses will be terminated, and all outdoor non-agricultural uses will be phased-out over the next few years.

Specifically, the terms of the agreement implement the following phase out schedules:

- For the indoor household use, the registration will be canceled on March 2001, and all retail sales will stop by December 2002.
- For all lawn, garden and turf uses, manufacturing stops in June 2003; all sales and distribution to retailers ends in August 2003. Further, the manufacturers will implement a product recovery program in 2004 to complete the phase-out of the product.
- Additionally, as part of the phase-out, for all lawn, garden, and turf uses, the agreement ratchets down the manufacturing amounts. Specifically, for 2002, there will be a 25 percent decrease in production; and for 2003, there will be a 50 percent decrease in production.
- Also, the agreement begins the process to cancel around 20 different uses on food crops.

In summary, the phase-out is designed to reduce diazinon use and sales, availability, and to increase its proper disposal. As a result of the phase-out, USEPA expects, on a national basis, that these actions will end over 90% of current diazinon uses. In the Chollas Creek watershed, since agricultural use is negligible, the phase-out should reduce current source loadings of diazinon, and the resulting aquatic toxicity, to negligible levels over time. For these reasons, the diazinon phase-out is by far the single most significant mechanism by which this TMDL will be implemented. The remaining TMDL implementation actions described below are designed to reduce the discharge of diazinon to the Chollas Creek watershed due to interim (during the phase-out) and residual (post phase-out) diazinon sales, use, and disposal. It should be noted that actions taken by the municipalities and other stakeholders to reduce diazinon discharges to the Chollas Creek watershed will likely be effective in reducing the discharges of alternative pesticides in the long-term as well.

(2) Modification of Existing Waste Discharge Requirements / NPDES Permits

The Regional Board's San Diego Municipal Storm Water Permit, also known as the San Diego MS4 Permit (Regional Board Order No. 2001-01 NPDES No. CAS0108758) is the primary broad-based NPDES permit which directly regulates most pollutant discharges, including diazinon, in the Chollas Creek watershed. Federal regulations require that NPDES permits contain effluent limitations that are consistent with Waste Load Allocations developed under a TMDL [40 CFR 122.44 (d)(vii)(B)]. The Regional Board will revise existing waste discharge requirements / NPDES permits to incorporate effluent limitations in conformance with the Waste Load Allocations for diazinon as specified above. Modifications to the MS4 Permit can occur when the permit is reopened or during scheduled permit reissuance.

¹ Regional Board Order No. 2001-01 NPDES No. CAS0108758, Waste Discharge Requirements for Discharges of Urban Runoff from the Municipal Separate Storm Sewer Systems (MS4s) Draining the Watersheds of the County of San Diego, and the San Diego Unified Port District.

Compliance with numeric limitations for diazinon will be required in accordance with a phased schedule of compliance. The compliance schedule will be jointly developed by the Regional Board and the Chollas Creek stakeholders and will be finalized no later than one year following adoption of this TMDL by the Regional Board. The phased compliance schedule will apply only to attainment of numeric limitations for diazinon. All other requirements of this TMDL will be immediately effective upon incorporation into applicable NPDES permits.

(3) Activities By Municipal Copermittees Pursuant to MS4 Permit and CWC Section 13267

Pursuant to the MS4 Permit and under the authority of Water Code section 13267, the Regional Board will direct the municipal Copermittees in the Chollas Creek watershed to do the following:

- a. **Legal Authority:** Enforce existing local ordinances, or adopt new legal authority, as needed to ensure Copermittee compliance with the Waste Load Allocations specified in this TMDL;
- b. **Diazinon Toxicity Control Plan:** Develop and implement a "Diazinon Toxicity Control Plan" to promote Copermittee compliance with the Waste Load Allocations specified in this TMDL. The Plan should consist of pollution prevention and source control BMPs designed to reduce the discharge of diazinon to Chollas Creek.
- c. **Diazinon Public Outreach / Education Program:** Develop and implement a focused Public Outreach / Education program designed to reduce the discharge of diazinon to the Chollas Creek watershed. By reducing the discharge of diazinon, the Program will promote Copermittee compliance with the Waste Load Allocations specified in this TMDL. The Program should contain the components described in the Regional Board Technical Report, Total Maximum Daily Load for Diazinon in Chollas Creek Watershed San Diego County, dated August 14, 2002, or equivalent components. The diazinon public outreach / education program may be incorporated into the Diazinon Toxicity Control Plan.

(4) Compliance with MS4 Permit

The municipal Copermittees in the Chollas Creek watershed shall implement the requirements of the MS4 Permit.

(5) Compliance with Existing Waste Discharge Prohibitions

Prohibitions against discharges of waste that cause pollution or nuisance, described in the Basin Plan, including discharges of diazinon that cause or contribute to violation of water quality objectives are applicable to the urban land users and land owners in the Chollas Creek watershed. Dischargers of diazinon in the watershed shall also comply with all other applicable waste discharge prohibitions contained in the Basin Plan.

(6) Enforcement Authority of Regional Board

The Regional Board will use its enforcement authority as necessary to ensure compliance with applicable waste discharge requirements and Basin Plan waste discharge prohibitions.

(7) Modification of Other Existing Waste Discharge Requirements

The State Board has issued three additional NPDES storm water permits that regulate the discharge of pollutants including diazinon in the Chollas Creek watershed. These permits are the statewide Caltrans Municipal Storm Water Permit (State Board Order No. 99-06-DWQ NPDES No. CAS 000003), the statewide General Industrial Storm Water Permit (State Board Order No. 97-03-DWQ NPDES No. CAS 000001), and the statewide General Construction Storm Water Permit (State Board Order No. 99-08-DWQ NPDES No. CAS 000002) which directly regulate discharges from Caltrans owned and operated facilities, and from industrial and construction sites respectively, located within the Chollas Creek watershed. Discharges from industrial and construction sites in the Chollas Creek watershed are also indirectly regulated under the MS4 Permit which holds each municipal Copermittee ultimately responsible for all discharges from industrial and construction sites within its jurisdiction. The Regional Board will request the State Board to amend each of these three statewide permits as needed for consistency with this TMDL. Modifications to waste discharge requirements can occur when permits are reopened or reissued.

In addition to the broad-based regulation of discharges under the MS4 Permit, the discharge of pollutants, including diazinon, from utility companies and utility vaults is directly regulated under the State Board's General Permit for Utility Vaults (State Board Order No. 2001-11-DWQ NPDES No. CAG 990002). The Regional Board will request the State Board to also revise the General Permit for Utility Vaults as needed for consistency with this TMDL.

(8) Adoption of New Waste Discharge Requirements / NPDES Permits

The Regional Board may adopt new waste discharge requirements / NPDES permits for any significant source(s) of diazinon identified by the municipal Copermittees or the Regional Board.

(9) Additional Investigations and Reports Pursuant to CWC Section 13225

The Regional Board may use its authority under Water Code section 13225 to request the municipalities in the Chollas Creek watershed to conduct additional investigations which are beyond the purview of the MS4 permit and to report on the findings of such investigations. Any such investigations will address diazinon-related issues in the Chollas Creek watershed for the ultimate purpose of reducing diazinon discharges to the watershed.

(10)Monitoring Plan

Pursuant to the MS4 permit and under the authority of Water Code section 13267, the Regional Board will direct the municipal Copermittees in the Chollas Creek watershed to develop and implement a Monitoring Plan. The Plan shall be designed to assess the effectiveness of this TMDL, its implementation measures, and progress towards the attainment of applicable water quality standards in the Chollas Creek watershed. The Plan should contain the components described in the Regional Board Technical Report, Total Maximum Daily Load for Diazinon in Chollas Creek Watershed San Diego County, dated August 14, 2002, or equivalent components.

(11)Schedule of Implementation

As described in Provision 2 above, Modification of Existing Waste Discharge Requirements/ NPDES Permits, compliance with numeric limitations for diazinon will be required in accordance with a phased schedule of compliance. All other requirements of this TMDL will be immediately effective upon incorporation into applicable NPDES permits as described below

Table 7.6. Schedule of Implementation

Schedule of Implementation			
Action	Description	Responsible Parties	Due Date
USEPA cancels registration for indoor household uses of diazinon		USEPA	March 31, 2001
IPM Workshop(s)	Conduct first workshop	Chollas Creek watershed municipal copermittees	Within 1 year after USEPA approves TMDL and annually thereafter
Monitoring Plan	Initiate Monitoring Plan	Chollas Creek watershed municipal copermittees	30-days after USEPA approves TMDL
Diazinon Toxicity Control Plan (DTCP)	Initiate DTCP	Chollas Creek watershed municipal copermittees	30-days after USEPA approves TMDL
Retail sales of diazinon (indoor uses) end		USEPA	December 31, 2002
Manufacturing of diazinon for all lawn, garden and turf uses end		USEPA	June 31, 2003
Sales and distribution to retailers ends		USEPA	August 31, 2003
Phase out and eliminate diazinon usage and sales in the Chollas Creek watershed. Ensure proper disposal.		USEPA	2003 for non-agriculture uses
Modify MS4 permit for consistency with TMDL		Regional Board	No later than 2006
Implement legal authority to reduce diazinon discharges in the Chollas Creek watershed.		Chollas Creek watershed municipal copermittees	6 months after USEPA approves TMDL
Compliance with MS4 permit		Chollas Creek watershed municipal copermittees	Ongoing
Compliance with existing Waste Discharge prohibitions		Diazinon dischargers	Ongoing
Enforcement authority of Regional Board		Regional Board	Ongoing
Modification of other existing Waste Discharge Requirements		Regional and State Board	No later than next reissuance
Adoption of new WDRs / NPDES permits	For significant diazinon sources only.	Regional Board	As needed
Additional investigations and reports pursuant to CWC section 13225		Diazinon dischargers	As needed
Submit Annual Reports	Effectiveness reports and monitoring reports	Chollas Creek watershed municipal copermittees	January 31 of each year.

TOTAL MAXIMUM DAILY LOAD FOR DISSOLVED COPPER, SHELTER ISLAND YACHT BASIN, SAN DIEGO BAY



On February 9, 2005, the Regional Board adopted Resolution No. R9-2005-0019, *A Resolution Adopting an Amendment to the Water Quality Control Plan for the San Diego Region to Incorporate a Total Maximum Daily Load for Dissolved Copper in the Shelter Island Yacht Basin, San Diego Bay*. The TMDL Basin Plan Amendment was subsequently approved by the State Water Resources Control Board on September 22, 2005, the Office of Administrative Law on December 2, 2005, and the United States Environmental Protection Agency on February 8, 2006. The TMDL is described in the *Total Maximum Daily Load for Dissolved Copper in Shelter Island Yacht Basin, San Diego Bay*, Technical Report dated February 9, 2006.

PROBLEM STATEMENT

Dissolved copper levels in Shelter Island Yacht Basin (SIYB) waters violate water quality objectives for copper, toxicity, and pesticides. Dissolved copper concentrations in SIYB threaten and impair the designated beneficial uses of marine habitat (MAR), and wildlife habitat (WILD).

NUMERIC TARGET

The TMDL Numeric Targets for copper, toxicity and pesticides are set equal to the numeric water quality objectives for dissolved copper as defined in the California Toxics Rule (CTR) and shown below.

Table 7-7. TMDL Numeric Targets

Exposure	Water Quality Objective*	Numeric Target*
Continuous or Chronic (4 day average)	3.1 µg/L** of copper (Cu)	3.1 µg/L** of Cu
Maximum or Acute (1 hour average)	4.8 µg/L** of Cu	4.8 µg/L** of Cu

* Concentrations should not be exceeded more than once every three years.

** micrograms/liter (µg/L)

If the water quality objectives for dissolved copper in SIYB are modified in the future, as in the case of a site-specific objective, then the numeric targets will be set equal to the new water quality objectives.

SOURCE ANALYSIS

Approximately 98 percent of all copper loading to SIYB is attributable to copper-based antifouling paints applied to the hulls of recreational boats. The passive leaching of copper from antifouling paint is 93 percent of the total loading. The remaining five percent of total copper loading results from underwater hull cleaning operations in SIYB.

Table 7-8. Summary of Dissolved Copper Sources to SIYB

Source	Mass Load (kg/year)	Percent Contribution (% Cu)
Passive Leaching	2,000	93
Hull Cleaning	100	5
Urban Runoff	30	1
Background	30	1
Direct Atmospheric Deposition	3	<1
Sediment	0	0
Combined Sources	2,163	100

TOTAL MAXIMUM DAILY LOAD

The TMDL or loading capacity for dissolved copper discharges into SIYB is 1.6 kilograms/day (kg/day) or 567 kilograms/year (kg/year).

MARGIN OF SAFETY

The TMDL includes an explicit and implicit margin of safety (MOS). Ten percent of the loading capacity was reserved as an explicit MOS and calculated to be 57 kg/year. The implicit MOS was incorporated into the TMDL source analysis through numerous conservative assumptions.

ALLOCATIONS AND REDUCTIONS

A 76 percent overall reduction of residual copper loading to SIYB is required to meet the TMDL of 567 kg/year as shown in the table below. The assigned allocations from each source translate into a percent reduction of dissolved copper from current loading. Loading due to passive leaching must be reduced by 81 percent from current loading. Loading due to underwater hull cleaning must be reduced by 28 percent from current loading. From an overall perspective, passive leaching loading must be reduced by 75 percent from the combined total loading of all sources to SIYB. Underwater hull cleaning loading must be reduced by one percent from the combined total loading of all sources to SIYB.

Table 7-9. TMDL and Allocation Summary

Source	Current Load (kg/year of Cu)	Percent Contribution (% Cu)	Allocation (kg/year of Cu)	Percent Reduction from Current Source Load (%)	Percent Reduction from Total Loading to SIYB (%)
Passive Leaching	2,000	93	375	81	75
Hull Cleaning	100	5	72	28	1
Urban Runoff	30	1	30	0	0
Background	30	1	30	0	0
Direct Atmospheric Deposition	3	<1	3	0	0
Sediment	0	0	0	0	0
Current Mass Load	2,163	100			0
Margin of Safety			57		0
TMDL			567		0
Total Load Reduction				76	76

RECALCULATIONS IF WATER QUALITY OBJECTIVES CHANGE

If the water quality objectives for dissolved copper in SIYB are changed in the future, then the MOS, TMDL and allocations will be recalculated using the method shown below in the section titled, *Method for Recalculation of the Total Maximum Daily Load for Dissolved Copper in the Shelter Island Yacht Basin, San Diego Bay.*

TMDL IMPLEMENTATION PLAN

The TMDL will be implemented as follows:

The Regional Board will coordinate with governmental agencies having legal authority over the use of copper-based antifouling paints to protect water quality from the adverse effects of copper-based antifouling paints in SIYB; and

The Regional Board will regulate discharges of copper to SIYB through the issuance of Waste Discharge Requirements (WDRs), Waivers of WDRs (waivers), or adoption of Waste Discharge Prohibitions. WDRs could build upon pollution control programs developed by discharger organizations or the Port. Likewise, waivers or prohibitions could be conditioned on implementation of pollution control programs through third party agreements between the Regional Board and discharger organizations, and/or other agencies.

The Regional Board will amend Order No. 2001-01, "Waste Discharge Requirements for Discharges of Urban Runoff from the Municipal Separate Storm /Sewer System" to require that discharges of copper into SIYB waters via the City's municipal separate storm/sewer system not exceed a 30 mg/kg wasteload for copper.

The dischargers will be required to monitor SIYB waters and provide monitoring reports to the Regional Board for the purpose of assessing the effectiveness of the alternatives implemented.

COMPLIANCE SCHEDULE

Copper load and wasteload reductions are required over a 17-year staged compliance schedule period. The first stage consists of an initial 2-year orientation period during which no copper load reductions are required. The subsequent 15-year reduction period is comprised of three stages during which incremental copper load and wasteload reductions are required as shown below.

Table 7-10. Interim Loading Targets for Attainment of the TMDL

Stage	Time Period	Percent Reduction from Current Estimated Loading	Reduction to be Attained by End of Year	Estimated Interim Target Loading (kg/year of dissolved Cu)
Stage 1	Years 1-2	0%	N/A	N/A
Stage 2	Years 2-7	10%	7	1,900
Stage 3	Years 7-12	40%	12	1,300
Stage 4	Years 12-17	76%	17	567

METHOD FOR RECALCULATION OF THE TOTAL MAXIMUM DAILY LOAD FOR DISSOLVED COPPER IN THE SHELTER ISLAND YACHT BASIN, SAN DIEGO BAY

This section describes the method for recalculating the Shelter Island Yacht Basin TMDL for dissolved copper if the water quality objectives for dissolved copper are modified in the future.

Numeric Target

The numeric targets are set equal to the new water quality objectives.

Margin of Safety

The explicit margin of safety (MOS) equals ten percent of the loading capacity. The equation to calculate the loading capacity is given below.

Total Maximum Daily Load

The TMDL or loading capacity is recalculated using equations 1 through 4 below.

The loading capacity is recalculated according to equation 1 below:

$$(1) \quad R_s = C_2 \left(\frac{KA_c}{\Delta x} + k_L V_2 \right) - A_c C_1 \left(\frac{eA_s}{A_c} + \frac{K}{\Delta x} \right)$$

where C_1 = average background concentration of copper measured in the area of San Diego Bay adjacent to SIYB, expressed as total copper, (0.05 $\mu\text{g/L}$)

C_2 = average target concentration for copper in the SIYB (expressed as total copper) when the maximum concentration of copper in SIYB is equal to or less than the numeric target (mass/volume)

K = dispersion coefficient calculated from salinity measurements and mixing length approximation (15.3 m^2/sec)

A_c = cross-sectional area of entrance to SIYB (1,000 m^2)

A_s = surface area of SIYB (740,000 m^2)

Δx = average mixing length between SIYB and adjacent area; estimated distance between the endpoints for S_1 and S_2 (2,000 m)

V_2 = volume of SIYB (31,000,000 m^3)

e = evaporation rate (0.43 cm/day)

k_L = rate of total copper loss to sediment (7%/day)

R_s = loading capacity, expressed as total copper (mass/time); R_s is calculated iteratively to find the maximum possible value that does not cause C_2 to exceed the numeric target.

The dispersion coefficient K is calculated using equation 2 below:

$$(2) \quad K \cong \frac{eA_s S_1 \Delta x}{A_c (S_2 - S_1)}$$

where S_1, S_2 = salinity data obtained in SIYB and San Diego Bay adjoining SIYB (33.62 practical salinity units (psu) and 33.46 psu, respectively).

The average target concentration, C_2 , must be lower than the numeric target concentration to ensure that the loading capacity will not cause an exceedance of the numeric target anywhere in SIYB.

C_2 is calculated by multiplying the numeric target for chronic exposure by the ratio of the average measured concentration of copper in SIYB to the maximum measured concentration as expressed in equation 3 below:

$$(3) \quad C_2 = \text{numeric target} \left[\frac{\text{average measured concentration}}{\text{maximum measured concentration}} \right]$$

or,

$$C_2 = \text{numeric target} * \left[\frac{5.45 \mu\text{g/L}}{8 \mu\text{g/L}} \right]$$

To convert C_2 from dissolved copper concentration to total copper concentration, the number calculated from equation 3 is multiplied by the ratio of dissolved copper to total copper in seawater. If site-specific data are not available, the ratio of 0.83 can be used. This is the USEPA's conversion factor for saltwater acute criteria.⁴

Finally, the TMDL is calculated according to equation 4 below:

$$(4) \quad \text{TMDL} = R_s - \text{MOS}$$

Allocations

Equation 5 is used to determine the new allocation for passive leaching. In equation 5, the only variable is the allocation for passive leaching (A_p), while the other source allocations are constants. The allocation for hull cleaning remains the same, since it was based on the assumption that all of the divers will use Management Practices (MPs) to clean boat hulls that have copper bottom paints. Allocations for the other sources, namely urban runoff, background and sediment will not be recalculated because these sources of copper are insignificant.

$$(5) \quad \text{TMDL} = \text{Wasteload Allocation} + \text{Load Allocations} + \text{MOS}$$

$$\text{TMDL} = A_u + A_p + A_h + A_s + A_b + A_a + \text{MOS}$$

where:

A_u = allocation for urban runoff = 30 kg/year

A_p = allocation for passive leaching

A_h = allocation for hull cleaning = 72 kg/year

A_s = allocation for sediment = load from sediment = 0 kg/year

A_b = allocation for background = load from background = 30 kg/year

A_a = allocation for direct atmospheric deposition = load from direct atmospheric deposition = 3 kg/year

⁴ USEPA. 2000. Water Quality Standards; Establishment of Numeric Criteria for Priority Toxic Pollutants for the State of California; Rule. 40 CFR Part 131. May 18, 2000.

TOTAL MAXIMUM DAILY LOADS (TMDLS) FOR TOTAL NITROGEN AND TOTAL PHOSPHORUS IN THE RAINBOW CREEK WATERSHED



Rainbow Valley, California

On February 9, 2005, the Regional Board adopted Resolution No. R9-2005-0036, *A Resolution Adopting an Amendment to the Water Quality Control Plan for the San Diego Region (9) to Incorporate Total Maximum Daily Loads (TMDLs) for Total Nitrogen and Total Phosphorus in the Rainbow Creek Watershed, San Diego County*. The Basin Plan amendment was subsequently approved by the State Water Resources Control Board on November 16, 2005, the Office of Administrative Law on February 1, 2006, and the United States Environmental Protection Agency on March 22, 2006. The TMDL is described in the Basin Plan Amendment and Technical Report for Total Nitrogen and Total Phosphorus Total Maximum Daily Loads for Rainbow Creek, dated February 9, 2005.

PROBLEM STATEMENT

Nitrate, total nitrogen, and total phosphorus concentrations in Rainbow Creek exceed the Inorganic Chemicals nitrate and Biostimulatory Substances water quality objectives. These exceedances threaten to unreasonably impair the municipal supply (MUN), warm freshwater habitat (WARM), cold freshwater habitat (COLD), and wildlife habitat (WILD) beneficial uses of Rainbow Creek. Excessive nutrient levels in Rainbow Creek promote the growth of algae in localized areas, creating a nuisance condition, that unreasonably interferes with aesthetics and contact and non-contact water recreation (REC1, REC2) and threatens to impair WARM, COLD and WILD beneficial uses. State highways, agricultural fields and orchards, commercial nurseries, residential and urban areas, and septic tank disposal systems contribute to increased nutrient levels in Rainbow Creek as a result of storm water runoff, irrigation return flows, and ground water contributions to the creek.

NUMERIC TARGETS

The Numeric Targets for nitrate, total nitrogen, and total phosphorus are set equal to the Inorganic Chemicals nitrate water quality objective for municipal water supply and the numeric goals of the Biostimulatory Substances water quality objective as defined in the Basin Plan and shown below.

Table 7-11. Rainbow Creek Nitrate, Total Nitrogen, and Total Phosphorus Numeric Targets

Constituent	Water Quality Objective	Numeric Target
Nitrate (as nitrogen)	10 mg NO ₃ -N/L	10 mg NO ₃ -N/L
Total Nitrogen	1.0 mg N/L	1.0 mg N/L
Total Phosphorus	0.1 mg P/L	0.1 mg P/L

If the Inorganic Chemicals nitrate and Biostimulatory Substances water quality objectives in Rainbow Creek are modified in the future then the TMDL will be recalculated and the numeric targets will be set equal to the new water quality objectives.

SOURCE ASSESSMENT

Seventy-nine percent (79%) and seventy percent (70%) of total nitrogen and total phosphorus mass loading, respectively, are attributable to controllable sources, which include certain land use activities, septic tank disposal systems (total nitrogen only), and Interstate 15 (I-15). The land use activities include commercial nurseries, agricultural fields, orchards, residential areas, urban areas, and park areas.

Background and direct atmospheric deposition are not considered to be controllable sources.

Table 7-12. Summary of Total Nitrogen and Total Phosphorus Sources to Rainbow Creek

Source	Total Nitrogen Mass Load (kg N/yr)	Percent Contribution (% N)	Total Phosphorus Mass Load (kg P/yr)	Percent Contribution (% P)
Land Uses Runoff	2,662	69	262	66
Background	779	20	116	29
Septic Tank Disposal Systems	200	5	0	0
I-15 Runoff (Caltrans)	153	4	14	4
Direct Atmospheric Deposition	40	1	2	1
Combined Sources	3,834	100	394	100

TOTAL MAXIMUM DAILY LOADS OR LOADING CAPACITY

The TMDLs for nutrients in Rainbow Creek are 1,658 kg N/yr for total nitrogen and 165 kg P/yr for total phosphorus in order to attain and maintain the Inorganic Chemicals – Nitrate and Biostimulatory Substances water quality objective in Rainbow Creek waters.

The annual loading limit of total nitrogen and total phosphorus to Rainbow Creek shall be reduced incrementally from the current load of 3,834 kg/yr and 394 kg/yr, respectively, to 1,658 kg/yr and 165 kg/yr, respectively, by no later than December 31, 2021. The annual nutrient loading limits to be attained by December 31, 2021 is listed in Table 7-13.

Table 7-13. Annual Nutrient Loading Capacity and Compliance Date

TMDL	December 31, 2021 ¹	
Total Nitrogen – Annual Load	1,658 kg/yr	3,648 lbs/yr
Total Phosphorus – Annual Load	154 kg/yr	365 lbs/yr

¹ Compliance to be achieved no later than this date. The Regional Board may require earlier compliance with these targets when it is reasonable and feasible.

MARGIN OF SAFETY

Explicit and implicit margins of safety (MOS) were considered for these TMDLs. An explicit MOS of 5% is reserved to account for uncertainties and calculated to be 83 kg/year total nitrogen and 8 kg/year total phosphorus. An implicit MOS has been incorporated through conservative assumptions in the analysis.

LOAD ALLOCATIONS AND WASTELOAD ALLOCATIONS

A seventy-four percent (74%) and an eighty-five percent (85%) overall reduction of total nitrogen and total phosphorus loading, respectively, to Rainbow Creek is required to meet the TMDLs described in Table 7.13.

The load allocations for the initial annual loading are provided in Table 7-14 and 7-15, below. A margin of safety (MOS) of 5% is subtracted from this nutrient TMDL to account for unknowns, errors in assumptions, and potential future development in the watershed. This 5% is reserved for unknowns and is not allocated to any source. Allocations (other than for background and margin of safety) will be further reduced by 20% every 4 years until the biostimulatory targets for nitrogen and phosphorus are met. In the event that a nonpoint source becomes a permitted discharge, the portion of the load allocation that is associated with the source can become a wasteload allocation.

Table 7–14. Annual Total Nitrogen Allocations for Rainbow Creek

Source	Annual Total Nitrogen Load Allocations			
	2009 kg/yr ¹	2013 kg/yr ¹	2017 kg/yr ¹	2021 kg/yr ¹
<u>Load Allocations (LA)</u>				
Commercial nurseries	390	299	196	116
Agricultural fields	504	386	253	151
Orchards	607	465	305	182
Park	5	3	3	3
Residential areas	507	390	260	149
Urban areas	40	27	27	27
Septic tank disposal systems	200	100	46	46
Air deposition	40	40	40	40
<u>Wasteload Allocations (WLA)</u>				
Caltrans highway runoff	118	90	59	49
Unidentified & future point sources	33	33	33	33
Total LA & WLA	2,444	1,833	1,222	796
Background	779	779	779	779
Margin of Safety (not allocated)	83	83	83	83
Total	3,306	2,695	2,084	1,658

¹ To calculate pounds per year, multiply by 2.2.

² Background is calculated based on reference concentrations in San Diego streams and Rainbow Creek annual flow volumes.

Table 7-15. Annual Total Phosphorus Allocations for Rainbow Creek

Source	Annual Total Phosphorus Load Allocations			
	2009 kg/yr ¹	2013 kg/yr ¹	2017 kg/yr ¹	2021 kg/yr ¹
<u>Load Allocations (LA)</u>				
Commercial nurseries	20	16	10	3
Agricultural fields	28	21	14	4
Orchards	50	37	24	6
Park	0.15	0.10	0.10	0.10
Residential areas	99	74	47	12
Urban areas	9	6	6	6
Air deposition	2	2	2	2
<u>Wasteload Allocations (WLA)</u>				
Caltrans highway runoff	11	8	5	5
Unidentified & future point sources	3	3	3	3
Total LA & WLA	223	116	111	41
Background	116	116	116	116
Margin of Safety (not allocated)	8	8	8	8
Total	346	291	235	165

¹ To calculate pounds per year, multiply by 2.2.

² Background is calculated based on reference concentrations in San Diego streams and Rainbow Creek annual flow volumes.

RECALCULATIONS IF WATER QUALITY OBJECTIVES CHANGE

If the water quality objectives for Biostimulatory Substances are changed in the future, then the MOS, TMDL and allocations and reductions will be recalculated using the method shown below in the section titled, *Method for Recalculation of the Total Maximum Daily Loads for Nitrogen and Phosphorus in Rainbow Creek*.

TMDL IMPLEMENTATION ACTION PLAN

The necessary actions to implement the TMDLs are described in section 9 of the *Technical Report for Total Nitrogen and Total Phosphorus Total Maximum Daily Loads (TMDLs) in Rainbow Creek*, dated February 9, 2005 and listed below.

A. Regional Board Actions

1. Caltrans – Incorporate Wasteload Allocations in NPDES Storm Water Permit

The Regional Board shall request that the State Water Resources Control Board amend the Caltrans statewide NPDES storm water permit⁵ to include the following requirements:

⁵ The term “statewide NPDES storm water permit” refers to Order No. 99-06-DWQ, NPDES No. CAS000003, *National Pollutant Discharge Elimination System Permit, Statewide Storm Water Permit, and Waste Discharge Requirements for the State of California, Department of Transportation (Caltrans)* or subsequent superceding NPDES renewal Orders.

- a. MS4 discharges to Rainbow Creek shall not exceed the following wasteloads for nitrogen and phosphorus:

Table 7-16. Wasteloads for nitrogen and phosphorus

Nitrogen Wasteload	Phosphorus Wasteload	Compliance Due Date
118 kg N/yr ¹	11 kg P/yr ¹	Dec. 31, 2009
90 kg N/yr ¹	8 kg P/yr ¹	Dec. 31, 2013
59 kg N/yr ¹	5 kg P/yr ¹	Dec. 31, 2017
49 kg N/yr ¹	5 kg P/yr ¹	Dec. 31, 2021

- b. A directive to submit annual progress reports to the Regional Board detailing progress made on attaining the nutrient wasteload reductions in Rainbow Creek. The report shall be due on April 1 of each year shall be incorporated within section 2, Program Management of Caltrans MS4 Order No. 99-06-DWQ, NPDES No. CAS000003. Reporting shall continue on an annual basis until the nutrient water quality objective is attained in Rainbow Creek.

2. County of San Diego – Issue Water Code Governmental Water Quality Investigation Request Order for Nutrient Reduction and Management Plan

The Regional Board shall issue an Order under Water Code section 13225 requiring the County of San Diego to investigate excessive levels of nutrients in Rainbow Creek and feasible management strategies to reduce nutrient loading in Rainbow Creek. A Nutrient Reduction and Management Plan (NRMP) for the Rainbow Creek watershed containing the elements described below in section C, County of San Diego Nutrient Reduction Management Plan Elements, would satisfy such an Order. The County may submit alternative or additional elements equivalent to those described in section C that would result in equivalent protection from, or prevention of, nutrient discharges to Rainbow Creek.

3. County of San Diego – Establish Management Agency Agreement (MAA)

The Regional Board shall consider, following concurrence with the County of San Diego’s Nutrient Reduction and Management Plan (NRMP) for Rainbow Creek, entering into a Management Agency Agreement (MAA) with the County of San Diego. The MAA shall set forth the commitment of both parties to undertake various oversight responsibilities for the nonpoint source nutrient load reduction component of this TMDL, and the County’s commitments to implement the NRMP.

4. County of San Diego – Issue Water Code Governmental Water Quality Investigation Request for Groundwater Investigation and Characterization Report

The Regional Board could issue an Order under Water Code section 13225 directing the County of San Diego to prepare and submit a workplan and report described below in section B, County of San Diego Actions, Item 3 Submit Groundwater Investigation and Characterization Workplan and Item 4 Groundwater Investigation and Characterization Report.

5. California Department of Forestry and Fire Protection – Issue Water Code Section 13267 Order

The Regional Board shall issue a Water Code section 13267 order directing the California Department of Forestry and Fire Protection, Rainbow Conservation Camp (CDFFP) to submit any additional technical information needed to 1) evaluate whether CDFFP’s discharge is surfacing and/or contributing to the impairment of Rainbow Creek; and 2) estimate the actual nutrient load originating from the septic tank and percolation ponds to Rainbow Creek via groundwater flow. Based on the review of this information the Regional Board may further direct the CDFFP to implement an alternate means of wastewater disposal or additional treatment necessary to attain and maintain nutrient water quality objectives in Rainbow Creek.

6. Establish Memorandum of Understanding (MOU) with Agencies or Organizations

The Regional Board shall consider entering into a memorandum of understanding (MOU) to document cooperative agreements with other agencies or organizations that are able to provide information, technical assistance, or financial assistance to dischargers to support the Regional Board's goals of attaining the nutrient load reductions required under this TMDL and compliance with the nutrient water quality objective. These agencies and organizations include, but are not limited to, the United States Department of Agriculture, Natural Resources Conservation Service (NRCS), Mission Resource Conservation District (MRCD), and the University of California Cooperative Extension (UCCE).

7. Adopt Waste Discharge Requirements (WDRs), Waivers, and Discharge Prohibitions

In conjunction with an MAA or MOU with another third-party representative, organization, or government agency describing an adequate NPS pollution control implementation program, the Regional Board shall adopt individual or general waivers or waste discharge requirements (WDRs) for NPS discharges in the Rainbow Creek watershed. The waivers or WDRs shall require NPS dischargers to either participate in the third party NPS program or, alternatively, submit individual pollution prevention plans that detail how they will comply with the waivers and WDRs. Alternatively, the Regional Board may adopt a discharge prohibition, which includes exceptions for those discharges that are adequately addressed in an acceptable third-party MAA or MOU NPS pollution control implementation program.

8. Take Enforcement Actions

The Regional Board shall take enforcement action⁶, as necessary, against any discharger failing to comply with applicable waiver conditions, waste discharge requirements (WDRs), discharge prohibitions, or take enforcement action, as necessary, to control the discharge of nutrients to Rainbow Creek, to attain compliance with the nutrient wasteload and load reductions specified in this TMDL, or to attain compliance with the nutrient water quality objectives. The Regional Board may also terminate the applicability of waivers and issue waste discharge requirements or take other appropriate action against any discharger(s) failing to comply with the waiver conditions.

9. Review and Revise Existing Waste Discharge Requirements

The Regional Board shall review and, if necessary, update existing waste discharge requirements for discharges to land as well as groundwater in the Rainbow Creek watershed to incorporate effluent limitations for nutrients consistent with applicable nutrient groundwater quality objectives and surface water quality objectives.⁷

⁶ An enforcement action is any formal or informal action taken to address an incidence of actual or threatened noncompliance with existing regulations or provisions designed to protect water quality. Potential enforcement actions include a notice of violation (NOV), notices to comply (NTC), imposition of time schedules (TSO), issuance of cease and desist orders (CDOs) and cleanup and abatement orders (CAOs), administrative civil liability (ACL), and referral to the attorney general (AG) or district attorney (DA). The Regional Board generally implements enforcement through an escalating series of actions to: (1) assist cooperative dischargers in achieving compliance; (2) compel compliance for repeat violations and recalcitrant violators; and (3) provide a disincentive for noncompliance.

⁷ There are currently three dischargers in the Rainbow Creek watershed regulated under waste discharge requirements for the discharge of waste to land or groundwaters: Oak Crest Mobile Estates (Order No. 1993-69), Rainbow Conservation Camp (Order No. 1995-20), and Temecula Truck Inspection Facility (Order No. 1992-56). The Rainbow Truck Weigh and Inspection Facility, discharges under the terms of a waiver of waste discharge requirements (Order No. 2000-235).

10. Recommend High Priority for Grant Funds

The Regional Board shall recommend that the State Board assign a high priority to awarding grant funding⁸ for projects to implement the Rainbow Creek nutrient TMDLs. Special emphasis will be given to projects that can achieve quantifiable nutrient load reductions consistent with the specific nutrient TMDL load allocations.

11. Incorporate Water Code Section 13291 Regulations in Basin Plan

The Regional Board shall incorporate regulations currently under development by the State Water Resources Control Board pertaining to onsite wastewater treatment systems⁹ into the Basin Plan as soon as practicable upon their adoption by the State Board.¹⁰

B. County of San Diego Actions

1. Control MS4 Discharges to Rainbow Creek

For nutrient discharges to or from Municipal Separate Storm Sewer Systems (MS4) within the Rainbow Creek watershed, the County has an existing obligation under the NPDES requirements for MS4s in San Diego County¹¹ to require increasingly stringent best management practices, pursuant to the iterative process described in Receiving Water Limitation C.2.a.¹² of the MS4 Requirements, to reduce nutrient discharges in the Rainbow Creek watershed to the maximum extent practicable and restore compliance with the nutrient water quality objective.

2. Submit Nutrient Reduction and Management Plan (NRMP)

The County of San Diego shall, upon request by the Regional Board pursuant to Water Code section 13225, prepare and submit a NRMP for the Rainbow Creek watershed, consistent with the SWRCB NPS Implementation and Enforcement Policy and containing the elements described in section C, County of San Diego Nutrient Reduction and Management Plan or their equivalent. The County may submit alternative or additional elements equivalent to those described in section C that would result in equivalent protection from, or prevention of, nutrient discharges to Rainbow Creek.

3. Submit and Implement Groundwater Investigation and Characterization Workplan

The County of San Diego shall, upon request by the Regional Board pursuant to Water Code section 13225, undertake an investigation of groundwater quality within the Rainbow Creek watershed, and shall prepare and submit a workplan designed to guide the collection of information to produce the technical report described in Item 4, Groundwater Investigation and Characterization Report below. The workplan shall include the following:

⁸ The State Water Resources Control Board administers the awarding of grants funded from Proposition 13, Proposition 50, Clean Water Act 319(h) and other federal appropriations to projects that can result in measurable improvements in water quality, watershed condition, and/or capacity for effective watershed management. Many of these grant fund programs have specific set-asides for expenditures in the areas of watershed management and TMDL implementation for NPS pollution.

⁹ "Onsite wastewater treatment system(s)" (OWTS) is any individual or community onsite wastewater treatment, pretreatment and dispersal system including, but not limited to, a conventional, alternative, or experimental sewage dispersal system such as septic tanks having a subsurface discharge.

¹⁰ Water Code section 13291 directs the Regional Board to incorporate the regulations in the Basin Plan upon their adoption by the State Water Resources Control Board.

¹¹ The term "MS4 NPDES Storm Water Permit" refers to Order No.2001-001, NPDES No. CAS0108758, *Waste Discharge Requirements For Discharges of Urban Runoff from the Municipal Separate Storm Sewer Systems (MS4s) Draining the Watersheds of the County of San Diego, the Incorporated Cities Of San Diego County, and the San Diego Unified Port District* or subsequent superceding NPDES renewal Orders.

¹² Groundwater beneath the Rainbow Creek watershed is interpreted to occur in both the alluvial deposits where present and in the fractured rock. The groundwater investigation report shall assess the relative contribution from each aquifer.

- a. A schedule for completion of all activities and submission of a final Groundwater Investigation and Characterization Report.
- b. A description of proposed actions including drilling methods, analytical methods, sampling locations, and purging and sampling methods.
- c. The location of existing monitoring wells and the proposed location of additional monitoring wells needed to characterize nutrient concentrations and their lateral and vertical extent in groundwater.
- d. Contingencies for collection of additional samples.
- e. Sufficient scope to meet the objectives of assessing nutrient loading from surface sources to groundwater and the contribution of groundwater to the nutrient loading and nutrient concentrations in Rainbow Creek.
- f. Consideration of the following elements or factors:
 - i. Nutrient mass loading to groundwater in the fractured rock aquifer and the alluvial deposits aquifer¹³ from septic systems, deep percolation of applied irrigation water, and any other sources.
 - ii. Base flow contribution to Rainbow Creek from the fractured rock aquifer and the alluvial deposits aquifer.
 - iii. Mass balance of nutrients in the fractured rock aquifer and alluvial deposits aquifer (nutrient mass loading to groundwater, removals from the groundwater system including denitrification, plant uptake, and groundwater discharge, and change in the load and concentration of nutrients in groundwater).

The County of San Diego shall implement the workplan within sixty (60) days after submission of the workplan, unless otherwise directed in writing by the Regional Board. Before beginning these activities the County shall notify the Regional Board of the intent to initiate the proposed actions included in the workplan submitted; and comply with any conditions set by the Regional Board.

4. Submit Groundwater Investigation and Characterization Report

The County of San Diego shall, on a schedule agreed to in writing by the Regional Board, submit a Groundwater Investigation and Characterization Report containing a technical analysis and interpretation of the data to assess the contribution of groundwater to the nutrient loading and concentrations in Rainbow Creek. The report shall meet the objectives and address the considerations described in the Groundwater Investigation and Characterization Workplan. The report shall also present recommendations to refine assumptions, resolve uncertainties, and improve the scientific foundation of the TMDL with regard to quantifying groundwater nutrient loading to Rainbow Creek.

5. Establish Management Agency Agreement (MAA)

The County of San Diego is requested to enter into a MAA with the Regional Board setting forth the commitment of both parties to undertake various implementation oversight responsibilities for the nonpoint source nutrient load reduction component of this TMDL and the County's commitments to implement the NRMP.

¹³ Groundwater beneath the Rainbow Creek watershed is interpreted to occur in both the alluvial deposits where present and in the fractured rock. The groundwater investigation report shall assess the relative contribution from each aquifer.

C. County Of San Diego Nutrient Reduction And Management Plan

1. NPS Nutrient Reduction and Management Plan (NRMP)

A NRMP for the Rainbow Creek watershed shall describe the activities the County of San Diego could undertake to oversee discharger efforts to reduce nutrients in the runoff or groundwater discharges from new and existing (1) commercial nurseries; (2) agricultural fields; (3) orchards; (4) parks; (5) residential area; (6) urban areas; and (7) septic tank disposal system land uses (hereinafter referred to as key nutrient sources). A NRMP should include the following elements as provided in items 2 through 17 below or alternative or additional elements equivalent to those described that would result in equivalent protection from, or prevention of, nutrient discharges to Rainbow Creek.

2. Legal Authority

The County of San Diego should review its legal authority and evaluate its adequacy to mandate compliance with the nutrient load reductions specified in this TMDL through ordinance, statute, permit, contract or similar means. The County, at a minimum, should evaluate its authority to:

- a. Control the discharge of nutrients from nonpoint sources; and
- b. Prohibit discharges of nutrients which cause or contribute to exceedances of the nutrient load reductions specified in this TMDL or nutrient water quality objectives.

Alternatively the County of San Diego may certify that its existing legal authority is adequate to mandate compliance with the nutrient load reductions specified in this TMDL and prevent increases in nutrient loading to Rainbow Creek.

3. General Plan Modification

The County of San Diego should evaluate the adequacy of its General Plan to ensure that future land use and zoning decisions do not result in an increase in the nutrient loading to Rainbow Creek. The County should also describe the steps it will take to modify the General Plan as necessary. Alternatively the County of San Diego may certify that its existing General Plan is adequate to prevent an increase in nutrient loading to Rainbow Creek.

4. Modify Development Project Approval Process

The County of San Diego should evaluate the adequacy of its development project approval / permitting process as necessary to ensure that discharges from proposed developments in the Rainbow Creek watershed will comply with the nutrient load reductions specified in this TMDL and ensure that nutrient water quality objectives are not exceeded. The County's evaluation should consider the need to ensure that all development in Rainbow Creek watershed will be in compliance with County's storm water ordinances, permits, and all other applicable ordinances and requirements. The County should also describe the steps it will take to modify the development project approval / permitting process as necessary. Alternatively the County of San Diego may certify that its project approval / permitting process is adequate to ensure that discharges from proposed developments in the Rainbow Creek watershed will comply with the nutrients load reductions specified in this TMDL and ensure that nutrient water quality objectives are not exceeded.

5. CEQA Reviews

The County of San Diego should evaluate the adequacy of its environmental review process pursuant to CEQA to ensure that new development in the Rainbow Creek watershed does not contribute to exceedances of the nutrient load allocations specified in this TMDL or violations of the nutrient water quality objective. For example, diligent performance of environmental review under CEQA and requirements for mitigation of the adverse environmental consequences to water quality of new development and detrimental agricultural practices can significantly reduce nutrient loading to Rainbow Creek. The County's evaluation should consider the need to aggressively review proposed projects that have the potential to contribute nitrogen and phosphorus to the Rainbow Creek watershed and require appropriate mitigation. The County should also describe the steps it will take to revise the development project approval / permitting process as necessary.

Alternatively the County of San Diego may certify that its environmental review process pursuant to CEQA is adequate to ensure that new development in the Rainbow Creek watershed does not contribute to exceedances of the nutrient load allocations specified in this TMDL or violations of the nutrient water quality objective.

6. Pollution Prevention (Nutrients)

The County of San Diego should describe the steps it will take to implement pollution prevention¹⁴ methods for nutrients at sites owned by the County and require its use by owners or operators of nutrient sources, where appropriate.

7. Source Identification (Nutrients)

The County of San Diego should describe the steps it will take to develop and update annually an inventory of the individual nutrient sources within the residential, urban, commercial nursery, agricultural field, orchard, park, and septic tank disposal system category of land uses. The use of an automated database system, such as Geographical Information System (GIS) is highly recommended.

8. Threat to Water Quality Prioritization (Nutrients)

The County of San Diego should describe the steps it will take to establish priorities for inspection and oversight activities. Each individual nutrient source in each nonpoint source category should be classified as high, medium, or low threat to water quality. The inventory should include the following minimum information for each site: name; address; SIC codes as appropriate which best reflects the type of site; a narrative description characterizing the nutrient waste generated; and the potential for nutrient discharges to Rainbow Creek.

9. MP Implementation (Nutrients)

The County of San Diego should describe the steps it will take to:

- a. Designate a set of minimum MMs / MPs¹⁵ for the high, medium, and low threat to water quality nutrient sources identified in item 7 above. The designated minimum MPs for the high threat to water quality nutrient sources should be site and source specific as appropriate.
- b. Establish a time line for installation of the designated minimum MPs at each nutrient source within its jurisdiction. If particular minimum MPs are infeasible for any specific site/source the county of San Diego should describe the steps it will take to require the implementation of other equivalent MPs.

10. Inspection of Sites and Sources (Nutrients)

The County of San Diego should describe the steps it will take to inspect high priority sites and sources for compliance with its ordinances and permits as well as nutrient load reductions required under this TMDL. Inspections should include review of MP implementation plans and effectiveness. The County should also describe the steps it will take to implement all inspection follow-up actions, including enforcement actions, as necessary to obtain discharger compliance in implementing MPs.

¹⁴ Pollution Prevention is defined as practices and processes that reduce or eliminate the generation of pollutants, in contrast to source control, treatment, or disposal.

¹⁵ In determining appropriate MPs the County of San Diego is encouraged to consult the State Water Resources Control Board's California Nonpoint Source Encyclopedia (2004) (<http://www.waterboards.ca.gov/nps/encyclopedia.html>). This publication contains extensive information on nutrient reduction management measures (MMs) and management practices (MPs) applicable to the NPS land use activities in the Rainbow Creek watershed. The County is also encouraged to consult the Regional Board's Watershed Management Approach for the San Diego Region, Nonpoint Source (<http://www.waterboards.ca.gov/sandiego/programs/wmc.html>) for additional information on management measures.

11. Enforcement of Sites and Sources (Nutrients)

The County of San Diego should describe the steps it will take to enforce its ordinances, statues, permits, and contracts as necessary to attain compliance with the nutrient load reductions specified in this TMDL.

12. Reporting of Non-compliant Sites (Nutrients)

The County of San Diego should describe the steps it will take to provide oral notification to the Regional Board of non-compliant sites that are determined to be recalcitrant in implementing MPs or attaining compliance with nutrient load reductions required under this TMDL within 24 hours of the discovery of noncompliance. The notification process should also include procedures for a follow-up written report to be submitted to the Regional Board within 5 days of the incidence of non-compliance.

13. Monitoring to Assess Compliance With Nutrient Load Reductions

The County of San Diego should describe the steps it will take to conduct, or require nutrient sites or sources to conduct, a monitoring program to assess compliance of runoff or groundwater discharges with the load reductions from each of the land use categories assigned a load reduction. This can be accomplished by placing sampling stations at strategic nodes that would monitor nutrient discharges from individual sources of a common land use category.

14. Community Education and Outreach

The County of San Diego should describe the steps it will take to develop a focused educational program to raise community awareness of the nutrient impairment problem, promote pollution prevention, and increase the use of applicable management measures and practices where needed to control and reduce nutrient discharges to Rainbow Creek. Public education, outreach, and training programs should involve applicable user groups and the community.¹⁶

15. Seek Financial Assistance

The County of San Diego is encouraged to seek grant funding¹⁷ for projects to implement the Rainbow Creek nutrient TMDLs, particularly those that can achieve quantifiable nutrient load reductions consistent with the specific nutrient TMDL load allocations.

16. Nutrient Reduction and Management Plan (NRMP) Effectiveness

The County of San Diego should describe the steps it will take to develop a long-term strategy for assessing the effectiveness of the NRMP. The long-term assessment strategy should identify specific direct and indirect measurements that the County will use to track the long-term progress towards achieving the nutrient load reductions required under this TMDL. Methods used for assessing effectiveness should include the following or their equivalent: surveys, pollutant loading estimations, and receiving water quality monitoring. The long-term strategy shall also discuss the role of monitoring data in substantiating or refining the assessment.

¹⁶ Consideration should be given to expanding the County of San Diego's ongoing community and education outreach program under the County's MS4 NPDES Storm Water Permit to address the Rainbow Creek nutrient impairment problem. Additional suggestions for the information to be included in pollution prevention and education programs is contained in the State Water Resources Control Board's *California Nonpoint Source Encyclopedia* (2004) (<http://www.waterboards.ca.gov/nps/encyclopedia.html>)

¹⁷ Information on available grant funds is contained in the State Water Resources Control Board's *California Nonpoint Source Encyclopedia* (2004) (<http://www.waterboards.ca.gov/nps/encyclopedia.html>).

17. Nutrient Reduction and Management Plan (NRMP) Annual Report

The County of San Diego should describe the steps it will take to submit an annual NRMP report to the Regional Board by January 31 of each year following USEPA approval of this TMDL. The reporting period for this annual report should be the previous fiscal year. For example, the report submitted January 31, 2006 would cover the reporting period July 1, 2004 to June 30, 2005. The report should be incorporated in the annual Jurisdictional URMP Annual Report and the Watershed Specific URMP Annual Reports under the County's MS4 NPDES Permit and include the following information:

- a. Comprehensive description of all activities conducted by the County of San Diego to oversee implementation of the NRMP.
- b. An accounting of all: inspections conducted; enforcement actions taken; and education efforts conducted.
- c. An assessment of whether actions to implement designated minimum MPs at each nutrient source were actually carried out by dischargers.
- d. An assessment of the compliance of runoff or groundwater discharges with the load reductions from each of the land use categories assigned a load reduction.
- e. Identification of water quality improvements or degradation in Rainbow Creek with regard to attainment of the nutrient water quality objectives.
- f. An evaluation of the effectiveness of the NRMP in achieving the nutrient load reductions required under this TMDL.

D. Discharger Actions

1. State of California, Department of Transportation (Caltrans) Actions

Caltrans shall take all actions necessary to meet the nutrient wasteload reductions assigned to Caltrans. These nutrient wasteload reductions will eventually be incorporated into Caltrans statewide NPDES storm water permit. It is assumed that compliance with the nutrient wasteload reductions will be accomplished through the development and implementation of best management practices (BMPs). Caltrans shall also prepare and submit progress reports in accordance with the Caltrans statewide NPDES storm water permit or as otherwise directed by the Regional Board in a Water Code section 13383 order.

2. State of California Department of Forestry and Fire Protection (CDFFP) Actions

CDFFP shall, upon direction by the Regional Board in a Water Code section 13267 order, undertake an investigation to 1) evaluate whether CDFFP's discharge is surfacing and/or contributing to the impairment of Rainbow Creek; and 2) estimate the actual nutrient load to Rainbow Creek from groundwater flow originating from the septic tank and percolation ponds.

3. Nonpoint Source Dischargers (NPS Dischargers) Actions

NPS discharges of nutrients in the Rainbow Creek watershed result from (1) commercial nurseries; (2) agricultural fields; (3) orchards; (4) parks; (5) residential areas; (6) urban areas; and (7) septic tank disposal system land use activities. Individual landowners and other persons (NPS Dischargers) engaged in these land use activities shall implement pollution prevention¹⁸ methods and increase the use of applicable management measures and practices¹⁹ where needed to control and reduce nutrient discharges to Rainbow Creek and attain nutrient load reductions. Individual landowners and other persons are encouraged to seek grant funding²⁰ for projects to implement the Rainbow Creek nutrient TMDLs, particularly those that can achieve quantifiable nutrient load reductions consistent with the specific nutrient TMDL load allocations. NPS dischargers will be subject to Regional Board enforcement action for failing to: comply with applicable waiver conditions, waste discharge requirements (WDRs), discharge prohibitions; attain compliance with the nutrient load reductions specified in this TMDL; or attain compliance with the nutrient water quality objectives. The Regional Board may also terminate the applicability of waivers and issue waste discharge requirements to any NPS dischargers failing to comply with waiver conditions.

TMDL IMPLEMENTATION MONITORING PLAN

The necessary actions to monitor TMDL implementation are described in section 10 of the *Technical Report for Total Nitrogen and Total Phosphorus Total Maximum Daily Loads (TMDLs) in Rainbow Creek*, dated February 9, 2005 and listed below.

A. Regional Board Actions

1. Issue Order to Submit Monitoring Plan to Caltrans and County of San Diego

The Regional Board shall issue an Order to Caltrans under Water Code section 13383 and a Governmental Water Quality Investigation Request Order to the County of San Diego under Water Code section 13225, to prepare and submit an Implementation Monitoring Plan containing the elements described in **Section C. Implementation Monitoring Plan Elements** below. The Regional Board may amend this order at any time to include other nutrient dischargers in the Rainbow Creek watershed on a case-by-case basis.

2. Issue Order to Implement Monitoring Plan to Caltrans and County of San Diego

Upon concurrence with the County of San Diego's and Caltrans' Implementation Monitoring Plan the Regional Board shall issue an Order to Caltrans under Water Code section 13383 and a Governmental Water Quality Investigation Request Order to the County of San Diego under Water Code section 13225, to implement monitoring. The Regional Board may amend this order at any time to include other nutrient dischargers in the Rainbow Creek watershed on a case-by-case basis.

¹⁸ Pollution Prevention is defined as practices and processes that reduce or eliminate the generation of pollutants, in contrast to source control, treatment, or disposal.

¹⁹ In determining appropriate management methods and practices to control nutrient discharges interested persons are encouraged to consult the State Water Resources Control Board's California Nonpoint Source Encyclopedia (2004) (<http://www.waterboards.ca.gov/nps/encyclopedia.html>). This publication contains extensive information on nutrient reduction management measures (MMs) and management practices (MPs) applicable to the NPS land use activities in the Rainbow Creek watershed. Interested persons are also encouraged to consult the Regional Board's Watershed Management Approach for the San Diego Region, Nonpoint Source (<http://www.waterboards.ca.gov/sandiego/programs/wmc.html>) for additional information on management measures.

²⁰ Information on available grant funds is contained in the in the State Water Resources Control Board's *California Nonpoint Source Encyclopedia* (2004) (<http://www.waterboards.ca.gov/nps/encyclopedia.html>).

B. County of San Diego and Caltrans Actions

1. Prepare and Submit Monitoring Plan

The County of San Diego and Caltrans shall collaborate to prepare and submit an Implementation Monitoring Plan for the Rainbow Creek watershed containing the elements described in **Section C. Implementation Monitoring Plan Elements** below, upon direction by the Regional Board in a Water Code section 13225 / Water Code section 13383 Order. The number of monitoring stations in Rainbow Creek assigned to Caltrans should be based on the number of stations needed by Caltrans to demonstrate compliance with the nutrient wasteload allocation and the success of the TMDL in attaining the nutrient water quality objective in the portion of Rainbow Creek affected by its discharge. The Implementation Monitoring Plan shall be modified as requested by the Regional Board.

2. Implement Monitoring Plan

The County of San Diego and Caltrans shall implement the Implementation Monitoring Plan upon direction by the Regional Board pursuant to a Water Code section 13225 / section 13383 Order. The Regional Board may amend this order at any time to include other nutrient dischargers in the Rainbow Creek watershed on a case-by case basis.

C. Implementation Monitoring Plan Elements

The Implementation Monitoring Plan shall contain the following elements:

1. Surface Water Monitoring Stations

Monitoring stations shall be proposed that best serve the monitoring objectives described above in section 10.2 Monitoring Objectives. Previously monitored locations that shall be considered include Jubilee, Hines Nursery, Oak Crest, Rainbow Glen Tributary, Margarita Glen Tributary, Willow Glen-4, Willow Glen Tributary, Riverhouse, Via Milpas Tributary, and Stage Coach (See Figure A-3, in Appendix A). An additional sampling location between Oak Crest and Willow Glen-4 should also be considered. For instance, a monitoring location might be placed downstream of Oak Crest Mobile Estates to assess nutrient loading from this property. Monitoring stations shall also be considered at strategic nodes in Rainbow Creek and its tributaries that would monitor nutrient discharges from individual sources of a common land use category.

2. Groundwater Monitoring Stations

The location of existing wells and the proposed location of additional monitoring wells needed to define nutrient concentration trends in groundwater. Methods for purging and sampling monitoring wells to provide representative samples for the waste constituents of interest should be described.

3. Surface Water Monitoring Frequency

Monitoring frequencies of the various monitoring parameters shall be proposed that best serve the monitoring objectives described above in section 10.2 Monitoring Objectives. The frequencies should be adequate to evaluate ambient conditions and address any impact from low dissolved oxygen concentrations and algal growth.

4. Groundwater Monitoring Frequency

Monitoring frequencies of the various monitoring parameters shall be proposed that best serve the monitoring objectives described above section 10.2 Monitoring Objectives. The magnitude and timing of nutrient variability may vary significantly in monitoring wells that are located varying distances from nutrient sources. Sampling these wells will likely obtain water from varying depths in the aquifer. To define the nitrate variability at each well, the network will be sampled quarterly for two years. The observed variability will serve as a basis for determining the long-term sampling frequency for the network.

5. Surface Water Quality Parameters

Surface Water Quality Parameters shall include nitrogen (including nitrate, nitrite, ammonia and total Kjeldahl nitrogen (TKN)), phosphorus (including orthophosphate and total), dissolved oxygen, pH, turbidity, and temperature.

6. Groundwater Quality Parameters

Groundwater Quality Parameters shall include total nitrogen, nitrate, ammonia, nitrites, TKN, orthophosphate, total phosphorus, pH, dissolved oxygen and TDS.

7. Hydrology

Flow rate measurements shall be taken to calculate nutrient loading, to provide additional information about the hydrology of the watershed, and to identify patterns in algal growth.

8. Algal Biomass

Characterization of algal species composition is needed to provide a more reliable indicator of trophic status and evidence of nutrient condition (USEPA, 2000). The growth of algae is stimulated principally by nutrients such as nitrogen and phosphorus, but also requires adequate water temperature, light, flow, and dissolved oxygen. It is assumed at this time that both factors are co-limiting. Characterization of algal species composition may give a better understanding of the relationships between all the factors that affect algal growth, including sunlight, nitrogen, phosphorus, temperature, and dissolved oxygen. Algal biomass should be quantified by mass and/or by % cover of bottom. Collection and measurement of algal biomass should be performed uniformly or by a standardized method.

9. Biological Assessment Monitoring

It is recommended that biological assessment monitoring of benthic macroinvertebrates be performed at a minimum of three stations on Rainbow Creek and a reference stream. Biological assessment monitoring should be performed in accordance with the California Stream Bioassessment Methods Manual (Harrington and Born, 2000). Changes in the stream's biological integrity (e.g., an increase or decrease in diversity and abundance of sensitive species) could be used as an indicator of changes in the health of the creek. Sampling done in 1998-99 for the San Diego Ambient Bioassessment Program (CDFG, 2000) indicates that benthic macroinvertebrate communities vary seasonally. The seasonal trend could be due in part to rainfall and consequent streamflow conditions (e.g., scouring). Thus, sites should be sampled for benthic macroinvertebrates at least twice each year: once during the spring (i.e., May), and again in the fall (preferably in October).

10. Monitoring Reports

Monitoring reports shall be submitted in both electronic and paper formats and include the following information:

- a. An executive summary addressing all sections of the monitoring report, comprehensive interpretations and conclusions, and recommendations for future actions.
- b. A description of monitoring station locations by latitude and longitude coordinates, frequency of sampling, quality assurance / quality control procedures and sampling and analysis protocols.
- c. The data/results, methods of evaluating the data, graphical summaries of the data, and an explanation / discussion of the data.
- d. An assessment of the compliance of runoff characteristics with the required load reductions from each of the land use categories assigned a load reduction.
- e. Identification and analysis of trends in surface and groundwater quality and assessment of compliance with nutrient water quality objectives.
- f. An evaluation of the effectiveness of the TMDL implementation actions and the need for revisions to improve the implementation action plan.

Table 7-17. Required Monitoring Parameters

Parameter	Type of Sample ¹
Surface Water Monitoring	
Total nitrogen, nitrate, ammonia ² , nitrates, TKN, orthophosphate, and total phosphorus concentrations.	Grab
Temperature	In situ
pH	In situ
Dissolved oxygen	In situ
Turbidity	In situ
TDS	Grab
Flow rate	Field measurement
Algal biomass (% cover of bottom and/or Chl a/ash free dry weight (AFDM))	In situ and / or grab
Benthic macroinvertebrate community analysis (recommended)	Grab
Groundwater Monitoring	
Total nitrogen, nitrate, ammonia ² , nitrites, TKN, orthophosphate, and total phosphorus concentrations	Grab
pH	Grab or In situ
Dissolved Oxygen	Grab or In situ
TDS	Grab or In situ

¹. A California certified laboratory should be used with an approved QA/QC plan.

². All laboratory detection limits should be sufficient to determine compliance with the water quality objective. For example, un-ionized ammonia in surface waters (25 µg/L).

11. Quality Assurance/ Quality Control Plan

The monitoring program shall develop and implement a QA/QC plan for field and laboratory operations to ensure that data collected are of adequate quality given the monitoring objectives²¹. The QA/QC plan for field operations shall cover the following, at a minimum:

- a. Quality assurance objectives;
- b. Sample container preparation, labeling and storage;
- c. Chain-of-custody tracking;
- d. Field setup;
- e. Sampler equipment check and setup;
- f. Sample collection;
- g. Use of field blanks to assess field contamination;
- h. Use of field duplicate samples;
- i. Transportation to the laboratory;
- j. Training of field personnel; and
- k. Evaluation, and enhancement if needed of the QA/QC plan.

The QA/QC plan for laboratory operations shall cover the following, at a minimum:

- a. Quality assurance objectives;
- b. Organization of laboratory personnel, their education, experience, and duties;
- c. Sample procedures;
- d. Sample custody;
- e. Calibration procedures and frequency;
- f. Analytical procedures;
- g. Data reduction, validation, and reporting;
- h. Internal quality control procedures;
- i. Performance and system audits;
- j. Preventive maintenance;
- k. Assessment of accuracy and precision;
- l. Correction actions; and
- m. Quality assurance report.

12. Reporting Period

Annual reports should cover the period of October 1 through September 30. The reports should be submitted to the Regional Board by January 31 of the following year and should be incorporated within the annual receiving water monitoring reports required under the County of San Diego's MS4 NPDES Permit Receiving Waters Monitoring and Reporting Program.²²

13. Reporting Frequency

The first report shall be due in the first January following initiation of the monitoring program. Reporting shall continue on an annual basis until the nutrient water quality objective has been attained and maintained in Rainbow Creek.

²¹ For more information on QA/QC activities, including guidelines and example QA/QC documents, refer to <http://www.waterboards.ca.gov/swamp/qapp.html>

²² The term "MS4 NPDES Storm Water Permit" currently refers to Order No.2001-001, NPDES No. CAS0108758, Waste Discharge Requirements For Discharges Of Urban Runoff from the Municipal Separate Storm Sewer Systems (MS4s) Draining the Watersheds of the County of San Diego, the Incorporated Cities Of San Diego County, and the San Diego Unified Port District or subsequent superceding NPDES renewal Orders. Attachment B to this Order contains the Receiving Waters Monitoring and Reporting Program for Order No. 2001-01. The annual receiving water monitoring report is described in Table 6, Item 28, page 51 of Order No. 2001-01.

Compliance Schedule

Total nitrogen and total phosphorus reductions are required over a 16-year phased compliance schedule period during which incremental load and wasteload reductions are required as shown in Table 7-18, below. Twenty percent (20%) reductions are required every fourth year for the first three phases (by the end of year 12). The last (fourth) phase requires the remaining 14% total nitrogen reduction and 25% total phosphorus reduction needed to meet the TMDLs.

Table 7-18. Total Nitrogen and Total Phosphorus Phased Load Reduction Compliance Schedule

Compliance Date	Total Nitrogen		Total Phosphorus	
	Current Load & Annual Loads (LA + WLA) kg N/yr	Cumulative % Reduction	Current Load & Annual Loads (LA + WLA) kg P/yr	Cumulative % Reduction
	3,055 ¹		278 ¹	
12/31/2009	2,444	20	222	20
12/31/2013	1,833	40	167	40
12/31/2017	1,222	60	111	60
12/31/2021	796	74	41	85

¹ Current annual nutrient loads from identified point and nonpoint sources (See Table 7-12). This value does not include the contribution for background.

Regardless of what actions are taken to achieve load and wasteload reductions, there may not be an immediate response in the water quality or biological condition of Rainbow Creek. For example, there may be significant time lags between when actions are taken to reduce nutrient loads and resulting changes in nutrient concentrations in Rainbow Creek. This is especially likely if nutrients from past activities are tightly bound to sediments or if nutrient-contaminated groundwater has a long residence time before its release to Rainbow Creek waters. A three-year response time is projected for Rainbow Creek to attain compliance with nutrient water quality objectives after reaching the desired nutrient wasteload and load reductions in 2021. Accordingly the projected date when Rainbow Creek will attain and maintain compliance with nutrient water quality objectives is December 31, 2024.

AGRICULTURAL PROGRAM COSTS AND POTENTIAL SOURCES OF FINANCING

Pursuant to Water Code section 13141 the Regional Board has estimated the TMDL Implementation Program cost for agricultural water quality control in Table 7-19.

Table 7-19. Cost of Implementing Agricultural Water Quality Control

	Initial Capital Costs \$ per Operation		Annual Operational Costs \$ per Operation	
	Low	High	Low	High
Commercial Nurseries	\$26	\$41,075	\$3	\$4,108
Orchards	\$26	\$57,705	\$3	\$5,771
Agricultural Fields	\$26	\$57,705	\$3	\$5,771

Potential sources of financing include:

- Federal Clean Water Act Section 319(h) grants.
- Federal Clean Water Act Section 205(j) grants.
- State of California Proposition 13 funded grants.
- Small Communities Grants for Water Reclamation and Wastewater Treatment Facilities.
- Other state, federal and business loans, grants, and other assistance programs. These may include assistance from U.S. Small Business Administration and from conservation programs through various agencies such as the U.S. Department of Agriculture and Natural Resource Conservation Service.
- Various secured and unsecured loans, including home equity loans and business loans.

METHOD FOR RECALCULATION OF THE TOTAL MAXIMUM DAILY LOADS FOR NITROGEN AND PHOSPHORUS IN RAINBOW CREEK

This section describes the method for recalculating Rainbow Creek TMDLs for nitrogen and phosphorus if the water quality objectives are modified in the future.

Numeric Target

The numeric targets are set equal to the new water quality objectives.

Margin of Safety

The explicit margin of safety (MOS) equals five percent of the loading capacity. The equation to calculate the loading capacity is given below.

Loading Capacity

The annual total nitrogen loading capacity is determined by multiplying the flow volume (in ft³/yr) by the new water quality objective (in mg N/L) that will allow the creek to attain water quality standards. The equations below also use terms to convert milligrams to kilograms and cubic feet to liters. The loading capacity for nitrogen is as follows:

Low Flow (0-2.9 cfs)

$$17,764 * 1 \text{ e-}3 \text{ ft}^3/\text{yr} * \text{new water quality objective in mg N/L} * 28.32 \text{ L/ft}^3 * 1 \text{ e-}6 \text{ kg/mg} \\ = \text{new low flow loading capacity in kg N/yr}$$

Moderate – High Flow (3 – 39 cfs)

$$40,775 * 1 \text{ e-}3 \text{ ft}^3/\text{yr} * \text{new water quality objective in mg N/L} * 28.32 \text{ L/ft}^3 * 1 \text{ e-}6 \text{ kg/mg} \\ = \text{new moderate - high flow loading capacity in kg N/yr}$$

Total Annual Nitrogen Loading Capacity = sum of low flow and moderate - high flow loading capacity

Similarly, the annual total loading capacity for phosphorus is as follows:

Low Flow (0-2.9 cfs)

$$17,764 * 1 \text{ e-}3 \text{ ft}^3/\text{yr} * \text{new water quality objective in mg P/L} * 28.32 \text{ L/ft}^3 * 1 \text{ e-}6 \text{ kg/mg} \\ = \text{new low flow loading capacity in kg P/yr}$$

Moderate – High Flow (3 – 39 cfs)

$$40,775 * 1 \text{ e-}3 \text{ ft}^3/\text{yr} * \text{new water quality objective in mg P/L} * 28.32 \text{ L/ft}^3 * 1 \text{ e-}6 \text{ kg/mg} \\ = \text{new moderate-high flow loading capacity in kg P/yr}$$

Total Annual Phosphorus Loading Capacity = sum of low flow and moderate - high flow loading capacity

Total Maximum Daily Load

The TMDLs for nitrogen and phosphorous are set equal to the total annual loading capacity for each pollutant. The allocations in Table 7-20 below use the following equation to determine the total load allocations for nonpoint sources (LA) by subtracting background, the margin of safety (MOS), and the point source waste load allocations (WLA) from the TMDL.

$$\text{TMDL} = \sum(\text{WLA}) + \sum(\text{LA}) + \text{Background} + \text{MOS}$$

Allocations

The allocations of the total annual nitrogen and phosphorous loading capacities to the margin of safety, background, and various point and non-point sources are presented in Table 7-20.

Table 7-20. Total Nitrogen and Phosphorus Allocations for Rainbow Creek TMDL

Source	Nitrogen Allocation	Phosphorus Allocation
Margin of Safety (MOS)	5% ¹	5% ¹
Background	779 kg	116 kg
Caltrans (WLA)	New WQO * volume of Caltrans runoff	New WQO * volume of Caltrans runoff
Unidentified and Future Point Sources (WLA)	2% ¹	2% ¹
Total Allocation for Nonpoint Sources (LA) = Total Annual Loading Capacity – MOS – Background – Caltrans – Unidentified and Future Point Sources		
Commercial nurseries	16% ²	9% ²
Agricultural fields	21% ²	12% ²
Orchards	25% ²	18% ²
Park	0.4%	0.3%
Residential areas	21% ²	36% ²
Urban areas	4% ²	18% ²
Septic tank disposal systems	6% ²	0% ²
Air deposition	6% ²	6% ²

¹ percent of the total annual nitrogen and phosphorus loading capacity

² percent of the total allocation for nonpoint sources

TOTAL MAXIMUM DAILY LOADS (TMDLS) FOR COPPER, LEAD, AND ZINC IN CHOLLAS CREEK

On June 13, 2007, the Regional Board adopted Resolution No. R9-2007-0043, *Amendment to the Water Quality Control Plan for the San Diego Region to Incorporate Total Maximum Daily Loads for Dissolved Copper, Lead and Zinc in Chollas Creek, Tributary to San Diego Bay*. The TMDL Basin Plan Amendment was subsequently approved by the State Water Resources Control Board on July 15, 2008, the Office of Administrative Law on October 22, 2008, and the USEPA on December 18, 2008.

PROBLEM STATEMENT

Dissolved copper, lead and zinc concentrations in Chollas Creek violate numeric water quality criteria for copper, lead, and zinc promulgated in the California Toxics Rule, and the narrative objective for toxicity. Concentrations of these metals in Chollas Creek threaten and impair the designated beneficial uses of warm freshwater habitat (WARM), and wildlife habitat (WILD).

NUMERIC TARGETS

The TMDL numeric targets for copper, lead, and zinc are set equal to the numeric water quality criteria as defined in the California Toxics Rule (CTR) and shown below. Because the concentration of a dissolved metal causing a toxic effect varies significantly with hardness, the water quality criteria are expressed in the CTR as hardness based equations. The numeric targets are equal to the loading capacity of these metals in Chollas Creek.

Table 7-21a. Water Quality Criteria /Numeric Targets for dissolved metals in Chollas Creek (wet weather only)

Metal	Numeric Target for Acute Conditions: Criteria Maximum Concentration	Numeric Target for Chronic Conditions: Criteria Continuous Concentration
Copper	$WER * (0.96) * \{e^{[0.9422 * \ln(\text{hardness}) - 1.700]}\}$	$WER * (0.96) * \{e^{[0.8545 * \ln(\text{hardness}) - 1.702]}\}$
Lead	$WER * \{1.46203 - [0.145712 * \ln(\text{hardness})]\} * \{e^{[1.273 * \ln(\text{hardness}) - 1.460]}\}$	$WER * \{1.46203 - [0.145712 * \ln(\text{hardness})]\} * \{e^{[1.273 * \ln(\text{hardness}) - 4.705]}\}$
Zinc	$WER * (0.978) * \{e^{[0.8473 * \ln(\text{hardness}) + 0.884]}\}$	$WER * (0.986) * \{e^{[0.8473 * \ln(\text{hardness}) + 0.884]}\}$

- The site-specific WER applies during “wet weather” as defined in applicable monitoring requirements. This is commonly defined as a storm event with greater than 0.1 inch of rainfall. During dry weather, the WERs are equal to 1.0.

Table 7- 21b. Site-specific WERs for dissolved metals in Chollas Creek (wet weather only)

Metal	Site-Specific WER
Copper	6.998
Zinc	1.711

SOURCE ANALYSIS

The vast majority of metals loading to Chollas Creek are believed to come through the storm water conveyance system. An analysis of source contributions reveals many land uses and activities associated with urbanization to be potential sources of copper, lead and zinc to Chollas Creek. Modeling efforts point toward freeways and commercial/industrial land uses as the major contributors.

TOTAL MAXIMUM DAILY LOADS

The TMDLs for dissolved copper, lead and zinc in Chollas Creek are concentration-based and set equal to 90 percent of the numeric targets/loading capacity.

MARGIN OF SAFETY

The TMDL includes an explicit margin of safety (MOS). Ten percent of the loading capacity was reserved as an explicit MOS.

ALLOCATIONS AND REDUCTIONS

The source analysis showed that nonpoint sources and background concentrations of metals are insignificant, and thus, were set equal to zero in the TMDL calculations. The wasteload allocations are set equal to 90 percent of the numeric targets/loading capacity. Concentrations of dissolved copper, lead and zinc require significant reductions from current concentrations to meet the loading capacity.

TMDL IMPLEMENTATION PLAN

Persons whose point source discharges contribute to exceedance of Water Quality Criteria (WQC) for copper, lead, and zinc in Chollas Creek will be required to meet the WLA hardness dependant concentrations in their urban runoff discharges before it is discharged to Chollas Creek. Actions to meet the WLAs in discharges to Chollas Creek will be required in WDRs that regulate MS4 discharges, industrial facility and construction activity stormwater discharges, and groundwater extraction discharges in the Chollas Creek watershed. The following orders may be reissued or revised by the Regional Board to include requirements to meet the WLAs. Alternatively, the Regional Board may issue new WDRs to meet the WLAs.

Order No. 2007-0001, NPDES No. CAS0108758, *Waste Discharge Requirements for Discharges of Urban Runoff from the Municipal Separate Storm Sewer Systems Draining the Watersheds of the County of San Diego, the Incorporated Cities of San Diego County, and the San Diego Unified Port District*, or subsequent superceding NPDES renewal orders.

Order No. 2000-90, NPDES No. CAG19001, *General Waste Discharge Requirements for Temporary Groundwater Extraction and Similar Waste Discharges to San Diego Bay and Storm Drains or other Conveyance Systems Tributary Thereto*, or subsequent superceding NPDES renewal orders.

Order No. 2001-96, NPDES No. CAG 919002, *General Waste Discharge Requirements for Groundwater Extraction Waste Discharges from Construction, Remediation and Permanent Groundwater Extraction Projects to Surface Waters within the San Diego Region Except for San Diego Bay* or subsequent superceding NPDES renewal orders.

Order No. 97-11, *General Waste Discharge Requirements for Post-Closure Maintenance of Inactive Nonhazardous Waste Landfills within the San Diego Region* or subsequent superceding NPDES renewal orders.

The Regional Board shall request the State Water Resources Control Board amend the following statewide orders:

Order No. 99-06-DWQ, NPDES No. CAS000003, *National Pollutant Discharge Elimination System (NPDES) Permit, Statewide Storm Water Permit, and Waste Discharge Requirements (WDRs) for the State of California, Department of Transportation (Caltrans)*, or subsequent superceding NPDES renewal orders.

Order No. 97-03-DWQ, NPDES No. CAS 000001, *Waste Discharge Requirements for Discharges of Storm Water Associated with Industrial Activities Excluding Construction Activities*, or subsequent superceding NPDES renewal orders.

Order No. 2003-0005-DWQ, NPDES No. CAS000004, *Waste Discharge Requirements for Storm Water Discharges from Small Municipal Separate Storm Sewer Systems*, or subsequent superceding NPDES renewal orders.

Order No. 99-08-DWQ, NPDES No. CAS000002, *General Permit for Storm Water Discharges Associated with Construction Activity*, or subsequent superceding NPDES renewal orders.

The Regional Board shall require the U.S. Navy to submit a Notice of Intent to enroll the Naval Base San Diego facility under statewide Order No. 2003-005-DWQ or subsequent superseding NPDES renewal orders.

IMPLEMENTATION MONITORING PLAN

The dischargers will be required to monitor Chollas Creek and provide monitoring reports to the Regional Board for the purpose of assessing the effectiveness of the management practices implemented to meet the TMDL allocations. The Regional Board shall amend the following order to include a requirement that the cities of San Diego, Lemon Grove, and La Mesa, the County of San Diego, the San Diego Unified Port District, and CalTrans investigate excessive levels of metals in Chollas Creek and feasible management strategies to reduce metal loadings in Chollas Creek, and conduct additional monitoring to collect the data necessary to refine the watershed wash-off model to provide a more accurate estimate of the mass loads of copper, lead and zinc leaving Chollas Creek each year.

Order No. R9-2004-0277, *California Department of Transportation and San Diego Municipal Separate Storm Sewer System Copermittees Responsible for the Discharge of Diazinon into the Chollas Creek Watershed, San Diego, California*

SCHEDULE OF COMPLIANCE

Concentrations of metals in urban runoff shall only be allowed to exceed the WLAs by a certain percentage for the first nineteen years after initiation of this TMDL. Allowable concentrations shall decrease as shown in Table 7-22. For example, if the measured hardness in year ten dictates the WLA for copper in urban runoff is 10 µg/l, the maximum allowable measured copper concentration would be 12.0 µg/L. By the end of the twentieth year of this TMDL, the WLAs of this TMDL shall be met. This will ensure that copper, lead and zinc water quality objectives are being met at all locations in the creek during all times of the year.

Table 7-22. Interim goals for achieving Wasteload Allocations

Compliance Year	Allowable Exceedance of the WLAs (allowable percentage above)		
	Copper	Lead	Zinc
1	100%	100%	100%
10	20%	20%	20%
20	0%	0%	0%

Compliance with the interim goals in this schedule can be assessed by showing that dissolved metals concentrations in the receiving water exceed the WQC for copper, lead, and zinc by no more than the allowable exceedances for WLAs shown in the table above. Regulated groundwater discharges to Chollas Creek must meet the WLAs at the initiation of the discharge. No schedule to meet interim goals will be allowed in the case of groundwater discharges.

The compliance schedule for implementation of the TMDLs shall be as follows in Table 7-23.

Table 7-23. Compliance Schedule

Item	Implementation Action	Responsible Parties	Date
1	Effective date of Chollas Creek Metals TMDL Waste Load Allocations.	San Diego Water Board, Municipal Dischargers, Caltrans, Navy, Industrial Stormwater Dischargers, Construction Stormwater Dischargers, Landfill Stormwater Dischargers	October 22, 2008 ²³
2	Recommend High Priority for grant funds.	San Diego Water Board	Immediately after effective date
3	Submit annual Progress Report to San Diego Water Board due January 1 of each year.	Municipal Dischargers	Annually after reissue of NPDES WDRs.
4	Submit annual Progress Report to San Diego Water Board due April 1 of each year.	Caltrans	Annually after reissue of NPDES WDRs.
5	Submit annual Progress Report to San Diego Water Board due July 1 of each year.	Industrial Stormwater Dischargers	Annually after reissue of NPDES WDRs.
6	Submit annual Progress Report to San Diego Water Board due July 1 of each year.	Construction Stormwater Dischargers	Annually after reissue of NPDES WDRs.
7	Municipal NPDES WDRs shall be issued, reissued, or revised to include WQBELs consistent with the assumptions and requirements of the Chollas Creek WLAs.	San Diego Water Board	Within 5 years of effective date
8	Caltrans NPDES WDRs shall be issued, reissued, or revised to include WQBELs consistent with the assumptions and requirements of the Chollas Creek WLAs.	State Water Board	Within 5 years of effective date
9	Construction NPDES WDRs shall be issued, reissued, or revised to include WQBELs consistent with the assumptions and requirements of the Chollas Creek WLAs.	State Water Board	Within 5 years of effective date
10	Industrial NPDES WDRs shall be issued, reissued, or revised to include WQBELs consistent with the assumptions and requirements of the Chollas Creek WLAs.	State Water Board	Within 5 years of effective date
11	Amend Orders No. 2000-90, and No. 2001-96 (or superseding renewal orders) which regulates temporary groundwater extraction discharges to San Diego Bay and its tributaries to include WQBELs consistent with the assumptions and requirements of the Chollas Creek WLAs.	San Diego Water Board	Within 5 years of effective date
12	Municipal and Navy WDR Order No. R9-2004-0277 shall amended to require additional monitoring for metals and hardness.	San Diego Water Board	Within 5 years of effective date
13	Landfill NPDES WDR Order No. 97-11 (or superseding renewal orders) shall be issued, reissued, or revised to monitor for metals and hardness.	San Diego Water Board	Within 5 years of effective date
14	Navy and all other Phase II small MS4 permittees in the Chollas Creek watershed shall be enrolled in Order No. 2003-0005-DWQ (or superseding renewal orders).	San Diego Water Board	Immediately after effective date.
15	Take enforcement actions	San Diego Water Board	As needed after effective date.

²³ Upon approval of by Office of Administrative Law.

Item	Implementation Action	Responsible Parties	Date
16	Meet 80% Chollas Creek Metals TMDL WLA reductions.	Municipal Dischargers, Caltrans, Navy, Industrial Stormwater Dischargers, Construction Stormwater Dischargers, Landfill Stormwater Dischargers	10 years after effective date.
17	Meet 100% Chollas Creek Metals TMDL WLA reductions.	Municipal Dischargers, Caltrans, Navy, Industrial Stormwater Dischargers, Construction Stormwater Dischargers, Landfill Stormwater Dischargers	20 years after effective date.

TOTAL MAXIMUM DAILY LOADS FOR INDICATOR BACTERIA, BABY BEACH AND SHELTER ISLAND SHORELINE PARK SHORELINES

On June 11, 2008, the San Diego Water Board adopted Resolution No. R9-2008-0027, *A Resolution Amending the Water Quality Control Plan for the San Diego Region (9) to Incorporate Total Maximum Daily Loads for Indicator Bacteria, Baby Beach in Dana Point Harbor and Shelter Island Shoreline Park in San Diego Bay*. The TMDL Basin Plan Amendment was subsequently approved by the State Water Resources Control Board on June 16, 2009, the Office of Administrative Law on September 15, 2009, and the USEPA on October 26, 2009.

PROBLEM STATEMENT

Bacteria densities along the shoreline segments of Baby Beach within Dana Point Harbor and Shelter Island Shoreline Park within San Diego Bay violate water quality objectives (WQOs) for indicator bacteria. Bacteria densities in waters at these shoreline segments unreasonably impair and threaten to impair the water quality needed to support designated beneficial uses of contact recreation (REC-1)²⁴.

The federal Clean Water Act requires the establishment of Total Maximum Daily Loads (TMDLs) for pollutants that exceed water quality objectives needed to support designated beneficial uses, i.e., that cause or contribute to violation of state “water quality standards.”

NUMERIC TARGETS

When calculating TMDLs, numeric targets are established to meet WQOs and subsequently ensure the protection of beneficial uses. The numeric targets for these TMDLs consist of the REC-1 WQOs for indicator bacteria contained in the Basin Plan. TMDLs were calculated for each impaired waterbody, for each indicator bacteria, for wet and dry weather. The numeric targets used in the TMDL calculations were equal to the WQOs for bacteria for REC-1.

Different dry weather and wet weather numeric targets were used for load calculations because the bacteria transport mechanisms to receiving waters are different under wet and dry weather conditions.

Single sample maximum WQOs were used as wet weather numeric targets. Dry weather numeric targets are typically best represented by geometric mean WQOs. However, due to extreme diurnal variations in bacteria densities that can result from tidal effects, in some cases the maximum hourly concentration could regularly exceed the single sample maximum WQOs. Therefore, both the REC-1 30-day geometric mean and single sample maximum WQOs were selected as numeric targets for dry weather. The numeric targets were equal to the total coliform, fecal coliform and *Enterococcus* WQOs for REC-1 in all cases.

The numeric targets for the scenarios described above are listed in the following tables:

Table 7-24. Wet Weather Numeric Targets

Basis for Numeric Target	Total Coliform (MPN/100mL)	Fecal Coliform (MPN/100mL)	Enterococcus (MPN/100mL)
Beneficial Use	REC-1	REC-1	REC-1
Single sample maximum	10,000	400	104

²⁴ Water quality objectives for indicator bacteria in waters with non-water-contact recreation (REC-2) are less stringent than the water quality objectives for REC-1, therefore, attainment of REC-1 objectives through the implementation of TMDLs will, *a fortiori*, provide the requisite water quality for REC-2.

Table 7-25. Dry Weather Numeric Targets

Basis for Numeric Target	Total Coliform (MPN/100mL)	Fecal Coliform (MPN/100mL)	Enterococcus (MPN/100mL)
Beneficial Use	REC-1	REC-1	REC-1
30-day geometric mean	1,000	200	35
Single sample maximum	10,000	400	104

SOURCE ANALYSIS

Sources of bacteria are the same under both wet weather and dry weather conditions. Bacteria can enter surface waters from both nonpoint and point sources. Nonpoint sources are typically diffuse sources that have multiple routes of entry into surface waters. Point sources typically discharge at a specific location from pipes, outfalls, and conveyance channels.

The only nonpoint sources identified to potentially affect the waterbodies addressed by these TMDLs were natural sources (e.g., direct inputs from birds, terrestrial and aquatic animals, wrack line and aquatic plants, sediments, or other unidentified or unquantified sources within the receiving waters), homeless encampments, or other background sources (e.g., “ambient” bacteria that may be influenced by illegal discharges from boats). Because the homeless encampments are illegal, these loads are not allowed and must be eliminated. Due to lack of data, bacteria loads from natural sources or other background sources could not be specifically identified or quantified for TMDL development. Until more information is obtained through further study to provide identification of the relative loading from each of these potential sources, they were combined into a single natural and background source for each shoreline segment.

The point sources identified to potentially affect the waterbodies addressed in this study were discharges from municipal separate storm sewer systems (MS4s) and illegal discharges from boats and/or wastewater collection systems and treatment plants. Because the Basin Plan includes waste discharge prohibitions specifically for the discharge of treated or untreated sewage from vessels to Dana Point Harbor and San Diego Bay and the unauthorized discharge of treated or untreated sewage to waters of the state, illegal discharges from boats and wastewater collection systems and treatment plants are not allowed must be eliminated. The watersheds that drain into the receiving waters at the impaired shoreline segments are wholly located within urbanized areas. Therefore, the only allowable point source identified was urban runoff discharged from MS4s, although other point sources may exist.

For both wet weather and dry weather conditions, there are natural and background sources of bacteria within the receiving waters at the impaired shoreline segments. However, for sources of bacteria that originate from the watersheds draining into the receiving waters, the method of transport for the two conditions is very different. Wet weather loading originating from the watersheds is dominated by episodic storm flows that wash off bacteria that build up on the surface of all land use types in the watershed during dry periods. Dry weather loading originating from the watersheds is dominated by nuisance flows from urban land use activities such as car washing, sidewalk washing, and lawn over-irrigation, which pick up bacteria and deposit it into receiving waters.

TOTAL MAXIMUM DAILY LOADS AND ALLOCATIONS

The TMDLs are equal to the assimilative or loading capacity of each shoreline segment for each pollutant. TMDLs for each type of indicator bacteria were developed for each impaired waterbody. TMDLs are defined as the maximum amount of a pollutant the waterbody can receive and still attain water quality objectives and protection of designated beneficial uses. Once calculated, a TMDL is set equal to the sum of all individual Waste Load Allocations (WLAs) for point sources and Load Allocations (LAs) for nonpoint sources. The TMDL includes a margin of safety (MOS) that takes into account any uncertainties in the TMDL calculation, which may be explicit or implicit. For these TMDLs, an implicit margin of safety is included via conservative estimates and assumptions used throughout the TMDL calculations. Separate TMDLs were calculated for wet weather and dry weather conditions to account for seasonal variations, and because the transport mechanism, flow, and bacteria loads from the watersheds draining to the receiving waters are different between dry and wet weather conditions.

Calibrated models were used to simulate flow and bacteria densities from the watersheds draining into the receiving waters and within the receiving waters of the shoreline segments. The models were used to calculate the existing bacteria loads, as well as TMDLs for each impaired shoreline segment. The modeled existing loads were compared to the TMDLs to calculate the necessary load reductions needed to achieve the TMDLs in the waterbodies. The TMDLs were allocated among point sources (WLAs) and nonpoint sources (LAs). The only allowable point source identified was urban runoff discharged from MS4s, which was assigned a WLA for each watershed. The only allowable nonpoint sources identified were natural or background sources, such as direct inputs from birds, terrestrial and aquatic animals, wrack line and aquatic plants, sediments, or other unidentified and unquantified sources within the receiving waters, which were lumped together and assigned a LA. Because only the point sources are considered controllable, a load reduction was only calculated for the bacteria loads from the MS4s. Bacteria loads from sources of illegal discharges were assigned WLAs and LAs of zero. The TMDLs, LAs for natural and background sources, WLAs for municipal MS4s, and load reductions for municipal MS4s are shown below in Tables 7-26 through 7-31.

MARGIN OF SAFETY

There are two ways to incorporate the MOS (USEPA, 1991): (1) implicitly incorporate the MOS using conservative model assumptions to develop allocations; and/or, (2) explicitly specify a portion of the total TMDL as the MOS and use the remainder for allocations. Throughout the TMDL development process, conservative assumptions were employed. Based on the incorporation of all these conservative assumptions, no explicit MOS was necessary.

Table 7-26. REC-1 Wet Weather TMDLs for Total Coliform for Baby Beach and Shelter Island Shoreline Park Shoreline Segments

Waterbody	Shoreline Segment/Area	Hydrologic Descriptor	Model Sub-watershed	TMDL (Billion MPN/ 30 days)	Load Allocations (LAs)	Wasteload Allocations (WLAs)	Existing Wasteloads	Percent Reduction of Municipal MS4 Existing Wasteload ²
					Natural/Background (Billion MPN/ 30 days) ¹	Municipal MS4 (Billion MPN/ 30 days)	Municipal MS4 (Billion MPN/ 30 days)	
Dana Point Harbor	Baby Beach	Dana Point HSA (901.14)	2101,2102 2103,2104	166,111	162,857	3,254	3,254	0%
San Diego Bay	Shelter Island Shoreline Park	Point Loma HA (908.10)	2201	482,598	482,400	198	198	0%

Abbreviations/Acronyms:

TMDL: total maximum daily load

LA: load allocation for nonpoint source

WLA: wasteload allocation for point source

MS4: Municipal Separate Storm Sewer System

MPN: most probable number

Notes:

¹ Calculated by dry weather EFDC model analysis (Dry weather LA from Table 7-29 multiplied by 30 days). No reduction required for natural/background sources.

² Percent Reduction of Existing Municipal MS4 Wasteload = (Existing Municipal MS4 Wasteload – Municipal MS4 WLA) ÷ (Existing Municipal MS4 Wasteload) x 100%

Table 7-27. REC-1 Wet Weather TMDLs for Fecal Coliform for Baby Beach and Shelter Island Shoreline Park Shoreline Segments

Waterbody	Shoreline Segment/Area	Hydrologic Descriptor	Model Sub-watershed	TMDL (Billion MPN/ 30 days)	Load Allocations (LAs)	Wasteload Allocations (WLAs)	Existing Wasteloads	Percent Reduction of Municipal MS4 Existing Wasteload ²
					Natural/Background (Billion MPN/ 30 days) ¹	Municipal MS4 (Billion MPN/ 30 days)	Municipal MS4 (Billion MPN/ 30 days)	
Dana Point Harbor	Baby Beach	Dana Point HSA (901.14)	2101,2102 2103,2104	32,585	32,473	112	112	0%
San Diego Bay	Shelter Island Shoreline Park	Point Loma HA (908.10)	2201	41,408	41,400	8	8	0%

Abbreviations/Acronyms:

TMDL: total maximum daily load

LA: load allocation for nonpoint source

WLA: wasteload allocation for point source

MS4: Municipal Separate Storm Sewer System

MPN: most probable number

Notes:

¹ Calculated by dry weather EFDC model analysis (Dry weather LA from Table 7-30 multiplied by 30 days). No reduction required for natural/background sources.

² Percent Reduction of Existing Municipal MS4 Wasteload = (Existing Municipal MS4 Wasteload – Municipal MS4 WLA) ÷ (Existing Municipal MS4 Wasteload) x 100%

Table7-28. REC-1 Wet Weather TMDLs for *Enterococcus* for Baby Beach and Shelter Island Shoreline Park Shoreline Segments

Waterbody	Shoreline Segment/Area	Hydrologic Descriptor	Model Sub-watershed	TMDL (Billion MPN/ 30 days)	Load Allocations (LAs)	Wasteload Allocations (WLAs)	Existing Wasteloads	Percent Reduction of Municipal MS4 Existing Wasteload ²
					Natural/Background (Billion MPN/ 30 days) ¹	Municipal MS4 (Billion MPN/ 30 days)	Municipal MS4 (Billion MPN/ 30 days)	
Dana Point Harbor	Baby Beach	Dana Point HSA (901.14)	2101,2102 2103,2104	5,730	5,616	114	301	62.2%
San Diego Bay	Shelter Island Shoreline Park	Point Loma HA (908.10)	2201	10,556	10,530	26	26	0%

Abbreviations/Acronyms:

TMDL: total maximum daily load
 LA: load allocation for nonpoint source
 WLA: wasteload allocation for point source
 MS4: Municipal Separate Storm Sewer System
 MPN: most probable number

Notes:

¹ Calculated by dry weather EFDC model analysis (Dry weather LA from Table 7-31 multiplied by 30 days). No reduction required for natural/background sources.
² Percent Reduction of Existing Municipal MS4 Wasteload = (Existing Municipal MS4 Wasteload – Municipal MS4 WLA) ÷ (Existing Municipal MS4 Wasteload) x 100%

Table7-29. REC-1 Dry Weather TMDLs for Total Coliform for Baby Beach and Shelter Island Shoreline Park Shoreline Segments

Waterbody	Shoreline Segment/Area	Hydrologic Descriptor	Model Sub-watershed	TMDL (Billion MPN/ day)	Load Allocations (LAs)	Wasteload Allocations (WLAs)	Existing Wasteloads	Percent Reduction of Municipal MS4 Existing Wasteload ²
					Natural/Background (Billion MPN/ day) ¹	Municipal MS4 (Billion MPN/ day)	Municipal MS4 (Billion MPN/ day)	
Dana Point Harbor	Baby Beach	Dana Point HSA (901.14)	2101,2102 2103,2104	5,430	5,429	0.86	9.0	90.4%
San Diego Bay	Shelter Island Shoreline Park	Point Loma HA (908.10)	2201	16,080	16,080	0	0	0%

Abbreviations/Acronyms:

TMDL: total maximum daily load
 LA: load allocation for nonpoint source
 WLA: wasteload allocation for point source
 MS4: Municipal Separate Storm Sewer System
 MPN: most probable number

Notes:

¹ Calculated by dry weather EFDC model analysis. No reduction required for natural/background sources.
² Percent Reduction of Existing Municipal MS4 Wasteload = (Existing Municipal MS4 Wasteload – Municipal MS4 WLA) ÷ (Existing Municipal MS4 Wasteload) x 100%

Table7-30. REC-1 Dry Weather TMDLs for Fecal Coliform for Baby Beach and Shelter Island Shoreline Park Shoreline Segments

Waterbody	Shoreline Segment/Area	Hydrologic Descriptor	Model Sub-watershed	TMDL (Billion MPN/day)	Load Allocations (LAs)	Wasteload Allocations (WLAs)	Existing Wasteloads	Percent Reduction of Municipal MS4 Existing Wasteload ²
					Natural/Background (Billion MPN/day) ¹	Municipal MS4 (Billion MPN/day)	Municipal MS4 (Billion MPN/day)	
Dana Point Harbor	Baby Beach	Dana Point HSA (901.14)	2101,2102 2103,2104	1,083	1,082	0.17	1.0	82.7%
San Diego Bay	Shelter Island Shoreline Park	Point Loma HA (908.10)	2201	1,380	1,380	0	0	0%

Abbreviations/Acronyms:

TMDL: total maximum daily load
 LA: load allocation for nonpoint source
 WLA: wasteload allocation for point source
 MS4: Municipal Separate Storm Sewer System
 MPN: most probable number

Notes:

¹ Calculated by dry weather EFDC model analysis. No reduction required for natural/background sources.
² Percent Reduction of Existing Municipal MS4 Wasteload = (Existing Municipal MS4 Wasteload – Municipal MS4 WLA) ÷ (Existing Municipal MS4 Wasteload) x 100%

Table7-31. REC-1 Dry Weather TMDLs for *Enterococcus* for Baby Beach and Shelter Island Shoreline Park Shoreline Segments

Waterbody	Shoreline Segment/Area	Hydrologic Descriptor	Model Sub-watershed	TMDL (Billion MPN/day)	Load Allocations (LAs)	Wasteload Allocations (WLAs)	Existing Wasteloads	Percent Reduction of Municipal MS4 Existing Wasteload ²
					Natural/Background (Billion MPN/day) ¹	Municipal MS4 (Billion MPN/day)	Municipal MS4 (Billion MPN/day)	
Dana Point Harbor	Baby Beach	Dana Point HSA (901.14)	2101,2102 2103,2104	187	187	0.03	0.8	96.2%
San Diego Bay	Shelter Island Shoreline Park	Point Loma HA (908.10)	2201	351	351	0	0	0%

Abbreviations/Acronyms:

TMDL: total maximum daily load
 LA: load allocation for nonpoint source
 WLA: wasteload allocation for point source
 MS4: Municipal Separate Storm Sewer System
 MPN: most probable number

Notes:

¹ Calculated by dry weather EFDC model analysis. No reduction required for natural/background sources.
² Percent Reduction of Existing Municipal MS4 Wasteload = (Existing Municipal MS4 Wasteload – Municipal MS4 WLA) ÷ (Existing Municipal MS4 Wasteload) x 100%

TMDL IMPLEMENTATION PLAN

By design, waste load allocations and load allocations are established at levels that when met, will result in the full attainment of water quality standards. For this reason, the San Diego Water Board expects that at the end of the TMDL compliance period, applicable load and waste load allocations, as well as the water quality objectives will be met at all times in the receiving water. In the event that water quality objectives are not met at the end of the compliance period, the Board will require the dischargers to conduct an investigation to identify the specific source(s) responsible for the failure to meet water quality objectives. If the source is found to be anthropogenic, the San Diego Water Board will initiate enforcement or other regulatory action as appropriate to correct the problem. If the source is natural, and if all of the conditions for using the natural sources exclusion approach (NSEA) have been met, the Board will consider the application of the NSEA, including the recalculation of the TMDLs to account for the natural sources. The necessary actions to implement the TMDLs are described in section 10 of the Technical Report entitled *Total Maximum Daily Loads for Indicator Bacteria, Baby Beach in Dana Point Harbor and Shelter Island Shoreline Park in San Diego Bay*, dated June 11, 2008, and listed below.

(A) Specific Implementation Objectives

Since 2002, the dischargers have implemented several non-structural best management practice (BMP) programs and structural BMPs that have resulted in noticeable improvements in water quality at the impaired shoreline segments. The County of Orange has already conducted numerous studies and implemented a variety of non-structural and structural BMPs in an effort to reduce bacteria levels at Baby Beach since before 2002. These efforts have included installing seasonal plugs in storm drains, increased street sweeping efforts, expedited trash collection to control birds, the installation of bird netting under the pier, public education efforts against bird-feeding at the beach, artificial circulation of water at Baby Beach, a dry weather flow diversion structure and media filter system on the west end of the beach, catch basin filters, and the collection and disposal of bird fecal droppings from the exposed intertidal areas of the beach. The San Diego Unified Port District has also implemented several non-structural BMP programs since 2002. Water quality data from 2002 to 2006 indicate that bacteria levels in the waters at Baby Beach and Shelter Island Shoreline Park have shown significant improvements in water quality since 2002.

As shown in Tables 7-26 through 7-31, the modeling results indicate that no load reductions are required for total coliform, fecal coliform, and *Enterococcus* indicator bacteria for Shelter Island Shoreline Park during wet weather or dry weather conditions. Additionally, the modeling results indicate only *Enterococcus* indicator bacteria wet weather load reductions are required for Baby Beach and no wet weather load reductions are required for total coliform and fecal coliform indicator bacteria. For dry weather, Baby Beach requires between approximately 83 percent and 96 percent wasteload reductions for total coliform, fecal coliform, and *Enterococcus* indicator bacteria. However, based only on the water quality data collected during 2006, the number of samples that exceed the REC-1 water quality objectives are less than the allowable number of exceedances for recommending removal from the 303(d) List. This trend implies that the past and current BMPs that have been implemented are effective in reducing bacteria loads to the receiving waters and that water quality in the impaired shoreline segments already meet REC-1 water quality objectives during dry weather. However, additional monitoring is required to confirm this trend, and additional BMPs may be needed to meet the REC-1 water quality objectives during wet weather.

While the Bacteria Load Reduction Plans (BLRPs), as described below, will still be required from the dischargers, if current trends continue, monitoring and permanent implementation of the current programs and BMPs may be adequate for meeting the wet weather and dry weather TMDLs. If the REC-1 water quality objectives cannot be met in the receiving waters by the end of the compliance schedules, and if natural and background sources appear to be the sole source of continued impairment, application of the natural sources exclusion approach (NSEA) to revise the TMDLs, as described below, may be appropriate.²⁵

²⁵ After adoption of a Basin Plan amendment authorizing the use of the Natural Sources Exclusion Approach by the San Diego Water Board and approval by the Office of Administrative Law.

Therefore, if the water quality data support delisting before the NPDES requirement revisions are considered, specific objectives of this Implementation Plan are as follows:

1. Persons responsible for monitoring the impaired shoreline segments of Baby Beach and Shelter Island Shoreline Park for bacteria will continue with the monitoring program to ensure REC-1 water quality objectives are maintained.
2. If REC-1 water quality objectives are exceeded, actions outlined in Attachment B of Order Nos. R9-2007-0001 and R9-2002-0001 in section II.C, Coastal Storm Drain Outfall Monitoring, and any subsequent amendment or renewal, will be implemented.
3. If sources of bacteria persist at levels that exceed water quality standards, then the persons responsible will take appropriate actions to identify and eliminate the controllable source or sources of the chronic contamination. If natural and background sources appear to be the sole source of the impairment, application of the NSEA to revise the TMDLs may be appropriate.

If the impaired shoreline segments of BB and SISP remain on or are put back on the List during subsequent iterations of the 303(d) listing process due to impacts from controllable sources of bacteria, the San Diego Water Board will revise the current NPDES requirements and/or issue additional waste discharge requirements to be consistent with these TMDLs.

(B) San Diego Water Board Actions

The San Diego Water Board regulates discharges of waste by issuing waste discharge prohibitions, waste discharge requirements, or conditional waivers of waste discharge requirements. Violation of a waste discharge prohibition, waste discharge requirement, or waiver condition is subject to enforcement actions. This section describes the actions that the San Diego Water Board will take to implement the TMDLs.

(1) Process and Schedule for Issuing NPDES Requirements

The TMDLs will be implemented primarily by reissuing or revising the existing NPDES waste discharge requirements for MS4 discharges to include water quality based effluent limitations (WQBELs) that are consistent with the assumptions and requirements of the bacteria WLAs for MS4 discharges, though there may be other or new point sources.

NPDES requirements should be issued, reissued, or revised “as expeditiously as practicable” to incorporate WQBELs derived from the TMDL WLAs. “As expeditiously as practicable” means the following:

1. **New point sources.** “New” point sources previously unregulated by NPDES requirements must obtain their NPDES requirements before they can lawfully discharge pollutants. For point sources receiving NPDES requirements for the first time, “as expeditiously as practicable” means that the San Diego Water Board incorporates WQBELs that are consistent with the assumptions and requirements of the WLAs into the NPDES requirements and requires compliance with the WQBELs upon the commencement of the discharge.
2. **Point Sources Currently Regulated Under NPDES Requirements.** For point sources currently regulated under NPDES requirements, “as expeditiously as practicable” means that:
 - a. WQBELs that are consistent with the assumptions and requirements of the WLAs should be incorporated into NPDES requirements during their 5-year term, prior to expiration, in accordance with the applicable NPDES requirement reopening provisions, taking into account factors such as available NPDES resources, staff and budget constraints, and other competing priorities.
 - b. In the event the NPDES requirement revisions cannot be considered during the 5-year term, the San Diego Water Board will incorporate WQBELs that are consistent with the assumptions and requirements of the WLAs into the NPDES requirements at the end of the 5-year term.

(2) Actions with Respect to Phase I Municipal Dischargers

The Phase I Municipal Dischargers in San Diego and Orange County are required under Receiving Water Limitations A.3.a.1 and C.2²⁶ of Orders No. R9-2007-0001 and R9-2002-0001, respectively (San Diego County and Orange County MS4 NPDES requirements), and any subsequent amendment or renewal, to implement additional BMPs to reduce bacteria discharges in impaired watersheds to the maximum extent practicable and to restore compliance with the bacteria water quality objectives. This obligation is triggered when either the discharger or the San Diego Water Board determines that MS4 discharges are causing or contributing to an exceedance of an applicable water quality objective, in this case the REC-1 indicator bacteria water quality objectives. Designation of the shoreline segments in San Diego Bay and Dana Point Harbor as water quality limited segments under Clean Water Act section 303(d) and the TMDL analysis provided sufficient evidence that that MS4 discharges may be causing or contributing to the violation of water quality standards. Thus, the Municipal Dischargers should be, and have been implementing the provisions of Receiving Water Limitation C.2 with respect to bacteria discharges into water quality limited segments.

In addition to enforcing the provisions of Receiving Water Limitation C.2, the San Diego Water Board shall reissue or revise Orders No. R9-2007-0001 and R9-2002-0001, to incorporate WQBELs consistent with the assumptions and requirements of the bacteria WLAs, and requirements for monitoring and reporting. In those orders, the Phase I Municipal Dischargers are referred to as “Copermittees.”²⁷ WQBELs and other requirements implementing the TMDLs can be incorporated into these NPDES requirements upon the normal renewal cycle or sooner, if appropriate. The requirements implementing the TMDLs shall include the following:

- a. WQBELs consistent with the requirements and assumptions of the bacteria WLAs described in Tables 7-26 through 7-31 and a schedule of compliance applicable to the MS4 discharges into the impaired shoreline segments described in Tables 7-32 through 7-34. At a minimum, WQBELs shall include a BMP program to attain the WLAs.
- b. If the WQBELs consist of BMP programs, then the reporting requirements shall consist of annual progress reports on BMP planning, implementation, and effectiveness in attaining the WQOs in impaired shoreline segments, and annual water quality monitoring reports. The first progress report shall consist of a Bacteria Load Reduction Plan (BLRP), which may be included as part of the annual NPDES reporting requirements. BLRPs must be specific to each impaired waterbody.

To provide guidance to the dischargers in preparing BLRPs, the following bullets describe components that should be considered for incorporation in the BLRPs.

Comprehensive Watershed Approach

- Dischargers should identify the Lead Watershed Contact for their BLRPs. The Lead Watershed Contact should serve as liaison between all other common watershed dischargers and the San Diego Water Board, where appropriate.
- Dischargers should describe a program for encouraging collaborative, watershed-based, land-use planning in their jurisdictional plans.

²⁶ Receiving Water Limitations A.3.a.1 and C.2.a provide that “[u]pon a determination by either the Copermittee or the San Diego Water Board that MS4 discharges are causing or contributing to an exceedance of an applicable water quality standard, the Copermittee shall promptly notify and thereafter submit a report to the San Diego Water Board that describes BMPs that are currently being implemented and additional BMPs that will be implemented to prevent or reduce any pollutants that are causing or contributing to the exceedance of water quality standards. The report may be incorporated in the annual update to the Jurisdictional URMP unless the San Diego Water Board directs an earlier submittal. The report shall include an implementation schedule. The San Diego Water Board may require modification to the report.” Additional requirements are included in sections C.2.b-d.

²⁷ Copermittees own or operate MS4s through which urban runoff discharges into waters of the U.S. within the San Diego Region. These MS4s fall into one or more of the following categories: (1) a medium or large MS4 that services a population of greater than 100,000 or 250,000 respectively; or (2) a small MS4 that is “interrelated” to a medium or large MS4; or (3) an MS4 which contributes to a violation of a water quality standard; or (4) an MS4 which is a significant contributor of pollutants to waters of the United States.

- Dischargers should develop and periodically update a map of the BLRP watershed, to facilitate planning, assessment, and collaborative decision-making. As appropriate, the map should include features such as receiving waters; Clean Water Act section 303(d) impaired receiving waters; water quality projects; land uses; MS4s; major highways; jurisdictional boundaries; and inventoried commercial, industrial, and municipal sites.
- Dischargers should annually assess the water quality of the impaired water body in their BLRPs in order to identify all water quality problems within the impaired water body. This assessment should use applicable water quality data, reports, and analysis generated in accordance with the requirements of the applicable NPDES MS4 monitoring and reporting programs, as well as applicable information available from other public and private organizations.
- Dischargers should develop and implement a collective watershed BLRP strategy to meet the bacteria TMDL. The strategy should guide dischargers in developing a Bacteria Compliance Schedule (BCS) which includes BMP planning and scheduling as outlined below.
- Dischargers should collaborate to develop and implement the BLRPs. The BLRP should include a proposal for regularly scheduled meetings among the dischargers in the impaired watershed.
- Because water quality data will ultimately determine if a waterbody will be delisted from the 303(d) List, the BLRP should include a monitoring and reporting program that contains the following elements:
 - Locations of water quality sampling sites that are spatially representative of the waterbody and appropriate for identifying potential sources, including, at a minimum, the monitoring stations currently used to monitor water quality.
 - Schedule of water quality sampling that is temporally representative of both wet weather and dry weather conditions. Wet weather samples are collected during storms of 0.2 inches of rainfall and the 72 hour period after the storm. Dry weather samples are collected from during times when rain has not fallen for the preceding 72 hours.
 - Presentation of past and present water quality data that have been collected.
 - Analysis of water quality data compared to the applicable Basin Plan water quality objectives. Dry weather water quality data are compared to long-term (e.g., geometric mean, mean, or median) water quality objectives, as well as short-term (e.g., single sample maximum) water quality objectives. Wet weather water quality data are compared to short-term (e.g., single sample maximum) water quality objectives.
 - Analysis of water quality data to correlate noticeable improvements in water quality with past and current BMPs that have been implemented and are effective.
 - Analysis of water quality data to correlate elevated bacteria levels with known or suspected sewage spills from wastewater collection systems and treatment plants or boats.
 - Recommendations for increased or decreased water quality sampling based on water quality data analyses.
- Each BLRP and BCS should be reviewed annually to identify needed modifications and improvements. The dischargers should develop and implement a plan and schedule, included in the BCS, to address the identified modifications and improvements. All updates to the BLRP should be documented in the BLRP, and submitted to the San Diego Water Board. Individual dischargers should also review and modify their jurisdictional ordinances and activities as necessary so that they are consistent with the requirements of the BLRP.

Bacteria Compliance Schedule - BMP Planning and Scheduling

The BCS should identify the BMPs/water quality projects that have been implemented or are planned for implementation and provide an implementation schedule for each BMP/water quality project. The BCS should demonstrate how the BMPs/water quality projects will address all the bacteria TMDLs. The BCS, at a minimum, should include scheduling for the following:

Non-structural BMP phasing:

- Completed Non-Structural BMP Analysis – Information should be provided regarding the non-structural BMPs completed and/or currently in practice, a timeline of BMP implementation and maintenance, and an assessment of effectiveness.

If the Completed Non-Structural BMP Analysis indicates additional non-structural BMPs are necessary, the following should be included in the BCS:

- New Non-Structural BMP Analysis - Watershed data should be analyzed to identify new effective non-structural BMPs for implementation. This should be completed and included in the BCS.
- Scheduled Annual Non-structural BMP Implementation - The above analysis should be used to identify BMPs that have and will be implemented and to develop an aggressive non-structural BMP implementation schedule. The BCS should include a schedule of the current BMP staffing for each impaired area, and provide a discussion on adjustments to staff scheduling to meet possible new non-structural BMP demands. Schedules should be realistic and justifiable.
- Scheduled Annual BMP Assessment and Optimizing Adjustments - As the non-structural BMPs are implemented, a scheduled in-depth assessment of the non-structural BMPs' performance should follow. Non-structural BMPs that are found to be ineffective should be modified to incorporate optimizing adjustments to improve performance or be replaced by other effective non-structural BMPs. The results from this assessment should also be used to determine structural BMP selection and the schedule for structural BMP implementation. The BCS should include an annual schedule for in-depth non-structural BMP assessment and optimizing adjustments.
- Scheduled Continuous Budget and Funding Efforts- Securing budget and funding for non-structural BMP staffing and equipment should be scheduled early and continue until the bacteria TMDLs are met. The BCS should include a schedule for staff time, including position and job description, authorized for securing budget and funding for non-structural BMP implementation.

Structural BMP phasing:

- Completed Structural BMP Analysis – Information should be provided regarding the structural BMPs completed and/or currently in practice, a timeline of BMP implementation and maintenance, and an assessment of effectiveness.

If the Completed Structural BMP Analysis indicates additional structural BMPs are necessary, the following should be included in the BCS:

- Scheduled New Structural BMP Analysis– Structural BMP analysis should utilize all available information, including the non-structural BMP assessment and existing structural BMP assessment, to identify, locate, design and build possible new structural BMPs, or a train of BMPs, to meet the these bacteria TMDLs. The BCS should include a schedule for structural BMP analysis.
- Scheduled Annual BMP Construction - The BCS should include a projected general construction schedule with a realistic and justifiable timeline for possible new BMP construction.

- Scheduled Annual BMP Assessment, Optimization Adjustments, and Maintenance - Assessment for structural BMPs should begin immediately upon initial BMP completion, followed by continuously scheduled BMP assessment, optimization adjustments, and maintenance, to both the individual structural BMPs and the structural BMP program as a whole. The BCS should include an annual schedule for in-depth structural BMP assessment.
- Scheduled Continuous Budget and Funding Effort - Securing budget and funding for structural BMPs and additional maintenance staff should be scheduled early and continue until the bacteria TMDLs are met. The BCS should include a schedule for staff time, including position and job description, authorized for securing budget and funding for structural BMP implementation.

Subsequent reports should assess and describe the effectiveness of implementing the Bacteria Load Reduction Plan. Effectiveness assessments should be based on a program effectiveness assessment framework, such as the one developed by the California Stormwater Quality Association (CASQA, 2005). Using the CASQA framework as an example, the assessments should address the framework's outcome levels 1-5 on an annual basis, and outcome level 6 once every five years.²⁸ Methods used for assessing effectiveness should include the following or their equivalent: surveys, pollutant loading estimations, and receiving water quality monitoring. The long-term strategy should also discuss the role of monitoring data in substantiating or refining the assessment. Once water quality objectives have been attained, or the anthropogenic sources have been eliminated and pollutant loads can be attributed to only natural and background sources, a reduced level of monitoring may be appropriate.

In addition to these requirements, if load-based numerical WQBELs are included in the NPDES requirements, the monitoring requirements should include flow and bacteria density measurements to determine if bacteria loads in effluent are in compliance with WQBELs.

The BLRPs are the municipal dischargers' opportunity to propose methods for assessing compliance with WQBELs that implement TMDLs. The monitoring components included in the BLRPs should be formulated according to particular compliance assessment strategies. The monitoring components are expected to be consistent with, and support whichever compliance assessment methods are proposed. The San Diego Water Board will coordinate with the municipal dischargers during the development of their proposed monitoring components and associated compliance assessment methods.

If NPDES requirements are not likely to be issued, reissued or revised within 6 months of Office of Administrative Law approval of these TMDLs, the San Diego Water Board may issue an investigative/monitoring order to dischargers pursuant to sections 13267 or 13383 of the Water Code. This order would require assessment of current BMPs, possible planning for additional BMPs, and receiving water quality monitoring in adherence to performance measures described above.

The BLRPs may be re-evaluated at set intervals (such as 5-year renewal cycles for NPDES requirements, or upon request from named dischargers, as appropriate and in accordance with the San Diego Water Board priorities). Plans may be iterative and adaptive according to assessments and any special studies.

(3) Actions with Respect to Wastewater Collection Systems and Treatment Plants

The San Diego Water Board will conduct surveillance of and enforce the provisions of State Water Board Order No. 2006-0003-DWQ, and San Diego Water Board Order No. R9-2007-0005 as needed to ensure that collection systems for wastewater treatment plants do not overflow, leak, or otherwise discharge into MS4s or surface waters. If necessary, San Diego Water Board Order No. R9-2007-0005 can be revised to require more aggressive collection system monitoring, maintenance, and repair schedules.

²⁸ Outcome level 1 assesses compliance with activity-based permit requirements. Outcome level 2 assesses changes in attitudes, knowledge, and awareness. Outcome level 3 assesses behavioral change and BMP implementation. Outcome level 4 assesses pollutant load reductions. Outcome level 5 assesses changes in urban runoff and discharge water quality. Outcome level 6 assesses changes in receiving water quality. See CASQA "An Introduction to Stormwater Program Effectiveness Assessment."

(4) Actions with Respect to Marinas and Boats

If discharges from boats are shown to be a significant source of bacteria contributing to exceedances of water quality objectives, the San Diego Water Board will enforce the waste discharge prohibitions in the Basin Plan to ensure that illegal discharges from boats to surface waters do not occur. This may require issuing enforcement actions, such as Cease and Desist Orders, or issuing NPDES requirements or waste discharge requirements to the marina and harbor operators and/or the municipalities requiring implementation of BMPs (e.g., public education and outreach, enforcing ordinances, and/or requiring dye tabs in boat sewage holding tanks) to eliminate illegal discharges of sewage, in addition to water quality monitoring and reporting.

(5) Additional Actions

Take Enforcement Actions

The San Diego Water Board shall consider enforcement actions,²⁹ as necessary and appropriate, against any discharger failing to comply with applicable waste discharge requirements or discharge prohibitions. Enforcement actions may be taken, as necessary and appropriate, to control the discharge of bacteria to impaired shorelines to attain compliance with the bacteria WLAs specified in Tables 7-26 through 7-31, or to attain compliance with the applicable water quality objectives.

Recommend High Priority for Grant Funds

The San Diego Water Board shall recommend that the State Water Board assign a high priority to awarding grant funding³⁰ for projects to implement the bacteria TMDLs. Special emphasis will be given to projects that can achieve quantifiable bacteria load reductions consistent with the specific bacteria TMDL WLAs and LAs.

Apply the Natural Sources Exclusion Approach³¹

Under the Natural Sources Exclusion Approach (NSEA), all anthropogenic sources of indicator bacteria to the water bodies subject to an indicator bacteria TMDL must be controlled. Dischargers must also demonstrate that all anthropogenic sources of indicator bacteria to the target water body are controlled and that residual indicator bacteria densities do not indicate a health risk.

Once control of all anthropogenic sources and demonstration of appropriate health risk levels have been achieved, the residual indicator bacteria loads in the waterbodies attributable to uncontrollable sources can be identified and measured. Likewise, the frequency that uncontrollable sources cause exceedances of indicator bacteria water quality objectives in the water body can be identified. The information can be used to establish an allowable indicator bacteria WQO exceedance frequency in the impaired water body based upon the residual exceedance frequency observed. This information can then be used to recalculate the TMDLs, WLAs, and LAs.

²⁹ An enforcement action is any formal or informal action taken to address an incidence of actual or threatened noncompliance with existing regulations or provisions designed to protect water quality. Potential enforcement actions including notices of violation (NOVs), notices to comply (NTCs), imposition of time schedules (TSO), issuance of cease and desist orders (CDOs) and cleanup and abatement orders (CAOs), administrative civil liability (ACL), and referral to the attorney general (AG) or district attorney (DA). The San Diego Water Board generally implements enforcement through an escalating series of actions to: (1) assist cooperative dischargers in achieving compliance; (2) compel compliance for repeat violations and recalcitrant violators; and (3) provide a disincentive for noncompliance.

³⁰ In most cases, the State Water Board administers the awarding of grants funded from Proposition 13, Proposition 50, Clean Water Act section 319(h) and other federal appropriations to projects that can result in measurable improvements in water quality, watershed condition, and/or capacity for effective watershed management. Many of these grant fund programs have specific set-asides for expenditures in the areas of watershed management and TMDL project implementation for non-point source pollution.

³¹ After adoption of a Basin Plan amendment authorizing the use of the Natural Sources Exclusion Approach by the San Diego Water Board and approval by the Office of Administrative Law.

The use of the NSEA is contingent upon demonstration of control of all anthropogenic sources of indicator bacteria to the waterbodies subject to an indicator bacteria TMDL. Since this task is likely to be formidable, use of the NSEA is not expected to occur immediately. Rather, the NSEA would be used to recalculate TMDLs at some point after their initial adoption, following demonstration of control of all anthropogenic sources.

The dischargers are responsible for collecting and providing the data to support the application of the NSEA. If the data support the application of the NSEA, the San Diego Water Board will recalculate the TMDLs, WLAs, and LAs to allow for the exceedances of the REC-1 indicator bacteria WQOs due to uncontrollable sources.

(C) Coordination and Execution of Special Studies

The San Diego Water Board recognizes that coordination and execution of special studies by dischargers and other interested persons could result in improved TMDL analyses that more accurately protect beneficial uses. Areas of study that could benefit TMDL analysis include collection of data that can be used to improve model output, improved understanding of bacteria levels and the relationship to health effects, and identification of an appropriate and affordable method(s) to measure pathogens directly. Additionally, studies designed to measure BMP effectiveness and bacteria source identification will be useful for dischargers in identifying appropriate strategies to meet the requirements of this TMDL.

(1) Collect Data Useful for Model Improvement

Calibration and validation of the computer models used for TMDL analysis was based on limited data (water quality and/or flow) and assumed values for input parameters such as rates for bacteria die-off and re-growth. Limited data are available related to fecal bacteria that can be attributed to natural and background sources (e.g., waterfowl, terrestrial and aquatic wildlife, wrack line and aquatic plants, sediments, and other unidentified and unquantified sources within the waters). Studies designed to collect additional data that can be used for model improvement will result in more detailed TMDL results and allocations. Also, actual flow and loading data from each watershed and expanded receiving water data can be used to construct models that can more accurately reflect site-specific conditions.

(2) Improve Understanding Between Bacteria Levels and Health Effects

The San Diego Water Board recognizes that there are potential problems associated with using indicator bacteria WQOs to indicate the presence of human pathogens in receiving waters free of sewage discharges. The indicator bacteria WQOs were developed, in part, based on epidemiological studies in waters with sewage inputs. The risk of contracting a water-borne illness from contact with urban runoff devoid of sewage, or human-source bacteria is not known. Some pathogens, such as *giardia* and *cryptosporidium* can be contracted from animal hosts. Likewise, domestic animals can pass on human pathogens through their feces. These and other uncertainties need to be addressed through special studies and, as a result, revisions to the TMDLs may be appropriate.

As information is gathered, initiating special studies to understand the uncertainties between bacteria levels and bacteria sources within the watersheds may be useful. Specifically, continuing research may be helpful to answer the following questions:

- What is the risk of illness from swimming in water contaminated with urban/stormwater runoff devoid of sewage?
- Do exceedances of the bacteria water quality objectives from animal sources (wildlife and domestic) increase the risk of illness?
- Are there other, more appropriate surrogates for measuring the risk of illness than the indicator bacteria WQOs currently used?

Addressing these uncertainties is needed to maximize effectiveness of strategies to reduce the risk of illness, which is currently measured by indicator bacteria densities. Dischargers may work with the San Diego Water Board to determine if such special studies are appropriate.

(3) Identification of Method for Direct Pathogen Measurement

Ultimately, the San Diego Water Board supports the idea of measuring pathogens (the agents causing impairment of beneficial uses) or an acceptable alternative indicator, rather than indicator bacteria (surrogates for pathogens). However, as stated previously, indicator bacteria have been used to measure water quality historically because measurement of pathogens is both difficult and costly. The San Diego Water Board is supportive of any efforts by the scientific community to perform epidemiological studies and/or investigate the feasibility of measuring pathogens directly. The San Diego Water Board further supports subsequent modification of WQOs as a result of such studies. Ultimately, TMDLs will be recalculated if WQOs are modified due to results from future studies.

(D) Compliance Schedule

Baby Beach Compliance Schedule

According to Tables 7-26 and 7-27, no wet weather wasteload reductions are required for total and fecal coliform indicator bacteria. This means that according to the wet weather models for Baby Beach, REC-1 water quality objectives for total and fecal coliform indicator bacteria are not expected to be exceeded due to discharges from the MS4s. The only wet weather wasteload reductions required for MS4s discharging into the receiving waters along the shoreline at Baby Beach is for *Enterococcus* indicator bacteria. The compliance schedule for Baby Beach to achieve wet weather TMDLs is as shown in Table 7-32.

Table7-32. Compliance Schedule for Baby Beach to Achieve Wet Weather TMDLs

Year (after OAL Approval)	Required Wasteload Reduction	TMDL Compliance Action
1	No reduction required	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
2	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
3	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
4	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
5	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
6	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
7	50 percent <i>Enterococcus</i> reduction	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
8	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
9	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
10	100 percent <i>Enterococcus</i> reduction	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs ▪ Submit request for removal from 303(d) List (if not requested and removed earlier)
10+	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs ▪ Submit request for TMDL revisions based on Natural Sources Exclusion Approach if supported by data (if not requested and recalculated earlier) ▪ Submit request for removal from 303(d) List (if not requested and removed earlier)

At this time, control of bacteria loads for MS4s during wet weather is inherently difficult because the MS4 systems are traditionally designed to convey water quickly for flood control purposes. However, new approaches to storm water runoff management and BMP implementation can reduce the storm water runoff flow and associated pollutant loads. The phased compliance schedule to achieve wet weather TMDLs will provide the MS4 dischargers time to identify sources, develop plans and implement enhanced and expanded BMPs capable of achieving the mandated decreases in bacteria densities at the Baby Beach shoreline.

According to Tables 7-29, 7-30, and 7-31, dry weather wasteload reductions are required for total coliform, fecal coliform, and Enterococcus indicator bacteria. The trend in the water quality data from Baby Beach indicate that the number of exceedances of the REC-1 water quality objectives have declined significantly beginning in 2006. If the current trend continues, the San Diego Water Board expects that the dry weather TMDLs for Baby Beach can be achieved within the next 5 years. The compliance schedule for Baby Beach to achieve dry weather TMDLs is as shown in Table 7-33.

Table 7-33. Compliance Schedule for Baby Beach to Achieve Dry Weather TMDLs

Year (after OAL Approval)	Required Wasteload Reduction	TMDL Compliance Action
1	No reduction required	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
2	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
3	50 percent reduction	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
4	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs
5	100 percent reduction	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs ▪ Submit request for removal from 303(d) List (if not requested and removed earlier)
5+	Same as above	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs ▪ Submit request for TMDL revisions based on Natural Sources Exclusion Approach if supported by data (if not requested and recalculated earlier) ▪ Submit request for removal from 303(d) List (if not requested and removed earlier)

For both of the Baby Beach compliance schedules, if the REC-1 water quality objectives cannot be met in the receiving waters, and if natural and background sources appear to be the sole source of continued impairment, the natural sources exclusion approach (NSEA) may be applied. However, the Municipal Dischargers are responsible for collecting the data to support the application of the NSEA to recalculate the TMDL.

Shelter Island Shoreline Park Compliance Schedule

According to Tables 7-26 through 7-31, there are no wasteload reductions required for MS4s discharging into the receiving waters along the shoreline at Shelter Island Shoreline Park under both wet weather and dry weather conditions. This means that according to the wet weather and dry weather models for Shelter Island Shoreline Park, REC-1 water quality objectives are not expected to be exceeded due to discharges from the MS4s.

Given that the modeled wasteload reductions for both wet weather and dry weather conditions for all indicator bacteria are zero percent, no compliance schedules were developed to meet wasteload reductions for Shelter Island Shoreline Park. However the existing wasteload cannot exceed the WLA and Shelter Island Shoreline Park will remain on the 303(d) List until enough data are collected to support removing it from the 303(d) List. Therefore, in order to comply with these TMDLs, the responsible municipalities must continue implementing BMPs and collecting data until there are enough data to support and maintain the removal of SISP from the 303(d) List. In addition, the reporting requirements for the Shelter Island Shoreline Park TMDL must also include a periodic demonstration, no less often than every 2 years, that wasteload allocations and water quality objectives are being met.

The trend in the water quality data from Shelter Island Shoreline Park indicate that the number of REC-1 WQO exceedances have declined significantly since 2003. If the current trend continues, the San Diego Water Board expects that Shelter Island Shoreline Park will have enough data to support removal of Shelter Island Shoreline Park from the 303(d) List by 2010, and no later than 2012. The compliance schedule for SISP to achieve wet weather and dry weather TMDLs is as shown in Table 7-34.

Table 7-34. Compliance Schedule for Shelter Island Shoreline Park to Achieve Wet Weather and Dry Weather TMDLs

Year	TMDL Compliance Action
2012	<ul style="list-style-type: none"> ▪ Water Quality Monitoring ▪ Implement BMPs ▪ Submit request for TMDL revisions based on Natural Sources Exclusion Approach if supported by data (if not requested and recalculated earlier) ▪ Submit request for removal from 303(d) List (if not requested and removed earlier)

If the REC-1 water quality objectives cannot be met in the receiving waters by 2012, and if natural and background sources appear to be the source of continued impairment, the NSEA may be applied. However, the Municipal Dischargers are responsible for collecting the data to support the application of the NSEA to recalculate the TMDLs.

(E) TMDL Implementation Milestones

Accomplishing the goals of the implementation plan will be achieved by cooperative participation from all responsible parties, including the San Diego Water Board. Major milestones are described below in Table 7-35.

Table 7-35. TMDL Implementation Milestones

Item	Implementation Action	Responsible Parties	Date
1	Effective date of Baby Beach and Shelter Island Shoreline Park Bacteria TMDL Waste Load Allocations (WLAs).	<ul style="list-style-type: none"> San Diego Water Board Phase I Municipal Dischargers 	Effective date*
2	Issue, reissue, or revise Phase I Municipal NPDES WDRs to include WQBELs consistent with the WLAs.	<ul style="list-style-type: none"> San Diego Water Board 	Within 5 years of effective date
3	Submit annual Progress Report to San Diego Water Board.	<ul style="list-style-type: none"> Phase I Municipal Dischargers 	Annually after reissue of NPDES WDRs
4	Recommend TMDL-related projects as high priority for grant funds.	<ul style="list-style-type: none"> San Diego Water Board 	As needed after effective date
5	Coordination and execution of special studies.	<ul style="list-style-type: none"> San Diego Water Board Phase I Municipal Dischargers 	As needed after effective date
6	Meet 50% wasteload reductions.	<ul style="list-style-type: none"> Baby Beach Phase I Municipal Dischargers 	3 years after effective date for dry weather 7 years after effective date for wet weather
		<ul style="list-style-type: none"> Shelter Island Shoreline Park Phase I Municipal Dischargers 	No load reductions required. Removal from 303(d) List by 2012.
7	Meet 100% wasteload reductions.	<ul style="list-style-type: none"> Baby Beach Phase I Municipal Dischargers 	5 years after effective date for dry weather 10 years after effective date for wet weather
		<ul style="list-style-type: none"> Shelter Island Shoreline Park Phase I Municipal Dischargers 	No load reductions required. Removal from 303(d) List by 2012.
8	Take enforcement actions to attain compliance with the WLAs.	<ul style="list-style-type: none"> San Diego Water Board 	As needed after effective date
9	Issue NPDES requirements or waste discharge requirements to marina and harbor operators and/or the municipalities to eliminate sewage discharges from boats	<ul style="list-style-type: none"> San Diego Water Board 	As needed after effective date
10	Apply NSEA and recalculate TMDLs	<ul style="list-style-type: none"> Baby Beach Phase I Municipal Dischargers 	As appropriate after effective date, if data are available to support the action.
		<ul style="list-style-type: none"> Shelter Island Shoreline Park Phase I Municipal Dischargers 	

* Effective date is date of approval of these TMDLs by the Office of Administrative Law

REVISED TOTAL MAXIMUM DAILY LOADS FOR INDICATOR BACTERIA, PROJECT I – TWENTY BEACHES AND CREEKS IN THE SAN DIEGO REGION (INCLUDING TECOLOTE CREEK)

On February 10, 2010, the San Diego Water Board adopted Resolution No. R9-2010-0001, *A Resolution Amending the Water Quality Control Plan for the San Diego Region (9) to Incorporate Revised Total Maximum Daily Loads for Indicator Bacteria, Project I – Twenty Beaches and Creeks in the San Diego Region (Including Tecolote Creek)* (referred to hereafter as Revised Bacteria TMDLs Project I). The TMDL Basin Plan Amendment was subsequently approved by the State Water Resources Control Board (SWRCB) on December 14, 2010, the Office of Administrative Law on April 4, 2011, and the USEPA on June 22, 2011.

Bacteria TMDLs have been established for the following 20 waterbodies listed on the 2002 Clean Water Act Section 303(d) List of Water Quality Limited Segments:

Table 7-36. Beaches and Creeks Addressed by Revised Bacteria TMDLs Project I

Watershed	Type of Listing	Waterbody Name ^{a,c}	Number of Listings
San Joaquin Hills HSA (901.11)/ Laguna Beach HSA (901.12)	Shoreline	Pacific Ocean Shoreline, San Joaquin Hills HSA ^b	2
	Shoreline	Pacific Ocean Shoreline, Laguna Beach HSA ^b	
Aliso HSA (901.13)	Creek	Aliso Creek	3
	Estuary	Aliso Creek (mouth)	
	Shoreline	Pacific Ocean Shoreline, Aliso HSA ^b	
Dana Point HSA (901.14)	Shoreline	Pacific Ocean Shoreline, Dana Point HSA ^b	1
Lower San Juan HSA (901.27)	Creek	San Juan Creek	3
	Estuary	San Juan Creek (mouth)	
	Shoreline	Pacific Ocean Shoreline, Lower San Juan HSA ^b	
San Clemente HA (901.30)	Shoreline	Pacific Ocean Shoreline, San Clemente HA ^b	1
San Luis Rey HU (903.00)	Shoreline	Pacific Ocean Shoreline, San Luis Rey HU ^b	1
San Marcos HA (904.50)	Shoreline	Pacific Ocean Shoreline, San Marcos HA ^b	1
San Dieguito HU (905.00)	Shoreline	Pacific Ocean Shoreline, San Dieguito HU ^b	1
Miramar Reservoir HA (906.10)	Shoreline	Pacific Ocean Shoreline, Miramar Reservoir HA ^b	1
Scripps HA (906.30)	Shoreline	Pacific Ocean Shoreline, Scripps HA ^b	1
Tecolote HA (906.50)	Creek	Tecolote Creek	1
Mission San Diego HSA (907.11)/ Santee HSA (907.12)	Creek	Forester Creek	3
	Creek	San Diego River (Lower)	
	Shoreline	Pacific Ocean Shoreline, San Diego HU ^b	
Chollas HSA (908.22)	Creek	Chollas Creek.	1
Total Number of Listings on 2002 303(d) List in Revised Bacteria TMDLs Project I			20

Note: HSA = hydrologic subarea; HA = hydrologic area; HU = hydrologic unit

^a Listed as impaired due to exceedances of REC-1 WQOs for fecal coliform, and/or total coliform, and/or enterococci.

^b On the 2002 303(d) List, the Pacific Ocean Shoreline for a HSA, HA, or HU is listed, and specific beaches are noted under the listing. Beginning with the 2008 303(d) List, specific beaches are listed.

^c Listings on the 2006 and 2008 303(d) List compared to listing shown above are provided in Appendix T to the Technical Report.

The TMDLs that have been developed for the Pacific Ocean shorelines are applicable to all the beaches located on the shorelines of the hydrologic subareas (HSAs), hydrologic areas (HAs), and hydrologic units (HUs) listed above. Beginning with the 2008 303(d) List, specific beach segments of the Pacific Ocean shoreline are listed individually. Specific beach segments from some of the Pacific Ocean shorelines listed in the above table have been delisted from the 2008 303(d) list that was approved by the San Diego Board on December 16, 2009, and therefore are not subject to any further action as long as monitoring data continues to support compliance with water quality standards.

PROBLEM STATEMENT

Bacteria densities in the Pacific Ocean at various beach and coastal creek mouth segments (referred to hereafter as “beaches”) exceed water quality objectives (WQOs) for indicator bacteria. Bacteria densities in ocean water at these beaches unreasonably impair and threaten to impair the water quality needed to support the contact water recreation (REC-1)³² designated beneficial use.

Bacteria densities in the waters of Aliso Creek, San Juan Creek, Tecolote Creek, Forrester Creek, the (lower) San Diego River, and Chollas Creek exceed WQOs for indicator bacteria. Bacteria densities in these creeks unreasonably impair and threaten to impair the water quality needed to support REC-1.

The federal Clean Water Act requires the establishment of Total Maximum Daily Loads (TMDLs) for pollutants that exceed the WQOs needed to support designated beneficial uses, i.e., that cause or contribute to exceedances of state “water quality standards.”



Aliso Beach, Orange County

NUMERIC TARGET

When calculating TMDLs, one or more numeric targets are required. Numeric targets are typically selected based on water quality standards, which include beneficial uses and the WQOs that are established at levels sufficient to protect those beneficial uses. The numeric targets for these TMDLs are based primarily on the REC-1 WQOs for indicator bacteria contained in the Ocean Plan and/or Basin Plan.

Different REC-1 WQOs were used as the basis for wet weather³³ and dry weather³⁴ allowable load (i.e., TMDL) calculations because the bacteria transport mechanisms to receiving waters are different under wet and dry weather conditions. Because wet weather conditions, or storm flow, are episodic and short in duration, and characterized by rapid wash-off and transport of high bacteria loads, with short residence times, from all land use types to receiving waters, the single sample maximum WQOs were appropriate for use as wet weather numeric targets. For dry weather conditions, because dry weather runoff is not generated from storm flows, is not uniformly linked to every land use, and is more uniform than stormflow, with lower flows, lower loads, and slower transport, making die-off and/or amplification processes more important, the geometric mean WQOs were appropriate for use as dry weather numeric targets. Wet weather TMDL calculations were based on the REC-1 single sample maximum WQOs while dry weather TMDL calculations were based on REC-1 geometric mean WQOs.

³² Water quality objectives for indicator bacteria in waters with non-water-contact recreation (REC-2) are less stringent than the water quality objectives for REC-1, therefore, attainment of REC-1 objectives through the implementation of TMDLs will, *a fortiori*, provide the requisite water quality for REC-2.

³³ Wet weather days defined as days with rainfall events of 0.2 inches or greater and the following 72 hours.

³⁴ Dry weather days defined as days with less than 0.2 inch of rainfall observed on each of the previous 3 days.

It is not the intent of these TMDLs to require treatment or diversion of natural waterbodies or to require treatment of natural sources of indicator bacteria. The Basin Plan authorizes the use of a reference system and antidegradation approach (RSAA) or natural sources exclusion approach (NSEA) during implementation of indicator bacteria water quality objectives within the context of a TMDL.

For these indicator bacteria TMDLs, the RSAA has been incorporated in the numeric targets as an allowable frequency that the REC-1 WQOs can be exceeded (i.e., allowable exceedance frequency). The purpose of the allowable exceedance frequency is to account for the natural, and largely uncontrollable sources of bacteria (e.g., bird and wildlife feces), which have been shown can, by themselves, cause exceedances of the REC-1 WQOs. The RSAA also incorporates antidegradation principles in that, if water quality is better than that of the reference system in a particular location, no degradation of existing bacteriological water quality is permitted.

Therefore, in addition to the REC-1 WQOs, the numeric targets used to calculate the indicator bacteria TMDLs include an allowable exceedance frequency. The numeric targets used to calculate of the wet weather TMDLs include a 22 percent allowable exceedance frequency of the REC-1 single sample maximum WQOs.³⁵ The numeric targets used to calculate dry weather TMDLs include a zero percent allowable exceedance frequency of the REC-1 geometric mean WQOs.³⁶

The allowable load (i.e., TMDL) that is calculated based on these numeric targets consists of the sum of two parts: 1) the bacteria load that is calculated with the REC-1 WQOs and, 2) the bacteria load that is associated with the allowable exceedance frequency, calculated using the existing load in exceedance of the REC-1 WQOs on the allowable exceedance days. Allowable exceedance days are calculated based on the allowable exceedance frequency and total number of wet days in a year.

Different enterococci REC-1 WQOs were used to calculate TMDLs in watersheds modeled with the inland freshwater creeks (i.e., San Juan Creek, Aliso Creek, Tecolote Creek, Forrester Creek, (lower) San Diego River, and Chollas Creek) and watersheds modeled only with coastal saltwater beaches. The WQOs applicable to ocean waters are provided in the Ocean Plan. The Ocean Plan is applicable only to ocean waters and does not apply to marine bays, estuaries and lagoons. The WQOs applicable to all other surface waters in the San Diego Region (e.g., marine bays, estuaries and lagoons, and freshwater inland surface waters) are contained in the Basin Plan.

There are different enterococci REC-1 WQOs in the Ocean Plan compared to the Basin Plan. Specifically, the Ocean Plan contains REC-1 single sample maximum and 30-day geometric mean WQOs for ocean waters that do not vary. In the Basin Plan, however, the REC-1 single sample maximum WQOs for enterococci are dependent upon the type (e.g., freshwater or saltwater) and usage frequency (e.g., designated beach, moderately or lightly used area, or infrequently used area) of the waterbody, and the REC-1 geometric mean WQOs are dependent of the type (e.g., freshwater or saltwater) of waterbody. The enterococci saltwater REC-1 WQOs in the Basin Plan, for waters designated with "designated beach" usage frequency, are the same as the enterococci REC-1 WQOs in the Ocean Plan.

³⁵ In the calculation of the wet weather TMDLs, the San Diego Regional Board chose to apply the 22 percent allowable exceedance frequency as determined for Leo Carillo Beach in Los Angeles County. At the time the wet weather watershed model was developed, the 22 percent exceedance frequency from Los Angeles County was the only reference beach exceedance frequency available. The 22 percent allowable exceedance frequency used to calculate the wet weather TMDLs is justified because the San Diego Region watersheds' exceedance frequencies will likely be close to the value calculated for Leo Carillo Beach, and is consistent with the exceedance frequency that was applied by the Los Angeles Regional Board.

³⁶ Available water quality data from San Diego Region reference systems indicate that exceedances of the single sample WQOs during dry weather conditions are uncommon. Furthermore, if the exceedance of the single sample WQOs during dry weather is unlikely, exceedances of the geometric mean are even more unlikely.

For the application of the Basin Plan's enterococci REC-1 WQOs, unless otherwise specified in the Basin Plan, all waterbodies in the San Diego Region designated with REC-1 beneficial use are assumed to have a "designated beach" usage frequency. The "designated beach" usage frequency has the lowest and most stringent enterococci REC-1 WQOs in the Basin Plan. The enterococci REC-1 single sample maximum WQOs in the Basin Plan are more stringent for freshwater (61 MPN/100mL) than for saltwater (104 MPN/100mL) waterbodies. The enterococci REC-1 geometric mean WQOs in the Basin Plan are also more stringent for freshwater (33 MPN/100mL) than for saltwater (35 MPN/100mL) waterbodies. Since coastal saltwater beaches are downstream of inland freshwater creeks, TMDLs for coastal saltwater beaches are calculated using the more conservative enterococci REC-1 WQOs applicable to freshwater creeks (i.e., 61 MPN/100mL and 33 MPN/100mL). The numeric targets used in the calculation of the TMDLs for Tecolote Creek and Chollas Creek are also based on the enterococci REC-1 WQOs applicable to freshwater creeks.

In some cases, the "designated beach" category may be over-protective of water quality because of the infrequent recreational use in the impaired freshwater creeks. The recreational usage frequency in these freshwater creeks may correspond to the "moderately to lightly used areas" category, which has an enterococci freshwater REC-1 single sample maximum WQO of 108 MPN/100mL. In such cases, the "designated beach" enterococci saltwater REC-1 single sample maximum WQO (104 MPN/100mL) would also be protective of the "moderately to lightly used area" freshwater creek.

Before the less stringent enterococci single sample maximum saltwater REC-1 WQO may be applied to a freshwater creek, the Basin Plan must be amended to designate a lower usage frequency (i.e., "moderately to lightly used area") for each freshwater creek. If information and evidence are provided to justify the "moderately to lightly used area" usage frequency for a freshwater creek, and the designated usage frequency of the freshwater creek is amended to "moderately to lightly used area" in the Basin Plan, the wet weather TMDLs that were calculated in a watershed that was modeled with a freshwater creek using the enterococci saltwater REC-1 WQOs can be implemented instead.

The numeric targets for the scenarios described above are summarized in the following tables.

Table 7-37. Wet Weather Numeric Targets

Indicator Bacteria	Numeric Target (MPN/100mL)	Allowable Exceedance Frequency ^a
Fecal coliform	400 ^b	22%
Total coliform	10,000 ^c	22%
Enterococci	104 ^d / 61 ^e	22%

- a. Percent of wet days (i.e., rainfall events of 0.2 inches or greater and the following 72 hours) allowed to exceed the wet weather numeric targets. Exceedance frequency based on reference system in the Los Angeles Region.
- b. Fecal coliform single sample maximum WQO for REC-1 use in creeks and at beaches.
- c. Total coliform single sample maximum WQO for REC-1 use at beaches and the point in creeks that discharges to beaches.
- d. Enterococci single sample maximum WQO for REC-1 use in creeks established and designated as “moderately or lightly used” in the Basin Plan and at beaches downstream of those creeks, as well as all other beaches.
- e. Enterococci single sample maximum WQO for REC-1 use in creeks not established and designated as “moderately or lightly used” in the Basin Plan and at beaches downstream of those creeks (“designated beach” frequency of use; applicable to San Juan Creek and downstream beach, Aliso Creek and downstream beach, Tecolote Creek, Forrester Creek, San Diego River and downstream beach, and Chollas Creek).

Table 7-38. Dry Weather Numeric Targets

Indicator Bacteria	Numeric Target (MPN/100mL)	Allowable Exceedance Frequency ^a
Fecal coliform	200 ^b	0%
Total coliform	1,000 ^c	0%
Enterococci	35 ^d / 33 ^e	0%

- a. Percent of dry days (i.e., days with less than 0.2 inch of rainfall observed on each of the previous 3 days) allowed to exceed the dry weather numeric targets.
- b. Fecal coliform 30-day geometric mean WQO for REC-1 use in creeks and at beaches.
- c. Total coliform 30-day geometric mean WQO for REC-1 at beaches and the point in creeks that discharges to beaches.
- d. Enterococci 30-day geometric mean WQO for REC-1 at beaches.
- e. Enterococci 30-day geometric mean WQO for REC-1 use in impaired creeks and beaches downstream of those creeks (applicable to San Juan Creek and downstream beach, Aliso Creek and downstream beach, Tecolote Creek, Forrester Creek, San Diego River and downstream beach, and Chollas Creek).

SOURCE ANALYSIS

Sources of bacteria are the same under both wet weather and dry weather conditions. Bacteria build up on the land surface as a result of various anthropogenic land uses (e.g., urban development and agriculture) and natural processes (e.g., birds and wildlife). Bacteria are washed off the land surface by surface runoff. In urban areas, bacteria are washed off the land surface by dry weather and wet weather flows and transported through pipes and conveyance channels of the municipal separate storm sewer systems (MS4s) to surface waters. Other significant point sources of bacteria include municipal wastewater treatment plants and industrial waste treatment facilities. In rural and undeveloped areas, bacteria are washed off the land surface primarily by wet weather flows directly to surface waters. Discharges from rural areas are typically considered nonpoint sources. These diffuse nonpoint sources (e.g., undeveloped land, agriculture, livestock, and horse ranch facilities) have multiple routes of entry into surface waters.

Nonpoint sources were separated into controllable and uncontrollable categories. Controllable nonpoint sources are identified by land use types and coverages. Controllable nonpoint sources include land uses associated with agriculture, dairy/intensive livestock, and horse ranches (collectively referred to as agriculture land uses). These were considered controllable because the land uses are anthropogenic in nature, and load reductions can be reasonably expected with the implementation of suitable management measures. Uncontrollable nonpoint sources include loads from open recreation, open space, and water land uses (collectively referred to as open space land uses). Loads from these areas are considered uncontrollable because they come from mostly natural sources (e.g. bird and wildlife feces).

In order to quantify bacteria loading from these various sources and transport mechanisms, 13 land-use types were identified in the TMDL analysis: Low Density Residential, High Density Residential, Commercial/Institutional, Industrial/Transportation, Military, Parks/Recreation, Open Recreation, Agriculture, Dairy/Intensive Livestock, Horse Ranches, Open Space, Water, and Transitional (Construction Activities). In the technical TMDL analysis, the 13 land use types were grouped into the following four land use categories: 1) owners/operators of municipal separate storm sewers (Municipal MS4s); 2) Caltrans (separated from other Municipal MS4s); 3) Agriculture; and 4) Open Space. Bacteria loads discharged from Low Density Residential, High Density Residential, Commercial/Institutional, Industrial/Transportation, Military, Parks/Recreation, and Transitional land use types are included in the Municipal MS4s category, which is considered a controllable point source. Bacteria loads discharged from the Industrial/Transportation land use type associated with Caltrans were separated into the Caltrans category, which is considered a controllable point source. Bacteria loads discharged from Agriculture, Dairy/Intensive Livestock, and Horse Ranch land use types are included in the Agriculture category, which is considered a controllable nonpoint source. Bacteria loads discharged from Open Recreation, Open Space, and Water land use types are included in the Open Space category, which is associated with natural and undeveloped areas and considered an uncontrollable nonpoint source.

CRITICAL CONDITIONS

The critical conditions are a set of environmental conditions for which controls designed to protect water quality will ensure attainment of the numeric targets for all other conditions. The critical conditions include the location and the period of time in which the waterbody is expected to exhibit the highest vulnerability.

To ensure that numeric targets are met throughout the impaired waterbodies, a critical location consisting of a node at the base of the watershed as it discharges to the ocean or bay was used as the point where the allowable load (i.e., TMDL) is calculated. A critical period associated with extreme rainfall conditions (i.e., critical wet year), and thus the highest potential bacteria load at the critical location, was selected for watershed modeling analysis. The year 1993 was selected as the critical wet period for assessment of extreme wet weather loading conditions because this year was the wettest year of the 12 years of record (1990 through 2002).

LINKAGE ANALYSIS

The purpose of the linkage analysis is to quantify the “existing” bacteria loads that are currently generated by the pollutant sources in the watershed under the critical conditions, and quantify the maximum allowable bacteria loading to each impaired waterbody that will result in attainment of numeric targets under the same critical conditions. This maximum allowable bacteria loading is, in other words, the TMDL.

The linkage analysis used mathematical modeling approaches to quantify the “existing” and allowable bacteria loadings for each impaired waterbody. Separate modeling approaches were used for the calculation of the wet weather TMDLs and dry weather TMDLs.

For the calculation of the wet weather TMDLs, the wet weather modeling approach chosen for the linkage analysis is based on the application of the USEPA's Loading Simulation Program in C++ (LSPC) model to estimate bacteria loading from streams and assimilation within the waterbodies. LSPC is a recoded C++ version of the USEPA's Hydrological Simulation Program-FORTRAN (HSPF) that relies on fundamental (and USEPA-approved) algorithms. In the wet weather linkage analysis, it is assumed that storm water flows wash off bacteria loads from the surface of all 13 land use types into the receiving waters. The LSPC model was used to predict flows and bacteria densities at the critical location during the wet days of the critical wet year, which were used to calculate the mass-based annual existing wet weather bacteria loads. The LSPC model-predicted wet weather flows at the critical location during the wet days of the critical wet year in combination with the numeric targets were used to calculate the mass-based annual allowable wet weather bacteria loads, or mass-based wet weather TMDLs.

For the calculation of the dry weather TMDLs, the dry weather modeling approach chosen for the linkage analysis consists of a steady-state mass balance model that was developed to simulate transport of bacteria in the impaired creeks and the creeks flowing to impaired shorelines. This predictive model represents the streams as a series of plug-flow reactors, with each reactor having a constant, steady-state flow and bacteria load. In the dry weather linkage analysis, it is assumed that dry weather non-storm water flows generated by anthropogenic activities wash off bacteria loads from the surface of specific land use types into the receiving waters. The dry weather steady-state model was used to predict flows and bacteria densities at the critical location during the dry weather days of the critical wet year, which were used to calculate the mass-based monthly existing dry weather bacteria loads. The dry weather steady-state model-predicted flows at the critical location during the dry days of the critical wet year in combination with the dry weather numeric targets were used to calculate the mass-based monthly allowable dry weather bacteria loads, or mass-based dry weather TMDLs.

TOTAL MAXIMUM DAILY LOADS AND ALLOCATIONS

TMDLs can be expressed as mass per time (i.e., mass-loading basis), or other appropriate measure (e.g., as a concentration).³⁷ For these TMDLs, the wet weather and dry weather TMDLs are expressed both in terms of concentration and on a mass loading basis. The concentration based TMDLs will be used to determine compliance with the TMDLs in the receiving waters. Mass-load based TMDLs were calculated for the impaired waterbodies in each watershed. The mass-load based TMDLs were allocated to the identified point and nonpoint sources and used to identify the controllable sources that need to reduce their bacteria loads in order for the concentration based TMDLs to be met in the receiving waters. The concentration based TMDLs, mass-load based TMDLs, and allocations are discussed below.

(1) Concentration Based TMDLs

The wet weather and dry weather concentration based TMDLs are based on meeting the numeric targets (i.e., numeric WQOs and allowable exceedance frequencies) in the receiving waters. The numeric WQOs for REC-1 beneficial uses are the basis of the numeric targets used to calculate the TMDLs, expressed as number of bacteria colonies per volume. An allowable exceedance frequency is included as part of the numeric target to allow for exceedances that may be caused by natural sources, based on a reference system. Tables 7-39 and 7-40 summarize the concentration based TMDLs, which are expressed as numeric objectives and allowable exceedance frequencies in the receiving waters for each watershed, for wet weather and dry weather, respectively. Meeting the concentration based TMDLs in the receiving waters will be used to determine compliance with the TMDLs.

³⁷ Code of Federal Regulations Title 40 section 130.2(1) [40CFR130.2(i)]

(2) Mass-Load Based TMDLs

The numeric targets were used to calculate the TMDLs on a mass loading basis under a set of critical conditions. The TMDLs that were calculated in terms of mass loading were used to identify the bacteria loads from controllable sources that need to be reduced in order for the numeric targets to be met in the receiving waters.

On a mass loading basis, TMDLs are defined as the maximum mass of a pollutant the waterbody can receive and still protect the designated beneficial uses. Separate mass-load based TMDLs were calculated for wet weather and dry weather conditions to account for seasonal variations, and because the transport mechanism, flow, and bacteria loads are different between dry and wet weather conditions.

On a mass-loading basis, the TMDLs are expressed as number of bacteria colonies per unit time. The wet weather mass-load based TMDLs are expressed as “annual loads” in terms of number of bacteria colonies per year (billion MPN/yr). The dry weather mass-load based TMDLs are expressed as “monthly loads” in terms of number of bacteria colonies per month (billion MPN/mth). In order for bacteria loading to be calculated, both flow rates and bacteria densities must be measured at a point in time and location. When multiplied together, these two parameters result in bacteria mass loading, or the number of bacteria colonies measured per unit time.

$$\text{Bacteria Loading} = \text{flow rate (volume / time)} \times \text{bacteria density (number of colonies / volume)}$$

Calibrated models were used to simulate flow and bacteria densities. This information was used to calculate the “existing” mass of bacteria loads to, and allowable mass of bacteria loads (i.e., mass-load based TMDLs) for, each impaired segment under critical conditions (i.e., worst case loading conditions). The existing mass loads that were calculated represent the worst case flows and bacteria densities that are expected from the watershed during the critical wet year. The mass-load based TMDLs were calculated with the numeric targets and modeled flows expected during the critical wet year. Existing mass loads were compared to the mass-load based TMDLs. The difference between the existing mass loads and the mass-load based TMDLs is the load reduction required to meet the REC-1 WQOs and allowable exceedance frequencies in the receiving water.

Existing mass loads and mass-load based TMDLs were calculated for wet weather and dry weather. The calculation of the mass-load based TMDLs included the use of an allowable exceedance frequency of the REC-1 WQOs. The purpose of the exceedance frequency is to account for the natural, and largely uncontrollable sources of bacteria (e.g., bird and wildlife feces) generated in the watersheds and at the beaches, which can, by themselves, cause exceedances of WQOs.

All of the wet weather mass-load based TMDLs were calculated using a 22 percent allowable exceedance frequency.³⁸ All of the dry weather mass-load based TMDLs were calculated using a 0 percent allowable exceedance frequency. These allowable exceedance frequencies were used to calculate the number of wet and dry weather allowable exceedance days during the critical wet year.

³⁸ In the calculation of the wet weather TMDLs, the San Diego Regional Board chose to apply the 22 percent allowable exceedance frequency as determined for Leo Carillo Beach in Los Angeles County. At the time the wet weather watershed model was developed, the 22 percent exceedance frequency from Los Angeles County was the only reference beach exceedance frequency available. The 22 percent allowable exceedance frequency used to calculate the wet weather TMDLs is justified because the San Diego Region watersheds' exceedance frequencies will likely be close to the value calculated for Leo Carillo Beach, and is consistent with the exceedance frequency that was applied by the Los Angeles Regional Board.

The mass-load based TMDLs are calculated as the sum of the allowable load associated with the numeric REC-1 WQO and the allowable load associated with the allowable exceedance frequency during the critical wet year. Tables 7-39 and 7-40 summarize the calculated existing bacteria mass loads, allowable mass loads based on the numeric REC-1 WQOs, allowable exceedance frequencies and days, allowable mass loads based on the allowable exceedance frequencies, and mass-load based TMDLs for each watershed, for wet weather and dry weather, respectively.

(3) Allocation of Mass-Load Based TMDLs

The mass-load based TMDLs were allocated among point sources (WLAs) and nonpoint sources (LAs) in each watershed. WLAs were assigned to discharges originating from urban land use areas (i.e., MS4s and Caltrans), all of which are considered controllable. LAs were assigned to discharges from rural and undeveloped land use areas (i.e., Agriculture and Open Space). Discharges from rural and undeveloped land use areas are separated into controllable and uncontrollable nonpoint sources. Agricultural land uses (e.g., agriculture, horse ranches, and intensive livestock) are considered controllable nonpoint source land use areas. Open space land uses (e.g., open space and open recreation) are considered uncontrollable nonpoint source land use areas.

Sources that are not identified are assumed to be assigned a zero allowable load as part of the mass-load based TMDL (i.e., WLA = 0 or LA = 0). In other words, discharges of pollutant loads from these sources are not allowed as part of the TMDLs. Sources that are assigned an allowable mass load equal to the existing mass load (i.e., WLA or LA = existing mass load) are not allowed to increase their pollutant loads over time.

Allocations of the mass-load based TMDLs were different for wet weather TMDLs and dry weather TMDLs, as discussed below.

(A) Wet Weather TMDL Allocations

The wet weather mass-load based TMDLs were divided and assigned to point sources as WLAs and nonpoint sources as LAs based on land uses. The portions of the wet weather mass-load based TMDLs assigned to WLAs and LAs were calculated based on the percent of the TMDL mass load generated by the urban, rural, and undeveloped land uses in each watershed as determined by the wet weather models under critical conditions.

The allocation of the wet weather mass-load based TMDLs assumes surface runoff discharge occurs from all land use categories, and allocated according to the following steps:

- 1) Sources are separated into controllable and uncontrollable sources. Discharges from Municipal MS4, Caltrans, and Agriculture land use categories are assumed to be controllable (i.e., subject to regulation), and discharges from Open Space land use categories are assumed to be uncontrollable (i.e., not subject to regulation).
- 2) Because discharges from Open Space land use categories are uncontrollable (i.e., not subject to regulation), the LAs for Open Space land use categories are set equal to the existing mass loads calculated under the critical conditions.
- 3) For discharges from controllable land use categories that do not contribute more than 5 percent of the total existing mass load for all three indicator bacteria, the WLA or LA is set equal to the existing mass loads from those land uses calculated under the critical conditions.
- 4) After the WLAs and LAs are assigned based on steps 2 and 3, the remaining portion of the mass-load based TMDL is assigned to discharges from controllable land use categories that contribute more than 5 percent of the total existing mass load for all three indicator bacteria. The allowable mass load for each source (WLA or LA) is calculated based on the ratio of the existing mass loads from those sources relative to each other.

The total watershed wet weather existing mass loads and mass-load based TMDLs, point source existing mass loads and mass-load based WLAs, nonpoint source existing mass loads and mass-load based LAs, and load reductions required to achieve the mass-load based TMDLs, WLAs, and LAs are shown below in Tables 7-41, 7-42 and 7-43.

In comments, the municipal dischargers pointed out that, for the impaired creeks, the “designated beach” usage frequency WQO for enterococci may be over-protective of water quality because of the infrequent recreational use in the impaired creeks. The dischargers claim that the recreational usage frequency in these inland freshwater creeks more likely corresponds to the “moderately to lightly used area” category in the Basin Plan, which has an enterococci WQO of 108 MPN/100mL. In these cases, using a less stringent numeric target, based on the saltwater enterococci WQO of 104 MPN/100 mL (“designated beaches” usage frequency) would result in wet weather TMDLs protective of REC-1 uses in the inland freshwater creeks and at the downstream coastal saltwater beaches.³⁹ Therefore, the “moderately to lightly used area” usage frequency may be appropriate for the six impaired creeks, and the enterococci saltwater REC-1 single sample maximum WQO of 104 MPN/100 mL could be used as basis of the numeric target for the enterococci wet weather TMDLs.

The six creeks included in these TMDLs, however, have not been designated in the Basin Plan as “moderately to lightly used area” waterbodies as of the adoption of these TMDLs. If the Basin Plan does not specify the usage frequency of a waterbody, the most stringent and conservative WQOs are appropriate and applicable. For enterococci, the most stringent and conservative WQOs for the freshwater creeks are associated with the “designated beach” usage frequency and freshwater waterbody type. Thus, the enterococci WQOs associated with the freshwater “designated beach” usage frequency are applicable until sufficient evidence is provided to warrant an amendment to the Basin Plan that designates a lower usage frequency to one or more of the six creeks addressed by these TMDLs (San Juan Creek, Aliso Creek, Tecolote Creek, Forrester Creek, San Diego River, and Chollas Creek).

According to the federal regulations,⁴⁰ usage frequencies are defined as follows:

- Designated Beach Area: those recreation waters that, during the recreation season, are heavily used (based upon a comparison of use within the state) and may have a lifeguard, bathhouse facilities, or public parking for beach access. States may include any other waters in this category even if the waters do not meet these criteria.
- Moderate Full Body Contact Recreation: those recreation waters that are not designated bathing beach waters but typically, during the recreation season, are used by at least half of the number of people as at typical designated bathing beach waters within the state. States may also include light use or infrequent use coastal recreation waters in this category.
- Lightly Used Full Body Contact Recreation: those recreation waters that are not designated bathing beach waters but typically, during the recreation season, are used by less than half of the number of people as at typical designated bathing beach waters within the state, but are more than infrequently used. States may also include infrequent use coastal recreation waters in this category.

³⁹ The enterococci WQOs in the Basin Plan are structured to reflect the frequency of recreational use. The enterococci freshwater REC-1 single sample maximum WQO for a “designated beach” area is 61 MPN/100 mL. For a “moderately or lightly used area,” the REC-1 single sample maximum WQO is 108 MPN/100 mL. The saltwater REC-1 single sample maximum WQO for “designated beach” area is 104 MPN/100 mL. Where the “moderately or lightly used area” designation is appropriate for creeks, the saltwater REC-1 single sample maximum WQO of 104 MPN/100 mL could be used as the numeric target because it is also protective of both the freshwater creek and the downstream marine beach.

⁴⁰ Code of Federal Regulations Title 40 section 131.41 [40CFR131.41]

- Infrequently Used Full Body Contact: those recreation waters that are rarely or occasionally used.

If sufficient evidence can be provided to the San Diego Water Board that can demonstrate the usage frequency for one or more of the six impaired creeks falls under the “Lightly Used Full Body Contact Recreation” or “Infrequently Used Full Body Contact” usage frequency, the Basin Plan may be amended to designate one or more of the creeks with the “moderately to lightly used area” usage frequency.

If one or more of the six creeks (San Juan Creek, Aliso Creek, Tecolote Creek, Forrester Creek, San Diego River, and/or Chollas Creek) are designated in the Basin Plan with the “moderately to lightly used area” usage frequency, the enterococci wet weather TMDLs, WLAs, and LAs based on the 104 MPN/100mL (Table 7-44) can be implemented. Otherwise, the more stringent and conservative enterococci wet weather TMDLs, WLAs, and LAs based on the freshwater “designated beach” usage frequency WQO of 61 MPN/100mL (Table 7-43) must be implemented.

(B) Dry Weather TMDL Allocations

The dry weather mass-load based TMDLs were assigned entirely to discharges from MS4 land uses because the runoff that transports bacteria loads to surface waters during dry weather are expected to occur only in urban areas. The allocation of the dry weather mass-load based TMDLs assumes that no surface runoff discharge to receiving waters occurs from Caltrans, Agriculture, or Open Space land use categories (i.e., $WLA_{Caltrans} = 0$, $LA_{Agriculture} = 0$, and $LA_{OpenSpace} = 0$), meaning the entire dry weather mass-load based TMDL (i.e., allowable mass load) is allocated to Municipal MS4 land use categories (i.e., $WLA_{MS4} = TMDL$).

The total watershed dry weather existing mass loads and mass-load based TMDLs, point source existing mass loads and mass-load based WLAs, nonpoint source existing mass loads and mass-load based LAs, and load reductions required to achieve the mass-load based TMDLs, WLAs, and LAs are shown below in Tables 7-45, 7-46, and 7-47.

Because the wet weather and dry weather modeling approaches used to calculate the mass-load based TMDLs, WLAs, LAs, and existing mass wasteloads and loads were based on critical conditions (i.e., worst case loading scenario), the mass-loading numbers (i.e., existing mass loads, and mass-load based TMDLs, WLAs, and LAs expressed in terms of billion MPN/year for wet weather and billion MPN/month for dry weather) presented in Tables 7-39 through 7-47 represent conservative mass-load estimates expected to be protective of the beneficial uses under extreme conditions. The mass-loading numbers also provide a tool for identifying bacteria sources that need to be controlled and existing bacteria loads that need to be reduced to meet the TMDLs in the receiving waters.

Ultimately, controllable point and nonpoint sources must reduce their anthropogenic loads so the concentration based wet weather and dry weather TMDLs, which are based on the numeric REC-1 WQOs in the Basin Plan and allowable exceedance frequencies, can be met during wet weather and dry weather conditions during each year. Meeting the wet weather and dry weather numeric targets in the discharge and/or receiving water will indicate the TMDLs, WLAs, and/or LAs have been met.

MARGIN OF SAFETY

The numeric targets used for the mass-load based and concentration based TMDLs are assumed to be conservative by utilizing the most stringent REC-1 WQOs contained in the Ocean Plan and/or Basin Plan. Additionally, the mass-load based TMDLs were calculated under a set of critical conditions that assumed the highest potential mass loading would occur at a critical point during a critical wet year, which is expected to be protective of beneficial uses during extreme conditions. The conservative assumptions that were used result in conservative mass-load based and concentration based TMDLs that are expected to restore and protect the beneficial uses of the receiving waters.

Because bacteria in wet weather runoff and streamflows have a quick travel time, and therefore, a short residence time in the waterbodies, the REC-1 single-sample maximum WQOs were determined to be most appropriate for calculating the wet weather TMDLs. The numeric targets used for the wet weather mass-load based and concentration based TMDLs are assumed to be conservative by utilizing the most stringent REC-1 single sample maximum WQOs contained in the Ocean Plan and/or Basin Plan.

Because dry weather conditions have flows and bacteria loads much smaller in magnitude than wet weather conditions, do not occur from all land use types, and are more uniform than stormflow, the REC-1 30-day geometric mean WQOs were determined to be most appropriate for the dry weather TMDLs. The numeric targets used for the dry weather mass-load based and concentration based TMDLs are assumed to be conservative by utilizing the most stringent REC-1 30 day geometric mean WQOs contained in the Ocean Plan and/or Basin Plan.

Because of the numeric targets and critical conditions that were included in the calculation of the TMDLs, there was no explicit margin of safety included. Instead, the TMDLs include an implicit margin of safety (MOS). The implicit MOS is included via conservative estimates and assumptions (meaning worst-case scenarios were assumed in terms of existing bacteria loading) throughout the calculations and not as a separate, additional factor.

Table 7-39. Summary of Wet Weather Existing and Allowable Indicator Bacteria Loads

Watershed - Impaired Waterbody	Indicator Bacteria	Existing Bacteria Load (Billion MPN/year)	Single Sample Maximum Objective (MPN/100mL)	Allowable Numeric Objective Load (Billion MPN/year)	Total Wet Days in Critical Year	Allowable Exceedance Frequency	Allowable Wet Exceedance Days in Critical Year	Allowable Exceedance Load (Billion MPN/year)	Total Allowable Load [=TMDL] (Billion MPN/year)
San Joaquin Hills HSA (901.11) and Laguna Hills HSA (901.12) - Pacific Ocean Shoreline	Fecal Coliform	705,015	400	16,043	69	22%	15	648,591	664,634
	Total Coliform	8,221,901	10,000	401,049				7,044,601	7,445,649
	Enterococcus	852,649	104	4,175				778,624	782,799
Aliso HSA (901.13) - Pacific Ocean Shoreline - Aliso Creek - Aliso Creek mouth	Fecal Coliform	1,752,096	400	84,562	69	22%	15	1,494,512	1,579,073
	Total Coliform	23,210,774	10,000	2,109,600				18,081,198	20,190,798
	Enterococcus	2,230,206	104*	22,682				1,929,834	1,952,517
		2,230,206	61	13,644				1,937,321	1,950,964
Dana Point HSA (901.14) - Pacific Ocean Shoreline	Fecal Coliform	403,911	400	14,894	69	22%	15	362,419	377,313
	Total Coliform	6,546,962	10,000	372,328				5,659,144	6,031,472
	Enterococcus	501,526	104	3,875				458,431	462,306
Lower San Juan HSA (901.27) - Pacific Ocean Shoreline - San Juan Creek - San Juan Creek mouth	Fecal Coliform	15,304,790	400	358,410	76	22%	17	14,356,423	14,714,833
	Total Coliform	130,258,863	10,000	8,947,114				113,932,076	122,879,189
	Enterococcus	12,980,098	104*	95,357				12,063,781	12,159,138
		12,980,098	61	56,119				12,096,327	12,152,446
San Clemente HA (901.30) - Pacific Ocean Shoreline	Fecal Coliform	1,441,723	400	36,481	73	22%	16	1,342,450	1,378,931
	Total Coliform	16,236,606	10,000	911,994				14,235,609	15,147,603
	Enterococcus	1,663,100	104	9,491				1,553,696	1,563,187
San Luis Rey HU (903.00) - Pacific Ocean Shoreline	Fecal Coliform	33,120,012	400	640,595	90	22%	20	31,803,647	32,444,242
	Total Coliform	231,598,677	10,000	15,993,384				208,157,151	224,150,535
	Enterococcus	18,439,920	104	167,152				17,296,466	17,463,618
San Marcos HA (904.50) - Pacific Ocean Shoreline	Fecal Coliform	20,886	400	1,559	49	22%	11	15,665	17,224
	Total Coliform	515,278	10,000	38,984				386,099	425,083
	Enterococcus	40,558	104	406				32,559	32,966
San Dieguito HU (905.00) - Pacific Ocean Shoreline	Fecal Coliform	21,286,910	400	425,968	98	22%	22	20,675,680	21,101,649
	Total Coliform	163,541,133	10,000	10,637,225				149,176,959	159,814,184
	Enterococcus	14,796,210	104	113,253				14,193,834	14,307,087
Miramar Reservoir HA (906.10) - Pacific Ocean Shoreline	Fecal Coliform	10,392	400	312	94	22%	21	9,943	10,256
	Total Coliform	212,986	10,000	7,809				202,371	210,180
	Enterococcus	11,564	104	81				11,323	11,405

Table 7-39. Summary of Wet Weather Existing and Allowable Indicator Bacteria Loads (Cont'd)

Watershed - Impaired Waterbody	Indicator Bacteria	Existing Bacteria Load (Billion MPN/year)	Single Sample Maximum Objective (MPN/100mL)	Allowable Numeric Objective Load (Billion MPN/year)	Total Wet Days in Critical Year	Allowable Exceedance Frequency	Allowable Wet Exceedance Days in Critical Year	Allowable Exceedance Load (Billion MPN/year)	Total Allowable Load [=TMDL] (Billion MPN/year)
Scripps HA (906.30) - Pacific Ocean Shoreline	Fecal Coliform	204,057	400	10,329	57	22%	13	166,578	176,907
	Total Coliform	5,029,519	10,000	258,228				4,098,745	4,356,973
	Enterococcus	377,839	104	2,686				321,347	324,032
Tecolote HA (906.50) - Tecolote Creek	Fecal Coliform	261,966	400	25,080	57	22%	13	204,241	229,322
	Total Coliform	7,395,789	10,000	626,414				5,753,355	6,379,770
	Enterococcus	708,256	104*	6,522				597,659	604,180
		708,256	61	3,825				599,936	603,761
Mission San Diego HSA (907.11) and Santee HSA (907.12) - Forrester Creek - San Diego River (lower) - Pacific Ocean Shoreline	Fecal Coliform	4,932,380	400	310,820	86	22%	19	4,370,018	4,680,838
	Total Coliform	72,757,569	10,000	7,752,284				58,352,938	66,105,222
	Enterococcus	7,255,759	104*	80,899				6,514,309	6,595,208
		7,255,759	61	47,479				6,543,487	6,590,966
Chollas HSA (908.22) - Chollas Creek	Fecal Coliform	603,863	400	55,516	65	22%	14	464,924	520,440
	Total Coliform	15,390,608	10,000	1,386,037				11,861,589	13,247,626
	Enterococcus	1,371,972	104*	15,008				1,138,590	1,153,599
		1,371,972	61	9,073				1,143,572	1,152,645

* Total Maximum Daily Load calculated using a Enterococcus numeric target of 61 MPN/mL that is conservatively protective of the REC-1 "designated beach" usage frequency for freshwater creeks and downstream beaches. If the usage frequency of the freshwater creeks can be established as "moderately to lightly used" in the Basin Plan, alternative Total Maximum Daily Loads calculated using an Enterococcus numeric target of 104 MPN/ml may be used.

Existing Bacteria Load = Predicted existing bacteria load discharged from the watershed calculated by the Loading Simulation Program in C++ (LSPC) model using modeled flows and bacteria densities for all wet days during the critical year 1993

Single Sample Maximum Objective = Target bacteria densities based on numeric single sample maximum water quality objectives that are protective of REC-1 beneficial uses

Allowable Numeric Objective Load = Allowable load from the watershed calculated by the LSPC model using modeled flows and the numeric single sample maximum water quality objective bacteria densities for all wet days during the critical year 1993

Total Wet Days in Critical Year = Number of wet days (i.e., rainfall events of 0.2 inches or greater and the following 72 hours) in the critical year 1993 (i.e., wettest year between 1990 and 2002)

Allowable Exceedance Frequency = Assumed to be 22 percent exceedance frequency. In the calculation of the wet weather TMDLs, the San Diego Regional Board chose to apply the 22 percent allowable exceedance frequency as determined for Leo Carillo Beach in Los Angeles County. At the time the wet weather watershed model was developed, the 22 percent exceedance frequency from Los Angeles County was the only reference beach exceedance frequency available. The 22 percent allowable exceedance frequency used to calculate the wet weather TMDLs is justified because the San Diego Region watersheds' exceedance frequencies will likely be close to the value calculated for Leo Carillo Beach, and is consistent with the exceedance frequency that was applied by the Los Angeles Regional Board.

Allowable Wet Exceedance Days = (Total Wet days in Critical Year) X (Allowable Exceedance Frequency)

Allowable Exceedance Load = Sum of exceedance loads from the allowable exceedance days with the highest exceedance loads calculated by the LSPC model using modeled flows and bacteria densities for all wet days during the critical year 1993

Total Allowable Load [i.e. TMDL] = (Allowable Numeric Objective Load) + (Allowable Exceedance Load)

Table 7-40. Summary of Dry Weather Existing and Allowable Indicator Bacteria Loads

Watershed - Impaired Waterbody	Indicator Bacteria	Existing Bacteria Load (Billion MPN/mth)	30-Day Geometric Mean Objective (MPN/100mL)	Allowable Numeric Objective Load (Billion MPN/mth)	Total Dry Days in Critical Year	Allowable Exceedance Frequency	Allowable Dry Exceedance Days in Critical Year	Allowable Exceedance Load (Billion MPN/mth)	Total Allowable Load [=TMDL] (Billion MPN/mth)
San Joaquin Hills HSA (901.11) and Laguna Hills HSA (901.12) - Pacific Ocean Shoreline	Fecal Coliform	2,741	200	227	296	0%	0	0	227
	Total Coliform	13,791	1,000	1,134				0	1,134
	Enterococcus	2,321	35	40				0	40
Aliso HSA (901.13) - Pacific Ocean Shoreline - Aliso Creek - Aliso Creek mouth	Fecal Coliform	5,470	200	242	296	0%	0	0	242
	Total Coliform	26,639	1,000	1,208				0	1,208
	Enterococcus	4,614	33*	40				0	40
Dana Point HSA (901.14) - Pacific Ocean Shoreline	Fecal Coliform	1,851	200	92	296	0%	0	0	92
	Total Coliform	9,315	1,000	462				0	462
	Enterococcus	1,567	35	16				0	16
Lower San Juan HSA (901.27) - Pacific Ocean Shoreline - San Juan Creek - San Juan Creek mouth	Fecal Coliform	6,455	200	1,665	289	0%	0	0	1,665
	Total Coliform	30,846	1,000	8,342				0	8,342
	Enterococcus	5,433	33*	275				0	275
San Clemente HA (901.30) - Pacific Ocean Shoreline	Fecal Coliform	3,327	200	192	292	0%	0	0	192
	Total Coliform	16,743	1,000	958				0	958
	Enterococcus	2,817	35	33				0	33
San Luis Rey HU (903.00) - Pacific Ocean Shoreline	Fecal Coliform	1,737	200	1,058	275	0%	0	0	1,058
	Total Coliform	8,549	1,000	5,289				0	5,289
	Enterococcus	1,466	35	185				0	185
San Marcos HA (904.50) - Pacific Ocean Shoreline	Fecal Coliform	149	200	26	316	0%	0	0	26
	Total Coliform	751	1,000	129				0	129
	Enterococcus	126	35	5				0	5
San Dieguito HU (905.00) - Pacific Ocean Shoreline	Fecal Coliform	1,631	200	1,293	267	0%	0	0	1,293
	Total Coliform	7,555	1,000	6,468				0	6,468
	Enterococcus	1,368	35	226				0	226
Miramar Reservoir HA (906.10) - Pacific Ocean Shoreline	Fecal Coliform	205	200	7	271	0%	0	0	7
	Total Coliform	1,030	1,000	36				0	36
	Enterococcus	173	35	1				0	1

Table 7-40. Summary of Dry Weather Existing and Allowable Indicator Bacteria Loads (Cont'd)

Watershed - Impaired Waterbody	Indicator Bacteria	Existing Bacteria Load (Billion MPN/mth)	30-Day Geometric Mean Objective (MPN/100mL)	Allowable Numeric Objective Load (Billion MPN/mth)	Total Dry Days in Critical Year	Allowable Exceedance Frequency	Allowable Dry Exceedance Days in Critical Year	Allowable Exceedance Load (Billion MPN/mth)	Total Allowable Load [=TMDL] (Billion MPN/mth)
Scripps HA (906.30) - Pacific Ocean Shoreline	Fecal Coliform	3,320	200	119	308	0%	0	0	119
	Total Coliform	16,707	1,000	594				0	594
	Enterococcus	2,811	35	21				0	21
Tecolote HA (906.50) - Tecolote Creek	Fecal Coliform	4,329	200	234	308	0%	0	0	234
	Total Coliform	21,349	1,000	1,171				0	1,171
	Enterococcus	3,657	33*	39				0	39
Mission San Diego HSA (907.11) and Santee HSA (907.12) - Forrester Creek (lower 1 mile) - San Diego River (lower 6 miles) - Pacific Ocean Shoreline	Fecal Coliform	4,928	200	1,506	279	0%	0	0	1,506
	Total Coliform	28,988	1,000	7,529				0	7,529
	Enterococcus	4,106	33*	248				0	248
Chollas HSA (908.22) - Chollas Creek	Fecal Coliform	5,068	200	398	300	0%	0	0	398
	Total Coliform	25,080	1,000	1,991				0	1,991
	Enterococcus	4,283	33*	66				0	66

* Total Allowable Load [=TMDL] calculated using a Enterococcus numeric target of 33 MPN/mL that is conservatively protective of the REC-1 "designated beach" usage frequency for watersheds with impaired freshwater creeks.

Existing Bacteria Load = Predicted existing bacteria load discharged from the watershed calculated by the plug-flow reactor model using estimated flows and bacteria densities for 30 dry days during the critical year 1993

30-Day Geometric Mean Objective = Target bacteria densities based on numeric 30-day geometric mean water quality objectives that are protective of REC-1 beneficial uses

Allowable Numeric Objective Load = Allowable load from the watershed calculated by the plug-flow reactor model using estimated flows and the numeric 30-day geometric mean water quality objective bacteria densities for 30 dry days during the critical year 1993

Total Dry Days in Critical Year = Number of dry days (i.e., day not including rainfall events of 0.2 inches or greater and the following 72 hours) in the critical year 1993 (i.e., wettest year between 1990 and 2002)

Allowable Exceedance Frequency = Assumed to be zero; data collected from reference systems generally do not show exceedances of REC-1 water quality objectives

Allowable Wet Exceedance Days = (Total Dry Days in Critical Year) X (Allowable Exceedance Frequency)

Allowable Exceedance Load = Sum of exceedance loads from the allowable exceedance days for all dry days during the critical year 1993

Total Allowable Load [i.e. TMDL] = (Allowable Numeric Objective Load) + (Allowable Exceedance Load) for a 30-day period

Table 7-41. Wet Weather Fecal Coliform Bacteria Existing Loads, TMDLs, WLA, LAs Expressed as Annual Loads (Billion MPN/year)

Watershed	Total Watershed		Point Sources						Nonpoint Sources					
	Existing Load	TMDL*	Municipal MS4			Caltrans			Agriculture			Open		
			Existing Load	WLA*	Reduction Required	Existing Load	WLA*	Reduction Required	Existing Load	LA*	Reduction Required	Existing Load	LA*	Reduction Required
San Joaquin Hills/Laguna Hills HSAs (901.11 and 901.12)	705,015	664,634	77,548	37,167	52.07%	179	179	0.00%	7,346	7,346	0.00%	619,942	619,942	0.00%
Aliso HSA (901.13)	1,752,096	1,579,073	650,092	477,069	26.62%	260	260	0.00%	26,508	26,508	0.00%	1,075,237	1,075,237	0.00%
Dana Point HSA (901.14)	403,911	377,313	179,043	152,446	14.86%	13	13	0.00%	0	0	0.00%	224,854	224,854	0.00%
Lower San Juan HSA (901.27)	15,304,790	14,714,833	1,326,469	1,156,419	12.82%	1,713	1,713	0.00%	3,275,477	2,855,570	12.82%	10,701,131	10,701,131	0.00%
San Clemente HA (901.30)	1,441,723	1,378,931	255,445	192,653	24.58%	335	335	0.00%	366	366	0.00%	1,185,577	1,185,577	0.00%
San Luis Rey HU (903.00)	33,120,012	32,444,242	943,501	914,026	3.12%	1,537	1,537	0.00%	20,687,954	20,041,659	3.12%	11,487,019	11,487,019	0.00%
San Marcos HA (904.50)	20,886	17,224	8,095	6,558	18.98%	8	8	0.00%	11,199	9,073	18.98%	1,585	1,585	0.00%
San Dieguito HU (905.00)	21,286,910	21,101,649	810,008	798,175	1.46%	1,310	1,310	0.00%	11,872,240	11,698,811	1.46%	8,603,352	8,603,352	0.00%
Miramar Reservoir HA (906.10)	10,392	10,256	6,839	6,703	1.99%	0	0	0.00%	0	0	0.00%	3,552	3,552	0.00%
Scripps HA (906.30)	204,057	176,907	128,403	101,253	21.14%	0	0	0.00%	0	0	0.00%	75,654	75,654	0.00%
Tecolote HA (906.5)	261,966	229,322	159,449	126,806	20.47%	553	553	0.00%	0	0	0.00%	101,963	101,963	0.00%
Mission San Diego/Santee HSAs (907.11 and 907.12)	4,932,380 +1,302**	4,680,838 +1,302*	472,660	221,117	53.22%	1,009	1,009	0.00%	414,721	414,721	0.00%	4,043,991	4,043,991	0.00%
Chollas HSA (908.22)	603,863	520,440	335,901	252,479	24.84%	892	892	0.00%	0	0	0.00%	267,070	267,070	0.00%

* TMDLs, WLAs, and LAs calculated based on numeric targets consisting of the single sample maximum WQO for fecal coliform (400 MPN/100mL) and a 22 percent allowable exceedance frequency. Meeting the numeric targets in the discharge and/or receiving water indicate the TMDLs, WLAs, and/or LAs have been met.

** Permitted existing fecal coliform bacteria load from Padre Dam Municipal Water District Water Reclamation Plant (Padre Dam), assigned as a separate point source wasteload allocation for discharges from Padre Dam equal to the permitted existing load

Watershed Existing Load = Predicted existing fecal coliform bacteria loads discharged from all land use categories in the watershed calculated by the Loading Simulation Program in C++ (LSPC) model using modeled flows and bacteria densities for all wet days during the critical year 1993

Watershed TMDL = Total Maximum Daily Load (TMDL) or total allowable load (Allowable Numeric Objective Load + Allowable Exceedance Load) that can be discharged from all land uses in the watershed on an annual basis

MS4 Existing Load = Predicted exiting fecal coliform bacteria loads discharged from Municipal Separate Storm Sewer System (MS4) land use categories in the watershed (i.e., commercial/institutional, high density residential, low density residential, parks/recreation, military, transitional, and industrial/transportation, not including Caltrans transportation) calculated by the LSPC model

MS4 WLA = Point source wasteload allocation (WLA) for discharges from Municipal MS4 land uses

MS4 Reduction Required = Percent of the MS4 Existing Load that must be reduced to meet the MS4 WLA = $(MS4 \text{ Existing Load} - MS4 \text{ WLA}) / (MS4 \text{ Existing Load})$

Caltrans Existing Load = Predicted exiting fecal coliform bacteria loads discharged from Caltrans land use areas in the watershed calculated as a fraction of the discharge from industrial/transportation land use category area

Caltrans WLA = Point source wasteload allocation (WLA) for discharges from Caltrans land uses, assumed to be equal to Caltrans Existing Load

Caltrans Reduction Required = Percent of the Caltrans Existing Load that must be reduced to meet the Caltrans WLA = $(\text{Caltrans Existing Load} - \text{Caltrans WLA}) / (\text{Caltrans Existing Load})$

Agriculture Existing Load = Predicted exiting fecal coliform bacteria loads discharged from Agriculture land use categories in the watershed (i.e., agriculture, dairy/livestock, horse ranch) calculated by the LSPC model

Agriculture LA = Non-point source load allocation (LA) for discharges from Agriculture land uses, assumed to be equal to Agriculture Existing Load in watersheds with existing bacteria load contributions for all three indicator bacteria of less than 5 percent; calculated as a relative load percent of the TMDL minus Caltrans WLA and Open Space LA, based on existing load contributions from MS4 and Agriculture land use categories in watersheds with existing bacteria load contributions for all three indicator bacteria of greater than 5 percent

Agriculture Reduction Required = Percent of the Agriculture Existing Load that must be reduced to meet the Agriculture LA = $(\text{Agriculture Existing Load} - \text{Agriculture LA}) / (\text{Agriculture Existing Load})$

Open Existing Load = Predicted exiting fecal coliform bacteria loads discharged from Open Space land use categories in the watershed (i.e., open space, open recreation, water) calculated by the LSPC model

Open LA = Non-point source load allocation (LA) for discharges from Open Space land uses, assumed to be equal to the Open Space Existing Load

Open Reduction Required = Percent of the Open Space Existing Load that must be reduced to meet the Open Space LA = $(\text{Open Space Existing Load} - \text{Open Space LA}) / (\text{Open Space Existing Load})$

Table 7-42. Wet Weather Total Coliform Bacteria Existing Loads, TMDLs, WLA, LAs Expressed as Annual Loads (Billion MPN/year)

Watershed	Total Watershed		Point Sources						Nonpoint Sources					
	Existing Load	TMDL*	Municipal MS4			Caltrans			Agriculture			Open		
			Existing Load	WLA*	Reduction Required	Existing Load	WLA*	Reduction Required	Existing Load	LA*	Reduction Required	Existing Load	LA*	Reduction Required
San Joaquin Hills/Laguna Hills HSAs (901.11 and 901.12)	8,221,901	7,445,649	1,656,904	880,652	46.85%	7,722	7,722	0.00%	50,774	50,774	0.00%	6,506,501	6,506,501	0.00%
Aliso HSA (901.13)	23,210,774	20,190,798	11,943,241	8,923,264	25.29%	11,003	11,003	0.00%	179,828	179,828	0.00%	11,076,702	11,076,702	0.00%
Dana Point HSA (901.14)	6,546,962	6,031,472	3,919,497	3,404,008	13.15%	634	634	0.00%	0	0	0.00%	2,626,830	2,626,830	0.00%
Lower San Juan HSA (901.27)	130,258,863	122,879,189	19,919,322	16,093,160	19.21%	60,480	60,480	0.00%	18,499,884	14,946,372	19.21%	91,779,178	91,779,178	0.00%
San Clemente HA (901.30)	16,236,606	15,147,603	4,566,742	3,477,739	23.85%	13,534	13,534	0.00%	2,370	2,370	0.00%	11,653,960	11,653,960	0.00%
San Luis Rey HU (903.00)	231,598,677	224,150,535	15,229,456	14,373,954	5.62%	54,508	54,508	0.00%	117,360,800	110,768,160	5.62%	98,953,913	98,953,913	0.00%
San Marcos HA (904.50)	515,278	425,083	366,021	298,430	18.47%	533	533	0.00%	122,414	99,809	18.47%	26,311	26,311	0.00%
San Dieguito HU (905.00)	163,541,133	159,814,184	17,406,569	16,660,538	4.29%	47,969	47,969	0.00%	69,551,416	66,570,499	4.29%	76,535,178	76,535,178	0.00%
Miramar Reservoir HA (906.10)	212,986	210,180	174,243	171,436	1.61%	9	9	0.00%	0	0	0.00%	38,734	38,734	0.00%
Scripps HA (906.30)	5,029,519	4,356,973	4,120,310	3,447,764	16.32%	0	0	0.00%	0	0	0.00%	909,209	909,209	0.00%
Tecolote HA (906.5)	7,395,789	6,379,770	6,152,484	5,136,598	16.51%	27,095	27,095	0.00%	0	0	0.00%	1,216,077	1,216,077	0.00%
Mission San Diego/Santee HSAs (907.11 and 907.12)	72,757,569	66,105,222	17,442,867	10,790,520	38.14%	53,141	53,141	0.00%	3,495,960	3,495,960	0.00%	51,765,601	51,765,601	0.00%
Chollas HSA (908.22)	15,390,608	13,247,626	12,023,766	9,880,784	17.82%	45,652	45,652	0.00%	0	0	0.00%	3,321,191	3,321,191	0.00%

* TMDLs, WLAs, and LAs calculated based on numeric targets consisting of the single sample maximum WQO for total coliform (10,000 MPN/100mL) and a 22 percent allowable exceedance frequency. Meeting the numeric targets in the discharge and/or receiving water indicate the TMDLs, WLAs, and/or LAs have been met.

Watershed Existing Load = Predicted existing total coliform bacteria loads discharged from all land use categories in the watershed calculated by the Loading Simulation Program in C++ (LSPC) model using modeled flows and bacteria densities for all wet days during the critical year 1993

Watershed TMDL = Total Maximum Daily Load (TMDL) or total allowable load (Allowable Numeric Objective Load + Allowable Exceedance Load) that can be discharged from all land uses in the watershed on an annual basis

MS4 Existing Load = Predicted existing total coliform bacteria loads discharged from Municipal Separate Storm Sewer System (MS4) land use categories in the watershed (i.e., commercial/institutional, high density residential, low density residential, parks/recreation, military, transitional, and industrial/transportation, not including Caltrans transportation) calculated by the LSPC model

MS4 WLA = Point source wasteload allocation (WLA) for discharges from Municipal MS4 land uses

MS4 Reduction Required = Percent of the MS4 Existing Load that must be reduced to meet the MS4 WLA = $(MS4 \text{ Existing Load} - MS4 \text{ WLA}) / (MS4 \text{ Existing Load})$

Caltrans Existing Load = Predicted existing total coliform bacteria loads discharged from Caltrans land use areas in the watershed calculated as a fraction of the discharge from industrial/transportation land use category area

Caltrans WLA = Point source wasteload allocation (WLA) for discharges from Caltrans land uses, assumed to be equal to Caltrans Existing Load

Caltrans Reduction Required = Percent of the Caltrans Existing Load that must be reduced to meet the Caltrans WLA = $(\text{Caltrans Existing Load} - \text{Caltrans WLA}) / (\text{Caltrans Existing Load})$

Agriculture Existing Load = Predicted existing total coliform bacteria loads discharged from Agriculture land use categories in the watershed (i.e., agriculture, dairy/livestock, horse ranch) calculated by the LSPC model

Agriculture LA = Non-point source load allocation (LA) for discharges from Agriculture land uses, assumed to be equal to Agriculture Existing Load in watersheds with existing bacteria load contributions for all three indicator bacteria of less than 5 percent; calculated as a relative load percent of the TMDL minus Caltrans WLA and Open Space LA, based on existing load contributions from MS4 and Agriculture land use categories in watersheds with existing bacteria load contributions for all three indicator bacteria of greater than 5 percent

Agriculture Reduction Required = Percent of the Agriculture Existing Load that must be reduced to meet the Agriculture LA = $(\text{Agriculture Existing Load} - \text{Agriculture LA}) / (\text{Agriculture Existing Load})$

Open Existing Load = Predicted existing total coliform bacteria loads discharged from Open Space land use categories in the watershed (i.e., open space, open recreation, water) calculated by the LSPC model

Open LA = Non-point source load allocation (LA) for discharges from Open Space land uses, assumed to be equal to the Open Space Existing Load

Open Reduction Required = Percent of the Open Space Existing Load that must be reduced to meet the Open Space LA = $(\text{Open Space Existing Load} - \text{Open Space LA}) / (\text{Open Space Existing Load})$

Table 7-43. Wet Weather Enterococcus Bacteria Existing Loads, TMDLs, WLA, LAs Expressed as Annual Loads (Billion MPN/year)

Watershed	Total Watershed		Point Sources						Nonpoint Sources					
	Existing Load	TMDL*	Municipal MS4			Caltrans			Agriculture			Open		
			Existing Load	WLA*	Reduction Required	Existing Load	WLA*	Reduction Required	Existing Load	LA*	Reduction Required	Existing Load	LA*	Reduction Required
San Joaquin Hills/Laguna Hills HSAs (901.11 and 901.12)	852,649	782,799	136,267	66,417	51.26%	365	365	0.00%	3,201	3,201	0.00%	712,816	712,816	0.00%
Aliso HSA (901.13)	2,230,206	1,950,964**	1,014,732	735,490	27.52%	516	516	0.00%	11,245	11,245	0.00%	1,203,713	1,203,713	0.00%
Dana Point HSA (901.14)	501,526	462,306	258,747	219,528	15.16%	25	25	0.00%	0	0	0.00%	242,753	242,753	0.00%
Lower San Juan HSA (901.27)	12,980,098	12,152,446**	1,900,520	1,385,094	27.12%	2,823	2,823	0.00%	1,151,266	839,040	27.12%	9,925,490	9,925,490	0.00%
San Clemente HA (901.30)	1,663,100	1,563,187	395,581	295,668	25.26%	635	635	0.00%	148	148	0.00%	1,266,736	1,266,736	0.00%
San Luis Rey HU (903.00)	18,439,920	17,463,618	1,472,296	1,300,235	11.69%	2,397	2,397	0.00%	6,881,755	6,077,514	11.69%	10,083,473	10,083,473	0.00%
San Marcos HA (904.50)	40,558	32,966	29,784	23,771	20.19%	26	26	0.00%	7,825	6,246	20.19%	2,923	2,923	0.00%
San Dieguito HU (905.00)	14,796,210	14,307,087	1,911,170	1,763,603	7.72%	2,288	2,288	0.00%	4,423,566	4,082,010	7.72%	8,459,187	8,459,187	0.00%
Miramar Reservoir HA (906.10)	11,564	11,405	8,269	8,109	1.93%	0	0	0.00%	0	0	0.00%	3,295	3,295	0.00%
Scripps HA (906.30)	377,839	324,032	285,842	232,035	18.82%	0	0	0.00%	0	0	0.00%	91,997	91,997	0.00%
Tecolote HA (906.5)	708,256	603,761**	575,708	471,211	18.15%	1,266	1,266	0.00%	0	0	0.00%	131,284	131,284	0.00%
Mission San Diego/Santee HSAs (907.11 and 907.12)	7,255,759	6,590,966*	1,555,411	890,617	42.74%	2,430	2,430	0.00%	213,149	213,149	0.00%	5,484,770	5,484,770	0.00%
Chollas HSA (908.22)	1,371,972	1,152,645**	1,022,245	802,918	21.46%	2,062	2,062	0.00%	0	0	0.00%	347,665	347,665	0.00%

* TMDLs, WLAs, and LAs calculated based on numeric targets consisting of the single sample maximum WQO for enterococcus (104 MPN/100mL or 61 MPN/100mL) and a 22 percent allowable exceedance frequency. Meeting the numeric targets in the discharge and/or receiving water indicate the TMDLs, WLAs, and/or LAs have been met.

** Total Maximum Daily Load calculated using a Enterococcus numeric target of 61 MPN/mL that is conservatively protective of the REC-1 “designated beach” usage frequency for freshwater creeks and downstream beaches. If the usage frequency of the freshwater creeks can be established as “moderately to lightly used,” alternative Total Maximum Daily Loads calculated using an Enterococcus numeric target of 104 MPN/ml presented in Table 7-44 may be used.

Watershed Existing Load = Predicted existing Enterococcus bacteria loads discharged from all land use categories in the watershed calculated by the Loading Simulation Program in C++ (LSPC) model using modeled flows and bacteria densities for all wet days during the critical year 1993

Watershed TMDL = Total Maximum Daily Load (TMDL) or total allowable load (Allowable Numeric Objective Load + Allowable Exceedance Load) that can be discharged from all land uses in the watershed on an annual basis

MS4 Existing Load = Predicted exiting Enterococcus bacteria loads discharged from Municipal Separate Storm Sewer System (MS4) land use categories in the watershed (i.e., commercial/institutional, high density residential, low density residential, parks/recreation, military, transitional, and industrial/transportation, not including Caltrans transportation) calculated by the LSPC model

MS4 WLA = Point source wasteload allocation (WLA) for discharges from Municipal MS4 land uses

MS4 Reduction Required = Percent of the MS4 Existing Load that must be reduced to meet the MS4 WLA = $(\text{MS4 Existing Load} - \text{MS4 WLA}) / (\text{MS4 Existing Load})$

Caltrans Existing Load = Predicted exiting Enterococcus bacteria loads discharged from Caltrans land use areas in the watershed calculated as a fraction of the discharge from industrial/transportation land use category area

Caltrans WLA = Point source wasteload allocation (WLA) for discharges from Caltrans land uses, assumed to be equal to Caltrans Existing Load

Caltrans Reduction Required = Percent of the Caltrans Existing Load that must be reduced to meet the Caltrans WLA = $(\text{Caltrans Existing Load} - \text{Caltrans WLA}) / (\text{Caltrans Existing Load})$

Agriculture Existing Load = Predicted exiting Enterococcus bacteria loads discharged from Agriculture land use categories in the watershed (i.e., agriculture, dairy/livestock, horse ranch) calculated by the LSPC model

Agriculture LA = Non-point source load allocation (LA) for discharges from Agriculture land uses, assumed to be equal to Agriculture Existing Load in watersheds with existing bacteria load contributions for all three indicator bacteria of less than 5 percent; calculated as a relative load percent of the TMDL minus Caltrans WLA and Open Space LA, based on existing load contributions from MS4 and Agriculture land use categories in watersheds with existing bacteria load contributions for all three indicator bacteria of greater than 5 percent

Agriculture Reduction Required = Percent of the Agriculture Existing Load that must be reduced to meet the Agriculture LA = $(\text{Agriculture Existing Load} - \text{Agriculture LA}) / (\text{Agriculture Existing Load})$

Open Existing Load = Predicted exiting Enterococcus bacteria loads discharged from Open Space land use categories in the watershed (i.e., open space, open recreation, water) calculated by the LSPC model

Open LA = Non-point source load allocation (LA) for discharges from Open Space land uses, assumed to be equal to the Open Space Existing Load

Open Reduction Required = Percent of the Open Space Existing Load that must be reduced to meet the Open Space LA = $(\text{Open Space Existing Load} - \text{Open Space LA}) / (\text{Open Space Existing Load})$

Table 7-44. Alternative Wet Weather Enterococcus Bacteria Existing Loads, TMDLs, WLA, LAs Expressed as Annual Loads (Billion MPN/year)

Watershed	Total Watershed		Point Sources						Nonpoint Sources					
	Existing Load	TMDL*	Municipal MS4			Caltrans			Agriculture			Open		
			Existing Load	WLA*	Reduction Required	Existing Load	WLA*	Reduction Required	Existing Load	LA*	Reduction Required	Existing Load	LA*	Reduction Required
Aliso HSA (901.13)	2,230,206	1,952,517**	1,014,732	737,042	27.37%	516	516	0.00%	11,245	11,245	0.00%	1,203,713	1,203,713	0.00%
Lower San Juan HSA (901.27)	12,980,098	12,159,138**	1,900,520	1,389,261	26.90%	2,823	2,823	0.00%	1,151,266	841,564	26.90%	9,925,490	9,925,490	0.00%
Tecolote HA (906.50)	708,256	604,180**	575,708	471,630	18.08%	1,266	1,266	0.00%	0	0	0.00%	131,284	131,284	0.00%
Mission San Diego/ Santee HSAs (907.11 and 907.12)	7,255,759	6,595,208**	1,555,411	894,859	42.47%	2,430	2,430	0.00%	213,149	213,149	0.00%	5,484,770	5,484,770	0.00%
Chollas HSA (908.22)	1,371,972	1,153,599**	1,022,245	803,871	21.36%	2,062	2,062	0.00%	0	0	0.00%	347,665	347,665	0.00%

* TMDLs, WLAs, and LAs calculated based on numeric targets consisting of the single sample maximum WQO for enterococcus (104 MPN/100mL) and a 22 percent allowable exceedance frequency. Meeting the numeric targets in the discharge and/or receiving water indicate the TMDLs, WLAs, and/or LAs have been met.

** Total Maximum Daily Load calculated using a Enterococcus numeric target of 104 MPN/ml protective of the REC-1 “moderately to lightly used area” usage frequency that is protective freshwater creeks and downstream beaches. Acceptable evidence that impaired freshwater creeks can be considered “moderately to lightly used areas” must be provided before these alternative wet weather TMDLs, WLAs, and LAs can be implemented in these watersheds.

Watershed Existing Load Predicted existing Enterococcus bacteria loads discharged from all land use categories in the watershed calculated by the Loading Simulation Program in C++ (LSPC) model using modeled flows and bacteria densities for all wet days during the critical year 1993

Watershed TMDL = Total Maximum Daily Load (TMDL) or total allowable load (Allowable Numeric Objective Load + Allowable Exceedance Load) that can be discharged from all land uses in the watershed on an annual basis

MS4 Existing Load = Predicted exiting Enterococcus bacteria loads discharged from Municipal Separate Storm Sewer System (MS4) land use categories in the watershed (i.e., commercial/institutional, high density residential, low density residential, parks/recreation, military, transitional, and industrial/transportation, not including Caltrans transportation) calculated by the LSPC model

MS4 WLA = Point source wasteload allocation (WLA) for discharges from Municipal MS4 land uses

MS4 Reduction Required = Percent of the MS4 Existing Load that must be reduced to meet the MS4 WLA = (MS4 Existing Load – MS4 WLA)/(MS4 Existing Load)

Caltrans Existing Load = Predicted exiting Enterococcus bacteria loads discharged from Caltrans land use areas in the watershed calculated as a fraction of the discharge from industrial/transportation land use category area

Caltrans WLA = Point source wasteload allocation (WLA) for discharges from Caltrans land uses, assumed to be equal to Caltrans Existing Load

Caltrans Reduction Required = Percent of the Caltrans Existing Load that must be reduced to meet the Caltrans WLA = (Caltrans Existing Load – Caltrans WLA)/(Caltrans Existing Load)

Agriculture Existing Load = Predicted exiting Enterococcus bacteria loads discharged from Agriculture land use categories in the watershed (i.e., agriculture, dairy/livestock, horse ranch) calculated by the LSPC model

Agriculture LA = Non-point source load allocation (LA) for discharges from Agriculture land uses, assumed to be equal to Agriculture Existing Load in watersheds with existing bacteria load contributions for all three indicator bacteria of less than 5 percent; calculated as a relative load percent of the TMDL minus Caltrans WLA and Open Space LA, based on existing load contributions from MS4 and Agriculture land use categories in watersheds with existing bacteria load contributions for all three indicator bacteria of greater than 5 percent

Agriculture Reduction Required = Percent of the Agriculture Existing Load that must be reduced to meet the Agriculture LA = $(\text{Agriculture Existing Load} - \text{Agriculture LA}) / (\text{Agriculture Existing Load})$

Open Existing Load = Predicted exiting Enterococcus bacteria loads discharged from Open Space land use categories in the watershed (i.e., open space, open recreation, water) calculated by the LSPC model

Open LA = Non-point source load allocation (LA) for discharges from Open Space land uses, assumed to be equal to the Open Space Existing Load

Open Reduction Required = Percent of the Open Space Existing Load that must be reduced to meet the Open Space LA = $(\text{Open Space Existing Load} - \text{Open Space LA}) / (\text{Open Space Existing Load})$

Table 7-45. Dry Weather Fecal Coliform Bacteria Existing Loads, TMDLs, WLA, LAs Expressed as Monthly Loads (Billion MPN/month)

Watershed	Total Watershed		Point Sources						Nonpoint Sources					
	Existing Load	TMDL*	Municipal MS4			Caltrans			Agriculture			Open		
			Existing Load	WLA*	Reduction Required	Existing Load	WLA*	Reduction Required	Existing Load	LA*	Reduction Required	Existing Load	LA*	Reduction Required
San Joaquin Hills/ Laguna Hills HSAs (901.11 and 901.12)	2,741	227	2,741	227	91.72%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Aliso HSA (901.13)	5,470	242	5,470	242	95.58%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Dana Point HSA (901.14)	1,851	92	1,851	92	95.03%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Lower San Juan HSA (901.27)	6,455	1,665	6,455	1,665	74.21%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Clemente HA (901.30)	3,327	192	3,327	192	94.23%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Luis Rey HU (903.00)	1,737	1,058	1,737	1,058	39.09%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Marcos HA (904.50)	149	26	149	26	82.55%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Dieguito HU (905.00)	1,631	1,293	1,631	1,293	20.72%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Miramar Reservoir HA (906.10)	205	7	205	7	96.59%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Scripps HA (906.30)	3,320	119	3,320	119	96.42%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Tecolote HA (906.5)	4,329	234	4,329	234	94.59%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Mission San Diego/ Santee HSAs (907.11 and 907.12)	4,928 +461**	1,506 +461*	4,928	1,506	69.44%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Chollas HSA (908.22)	5,068	398	5,068	398	92.15%	0	0	0.00%	0	0	0.00%	0	0	0.00%

* TMDLs, WLAs, and LAs calculated based on numeric targets consisting of the 30-day geometric mean WQO for fecal coliform (200 MPN/100mL) and a 0 percent allowable exceedance frequency. Meeting the numeric targets in the discharge and/or receiving water indicate the TMDLs, WLAs, and/or LAs have been met.

** Permitted existing fecal coliform bacteria load from Padre Dam Municipal Water District Water Reclamation Plant (Padre Dam), assigned as a separate point source wasteload allocation for discharges from Padre Dam equal to the permitted existing load

Watershed Existing Load = Predicted existing fecal coliform bacteria loads discharged from all land use categories in the watershed calculated by a plug-flow reactor model using estimated flows and bacteria densities for 30 dry days during the critical year 1993

Watershed TMDL = Total Maximum Daily Load (TMDL) or total allowable load (Allowable Numeric Objective Load + Allowable Exceedance Load) that can be discharged from all land uses in the watershed for a 30-day period

MS4 Existing Load = Predicted exiting fecal coliform bacteria loads discharged from Municipal Separate Storm Sewer System (MS4) land use categories in the watershed (i.e., commercial/institutional, high density residential, low density residential, parks/recreation, military, transitional, and industrial/transportation, not including Caltrans transportation) calculated by the plug-flow reactor model

MS4 WLA = Point source wasteload allocation (WLA) for discharges from Municipal MS4 land uses

MS4 Reduction Required = Percent of the MS4 Existing Load that must be reduced to meet the MS4 WLA = (MS4 Existing Load – MS4 WLA)/(MS4 Existing Load)

Caltrans Existing Load = Fecal coliform bacteria loads discharged from Caltrans land use areas in the watershed assumed to be unlikely during dry weather conditions, or zero bacteria load during dry weather

Caltrans WLA = Point source wasteload allocation (WLA) for discharges from Caltrans land uses, assumed to be equal to the Caltrans Existing Load

Caltrans Reduction Required = Percent of the Caltrans Existing Load that must be reduced to meet the Caltrans WLA = $(\text{Caltrans Existing Load} - \text{Caltrans WLA}) / (\text{Caltrans Existing Load})$

Agriculture Existing Load = Fecal coliform bacteria loads discharged from Agriculture land use categories in the watershed (i.e., agriculture, dairy/livestock, horse ranch) assumed to be unlikely during dry weather conditions, or zero bacteria load during dry weather

Agriculture LA = Non-point source load allocation (LA) for discharges from Agriculture land uses, assumed to be equal to the Open Space Existing Load

Agriculture Reduction Required = Percent of the Agriculture Existing Load that must be reduced to meet the Agriculture LA = $(\text{Agriculture Existing Load} - \text{Agriculture LA}) / (\text{Agriculture Existing Load})$

Open Existing Load = Fecal coliform bacteria loads discharged from Open Space land use categories in the watershed (i.e., open space, open recreation, water) assumed to be unlikely during dry weather conditions, or zero bacteria load during dry weather

Open LA = Non-point source load allocation (LA) for discharges from Open Space land uses, assumed to be equal to the Open Space Existing Load

Open Reduction Required = Percent of the Open Space Existing Load that must be reduced to meet the Open Space LA = $(\text{Open Space Existing Load} - \text{Open Space LA}) / (\text{Open Space Existing Load})$

Table 7-46. Dry Weather Total Coliform Bacteria Existing Loads, TMDLs, WLA, LAs Expressed as Monthly Loads (Billion MPN/month)

Watershed	Total Watershed		Point Sources						Nonpoint Sources					
	Existing Load	TMDL*	Municipal MS4			Caltrans			Agriculture			Open		
			Existing Load	WLA*	Reduction Required	Existing Load	WLA*	Reduction Required	Existing Load	LA*	Reduction Required	Existing Load	LA*	Reduction Required
San Joaquin Hills/ Laguna Hills HSAs (901.11 and 901.12)	13,791	1,134	13,791	1,134	91.78%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Aliso HSA (901.13)	26,639	1,208	26,639	1,208	95.47%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Dana Point HSA (901.14)	9,315	462	9,315	462	95.04%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Lower San Juan HSA (901.27)	30,846	8,342	30,846	8,342	72.96%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Clemente HA (901.30)	16,743	958	16,743	958	94.28%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Luis Rey HU (903.00)	8,549	5,289	8,549	5,289	38.13%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Marcos HA (904.50)	751	129	751	129	82.82%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Dieguito HU (905.00)	7,555	6,468	7,555	6,468	14.39%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Miramar Reservoir HA (906.10)	1,030	36	1,030	36	96.50%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Scripps HA (906.30)	16,707	594	16,707	594	96.44%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Tecolote HA (906.5)	21,349	1,171	21,349	1,171	94.51%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Mission San Diego/ Santee HSAs (907.11 and 907.12)	28,988	7,529	28,988	7,529	74.03%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Chollas HSA (908.22)	25,080	1,991	25,080	1,991	92.06%	0	0	0.00%	0	0	0.00%	0	0	0.00%

* TMDLs, WLAs, and LAs calculated based on numeric targets consisting of the 30-day geometric mean WQO for total coliform (1,000 MPN/100mL) and a 0 percent allowable exceedance frequency. Meeting the numeric targets in the discharge and/or receiving water indicate the TMDLs, WLAs, and/or LAs have been met.

Watershed Existing Load = Predicted existing total coliform bacteria loads discharged from all land use categories in the watershed calculated by a plug-flow reactor model using estimated flows and bacteria densities for 30 dry days during the critical year 1993

Watershed TMDL = Total Maximum Daily Load (TMDL) or total allowable load (Allowable Numeric Objective Load + Allowable Exceedance Load) that can be discharged from all land uses in the watershed for a 30-day period

MS4 Existing Load = Predicted existing total coliform bacteria loads discharged from Municipal Separate Storm Sewer System (MS4) land use categories in the watershed (i.e., commercial/institutional, high density residential, low density residential, parks/recreation, military, transitional, and industrial/transportation, not including Caltrans transportation) calculated by the plug-flow reactor model

MS4 WLA = Point source wasteload allocation (WLA) for discharges from Municipal MS4 land uses

MS4 Reduction Required = Percent of the MS4 Existing Load that must be reduced to meet the MS4 WLA = (MS4 Existing Load – MS4 WLA)/(MS4 Existing Load)

Caltrans Existing Load = Total coliform bacteria loads discharged from Caltrans land use areas in the watershed assumed to be unlikely during dry weather conditions, or zero bacteria load during dry weather

Caltrans WLA = Point source wasteload allocation (WLA) for discharges from Caltrans land uses, assumed to be equal to the Caltrans Existing Load

Caltrans Reduction Required = Percent of the Caltrans Existing Load that must be reduced to meet the Caltrans WLA = $(\text{Caltrans Existing Load} - \text{Caltrans WLA}) / (\text{Caltrans Existing Load})$

Agriculture Existing Load = Total coliform bacteria loads discharged from Agriculture land use categories in the watershed (i.e., agriculture, dairy/livestock, horse ranch) assumed to be unlikely during dry weather conditions, or zero bacteria load during dry weather

Agriculture LA = Non-point source load allocation (LA) for discharges from Agriculture land uses, assumed to be equal to the Open Space Existing Load

Agriculture Reduction Required = Percent of the Agriculture Existing Load that must be reduced to meet the Agriculture LA = $(\text{Agriculture Existing Load} - \text{Agriculture LA}) / (\text{Agriculture Existing Load})$

Open Existing Load = Total coliform bacteria loads discharged from Open Space land use categories in the watershed (i.e., open space, open recreation, water) assumed to be unlikely during dry weather conditions, or zero bacteria load during dry weather

Open LA = Non-point source load allocation (LA) for discharges from Open Space land uses, assumed to be equal to the Open Space Existing Load

Open Reduction Required = Percent of the Open Space Existing Load that must be reduced to meet the Open Space LA = $(\text{Open Space Existing Load} - \text{Open Space LA}) / (\text{Open Space Existing Load})$

Table 7-47. Dry Weather Enterococcus Bacteria Existing Loads, TMDLs, WLA, LAs Expressed as Monthly Loads (Billion MPN/month)

Watershed	Total Watershed		Point Sources						Nonpoint Sources					
	Existing Load	TMDL*	Municipal MS4			Caltrans			Agriculture			Open		
			Existing Load	WLA*	Reduction Required	Existing Load	WLA*	Reduction Required	Existing Load	LA*	Reduction Required	Existing Load	LA*	Reduction Required
San Joaquin Hills/ Laguna Hills HSAs (901.11 and 901.12)	2,321	40	2,321	40	98.28%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Aliso HSA (901.13)	4,614	40**	4,614	40	99.13%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Dana Point HSA (901.14)	1,567	16	1,567	16	98.98%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Lower San Juan HSA (901.27)	5,433	275**	5,433	275	94.94%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Clemente HA (901.30)	2,817	33	2,817	33	98.83%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Luis Rey HU (903.00)	1,466	185	1,466	185	87.38%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Marcos HA (904.50)	126	5	126	5	96.03%	0	0	0.00%	0	0	0.00%	0	0	0.00%
San Dieguito HU (905.00)	1,368	226	1,368	226	83.48%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Miramar Reservoir HA (906.10)	173	1	173	1	99.42%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Scripps HA (906.30)	2,811	21	2,811	21	99.25%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Tecolote HA (906.5)	3,657	39**	3,657	39	98.94%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Mission San Diego/ Santee HSAs (907.11 and 907.12)	4,106	248**	4,106	248	93.96%	0	0	0.00%	0	0	0.00%	0	0	0.00%
Chollas HSA (908.22)	4,283	66**	4,283	66	98.46%	0	0	0.00%	0	0	0.00%	0	0	0.00%

* TMDLs, WLAs, and LAs calculated based on numeric targets consisting of the 30-day geometric mean WQO for enterococcus (35 MPN/100mL or 33 MPN/100mL) and a 0 percent allowable exceedance frequency. Meeting the numeric targets in the discharge and/or receiving water indicate the TMDLs, WLAs, and/or LAs have been met.

** Total Maximum Daily Load calculated using a Enterococcus numeric target of 33 MPN/mL that is conservatively protective of the REC-1 “designated beach” usage frequency for freshwater creeks and downstream beaches.

Watershed Existing Load = Predicted existing Enterococcus bacteria loads discharged from all land use categories in the watershed calculated by a plug-flow reactor model using estimated flows and bacteria densities for 30 dry days during the critical year 1993

Watershed TMDL = Total Maximum Daily Load (TMDL) or total allowable load (Allowable Numeric Objective Load + Allowable Exceedance Load) that can be discharged from all land uses in the watershed for a 30-day period

MS4 Existing Load = Predicted exiting Enterococcus bacteria loads discharged from Municipal Separate Storm Sewer System (MS4) land use categories in the watershed (i.e., commercial/institutional, high density residential, low density residential, parks/recreation, military, transitional, and industrial/transportation, not including Caltrans transportation) calculated by the plug-flow reactor model

MS4 WLA = Point source wasteload allocation (WLA) for discharges from MS4 land uses

MS4 Reduction Required = Percent of the MS4 Existing Load that must be reduced to meet the MS4 WLA = (MS4 Existing Load – MS4 WLA)/(MS4 Existing Load)

Caltrans Existing Load = Enterococcus bacteria loads discharged from Caltrans land use areas in the watershed assumed to be unlikely during dry weather conditions, or zero bacteria load during dry weather

Caltrans WLA = Point source wasteload allocation (WLA) for discharges from Caltrans land uses, assumed to be equal to the Caltrans Existing Load

Caltrans Reduction Required = Percent of the Caltrans Existing Load that must be reduced to meet the Caltrans WLA = $(\text{Caltrans Existing Load} - \text{Caltrans WLA}) / (\text{Caltrans Existing Load})$

Agriculture Existing Load = Enterococcus bacteria loads discharged from Agriculture land use categories in the watershed (i.e., agriculture, dairy/livestock, horse ranch) assumed to be unlikely during dry weather conditions, or zero bacteria load during dry weather

Agriculture LA = Non-point source load allocation (LA) for discharges from Agriculture land uses, assumed to be equal to the Open Space Existing Load

Agriculture Reduction Required = Percent of the Agriculture Existing Load that must be reduced to meet the Agriculture LA = $(\text{Agriculture Existing Load} - \text{Agriculture LA}) / (\text{Agriculture Existing Load})$

Open Existing Load = Enterococcus bacteria loads discharged from Open Space land use categories in the watershed (i.e., open space, open recreation, water) assumed to be unlikely during dry weather conditions, or zero bacteria load during dry weather

Open LA = Non-point source load allocation (LA) for discharges from Open Space land uses, assumed to be equal to the Open Space Existing Load

Open Reduction Required = Percent of the Open Space Existing Load that must be reduced to meet the Open Space LA = $(\text{Open Space Existing Load} - \text{Open Space LA}) / (\text{Open Space Existing Load})$

TMDL IMPLEMENTATION PLAN

The ultimate goal of the Implementation Plan is to restore the impaired beneficial uses of the waterbodies addressed by these TMDLs. Restoring the impaired beneficial uses will be accomplished by achieving the TMDLs in the receiving waters, and the wasteload allocations (WLAs) for point sources and load allocations (LAs) for nonpoint sources. The actions taken by the San Diego Water Board depends on the regulatory authority and the source. The regulatory authorities and actions that the San Diego Water Board will use to compel the controllable sources to implement these TMDLs are as follows.

(1) Basin Plan Waste Discharge Prohibitions

The San Diego Water Board may specify certain conditions or areas where the discharge of waste or certain types of waste is not permitted, known as “waste discharge prohibitions,” in the Basin Plan.⁴¹ Basin Plan waste discharge prohibitions that are applicable to the implementation of these TMDLs include the following:

- The discharge of waste to waters of the state in a manner causing, or threatening to cause a condition of pollution, contamination or nuisance as defined in Water Code section 13050, is prohibited.
- The discharge of waste to inland surface waters, except in cases where the quality of the discharge complies with applicable receiving water quality objectives, is prohibited. Allowances for dilution may be made at the discretion of the Regional Board. Consideration would include streamflow data, the degree of treatment provided and safety measures to ensure reliability of facility performance. As an example, discharge of secondary effluent would probably be permitted if streamflow provided 100:1 dilution capability.
- The dumping, deposition, or discharge of waste directly into waters of the state, or adjacent to such waters in any manner which may permit its being transported into the waters, is prohibited unless authorized by the Regional Board.
- Any discharge to a storm water conveyance system that is not composed entirely of "storm water" is prohibited unless authorized by the Regional Board. [The federal regulations, 40 CFR 122.26(b)(13), define storm water as storm water runoff, snow melt runoff, and surface runoff and drainage. 40 CFR 122.26(b)(2) defines an illicit discharge as any discharge to a storm water conveyance system that is not composed entirely of storm water except discharges pursuant to a NPDES permit and discharges resulting from fire fighting activities.] [Section 122.26 amended at 56 FR 56553, November 5, 1991; 57 FR 11412, April 2, 1992].
- The unauthorized discharge of treated or untreated sewage to waters of the state or to a storm water conveyance system is prohibited.

Existing discharges are violating one or more of these of these Basin Plan prohibitions. The existing Basin Plan prohibitions are consistent with the TMDLs, WLAs, and LAs. If necessary, the San Diego Water Board may amend the Basin Plan to revise current waste discharge prohibitions or include new waste discharge prohibitions. The controllable sources must comply with the Basin Plan waste discharge prohibitions.

⁴¹ Authorized pursuant to Water Code section 13243

(2) Waste Discharge Requirements

The primary regulatory authority used by the San Diego Water Board to protect water resources and water quality in the San Diego Region is the issuance of waste discharge requirements (WDRs).⁴² The San Diego Water Board will issue, or revise and re-issue WDRs to point sources and/or nonpoint sources in the San Diego Region to be consistent with the TMDLs, WLAs, and LAs. The controllable sources regulated under WDRs must comply with the requirements to be consistent with the TMDLs, WLAs, and LAs. Specific San Diego Water Board actions with regard to WDRs for point sources and nonpoint sources are discussed in the following subsections.

(A) Point Sources

The San Diego Water Board regulates discharges from point sources to surface waters with WDRs that implement federal NPDES regulations (NPDES requirements). NPDES requirements must contain water quality-based effluent limitations (WQBELs) consistent with the assumptions and requirements of the WLAs of any applicable TMDL.⁴³

When developing WQBELs to be incorporated in to NPDES requirements, the following summarizes the requirements and assumptions included in the calculation of the TMDLs, WLAs, and LAs that should be considered:

Numeric Targets

- The numeric targets consist of the numeric WQOs from the Basin Plan and/or Ocean Plan and an allowable exceedance frequency.
- The numeric targets for the wet weather TMDLs consist of the REC-1 single sample maximum WQOs and a 22 percent allowable exceedance frequency.
- The numeric targets for dry weather TMDLs consist of the REC-1 30-day geometric metric mean WQOs and a 0 percent allowable exceedance frequency.
- The TMDL calculations are based on either the single sample maximum WQO (for wet weather) or 30-day geometric mean WQOs (for dry weather), but both the single sample maximum and 30-day geometric mean numeric WQOs and allowable exceedance frequencies must be met in the receiving waters.
- The TMDLs, and in turn the WLAs for point sources and LAs for nonpoint sources, are assumed to be met when the numeric targets for all three indicator bacteria (fecal coliform, total coliform, and *Enterococcus*) are met in the receiving waters.

⁴² Authorized pursuant to Water Code sections 13263 and 13264

⁴³ Code of Federal Regulations Title 40 section 122.44(d)(1)(vii)(B)

Critical Conditions

- The mass-load based TMDLs were calculated under critical conditions consisting of flows generated during a critical wet year and estimation of existing and allowable loads at a critical location.
- The flow from the critical wet year is a “worst case” annual wet weather flow and loading scenario. Actual annual wet weather flow and loading will vary from year to year.
- The mass-load based TMDLs calculated at the critical location are dependent on the flow, which can vary from year to year, but the numeric targets will not vary. When the numeric targets are met in the receiving water, the TMDLs are assumed to be met.
- The mass-load based TMDLs, WLAs, and LAs are calculated for the critical location, but the appropriate numeric targets (based on freshwater and/or saltwater REC-1 WQOs and allowable exceedance frequencies) must be met throughout the waterbodies addressed by these TMDLs.

Linkage Analysis

- The linkage analysis was performed by utilizing calibrated and validated models to predict flow from surface runoff and predict bacteria densities under the critical conditions (i.e., during the critical wet year at the critical location). Existing mass loads and allowable mass loads (i.e., TMDLs) were calculated for each watershed. The existing mass loads were calculated based on model-predicted flow and model-predicted bacteria densities. The allowable mass loads (i.e., TMDLs) were calculated based on model-predicted flow and the numeric targets (i.e., numeric WQOs and allowable exceedance frequencies).
- The wet weather existing mass loads and allowable mass loads (i.e., wet weather mass-load based TMDLs) are calculated assuming surface runoff is generated by rainfall from storm events and discharged from all land use categories to receiving waters.
- The dry weather existing mass loads and allowable mass loads (i.e., dry weather mass-load based TMDLs) are calculated assuming surface runoff is generated only by anthropogenic activities and discharged from specific land use categories to receiving waters. The possible contribution of subsurface or groundwater flows to bacteria loads in receiving waters during dry weather was not accounted for in any land use category.

Allocations

- Each mass-load based TMDL is allocated to known point sources and nonpoint sources. Wasteload allocations (WLAs) are assigned to point sources, and load allocations (LAs) are assigned to nonpoint sources. WLAs and LAs are the maximum load a source can discharge and still achieve the TMDL in the receiving water.
- The TMDLs, and in turn the WLAs for point sources and LAs for nonpoint sources, are assumed to be met when the numeric targets are met in the receiving waters.
- The sources were identified based on land use and grouped in to Municipal MS4, Caltrans MS4 (Caltrans), Agriculture, and Open Space categories. The Municipal MS4 and Caltrans land use categories are point sources, and the Agriculture and Open Space land use categories are nonpoint sources.
- Sources that are not identified are assumed to be assigned a zero allowable load as part of the mass-load based TMDL (i.e., WLA = 0 or LA = 0). In other words, discharges of pollutant loads from these sources are not expected or allowed as part of the TMDLs.

- Sources that are assigned an allowable load equal to the existing mass load as part of the mass-load based TMDL (i.e., WLA or LA = existing mass load) are not expected or allowed to increase their mass load in the future. In other words, discharges of pollutant loads (i.e., flows and bacteria densities) from these sources are not allowed to increase.
- The allocation of the dry weather mass-load based TMDLs assumes that no surface runoff discharge to receiving waters occurs from Caltrans, Agriculture, or Open Space land use categories (i.e., $WLA_{\text{Caltrans}} = 0$, $LA_{\text{Agriculture}} = 0$, and $LA_{\text{OpenSpace}} = 0$), meaning the entire dry weather mass-load based TMDL (i.e., allowable mass load) is allocated to Municipal MS4 land use categories (i.e., $WLA_{\text{MS4}} = \text{TMDL}$) (see Tables 7-45 through 7-47).
- The allocation of the wet weather mass-load based TMDLs assumes surface runoff discharge occurs from all land use categories, and allocated according to the following steps (see Tables 7-41 through 7-44):
 - 1) Sources are separated into controllable and uncontrollable sources. Discharges from Municipal MS4, Caltrans, and Agriculture land use categories are assumed to be controllable (i.e., subject to regulation), and discharges from Open Space land use categories are assumed to be uncontrollable (i.e., not subject to regulation).
 - 2) Because discharges from Open Space land use categories are uncontrollable (i.e., not subject to regulation), the LAs for Open Space land use categories are set equal to the existing mass loads calculated under the critical conditions.
 - 3) For discharges from controllable land use categories that do not contribute more than 5 percent of the total existing mass load for all three indicator bacteria, the WLA or LA is set equal to the existing mass loads from those land uses calculated under the critical conditions.
 - 4) After the WLAs and LAs are assigned based on steps 2 and 3, the remaining portion of the mass-load based TMDL is assigned to discharges from controllable land use categories that contribute more than 5 percent of the total existing mass load for all three indicator bacteria. The allowable mass load for each source (WLA or LA) is calculated based on the ratio of the existing mass loads from those sources relative to each other.

Load Reductions

- The load reductions required to meet the mass-load based TMDLs, WLAs, and LAs are based on reducing the loads compared to pollutant loads from 2001 to 2002.
- Load reductions for each source are calculated based on the difference between the existing mass load and the mass-load based WLA or LA for each source (see Tables 7-41 through 7-47).
- WLAs and LAs that are set equal to the existing mass loads do not require load reductions to be calculated, but this also means that existing mass loads from those sources cannot increase over time (i.e., pollutant loads should be less than or equal to pollutant loads relative to 2001 to 2002).
- The load reductions needed to meet the WLAs for point sources and LAs for nonpoint sources are assumed to be achieved when the numeric targets are met in the receiving waters.

The persons identified as responsible for point source discharges causing or contributing to bacteria impairments at the beaches and creeks addressed in these TMDLs include:

- Phase I MS4s,
- Phase II MS4s,
- Caltrans,
- POTWs and wastewater collection systems, and
- CAFOs.

According to Tables 7-41 through 7-47, Municipal (Phase I and Phase II) MS4s and Caltrans are the only point sources that have been assigned WLAs. POTWs,⁴⁴ CAFOs, and any other unidentified point sources were not assigned WLAs, which is equivalent to being assigned a WLA of zero. All these identified point sources are subject to NPDES regulations.

In order for the WDRs, NPDES requirements, and discharges from these point sources to be consistent with the TMDLs and WLAs, the San Diego Water Board will issue or revise and re-issue the WDRs for these point sources as follows:

(i) Phase I MS4s

The TMDLs and Municipal MS4 WLAs, with respect to discharges from Phase I MS4s, will be implemented primarily by revising and re-issuing the existing NPDES requirements that have been issued for Phase I MS4 discharges.

The Phase I MS4s subject to these TMDLs are regulated under San Diego Water Board WDRs that implement NPDES requirements.⁴⁵ The NPDES requirements regulating the Phase I MS4s include discharge prohibitions and receiving water limitations that are applicable to the implementation of these TMDLs, as summarized below:

- Discharges from MS4s are subject to all Basin Plan prohibitions.
- Discharges from MS4s that cause or contribute to the violation of water quality standards (designated beneficial uses and water quality objectives developed to protect beneficial uses) are prohibited.
- Discharges into and from MS4s in a manner causing, or threatening to cause, a condition of pollution, contamination, or nuisance, in waters of the state are prohibited.
- Effectively prohibit all types of non-storm water discharges into the MS4 unless such discharges are either authorized by separate NPDES requirements, or not prohibited (i.e., exempted) by the NPDES requirements regulating the MS4. Exempted non-storm water discharges into the MS4 are not prohibited unless the discharge category is identified as a significant source of pollutants to waters of the United States.

⁴⁴ Not including Padre Dam, which has been allocated a fecal coliform TMDL based on the effluent limitations in the WDRs for Padre Dam

⁴⁵ Phase I MS4s in Orange County are regulated under San Diego Water Board Order No. R9-2002-0001 or subsequent orders; Phase I MS4s in San Diego County are regulated under San Diego Water Board Order No. R9-2007-0001 or subsequent orders.

The available data reported by the Phase I MS4s and the results of the technical TMDL analysis indicate that discharges into and from MS4s are in violation of the discharge prohibitions and receiving water limitations above. Enforcement of the current discharge prohibitions and receiving water limitations is an action that the San Diego Water Board can immediately implement to compel the MS4s to reduce discharge of bacteria to the receiving waters.

In addition to the discharge prohibitions and receiving water limitations, WQBELs consistent with the assumptions and requirements of the WLAs of any applicable TMDL must also be incorporated into the NPDES requirements. The San Diego Water Board will revise and re-issue the WDRs and NPDES requirements for Phase I MS4s to incorporate the following:

- WQBELs consistent with the requirements and assumptions of the Municipal MS4 WLAs. WQBELs may be expressed as numeric effluent limitations, when feasible, and/or as a BMP program of expanded or better-tailored BMPs.⁴⁶
- If the WQBELs include a BMP program, periodic reporting requirements on BMP planning, implementation, and effectiveness in improving water quality at impaired beaches and creeks (i.e., progress reports). Progress reports will also be required to include water quality monitoring results. Progress reports will be required as long as necessary to ensure that the beneficial uses of the impaired waterbodies have been restored and maintained.
- Compliance schedule for Phase I MS4s to attain the MS4 WLAs and TMDLs in the receiving waters.

The WQBELs will likely consist of receiving water limitations (based on the numeric targets) and require the implementation of a BMP program to achieve the TMDLs in the receiving waters. The Phase I MS4s will be required to submit Bacteria Load Reduction Plans (BLRPs) or Comprehensive Load Reduction Plans (CLRPs) outlining a proposed BMP program that will be capable of achieving the necessary load reductions required to attain the TMDLs in the receiving waters, acceptable to the San Diego Water Board, within 18 months after the effective date of these TMDLs.⁴⁷ The San Diego Water Board will require the BLRPs or CLRPs to be developed on a watershed or region wide scale. The BLRPs or CLRPs should be developed and incorporated as part of the Watershed Runoff Management Programs required under the Phase I MS4 NPDES requirements. Ideally, the Phase I MS4s and Caltrans will develop and coordinate the elements of their BLRPs or CLRPs together.

If the receiving water limitations (based on the numeric targets) are met in the receiving waters, the assumption will be that the MS4s have met their WLAs. If, however, the receiving water limitations are not being met in the receiving waters, the Phase I MS4s will be responsible for reducing their bacteria loads and/or demonstrating that controllable anthropogenic discharges from the Phase I MS4s are not causing the exceedances, as outlined below in the Monitoring for TMDL Compliance section below.

(ii) Phase II MS4s

The TMDLs and MS4 WLAs, with respect to discharges from Phase II MS4s, will be implemented primarily by requiring compliance with the existing general WDRs and NPDES requirements that have been issued for Phase II MS4 discharges. Phase II MS4s are subject to regulation under State Water Board general WDRs implementing NPDES requirements.⁴⁸

⁴⁶ Code of Federal Regulations Title 40 section 122.44(k)(2)&(3)

⁴⁷ The effective date is the date the Office of Administrative Law approves this Basin Plan amendment.

⁴⁸ Phase II MS4s in the San Diego Region are subject to regulation under State Water Board Order No. 2003-0005-DWQ, or subsequent orders.

Owners and operators of Phase II MS4s in the watersheds subject to these TMDLs, identified by the San Diego Water Board as significant sources of bacteria discharging to the receiving waters and/or Phase I MS4s, will be required to submit a Notice of Intent⁴⁹ to comply with the NPDES requirements in the State Water Board general WDRs as soon as possible after the effective date of these TMDLs.⁵⁰ Once enrolled under the general WDRs, Phase II MS4 owners and operators are required to comply with the provisions of the State Water Board general WDRs and NPDES requirements to reduce the discharge of bacteria as specified in their Stormwater Management Plans/Programs (SWMPs).

For any individual Phase II MS4s that are identified as a significant source of pollutants, the San Diego Water Board may also issue individual WDRs requiring the implementation of WQBELs that are consistent with the requirements and assumptions of the Municipal MS4 WLAs. Upon issuance of such individual WDRs by the San Diego Water Board, the State Water Board general WDRs for Phase II MS4s shall no longer regulate the affected individual Phase II MS4s.⁵¹

Similarly, for any category of Phase II MS4s that are identified as a significant source of pollutants, the San Diego Water Board may issue general WDRs requiring the implementation of WQBELs that are consistent with the requirements and assumptions of the Municipal MS4 WLAs above. Upon issuance of such general WDRs by the San Diego Water Board, the State Water Board general WDRs for Phase II MS4s shall no longer regulate the affected category of Phase II MS4s.⁵²

In the event that the San Diego Water Board issues individual or general WDRs for Phase II MS4s in the San Diego Region, the WQBELs will likely consist of receiving water limitations (based on the numeric targets) and require the implementation of a BMP program to achieve the TMDLs in the receiving waters. The Phase II MS4s will likely be required to submit Bacteria Load Reduction Plans (BLRPs) or Comprehensive Load Reduction Plans (CLRPs) outlining a proposed BMP program that will be capable of achieving the necessary load reductions required to attain the TMDLs in the receiving water, acceptable to the San Diego Water Board. When and where possible, the San Diego Water Board will require the BLRPs or CLRPs to be developed on a watershed or region wide scale and have the Phase II MS4 BMP programs coordinate with the BMPs programs for Phase I MS4s and Caltrans.

If the receiving water limitations (based on the numeric targets) are met in the receiving waters, the assumption will be that the Phase II MS4s have met their WLAs. If, however, the receiving water limitations are not being met in the receiving waters and one or more Phase II MS4 dischargers are identified as sources of bacteria causing exceedances, the specific Phase II MS4s will be responsible for reducing their bacteria loads and/or demonstrating that controllable anthropogenic discharges from those specific Phase II MS4s are not causing the exceedances, as outlined below in the Monitoring for TMDL Compliance section below.

(iii) Caltrans

The TMDLs and Caltrans WLAs will be implemented primarily by revising and re-issuing the existing NPDES requirements that have been issued for Caltrans discharges.

Caltrans is regulated under State Water Board general WDRs that implement NPDES requirements.⁵³ The San Diego Water Board will request the State Water Board to revise and re-issue the WDRs and NPDES requirements to incorporate the following for Caltrans discharges in the San Diego Region:

- WQBELs consistent with the requirements and assumptions of the Caltrans WLAs. WQBELs may be expressed as numeric effluent limitations, when feasible, and/or as a BMP program of expanded or better-tailored BMPs.⁵⁴

⁴⁹ The Notice of Intent, or NOI, is attachment 7 to Order No. 2003-0005-DWQ.

⁵⁰ The effective date is the date the Office of Administrative Law approves this Basin Plan amendment.

⁵¹ As authorized under State Water Board Order No. 2003-0005-DWQ, section G.

⁵² Ibid.

⁵³ Caltrans is subject to regulation under State Water Board Order No. 99-06-DWQ, and subsequent orders.

⁵⁴ Code of Federal Regulations Title 40 section 122.44(k)(2)&(3)

- If the WQBELs include a BMP program, periodic reporting requirements on BMP planning, implementation, and effectiveness in improving water quality at impaired beaches and creeks (i.e., progress reports). Progress reports will also be required to include water quality monitoring results. Progress reports will be required as long as necessary to ensure that the beneficial uses of the impaired waterbodies have been restored and maintained.
- Compliance schedule for Caltrans to attain the Caltrans WLAs and TMDLs in the receiving waters.

The WQBELs will likely consist of receiving water limitations (based on the numeric targets) and require the implementation of a BMP program to achieve TMDLs in the receiving waters. Caltrans will be required to submit Bacteria Load Reduction Plans (BLRPs) or Comprehensive Load Reduction Plans (CLRPs) outlining a proposed BMP program that will be capable of attaining the TMDLs in the receiving waters, acceptable to the San Diego Water Board, within 18 months after the effective date of these TMDLs.⁵⁵ The San Diego Water Board will require the BLRPs or CLRPs to be developed on a watershed or region wide scale. Ideally, Caltrans and the Phase I MS4s will develop and coordinate the elements of their BLRPs or CLRPs together.

If the receiving water limitations (based on the numeric targets) are met in the receiving waters, the assumption will be that Caltrans has met its WLAs. If, however, the receiving water limitations are not being met in the receiving waters, and Caltrans MS4s are identified as a source of bacteria causing exceedances, Caltrans will be responsible for reducing its bacteria loads and/or demonstrating that controllable anthropogenic discharges from the Caltrans MS4s are not causing the exceedances, as outlined below in the Monitoring for TMDL Compliance section below.

(iv) Publicly Owned Treatment Works and Wastewater Collection Systems

The TMDLs, with respect to discharges from POTWs and wastewater collection systems, will be implemented primarily by requiring compliance with any existing individual and/or general WDRs and NPDES requirements that have been issued. POTWs are subject to regulation under individual WDRs that implement NPDES requirements. Wastewater collection systems are subject to regulation under general WDRs issued by the State Water Board and San Diego Water Board.⁵⁶

Because POTWs and wastewater collection systems have been assigned WLAs of zero,⁵⁷ no discharges of bacteria are expected or allowed under the wet weather TMDLs or dry weather TMDLs. If discharges of bacteria from POTWs and/or wastewater collection systems do occur as a result of sanitary sewer overflows and result in WQO exceedances, these exceedances will not apply to the compliance status of other dischargers.

If necessary, individual WDRs for POTWs and/or the San Diego Water Board WDRs for wastewater collection systems can be revised to require more aggressive monitoring, maintenance, and repair schedules to ensure discharges of bacteria wasteloads to surface waters are eliminated.

⁵⁵ The effective date is the date the Office of Administrative Law approves this Basin Plan amendment.

⁵⁶ State Water Board Order No. 2006-0003-DWQ and San Diego Water Board Order No. R9-2007-0005

⁵⁷ With the exception of Padre Dam, which has a fecal coliform mass-load based WLA that is calculated based on numeric effluent limitations derived from the REC-1 WQOs in the Basin Plan.

(v) Concentrated Animal Feeding Operations

The TMDLs, with respect to discharges from CAFOs, will be implemented primarily by requiring compliance with any existing individual and/or general WDRs and NPDES requirements that have been issued. CAFOs that discharge to surface waters are subject to regulation under general WDRs that implement NPDES requirements.

Because CAFOs have been assigned WLAs of zero, no discharges of bacteria are expected or allowed under the wet weather TMDLs or dry weather TMDLs.

If necessary, the general WDRs and NPDES requirements for CAFOs can be revised to require more aggressive monitoring, maintenance, and repair schedules to ensure discharges of bacteria wasteloads to surface waters are minimized and/or eliminated.

(vi) Other Unidentified Point Sources

Unidentified point sources have not been assigned WLAs, which is equivalent to being assigned a WLA of zero. No discharges of bacteria are expected or allowed from unidentified point sources under the wet weather TMDLs or dry weather TMDLs.

Therefore, the TMDLs, with respect to discharges from unidentified point sources to surface waters, will be implemented primarily by issuing WDRs implementing NPDES requirements, or requiring the point sources to cease their discharges.

(B) Nonpoint Sources

The persons identified as responsible for controllable nonpoint source bacteria discharges causing or contributing to bacteria impairments at the beaches and creeks in these watersheds include the owners and operators of the following:

- agricultural facilities,
- nurseries,
- dairy/intensive livestock facilities,
- horse ranches,
- manure composting and soil amendment operations not regulated by NPDES requirements, and
- individual septic systems.

Agriculture (including nurseries), dairy/livestock, and horse ranch land uses (collectively called “agriculture” land uses) are controllable nonpoint sources that have been assigned LAs, as shown in Tables 7-41 through 7-47. Manure composting operations, soil amendment operations, and individual septic systems that are not part of agriculture land uses, and any other unidentified controllable nonpoint sources were not assigned LAs, which is equivalent to being assigned a LA of zero. Any controllable nonpoint source that has not been assigned a LA or has a LA of zero is not expected or allowed to discharge a pollutant load as part of the TMDL.

Controllable nonpoint source discharges are present in most watersheds, however, in only four watersheds do these discharges require load reductions to meet the Agriculture LAs. These watersheds are the Lower San Juan HSA, San Luis Rey HU, San Marcos HA, and San Dieguito HU watersheds (see Tables 7-41 through 7-44).

If individual or general WDRs are developed and issued to controllable nonpoint sources, the WDRs should incorporate one or more the following:

- Effluent limitations that are consistent with the requirements and assumptions of the nonpoint source LAs. Effluent limitations should be expressed as numeric effluent limitations, if feasible, and/or as a BMP program.
- Periodic reporting requirements on BMP planning, implementation, and effectiveness in improving the water quality of discharges from the nonpoint source (i.e., progress reports). Progress reports will also be required to include water quality monitoring results. Progress reports will be required as long as necessary to ensure that the beneficial uses of the impaired waterbodies have been restored and maintained.
- Compliance schedule and/or implementation milestones.

The San Diego Water Board will work with the nonpoint source dischargers and/or stakeholders when developing the WDRs. When and where possible, the San Diego Water Board will have the nonpoint source BMP programs coordinate with the BMPs programs for Phase I MS4s and Caltrans.

If the receiving water limitations (based on the numeric targets) are met in the receiving waters, the assumption will be that controllable nonpoint sources have met their LAs. If, however, the receiving water limitations are not being met in the receiving waters, and one or more controllable nonpoint source dischargers are identified as sources of bacteria causing exceedances, the San Diego Water Board may regulate those identified nonpoint sources, as needed, with WDRs or other enforcement actions, and those nonpoint sources will be responsible for reducing their bacteria loads and/or demonstrating that discharges from those nonpoint sources are not causing the exceedances, as outlined below in the Monitoring for TMDL Compliance section below.

(3) Conditional Waivers of Waste Discharge Requirements

There are several types of point source discharges to land, as well as nonpoint source discharges to land and surface waters that may not have an adverse affect on the quality of the waters of the state, and/or are not readily amenable to regulation under WDRs. For these types of discharge, the San Diego Water Board has the authority to issue conditional waivers of WDRs.⁵⁸

There are controllable nonpoint source land uses (agriculture, horse ranches, and dairies/intensive livestock) that were identified in 8 watersheds that are contributing to the bacteria impairments. Four of the 8 watersheds were identified as requiring load reductions (Lower San Juan HSA, San Luis Rey HU, San Marcos HA, and San Dieguito HU) to meet the assigned wet weather Agriculture LAs.

In general, the San Diego Water Board utilizes conditional waivers of WDRs to address the discharges from controllable nonpoint sources. Development and enforcement of waiver conditions that are protective of water quality will likely be sufficient to implement the Agriculture LAs. The controllable nonpoint sources eligible for conditional waivers must comply with the conditions of the waiver to be consistent with the TMDLs and Agriculture LAs. Controllable nonpoint sources that do not comply with the waiver conditions are no longer eligible for the waiver and must either come into compliance with the waiver conditions, become regulated under WDRs, or cease any discharge of wastes to waters of the state.

⁵⁸ Authorized pursuant to Water Code section 13269

Currently, discharges from these controllable nonpoint sources may be eligible for one of the general conditional waivers of WDRs, which are currently provided in the Basin Plan.⁵⁹ Conditional waivers of WDRs may not exceed 5 years in duration, but may be revised and renewed, or may be terminated at any time.⁶⁰ The San Diego Water Board will implement the conditional waivers of WDRs applicable to the Agriculture land uses to be consistent with the TMDLs and Agriculture LAs.

Because the conditional waivers of WDRs that may be utilized to implement the Agriculture LAs are contained in the Basin Plan, any revision of the conditions will require a Basin Plan amendment. If needed, the San Diego Water Board may amend the Basin Plan to remove these conditional waivers of WDRs from the Basin Plan and re-issue the conditional waivers of WDRs as a general order to reduce the administrative requirements for revising waiver conditions.

As required, the effectiveness of the conditional waivers of WDRs must be evaluated at least once every 5 years. If the conditions in the waivers of WDRs are not sufficient to implement the TMDLs and Agriculture LAs, the San Diego Water Board will amend the waiver conditions to include more stringent conditions, including, but not limited to, additional BMP implementation, monitoring, and/or reporting.

If a conditional waiver of WDRs no longer appears to be effective in protecting water quality from discharges from specific nonpoint source facilities or category of nonpoint source facilities, the waiver may be terminated. For nonpoint source facilities that are no longer eligible for a conditional waiver of WDRs, they will need to be regulated under WDRs, or cease any discharges of waste to waters of the state.

(4) Enforcement Actions

The San Diego Water Board shall consider enforcement actions, as necessary, for any discharger failing to comply with applicable waiver conditions, WDRs, or Basin Plan waste discharge prohibitions.⁶¹ Enforcement actions can also be taken, as necessary, to control the discharge of bacteria to impaired beaches and creeks, to attain compliance with the assumptions and requirements of the TMDLs, WLAs, and LAs.

In order for implementation of the TMDLs to begin as soon as possible, the San Diego Water Board may issue enforcement actions, in lieu of or before revising and re-issuing general WDRs and NPDES requirements, for Phase I MS4s and Caltrans, directing them to begin implementing additional measures to restore compliance with the bacteria WQOs. Enforcement actions may also be issued to require the submission of Bacteria Load Reduction Plans (BLRPs) or Comprehensive Load Reduction Plans (CLRPs) to the San Diego Water Board within 18 months after the effective date of these TMDLs,⁶² or sooner. The San Diego Water Board will require the BLRPs or CLRPs to be developed on a watershed or region wide scale.

The San Diego Water Board will also issue enforcement actions, as necessary, to any other discharger that is identified by the San Diego Water Board and/or other parties as a significant source causing or contributing to the bacteria impairments in the waterbodies addressed in these TMDLs.

⁵⁹ The current general conditional waivers in the Basin Plan were adopted under San Diego Water Board Resolution No. R9-2007-0104. These waivers will expire December 31, 2012. Conditional Waiver No. 3 (Animal Operations) and Conditional Waiver No. 4 (Agriculture and Nursery Operations) may be utilized to implement the Agriculture LAs. Future iterations of these conditional waivers may be issued in a separate implementing order and removed from the Basin Plan.

⁶⁰ Pursuant to Water Code section 13269(a)(2)

⁶¹ Authorized pursuant to Water Code sections 13300-13304, 13308, 13350, 13385, and/or 13399

⁶² The effective date is the date the Office of Administrative Law approves this Basin Plan amendment.

(5) Investigative Orders

The San Diego Water Board has the authority to require any state or local agency to investigate and report on any technical factors involved in water quality control or to obtain and submit analyses of water.⁶³ The San Diego Water Board has the authority to require technical or monitoring program reports from persons who have discharged or are discharging waste that could affect the quality of the waters in the San Diego Region.⁶⁴ The San Diego Water Board also has the authority to establish monitoring and recordkeeping requirements for discharges regulated under NPDES requirements.⁶⁵

Investigative orders may be issued requiring the submission of Bacteria Load Reduction Plans (BLRPs) or Comprehensive Load Reduction Plans (CLRPs), acceptable to the San Diego Water Board, within 18 months after the effective date of these TMDLs,⁶⁶ or sooner. The San Diego Water Board will require the BLRPs or CLRPs to be developed on a watershed or region wide scale. The San Diego Water Board may require the Phase I MS4s and Caltrans to develop and coordinate the elements of their BLRPs or CLRPs together. The BLRPs or CLRPs will be incorporated into the WDRs and NPDES requirements.

The San Diego Water Board may issue subsequent investigative orders to confirm items in the BLRPs or CLRPs. The BLRPs or CLRPs must be capable of achieving the WLAs for the bacteria TMDLs. The CLRPs must also be capable of restoring the beneficial uses in receiving waters for other impairing pollutants in the watershed, and achieving the goals and objectives of any other water quality improvement projects included in the CLRPs within the time frame of the compliance schedule.

The San Diego Water Board will also issue investigative orders requiring BLRPs or CLRPs, or other technical or monitoring program reports, as necessary, to any other discharger that is identified by the San Diego Water Board or other parties as a significant source causing or contributing to the bacteria impairments in the waterbodies addressed in these TMDLs.

(6) Basin Plan Amendments

As the implementation of these TMDLs progress, the San Diego Water Board recognizes that revisions to the Basin Plan may be necessary in the future. The San Diego Water Board will initiate a Basin Plan amendment project to revise the requirements and/or provisions for implementing these TMDLs within 5 years from the effective date of this Basin Plan amendment or earlier if all the following conditions are met:

- Sufficient data are collected to provide the basis for the Basin Plan amendment.
- A report is submitted to the San Diego Water Board documenting the findings from the collected data.
- A request is submitted to the San Diego Water Board with specific revisions proposed to the Basin Plan, and the documentation supporting such revisions.

The San Diego Water Board will work with the project proponents to ensure that the data and documentation will be adequate for the initiation of the Basin Plan amendment. The San Diego Water Board staff will be responsible for taking the Basin Plan amendment project through the administrative and regulatory processes for adoption by the San Diego Water Board, and approval by the State Water Board, OAL, and USEPA.

⁶³ Authorized pursuant to Water Code section 13225

⁶⁴ Authorized pursuant to Water Code section 13267

⁶⁵ Authorized pursuant to Water Code section 13383

⁶⁶ The effective date is the date the Office of Administrative Law approves this Basin Plan amendment.

If no Basin Plan amendment has been initiated within 5 years of the effective date of this TMDL Basin Plan amendment, and the Executive Officer determines, with Regional Board concurrence, that insufficient data exist to support the initiation of a Basin Plan amendment, a subsequent Basin Plan amendment to revise the requirements and/or provisions for the implementation of these TMDLs will not be initiated until the Executive Officer determines the conditions specified above are met.

(7) Other Actions

For these TMDLs, the San Diego Water Board shall recommend that the State Water Board assign a high priority to awarding grant funding⁶⁷ for projects to implement the bacteria TMDLs. Special emphasis will be given to projects that can achieve quantifiable bacteria load reductions consistent with the specific bacteria TMDLs, WLAs, and LAs.

Implementation of these TMDLs by the San Diego Water Board should not require any special studies to be conducted by the dischargers or other entities. The San Diego Water Board, however, will encourage and support any special studies proposed and undertaken by the dischargers or other entities that will provide information to refine and improve the implementation of these TMDLs. The San Diego Water Board may develop agreements (e.g., a Memorandum of Understanding) with one or more entities to support and use the findings from any special studies that may be conducted. Proposing a special study project and initiating an agreement with the San Diego Water Board to use the results of the study to modify this TMDL Implementation Plan is the responsibility of the project proponent(s).

(i) Monitoring for TMDL Compliance and Compliance Assessment

An essential component of implementation is water quality monitoring. Monitoring is needed to evaluate the progress toward attainment of the TMDLs and restoring the beneficial uses in the receiving waters. When all discharges from controllable sources meet their assigned WLAs and LAs, and the numeric targets (i.e., numeric WQOs and allowable exceedance frequencies) are also met in the receiving waters, compliance with the TMDLs will be achieved. Additionally, sufficient water quality data are necessary to support the removal of a waterbody from the 303(d) List. Water quality data can also be used identify additional regulatory actions that may need to be implemented by the San Diego Water Board to restore and protect beneficial uses.

Monitoring for compliance will initially be conducted by the Phase I MS4s and Caltrans. The minimum components for any monitoring program that will be used to evaluate progress toward attainment of the TMDLs should include the following:

- For beaches addressed by these TMDLs, monitoring locations should consist of, at a minimum, the same locations used to collect data required under MS4 NPDES monitoring requirements and beach monitoring for Health and Safety Code section 115880.⁶⁸ If exceedances of the receiving water limitations are observed in the monitoring data, additional monitoring locations and/or other source identification methods must be implemented to identify the sources causing the exceedances. The additional monitoring locations and/or other source identification methods must also be used to demonstrate that the bacteria loads from the identified sources have been addressed and are no longer causing exceedances in the receiving waters.

⁶⁷ The State Water Board administers the awarding of grants funded from Proposition 13, Proposition 50, Clean Water Act section 319(h) and other federal appropriations to projects that can result in measurable improvements in water quality, watershed condition, and/or capacity for effective watershed management. Many of these grant fund programs have specific set-asides for expenditures in the areas of watershed management and TMDL project implementation for non-point source pollution.

⁶⁸ Commonly referred to as AB 411 monitoring

- For creeks addressed by these TMDLs, monitoring locations should consist of, at a minimum, a location at or near the mouth of the creek (e.g., Mass Loading Station or Mass Emission Station) and one or more locations upstream of the mouth (e.g., Watershed Assessment Stations). If exceedances of the receiving water limitations are observed in the monitoring data, additional monitoring locations and/or other source identification methods must be implemented to identify the sources causing the exceedances. The additional monitoring locations and/or other source identification methods must also be used to demonstrate that the bacteria loads from the identified sources have been addressed and are no longer causing exceedances in the receiving waters.
- Because there are dry weather and wet weather TMDLs, monitoring under both conditions is needed. Wet weather⁶⁹ monitoring should occur at least once within 24 hours of the end of a storm event⁷⁰ that occurs during the rainy season (i.e., October 1 through April 30). Dry weather⁷¹ monitoring should occur at least on a monthly basis, and may be required more often during the summer months (e.g., weekly) when the REC-1 and REC-2 beneficial uses occur most frequently in the creeks and at the beaches.

Compliance with the TMDLs, WLAs, and LAs will be assessed primarily by comparing receiving water indicator bacteria results from the monitoring locations outlined above with receiving water limitations expressed in terms of the appropriate numeric REC-1 WQOs and allowable exceedance frequencies of the appropriate numeric REC-1 WQOs. The appropriate numeric WQOs and allowable exceedance frequencies are dependent upon the type of receiving water (i.e., beach or creek) and weather conditions (i.e., dry weather or wet weather), as shown in Tables 7-48 and 7-49.

Table 7-48. Receiving Water Limitations for Beaches

Indicator Bacteria	Wet Weather Days ^a		Dry Weather Days ^b	
	Wet Weather Numeric Objective ^c (MPN/100mL)	Wet Weather Allowable Exceedance Frequency ^d	Dry Weather Numeric Objective ^e (MPN/100mL)	Dry Weather Allowable Exceedance Frequency
Fecal Coliform	400	22%	200	0%
Total Coliform	10,000	22%	1,000	0%
Enterococcus	104	22%	35	0%

a. Wet weather days defined as days with rainfall events of 0.2 inches or greater and the following 72 hours.

b. Dry weather days defined as days with less than 0.2 inch of rainfall observed on each of the previous 3 days.

c. Wet weather numeric objectives based on the single sample maximum water quality objectives in the California Ocean Plan (2005). Compliance with the wet weather TMDLs in the receiving water is based on the frequency that the wet weather days in any given year exceed the wet weather numeric objective, but 30-day geometric mean must also be met.

d. The wet weather allowable exceedance frequency is set at 22%. In the calculation of the wet weather TMDLs, the San Diego Regional Board chose to apply the 22 percent allowable exceedance frequency as determined for Leo Carillo Beach in Los Angeles County. At the time the wet weather watershed model was developed, the 22 percent exceedance frequency from Los Angeles County was the only reference beach exceedance frequency available. The 22 percent allowable exceedance frequency used to calculate the wet weather TMDLs is justified because the San Diego Region watersheds' exceedance frequencies will likely be close to the value calculated for Leo Carillo Beach, and is consistent with the exceedance frequency that was applied by the Los Angeles Regional Board.

e. Dry weather numeric objectives based on the 30-day geometric mean water quality objectives in the California Ocean Plan (2005). Compliance with the dry weather TMDLs in the receiving water is based on the frequency that the dry weather days in any given year exceed the dry weather numeric objective.

⁶⁹ Defined as days with a storm with at least 0.2 inches of rainfall and the 72 hour period after the storm event

⁷⁰ The end of a storm event is when there is no more precipitation

⁷¹ Defined as days with less than 0.2 inches of rainfall on each of the previous three days

Table 7-49. Receiving Water Limitations for Creeks

Indicator Bacteria	Wet Weather Days ^a		Dry Weather Days ^b	
	Wet Weather Numeric Objective ^c (MPN/100mL)	Wet Weather Allowable Exceedance Frequency ^d	Dry Weather Numeric Objective ^e (MPN/100mL)	Dry Weather Allowable Exceedance Frequency
Fecal Coliform	400	22%	200	0%
Enterococcus	61 (104) ^f	22%	33	0%

a. Wet weather days defined as days with rainfall events of 0.2 inches or greater and the following 72 hours.

b. Dry weather days defined as days with less than 0.2 inch of rainfall observed on each of the previous 3 days.

c. Wet weather numeric objectives based on the single sample maximum (or equivalent) water quality objectives in the Water Quality Control Plan for the San Diego Basin (1994). Compliance with the wet weather TMDLs in the receiving water is based on the frequency that the wet weather days in any given year exceed the wet weather numeric objective, but 30-day geometric mean must also be met.

d. The wet weather allowable exceedance frequency is set at 22%. In the calculation of the wet weather TMDLs, the San Diego Regional Board chose to apply the 22 percent allowable exceedance frequency as determined for Leo Carillo Beach in Los Angeles County. At the time the wet weather watershed model was developed, the 22 percent exceedance frequency from Los Angeles County was the only reference beach exceedance frequency available. The 22 percent allowable exceedance frequency used to calculate the wet weather TMDLs is justified because the San Diego Region watersheds' exceedance frequencies will likely be close to the value calculated for Leo Carillo Beach, and is consistent with the exceedance frequency that was applied by the Los Angeles Regional Board.

e. Dry weather numeric objectives based on the 30-day geometric mean (or equivalent) water quality objectives in Water Quality Control Plan for the San Diego Basin (1994). Compliance with the dry weather TMDLs in the receiving water is based on the frequency that the dry weather days in any given year exceed the dry weather numeric objective.

f. A wet weather numeric objective for *Enterococcus* of 104 MPN/100mL may be applied as a receiving water limitation for creeks, instead of 61 MPN/100mL, if one or more of the creeks addressed by these TMDLs (San Juan Creek, Aliso Creek, Tecolote Creek, Forrester Creek, San Diego River, and/or Chollas Creek) is designated with a "moderately to lightly used area" or less frequent usage frequency in the Basin Plan. Otherwise, the wet weather numeric objective of 61 MPN/100mL for *Enterococcus* will be used to assess compliance with the wet weather allowable exceedance frequency.

At the end of the TMDL Compliance Schedules, which are given in the following section, the receiving waters must meet the receiving water limitations above to be considered in compliance with these TMDLs, WLAs, and LAs. Determination of compliance with the TMDLs will be assessed differently for dry weather and wet weather as follows:

1. **Compliance with Dry Weather TMDLs:** At the end of the dry weather TMDL compliance schedule, the bacteria densities in the receiving waters for all dry weather days⁷² must be less than or equal to the 30-day geometric mean REC-1 WQOs 100 percent of the time (i.e., dry weather days in a 30-day period shall not exceed the 30-day geometric mean REC-1 WQOs more than 0 percent of the time). In addition, the bacteria densities must be consistent with the single sample maximum REC-1 WQOs in the Ocean Plan for beaches, and the Basin Plan for creeks.

The method and number of samples needed for calculating the 30-day geometric mean should be consistent with the number of samples required by the Ocean Plan for beaches, and the Basin Plan for creeks. Analysis of the monitoring results should also be consistent with the methods given in the Water Quality Control Policy For Developing California's Clean Water Act Section 303(d) List.

⁷² Defined as days with less than 0.2 inches of rainfall on each of the previous three days

Because the dry weather TMDLs are assigned entirely to the Municipal MS4s as WLAs, the Municipal MS4s are assumed to be the only source of bacteria during dry weather (i.e., dry weather TMDL = MS4 WLA). Discharges from other controllable sources (i.e., Caltrans, Agriculture) during dry weather are not expected and/or not allowed (i.e., WLA = 0 or LA = 0). If at the end of the dry weather TMDL compliance schedule the receiving waters exceed the 30-day geometric mean REC-1 WQOs more than 0 percent of the time, the municipal Phase I MS4s are responsible for demonstrating their discharges into the receiving waters are not causing the exceedances, or they will be considered out of compliance. If controllable sources other than the Phase I MS4s are identified as causing the exceedances, and the Phase I MS4s have demonstrated they are not causing or contributing to the exceedances, the Phase I MS4s will not be considered out of compliance.

The Phase I MS4s may demonstrate that their discharges are not causing the exceedances in the receiving waters by providing data from their discharge points to the receiving waters, by providing data collected at jurisdictional boundaries, and/or by using other methods accepted by the San Diego Water Board. Otherwise, at the end of the dry weather TMDL compliance schedule, the municipal Phase I MS4s will be held responsible and considered out of compliance unless other information or evidence indicates another controllable or uncontrollable source is responsible for the exceedances in the receiving waters. If controllable sources other than discharges from the municipal Phase I MS4s are identified before or after the end of the dry weather TMDL Compliance Schedule as causing the exceedances, those controllable sources will be responsible for reducing their bacteria loads and/or demonstrating that discharges from those sources are not causing the exceedances. The San Diego Water Board shall implement additional actions (e.g., issue enforcement actions, amend existing NPDES requirements or conditional waivers), as needed, to bring all controllable sources into compliance with the dry weather TMDLs.

2. *Compliance with Wet Weather TMDLs:* At the end of the wet weather TMDL compliance schedule, the bacteria densities in the receiving waters for all wet weather days⁷³ cannot exceed the single sample maximum REC-1 WQOs more than the allowable exceedance frequency. In addition, the bacteria densities must be less than or equal to the 30-day geometric mean REC-1 WQOs 100 percent of the time (i.e., both dry and wet weather days in a 30-day period shall not exceed the 30-day geometric mean REC-1 WQOs more than 0 percent of the time).

As described in the minimum monitoring components above, wet weather samples should be collected within 24 hours of the end of a storm event that occurs during the rainy season (i.e., October 1 through April 30). At least one wet weather sample per storm is expected to be collected for each waterbody in each watershed (i.e., Pacific Ocean shoreline, creek mouth, and/or creek). Because of the many issues related to collecting wet weather samples from multiple sites within a short time frame, dischargers are expected to develop a wet weather monitoring and sampling approach in their BLRPs or CLRPs. If only one sample is collected for a storm event, the bacteria density for every wet weather day associated with that storm event shall be equal to the results from that one sample. If more than one sample is collected for a storm event, but not on a daily basis, the bacteria density for all the wet weather days not sampled shall be equal to the highest bacteria density result reported from samples collected. The exceedance frequency shall be calculated by dividing the number of wet weather days that exceed the single sample maximum REC-1 WQOs by the total number of wet weather days during the rainy season. If at the end of the wet weather TMDL Compliance Schedule the receiving waters exceed the single sample maximum REC-1 WQOs more than the allowable exceedance frequency, all controllable sources are responsible for demonstrating their discharges into the receiving waters are not causing the exceedances, or they will be considered out of compliance.

⁷³ Defined as days with a storm with at least 0.2 inches of rainfall and the 72 hour period after the storm event

The data collected for compliance with the dry weather TMDLs, described above, shall be used in addition to the data collected for wet weather with the wet weather TMDLs to calculate the wet weather 30-day geometric mean. If at the end of the wet weather TMDL Compliance Schedule the receiving waters exceed the 30-day geometric mean REC-1 WQOs at any time, all controllable sources are responsible for demonstrating their discharges into the receiving waters are not causing the exceedances, or they will be considered out of compliance.

Because the Phase I MS4s are located at the base of the watersheds and have been identified as the most significant controllable source of bacteria, the municipal Phase I MS4s will have the primary responsibility for monitoring the receiving waters. Caltrans will also have monitoring responsibilities. Phase II MS4s, agricultural dischargers, and other sources that are identified as significant sources (i.e., causing or contributing to exceedances in the receiving waters) will also be responsible for monitoring the receiving waters. The municipal Phase I MS4s and other dischargers are responsible for reducing their bacteria loads and/or demonstrating their discharges into the receiving waters are not causing the exceedances.

The municipal MS4s may demonstrate that their discharges are not causing the exceedances in the receiving waters by providing data from their discharge points to the receiving waters, by providing data collected at jurisdictional boundaries, and/or by using other methods accepted by the San Diego Water Board. Otherwise, at the end of the wet weather TMDL compliance schedule, the municipal Phase I MS4s will be held responsible and considered out of compliance unless other information or evidence indicates another controllable or uncontrollable source is responsible for the exceedances in the receiving waters. If controllable sources other than discharges from the municipal Phase I MS4s are identified before or after the end of the wet weather TMDL Compliance Schedules as causing the exceedances, those controllable sources will be responsible for reducing their bacteria loads and/or demonstrating that discharges from those sources are not causing the exceedances. If controllable sources other than the Phase I MS4s are identified as causing the exceedances, and the Phase I MS4s have demonstrated they are not causing or contributing to the exceedances, the Phase I MS4s will not be considered out of compliance. The San Diego Water Board shall implement additional actions (e.g., issue enforcement actions, amend existing NPDES requirements or conditional waivers), as needed, to bring all those controllable sources into compliance with the wet weather TMDLs.

Between the effective date of these TMDLs and the end of the TMDL Compliance Schedules, monitoring is also required to demonstrate progress toward achieving and complying with the TMDLs, WLAs, and LAs. Progress can be demonstrated with reductions in exceedance frequencies in the receiving waters until the allowable exceedance frequencies ultimately are achieved at the end of the TMDL Compliance Schedules. Demonstrating progress toward attaining the TMDLs in the receiving waters will be assessed differently for dry weather and wet weather as follows:

1. *Measuring Progress Toward Attaining Dry Weather TMDLs:* For the dry weather TMDLs, available historical monitoring data from the years 1996-2002 should be used to calculate the “existing” dry weather exceedance frequency of the 30-day geometric mean REC-1 WQOs for each watershed. “Existing” dry weather exceedance frequencies may be calculated separately for each impaired waterbody listed, or an “existing” dry weather exceedance frequency may be calculated that is applicable to the entire watershed.

The “existing” dry weather exceedance frequencies should be reduced until the final allowable dry weather exceedance frequency is achieved by the end of the dry weather TMDL Compliance Schedule. If the TMDL Compliance Schedules include interim milestones that must be achieved to demonstrate progress toward attaining the dry weather TMDLs, reductions in the exceedance frequencies in the receiving water may be used. For example, if the “existing” dry weather exceedance frequency is 60 percent, the final dry weather exceedance frequency is 0 percent, and an interim milestone requires a 50 percent reduction, the exceedance frequency in the receiving water should be 30 percent or less by the interim milestone date. By the end of the dry weather TMDL Compliance Schedule, the final allowable dry weather exceedance frequency of the 30-day geometric mean REC-1 WQOs is 0 percent in the receiving waters for both beaches and creeks.

2. *Measuring Progress Toward Attaining Wet Weather TMDLs:* For the wet weather TMDLs, the number of wet days and number of wet exceedance days during the critical wet year from the wet weather model were used to calculate the “existing” wet weather exceedance frequency that needs to be reduced to the allowable wet weather exceedance frequency. For example, if a watershed had 69 wet weather days during the critical wet year, and the wet weather model predicted that all the subwatersheds had an average of 41 wet weather exceedance days during the critical wet year, the “existing” wet weather exceedance frequency is 41/69=59%. For the watershed addressed by these TMDLs, the number of wet weather exceedance days for each indicator bacteria predicted by the wet weather model for the critical wet year are summarized below in Table 7-50:

**Table 7-50. Modeled Estimate of Critical Year
“Existing” Wet Weather Exceedance Frequencies by Watershed**

Watershed	Number of Wet Days in Critical Wet Year	“Existing” Wet Weather Exceedance Frequency of Single Sample Maximum REC-1 WQO ^a		
		Fecal Coliform	Total Coliform	Enterococcus
San Joaquin Hills HSA/ Laguna Beach HSA	69	52%	54%	55%
Aliso HSA	69	59%	59%	62% (62%) ^b
Dana Point HSA	69	50%	50%	50%
Lower San Juan HSA	76	66%	66%	74% (72%) ^b
San Clemente HA	73	47%	47%	50%
San Luis Rey HU	90	68%	66%	76%
San Marcos HA	49	57%	57%	59%
San Dieguito HU	98	43%	44%	49%
Miramar Reservoir HA	94	30%	30%	30%
Scripps HA	57	52%	52%	52%
Tecolote HA	57	75%	75%	81% (79%) ^b
Mission San Diego HSA/ Santee HSA	86	70%	63%	79% (76%) ^b
Chollas HSA	65	60%	60%	63% (63%) ^b

a. Calculated by taking the average number of wet days that are predicted by the wet weather model to exceed the single sample maximum REC-1 water quality objective (400 MPN/100mL for fecal coliform, 10,000 MPN/100mL for total coliform, and 61 or 104 MPN/100mL) divided by the total number of wet days in the critical wet year (1993).

b. Allowable exceedance frequency calculated based on an *Enterococcus* single sample maximum REC-1 water quality objective of 61 MPN/100mL. Allowable exceedance frequency in parenthesis calculated based on an *Enterococcus* single sample maximum REC-1 water quality objective of 104 MPN/100mL, which may be applicable if the usage frequency of the creeks in these watersheds are designated as “moderately to lightly used area” or less frequent usage frequency in the Basin Plan.

The “existing” wet weather exceedance frequencies should be reduced until the final allowable wet weather exceedance frequency is achieved by the end of the wet weather TMDL Compliance Schedule. If the TMDL Compliance Schedules include interim milestones that must be achieved to demonstrate progress toward attaining the wet weather TMDLs, reductions in the exceedance frequencies in the receiving water may be used. For example, if the “existing” wet weather exceedance frequency is 59 percent, the final wet weather exceedance frequency is 22 percent, and an interim milestone requires a 50 percent reduction, the exceedance frequency in the receiving water should be 41 percent or less by the interim milestone date. By the end of the wet weather TMDL Compliance Schedule, the allowable wet weather exceedance frequency is 22 percent in the receiving waters for both beaches and creeks.

The specific receiving waters (i.e., specific beaches and creek segments) identified on the 2002 303(d) List are shown in the TMDL Compliance Schedule in the following section. Because the REC-1 WQOs and allowable exceedance frequencies must be met throughout the 20 waterbodies addressed by these bacteria TMDLs, monitoring data from these locations and any other beach segments and/or creek monitoring points in the watersheds addressed by these TMDLs may be used to determine compliance.

Because the municipal MS4s are the most significant controllable sources of bacteria and the Phase I MS4s often discharge directly to the receiving waters addressed by these TMDLs, the municipal Phase I MS4s will be primarily responsible for conducting the monitoring. Caltrans will also have monitoring responsibilities. Phase II MS4s, agricultural dischargers, and other sources that are identified as significant sources (i.e., causing or contributing to exceedances in the receiving waters) will also be responsible for monitoring the receiving waters. Additional monitoring locations and frequency may be required to identify sources that need additional controls to reduce bacteria loads. While this TMDL Implementation Plan recommends monitoring at one or two locations for each waterbody, monitoring only one or two locations in the receiving waters may not provide the data to differentiate between and locate sources of bacteria in the watershed. Therefore, the municipal Phase I MS4s and other dischargers may wish to establish additional monitoring locations at key jurisdictional boundaries as part of their monitoring programs, especially in watersheds where Caltrans and Agriculture have been identified as sources contributing bacteria loads to the receiving waters.

Investigative orders, enforcement actions, WDRs, or conditional waiver of WDRs issued by the San Diego Water Board should require monitoring program plans that include, as applicable, the minimum monitoring locations and frequencies outlined above, but also provide the dischargers an opportunity to propose additional or alternative monitoring locations and frequency of monitoring events. The San Diego Water Board may also issue investigative orders, enforcement actions, WDRs, or conditional waiver of WDRs that specify additional or alternative monitoring, monitoring locations, and/or frequency of monitoring events.

The San Diego Water Board will coordinate, to the extent possible, the monitoring that is required by the dischargers, to minimize the monitoring resources required and maximize the temporal and spatial coverage of the data collection.

TMDL COMPLIANCE SCHEDULE

The purpose of these TMDLs is to restore the impaired beneficial uses of the waterbodies addressed through mandated reductions of bacteria from controllable point and nonpoint sources discharging to impaired waters. The requirements of these TMDLs mandate that the San Diego Water Board require dischargers improve water quality conditions in impaired waters by achieving the assigned WLAs and LAs. After the controllable sources achieve their assigned WLAs and LAs, the TMDLs in the receiving waters will be met and beneficial uses restored.

Until the dischargers achieve their assigned WLAs and LAs, the beneficial uses of the waterbodies addressed by this project will likely remain impaired, and the dischargers will continue violating one or more Basin Plan waste discharge prohibitions. The San Diego Water Board recognizes that restoring the beneficial uses of the waterbodies impaired by elevated bacteria levels will require time and multiple approaches to implement. Therefore, the bacteria TMDLs are expected to be implemented in a phased approach with a monitoring component to identify bacteria sources, determine the effectiveness of each phase, and guide the selection of BMPs, as outlined in the BMP programs proposed in the BLRPs or CLRPs that are accepted by the San Diego Water Board.

(1) Prioritization of Waterbodies

“Impaired” waters were prioritized based on several factors, because the waterbodies included in these TMDLs are numerous and diverse in terms of geographic location, swimmer accessibility and use, and degree of contamination.

Dischargers accountable for attaining load reductions in multiple watersheds may have difficulty providing the same level of effort simultaneously in all watersheds. In order to address these concerns a scheme for prioritizing implementation of bacteria reduction strategies in waterbodies within watersheds was developed. The prioritization scheme is largely based on the following criteria:

- Level of beach (marine or freshwater) swimmer usage;
- Frequency of exceedances of WQOs; and
- Existing programs designed to reduce bacteria loading to surface waters.

Dischargers were placed into one of three groups (North, Central, and South), based on geographic location. Group N consists of dischargers located in watersheds within Orange County, the northernmost region watersheds included in these TMDLs. Group C consists of dischargers located in watersheds in northern San Diego County, outside the City of San Diego limits, the central region watersheds included in these TMDLs. Group S consists of dischargers who are located in watersheds within and south of the City of San Diego limits, the southernmost region watersheds included in these TMDLs. Table 7-51 shows the dischargers in each of the three groups.

Table 7-51. Responsible Municipalities and Lead Jurisdictions†

Watershed	Waterbody***	Segment or Area**	Responsible Municipalities	Group
San Joaquin Hills HSA (901.11) & Laguna Beach HSA (901.12)	Pacific Ocean Shoreline	Cameo Cove at Irvine Cove Dr. - Riviera Way	City of Laguna Beach County of Orange Orange County Flood Control District Caltrans Owners/operators of small MS4s*	N
		at Heisler Park – North		
	Pacific Ocean Shoreline	at Main Laguna Beach	City of Aliso Viejo County of Orange City of Laguna Beach City of Laguna Woods Orange County Flood Control District Caltrans Owners/operators of small MS4s*	
		Laguna Beach at Ocean Avenue		
		Laguna Beach at Laguna Avenue		
		Laguna Beach at Cleo Street		
		Arch Cove at Bluebird Canyon Road		
Laguna Beach at Dumond Drive				
Aliso HSA (901.13)	Pacific Ocean Shoreline	Laguna Beach at Lagunita Place/Blue Lagoon Place at Aliso Beach	City of Aliso Viejo City of Laguna Beach City of Laguna Hills City of Laguna Niguel City of Laguna Woods City of Lake Forest City of Mission Viejo County of Orange Orange County Flood Control District Caltrans Owners/operators of small MS4s*	N
	Aliso Creek	The entire reach (7.2 miles) and associated tributaries Aliso Hills Channel, English Canyon Creek, Dairy Fork Creek, Sulphur Creek, and Wood Canyon Creek		
		Aliso Creek (mouth)	At creek mouth	
Dana Point HSA (901.14)	Pacific Ocean Shoreline	Aliso Beach at West Street	City of Dana Point City of Laguna Beach City of Laguna Niguel County of Orange Orange County Flood Control District Caltrans Owners/operators of small MS4s*	N
		Aliso Beach at Table Rock Drive		
		1000 Steps Beach at Pacific Coast Hwy at Hospital (9th Ave)		
		at Salt Creek (large outlet)		
		Salt Creek Beach at Salt Creek service road		
Salt Creek Beach at Dana Strand Road				

Table 7-51. Responsible Municipalities and Lead Jurisdictions† (Cont'd)

Watershed	Waterbody***	Segment or Area**	Responsible Municipalities	Group
Lower San Juan HSA (901.27)	Pacific Ocean Shoreline	At San Juan Creek	City of San Juan Capistrano City of Mission Viejo City of Laguna Hills City of Laguna Niguel City of Dana Point City of Rancho Santa Margarita	N
	San Juan Creek	Lower 1 mile	County of Orange Orange County Flood Control District Caltrans	
	San Juan Creek (mouth)	At creek mouth	Owners/operators of small MS4s*	
San Clemente HA (901.30)	Pacific Ocean Shoreline	Poche Beach	City of San Clemente County of Orange Orange County Flood Control District Dana Point Caltrans Owners/operators of small MS4s*	N
		Ole Hanson Beach Club		
		Beach at Pico Drain		
		San Clemente City Beach at El Portal Street Stairs		
		San Clemente City Beach at Mariposa Street		
		San Clemente City Beach at Linda Lane		
		San Clemente City Beach at South Linda Lane		
		San Clemente City Beach at Lifeguard Headquarters		
		Under San Clemente Municipal Pier		
		San Clemente City Beach at Trafalgar Canyon (Trafalgar Lane)		
		San Clemente State Beach at Riviera Beach		
San Clemente State Beach at Cypress Shores				
San Luis Rey HU (903.00)	Pacific Ocean Shoreline	at San Luis Rey River Mouth	City of Oceanside City of Vista County of San Diego Caltrans Owners/operators of small MS4s* Controllable nonpoint sources	C

Table 7-51. Responsible Municipalities and Lead Jurisdictions[†] (Cont'd)

Watershed	Waterbody***	Segment or Area**	Responsible Municipalities	Group
San Marcos HA (904.50)	Pacific Ocean Shoreline	at Moonlight State Beach	City of Carlsbad City of Encinitas City of Escondido City of San Marcos County of San Diego Caltrans Owners/operators of small MS4s* Controllable nonpoint sources	C
San Dieguito HU (905.00)	Pacific Ocean Shoreline	at San Dieguito Lagoon Mouth	City of Del Mar City of Escondido City of Poway City of San Diego City of Solana Beach County of San Diego Caltrans Owners/operators of small MS4s* Controllable nonpoint sources	C/S
Miramar Reservoir HA (906.10)	Pacific Ocean Shoreline	Torrey Pines State Beach at Del Mar (Anderson Canyon)	City of Del Mar City of Poway City of San Diego County of San Diego Caltrans Owners/operators of small MS4s*	S
Scripps HA (906.30)	Pacific Ocean Shoreline	La Jolla Shores Beach at El Paseo Grande	City of San Diego Owners/operators of small MS4s*	S
		La Jolla Shores Beach at Caminito Del Oro		
		La Jolla Shores Beach at Vallecitos		
		La Jolla Shores Beach at Ave de la Playa		
		at Casa Beach, Children's Pool		
		South Casa Beach at Coast Blvd.		
		Whispering Sands Beach at Ravina Street		
		Windansea Beach at Vista de la Playa		
		Windansea Beach at Bonair Street		
		Windansea Beach at Playa del Norte		
		Windansea Beach at Palomar Ave.		
		at Tourmaline Surf Park		
Pacific Beach at Grand Ave.				

Table 7-51. Responsible Municipalities and Lead Jurisdictions† (Cont'd)

Watershed	Waterbody***	Segment or Area**	Responsible Municipalities	Group
Tecolote HA (906.50)	Tecolote Creek	Tecolote Creek	City of San Diego Owners/operators of small MS4s*	S
Mission San Diego HSA (907.11) & Santee HSA (907.12)	Forrester Creek	Lower 1 mile	City of El Cajon City of Santee County of San Diego Caltrans Owners/operators of small MS4s*	S
	San Diego River, Lower	Lower 6 miles	City of El Cajon City of La Mesa City of San Diego City of Santee County of San Diego Caltrans Owners/operators of small MS4s* Padre Dam Water Treatment Facility	S
	Pacific Ocean Shoreline	At San Diego River Mouth at Dog Beach		
Chollas HSA (908.22)	Chollas Creek	Lower 1.2 miles	City of La Mesa City of Lemon Grove City of San Diego County of San Diego San Diego Unified Port District Caltrans Owners/operators of small MS4s*	S

† Developed based on the 2002 Clean Water Act Section 303(d) List

*Owners/operators of small MS4s are listed in Appendix Q.

** As listed on the 2002 Clean Water Act Section 303(d) List

*** Listings on the 2006 and 2008 303(d) List compared to listing shown above are provided in Appendix T to the Technical Report.

Impaired waters were given a priority number of 1, 2, or 3 with 1 being the highest priority. Priority 1 waters also included waterbodies likely to be removed from the Clean Water Act Section 303(d) List of Water Quality Limited Segments. Priority schemes are designated within watersheds. A prioritized list of impaired beaches and creeks included in this project is shown below in Table 7-52.

Table 7-52. Prioritized List of Impaired Waters for TMDL Implementation

Watershed	Waterbody^b	Segment or Area^a	Priority
San Joaquin Hills HSA (901.11) & Laguna Beach HSA (901.12)	Pacific Ocean Shoreline	Cameo Cove at Irvine Cove Dr. - Riviera Way	1
		at Heisler Park – North	1
	Pacific Ocean Shoreline	at Main Laguna Beach	1
		Laguna Beach at Ocean Avenue	1
		Laguna Beach at Laguna Avenue	1
		Laguna Beach at Cleo Street	1
		Arch Cove at Bluebird Canyon Road	1
Laguna Beach at Dumond Drive	1		
Aliso HSA (901.13)	Pacific Ocean Shoreline	Laguna Beach at Lagunita Place/Blue Lagoon Place at Aliso Beach	1
	Aliso Creek	The entire reach (7.2 miles) and associated tributaries Aliso Hills Channel, English Canyon Creek, Dairy Fork Creek, Sulphur Creek, and Wood Canyon Creek	3
	Aliso Creek (mouth)	At creek mouth	3
Dana Point HSA (901.14)	Pacific Ocean Shoreline	Aliso Beach at West Street	1
		Aliso Beach at Table Rock Drive	1
		1000 Steps Beach at Pacific Coast Hwy at Hospital (9th Ave)	1
		at Salt Creek (large outlet)	1
		Salt Creek Beach at Salt Creek service road	2
		Salt Creek Beach at Dana Strand Road	2
Lower San Juan HSA (901.27)	Pacific Ocean Shoreline	At San Juan Creek	1
	San Juan Creek	Lower 1 mile	3
	San Juan Creek (mouth)	At creek mouth	1

Table 7-52. Prioritized List of Impaired Waters for TMDL Implementation † (Cont'd)

Watershed	Waterbody^b	Segment or Area^a	Priority
San Clemente HA (901.30)	Pacific Ocean Shoreline	at Poche Beach (large outlet)	1
		Ole Hanson Beach Club Beach at Pico Drain	1
		San Clemente City Beach at Linda Lane	1
		San Clemente State Beach at Riviera Beach	1
		San Clemente City Beach at Mariposa Street	2
		San Clemente State Beach at Cypress Shores	2
		San Clemente City Beach at Lifeguard Headquarters	2
		Under San Clemente Municipal Pier	2
		San Clemente City Beach at El Portal Street Stairs	2
		San Clemente City Beach at South Linda Lane	3
		San Clemente City Beach at Trafalgar Canyon (Trafalgar Lane)	3
		San Luis Rey HU (903.00)	Pacific Ocean Shoreline
San Marcos HA (904.50)	Pacific Ocean Shoreline	at Moonlight State Beach	1
San Dieguito HU (905.00)	Pacific Ocean Shoreline	at San Dieguito Lagoon Mouth	1
Miramar Reservoir HA (906.10)	Pacific Ocean Shoreline ^a	Torrey Pines State Beach at Del Mar (Anderson Canyon)	1
Scripps HA (906.30)	Pacific Ocean Shoreline	La Jolla Shores Beach at El Paseo Grande	1
		La Jolla Shores Beach at Caminito Del Oro	1
		La Jolla Shores Beach at Vallecitos	1
		La Jolla Shores Beach at Ave de la Playa	1
		at Casa Beach, Children's Pool	1
		South Casa Beach at Coast Blvd.	1
		Whispering Sands Beach at Ravina Street	1
		Windansea Beach at Vista de la Playa	1
		Windansea Beach at Bonair Street	1
		Windansea Beach at Playa del Norte	1
		Windansea Beach at Palomar Ave.	1
		at Tourmaline Surf Park	1
		Pacific Beach at Grand Ave.	1
Tecolote HA (906.10)	Tecolote Creek	The entire reach and associated tributaries	1

Table 7-52. Prioritized List of Impaired Waters for TMDL Implementation † (Cont'd)

Watershed	Waterbody^b	Segment or Area^a	Priority
Mission San Diego HSA (907.11) & Santee HSA (907.12)	San Diego River, Lower	Lower 6 miles	3
	Pacific Ocean Shoreline	At San Diego River Mouth at Dog Beach	3
	Forrester Creek	Lower 1 mile	3
Chollas HSA (908.22)	Chollas Creek	Bottom 1.2 miles	3

† Developed based on the 2002 Clean Water Act Section 303(d) List

a As listed on the 2002 Clean Water Act Section 303(d) List

b Listings on the 2006 and 2008 303(d) List compared to listing shown above are provided in Appendix T to the Technical Report.

Beginning with the 2008 303(d) List, specific beach segments of the Pacific Ocean shoreline are listed individually, and may not be identified in the same way as those segments listed in the table above. Several of the segments or areas in the list above have been delisted or redefined in the 2008 303(d) List. In addition, other segments or areas have been added to the Pacific Ocean shorelines listed above. The TMDLs that address the Pacific Ocean shorelines identified in the 2002 303(d) List are assumed to be applicable to all the beaches located on the shorelines of the hydrologic subareas (HSAs), hydrologic areas (HAs), and hydrologic units (HUs) listed above, or as listed individually in the 2008 and future 303(d) Lists.

The prioritized list above recognizes that there are segments or areas where bacterial water quality improvements are most likely to occur first (Priority 1), and segments or areas where bacterial water quality improvements are most likely to require more time to achieve (Priority 3). In some cases, receiving water limitations are already being met, resulting in the delisting of those segments or areas from the 2006 and/or 2008 303(d) Lists. The protection of the REC-1 beneficial use of those delisted segments or areas, however, must also be maintained, and those segments or areas must remain off future iterations of the 303(d) List.

The BLRPs or CLRPs that are developed are expected to focus on implementing BMP programs to reduce bacteria loads to those segments or areas where exceedances of the receiving water limitations continue to occur. The BMP programs that are included in the BLRPs or CLRPs should include short-term and long-term implementation strategies. The short-term strategies should be able to result in bacteria load reductions that can result in achieving the TMDLs for Priority 1 segments or areas. The long-term strategies should be able to result in bacteria load reductions that will result in achieving the TMDLs in all segments or areas by the end of the TMDL compliance schedules and maintain the protection of the REC-1 beneficial use after the end of the TMDL compliance schedules.

In the segments or areas where the receiving water limitations are being met, the BLRPs or CLRPs also need to include a monitoring component to ensure that protection of the REC-1 beneficial use is maintained. If receiving water limitations are exceeded in the future in those locations, the BLRPs or CLRPs must include the implementation of a BMP program that will ensure that the TMDLs will be achieved by the end of the TMDL compliance schedules.

(2) Compliance Schedule

Full implementation of the TMDLs for indicator bacteria shall be completed as soon as possible, but no later than 10 years⁷⁴ from the effective date⁷⁵ for both the dry weather and wet weather TMDLs, unless an alternative compliance schedule is approved as part of a Comprehensive Load Reduction Plan, as described in the following section. The effective date of these TMDLs is April 4, 2011.

The San Diego Water Board will require the Phase I MS4s to submit Bacteria Load Reduction Plan (BLRPs) outlining a proposed BMP program that will be capable of achieving the necessary load reductions required to attain the bacteria TMDLs in the receiving waters, acceptable to the Regional Board within 18 months after the effective date of these TMDLs. The Phase I MS4 BLRPs should be incorporated into their Watershed Runoff Management Programs. Caltrans will also be required to develop and submit BLRPs outlining a proposed BMP program that will be capable of achieving the necessary load reductions required to attain the TMDLs in the receiving waters, acceptable to the Regional Board, within 18 months after the effective date of these TMDLs. To the extent possible, the Phase I MS4s and Caltrans should develop and coordinate the elements of their BLRPs together. The BLRPs will allow the Phase I MS4s and Caltrans to propose a compliance schedule for WQBELs that implement the bacteria TMDLs. The compliance schedule for the Phase I MS4s and Caltrans to attain their respective WLAs and the TMDLs in the receiving waters will be based on the BMP program proposed in the BLRPs.

For watersheds in Table 7-52 where there are no longer any impairments listed on the 2008 303(d) List, the Phase I MS4s and Caltrans are not required to submit a BLRP or CLRP within 18 months of the effective date of these TMDLs. If, however, any segment of a waterbody for the watershed (Pacific Ocean shoreline, creek, or mouth as shown in Table 7-36) is re-listed on a future 303(d) List for any type of indicator bacteria, the Phase I MS4s and Caltrans will be required to submit a BLRP or CLRP within 6 months of the adoption of the 303(d) List by the San Diego Regional Board.

If the Phase I MS4s and Caltrans choose to submit BLRPs that address only bacteria, the proposed schedule for compliance with the wet weather and dry weather TMDLs cannot extend beyond 10 years from the effective date, and must include at least a milestone for achieving a 50 percent exceedance frequency reduction. Additional milestones for achieving exceedance frequency reductions (e.g., 25 and 75 percent) are encouraged, but may also be required by the Regional Board. If the BLRPs do not include a proposed compliance schedule that is acceptable to the Regional Board, the compliance schedule will be as follows.

The compliance schedule for achieving the dry weather and wet weather bacteria TMDLs (Tables 7-53 and 7-54, respectively) are structured in a phased manner, with 100 percent of dry weather exceedance frequency reductions, and 100 percent of wet weather exceedance frequency reductions within 10 years from the effective date. At the end of the dry weather TMDL compliance schedule, the receiving waters must not exceed the 30-day geometric mean REC-1 WQOs more than 0 percent of the time. At the end of the wet weather TMDL compliance schedule, the receiving waters must not exceed the single sample maximum REC-1 WQOs more than the wet weather allowable exceedance frequency. All of these reductions are aimed at restoring water quality to a level that supports REC-1 beneficial uses in the ocean shoreline and in impaired creeks. These reductions required by the compliance schedule vary on the timeline based on the priority scheme described in Table 7-52. Intermediate milestone reductions in bacteria wasteloads are required sooner in the higher priority waters.

⁷⁴ If a Comprehensive Load Reduction Plan (CLRP) is developed to address several pollutants, including bacteria, the implementation of the wet weather bacteria TMDLs shall be completed as soon as possible, but no later than 20 years from the effective date. See Alternative Compliance Schedules under section (j)(3).

⁷⁵ The effective date is the date the Office of Administrative Law approves this Basin Plan amendment.

Table 7-53. Dry Weather Compliance Schedule and Milestones for Exceedance Frequency Reductions

Compliance Year (year after OAL approval)	Required Exceedance Frequency Reduction		
	Priority 1	Priority 2	Priority 3
5	50% (All Dry Weather)		
6		50% (All Dry Weather)	
7			50% (All Dry Weather)
10+	100% (All Dry Weather)	100% (All Dry Weather)	100% (All Dry Weather)

Table 7-54. Wet Weather Compliance Schedule and Milestones for Achieving Exceedance Frequency Reductions

Compliance Year (year after OAL approval)	Required Exceedance Frequency Reduction		
	Priority 1	Priority 2	Priority 3
5	50% (All Wet Weather)		
6		50% (All Wet Weather)	
7			50% (All Wet Weather)
10+	100% (All Wet Weather)	100% (All Wet Weather)	100% (All Wet Weather)

The first four years of the compliance schedules above do not require any exceedance frequency reductions from current conditions. These years will provide the dischargers time to identify sources, develop plans and implement enhanced and expanded BMPs capable of achieving the mandated decreases in exceedance frequencies of the REC-1 WQOs in the impaired beaches and creeks. The Regional Board may also include additional milestones for achieving exceedance frequency reductions (e.g., 25 and 75 percent).

If appropriate and acceptable to the Regional Board, the proposed compliance schedules included in the BLRPs will be incorporated into the various TMDL implementing orders, such as the municipal Phase I MS4 stormwater WDRs and NPDES requirements. Otherwise, the compliance schedules given above will be implemented.

(3) Alternative Compliance Schedules

The dischargers to Chollas Creek in the Chollas HSA watershed will have to address reductions from multiple water quality improvement projects in addition to bacteria, namely TMDLs for copper, lead, zinc, and diazinon,⁷⁶ and a trash reduction program. Addressing multiple pollutants (in addition to bacteria) will require the development and submittal of a Comprehensive Load Reduction Plan (CLRP) by the Phase I MS4s and Caltrans. The CLRP will allow the Phase I MS4s and Caltrans to propose a compliance schedule to address impairments due to loads from multiple pollutants, including bacteria.

⁷⁶ As described in *Total Maximum Daily Loads for Dissolved Copper, Lead, and Zinc in Chollas Creek, Tributary to San Diego Bay*, adopted under Resolution No. R9-2007-0043, and *Total Maximum Daily Load for Diazinon in Chollas Creek Watershed, San Diego County*, adopted under Resolution No. R9-2002-0123.

Full implementation of the TMDLs for indicator bacteria included under the CLRP for the Chollas HSA watershed shall be completed as soon as possible, but cannot extend beyond 10 years for the dry weather bacteria TMDLs and 20 years for the wet weather bacteria TMDLs. The proposed compliance schedules for the bacteria TMDLs included under the CLRP must include at least a milestone for achieving a 50 percent exceedance frequency reduction. Additional milestones for achieving exceedance frequency reductions (e.g., 25 and 75 percent) are encouraged. If the CLRP for the Chollas HSA watershed does not include a proposed compliance schedule, specifically for bacteria, the compliance schedule will be as given in Table 7-55.

Table 7-55. Alternative Compliance Schedule Chollas Creek

Compliance Year*	Exceedance Frequency Reduction Milestone**
7	50% for dry weather
10	100% for dry weather 50% for wet weather
20	100% for wet weather

* Year after effective date for the TMDL that initiated the development of the CLRP.

** The Regional Board may also include additional milestones for achieving exceedance frequency reductions (e.g., 25 and 75 percent).

Likewise, dischargers in other bacteria-impaired watersheds may also find that undertaking concurrent load reduction programs for other pollutant constituents (e.g. metals, pesticides, trash, nutrients, sediment, etc.) together with the bacteria load reduction requirements in these TMDLs, is more cost effective, and has fewer potential environmental impacts from structural BMP construction. In these cases, the dischargers may develop and submit a CLRP for all constituents of concern in lieu of the BLRP, and to propose an appropriately tailored alternative compliance schedule. Proposed alternative compliance schedules tailored under this provision may not extend beyond 10 years for the dry weather bacteria TMDLs and 20 years for the wet weather bacteria TMDLs from the effective date, and must include at least a milestone for achieving a 50 percent exceedance frequency reduction. Additional milestones for achieving exceedance frequency reductions (e.g., 25 and 75 percent) are encouraged, but may also be required by the Regional Board.

If appropriate and acceptable to the Regional Board, the proposed alternative compliance schedules included in the CLRPs will be incorporated into the various TMDL implementing orders. Otherwise, the alternative compliance schedule given above as an example for Chollas Creek will be implemented for a CLRP that is developed for any other watershed.

TMDL IMPLEMENTATION MILESTONES

Accomplishing the goals of the implementation plan will be achieved by cooperative participation from all responsible parties, including the San Diego Water Board. Major milestones are described in Table 7-56.

Table 7-56. TMDL Implementation Milestones

Item	Implementation Action	Responsible Parties	Date
1	Obtain approval of Beaches and Creeks Indicator Bacteria TMDLs from the State Water Board, OAL, and USEPA.	San Diego Water Board	Effective date ^a April 4, 2011
2	Issue investigative orders to Phase I MS4s and Caltrans requiring the development and submittal of BLRPs or CLRPs acceptable to the Regional Board within 18 months of effective date	San Diego Water Board	As soon as possible (if necessary)
3	Issue, reissue, or revise general WDRs and NPDES requirements for the Phase I MS4s to incorporate the requirements for complying with the TMDLs and MS4 WLAs.	San Diego Water Board	Within 5 years of effective date ^b
4	Issue, reissue, or revise general WDRs and NPDES requirements for Caltrans to incorporate the requirements for complying with the TMDLs and Caltrans WLAs.	San Diego Water Board, State Water Board	Within 5 years of effective date ^b
5	Issue, reissue, or revise the WDRs and NPDES requirements for POTWs and wastewater collection systems to incorporate new requirements for sewer line surveillance and maintenance, consistent with the zero WLA.	San Diego Water Board	Within 5 years of effective date ^b
6	Meet 50% Dry Weather exceedance frequency reductions required to achieve TMDLs in receiving waters in Priority 1 watersheds.	Municipal Dischargers, ^d Caltrans, Agriculture/Livestock Dischargers	5 years after effective date ^b
7	Meet 50% Wet Weather exceedance frequency reductions required to achieve TMDLs in receiving waters in Priority 1 watersheds.	Municipal Dischargers, ^d Caltrans, Agriculture/Livestock Dischargers	5 years after effective date ^b
8	Meet 50% Dry Weather exceedance frequency reductions required to achieve TMDLs in receiving waters in Priority 2 watersheds.	Municipal Dischargers, ^d Caltrans, Agriculture/Livestock Dischargers	6 years after effective date ^b
9	Meet 50% Wet Weather exceedance frequency reductions required to achieve TMDLs in receiving waters in Priority 2 watersheds.	Municipal Dischargers, ^d Caltrans, Agriculture/Livestock Dischargers	6 years after effective date ^b
10	Meet 50% Dry Weather exceedance frequency reductions required to achieve TMDLs in receiving waters in Priority 3 watersheds.	Municipal Dischargers, ^d Caltrans, Agriculture/Livestock Dischargers	7 years after effective date ^b
11	Meet 50% Wet Weather exceedance frequency reductions required to achieve TMDLs in receiving waters in Priority 3 watersheds.	Municipal Dischargers, ^d Caltrans, Agriculture/Livestock Dischargers	7 years after effective date ^b
12	Meet 100% Dry Weather exceedance frequency reductions required to achieve TMDLs in receiving waters in all watersheds.	Municipal Dischargers, ^d Caltrans, Agriculture/Livestock Dischargers	10 years after effective date ^{b,c}
13	Meet 100% Wet Weather exceedance frequency reductions required to achieve TMDLs in receiving waters in all watersheds.	Municipal Dischargers, ^d Caltrans, Agriculture/Livestock Dischargers	10 to 20 years after effective date ^{b,c}

Item	Implementation Action	Responsible Parties	Date
14	Amend discharge conditions of appropriate waivers to be consistent with the requirements for complying with the TMDLs and Agriculture LAs.	San Diego Water Board	As needed after effective date
15	Issue individual or general WDRs or Basin Plan prohibitions consistent with the TMDLs and LAs for controllable nonpoint source discharges not eligible conditional waivers.	San Diego Water Board	As needed after effective date
16	Submit BLRP or CLRP Progress Reports to San Diego Water Board	Phase I MS4s, Phase II MS4s, Caltrans	In accordance with BLRPs or CLRPs accepted by the Regional Board
17	Enroll Phase II MS4s identified as significant sources of bacteria to receiving waters under State Water Board general WDRs and NPDES requirements.	San Diego Water Board	As needed after effective date
18	Issue individual or general WDRs and NPDES requirements consistent with the TMDLs and WLAs for specific Phase II MS4s or category of Phase II MS4s.	San Diego Water Board	As needed after effective date
19	Take enforcement actions against controllable point sources and nonpoint sources to attain compliance with the WLAs and LAs.	San Diego Water Board	As needed after effective date
20	Recommend TMDL-related projects as high priority for grant funds.	San Diego Water Board	As needed after effective date
21	Amend the Basin Plan and/or provisions of these TMDLs (e.g., usage frequency or creeks or watershed-specific allowable exceedance frequency) based on evidence provided by dischargers and/or other entities	San Diego Water Board, Municipal Dischargers, ^d Caltrans, Agriculture/Livestock Dischargers	Within 5 years after effective date ^e

^a Effective date = date of approval by OAL

^b May defer to alternative compliance schedule proposed in BLRPs or CLRPs that have been incorporated into implementing orders (e.g., WDRs, cleanup and abatement orders)

^c Compliance schedules for dry weather and wet weather TMDLs proposed in BLRPs cannot extend beyond 10 years from the effective date. Compliance schedules proposed in CLRPs for dry weather TMDLs cannot extend beyond 10 years and for wet weather TMDLs cannot extend beyond 20 years from the effective date.

^d Because there are no Phase II MS4s enrolled under the State General Permit for Small MS4s, discharges from Phase II MS4s are not permitted (i.e., WLA = 0) and Municipal Dischargers are only the Phase I MS4s in this Implementation Milestone item. When a Phase II MS4 is enrolled under the State General Permit for Small MS4s or issued an individual NPDES permit, the Municipal Dischargers will be both the Phase I MS4s and Phase II MS4s in this Implementation Milestone item.

^e If no Basin Plan amendment has been initiated within 5 years of the effective date of this TMDL Basin Plan amendment, and the Executive Officer determines, with Regional Board concurrence, that insufficient data exist to support the initiation of a Basin Plan amendment, a subsequent Basin Plan amendment to revise the requirements and/or provisions for the implementation of these TMDLs will not be initiated until the Executive Officer determines the conditions to initiate a Basin Plan amendment are met.

TOTAL MAXIMUM DAILY LOADS FOR SEDIMENT IN LOS PEÑASQUITOS LAGOON

On June 13, 2012, the San Diego Water Board adopted *Resolution No. R9-2012-0033, A Resolution Amending the Water Quality Control Plan For The San Diego Basin (9) to Incorporate the Sediment Total Maximum Daily Load for Los Peñasquitos Lagoon*. The TMDL Basin Plan Amendment was subsequently approved by the State Water Resources Control Board (State Board) on January 21, 2014, the Office of Administrative Law (OAL) on July 14, 2014 and the USEPA on October 30, 2014. For purposes of state law, Resolution No. R9-2012-0033 became effective following OAL approval on October 30, 2014.

PROBLEM STATEMENT

Under section 303(d) of the Clean Water Act (CWA), states are required to identify waters whose beneficial uses have been impaired due to specific constituents. Los Peñasquitos Lagoon was placed on the Section 303(d) list of Water Quality Limited Segments in 1996 for sedimentation and siltation with an estimated 469 acres affected. The Lagoon is subject to the development of a total maximum daily load (TMDL) (US EPA, 2009).

The Lagoon is an estuarine system that is part of the Torrey Pines State Natural Reserve. In addition to its marine influence, the Lagoon receives freshwater inputs from an approximately 60,000-acre watershed comprised of three major canyons (Carroll Canyon, Los Peñasquitos Canyon, and Carmel Canyon). Given the status of "Natural Preserve" by the California State Parks, the Lagoon is one of the few remaining native saltmarsh lagoons in southern California, providing a home to several endangered species (California State Parks, 2009). The Lagoon is ecologically diverse, supporting a variety of plant species, and provides nursery grounds and habitat for numerous bird, fish, and small mammal populations. The Lagoon also serves as a stopover for the Pacific Flyway, offering migratory birds a safe place to rest and feed, as well as providing refuge for coastal marine species that use the Lagoon to feed and hide from predators.

The San Diego Basin Plan states, "The suspended sediment load and suspended sediment discharge rate of surface waters shall not be altered in such a manner as to cause nuisance or adversely affect beneficial uses." Beneficial uses listed in the Basin Plan for the Lagoon include contact water recreation; non-contact water recreation (although access is not permitted in some areas per California State Parks); preservation of biological habitats of special significance; estuarine habitat; wildlife habitat; rare, threatened or endangered species; marine habitat; migration of aquatic organisms; spawning, reproduction and/or early development; and shellfish harvesting. The beneficial uses that are most sensitive to increased sedimentation are estuarine habitat (EST) and preservation of biological habitats of special significance (BIOL). Estuarine uses may include preservation or enhancement of estuarine habitats, vegetation, fish, shellfish, or wildlife (such as marine mammals or shorebirds).

Impacts associated with increased and rapid sedimentation include: reduced tidal mixing within Lagoon channels, degraded and (in some cases) net loss of saltmarsh vegetation, increased vulnerability to flooding for surrounding urban and industrial developments, increased turbidity associated with siltation in Lagoon channels, and constricted wildlife corridors.

The Los Peñasquitos Lagoon Enhancement Plan and Program (1985), San Diego Basin Plan, and Clean Water Act section 303(d) highlight sedimentation as a significant impact associated with urban development and a leading cause in the rapid loss of saltmarsh habitat in the Lagoon. Sediment reduction is a management priority.

The Lagoon's 565 acres include 262 acres of tidal saltmarsh (including salt panne, tidal channels, and mudflats) and non-tidal saltmarsh and 132 acres of freshwater marsh, herbaceous wetland, and woody riparian (for example southern willow scrub and mulefat scrub) habitats. The remaining 171 acres of saltmarsh and brackish marsh vegetation are impaired by excessive sedimentation, which converted the coastal saltmarsh to *Lolium perenne* infested non-tidal saltmarsh, freshwater marsh, and woody riparian habitats. (California State Parks, 2011) The environmental processes that support wetland habitats in the Lagoon have been altered by urban development in three ways:

- 1) Increase in the volume and frequency of freshwater input,
- 2) Increase in sediment deposition, and
- 3) Decrease in the tidal prism.

These factors have led to decreases in tidal and non-tidal saltmarsh habitats and increases in freshwater habitats and the abundance of non-native species.

NUMERIC TARGET

The sediment water quality standard applies to sediment loading to the Lagoon and the accumulation of sediment in the Lagoon. The minimum protective target would be to reduce watershed sediment loads to non-anthropogenic levels and return the Lagoon to non-anthropogenic conditions with consideration given to background loading and other factors that also lend to impairment of beneficial uses. The numeric targets are calculated upon the historic condition (mid-1970s) when the sediment water quality standard was once met.

A historic coverage for the Los Peñasquitos watershed was developed for this period using US Geological Survey topographic maps from the 1970s. This land-use distribution was used to calculate the watershed numeric target using the LSPC watershed model. This historic (mid-1970s) sediment load of 12,360 tons per critical wet period (211 days), or 58.6 tons per day, represents the sediment TMDL watershed numeric target.

An analysis of the vegetation types present in the Lagoon was developed for the mid-1970s using historic aerial photographs from which the Lagoon numeric target was calculated. The Lagoon numeric target is expressed as an increasing trend in the total area of tidal and non-tidal saltmarsh toward 346 acres. This target acreage represents 80 percent of the total acreage of tidal and non-tidal saltmarsh present in 1973.

WATERSHED POINT AND NON-POINT SEDIMENT SOURCES

Sources of sediment include erosion of canyon banks, exposed soils, bluffs, scouring stream banks, and tidal influx. Some of these processes are exacerbated by anthropogenic disturbances, such as land development within the watershed. Land development transforms the natural landscape by exposing sediment and converting pervious surfaces to impervious surfaces, which increases the volume and velocity of runoff resulting in scouring of sediment, primarily below storm water outfalls that discharge into canyon areas. Sediment loads are transported downstream to the Lagoon during storm events causing deposits on the salt flats and in Lagoon channels. These sediment deposits have gradually built-up over time due to increased sediment loading and inadequate flushing, which directly and indirectly affects Lagoon functions and salt marsh characteristics.

There are two broad categories of sediment sources to the Lagoon: 1) watershed sources, and 2) the Pacific Ocean. The watershed sources consist of all of point and non-point sources of sediment in the watershed area draining to Los Peñasquitos Lagoon. The total sediment contribution from all watershed sources, currently, is presented as the total wasteload allocation (WLA). The watershed sources of sediment due to past historical activities that have resulted in accumulated sediment in the Lagoon over time are presented as the Watershed Load Allocation (LA). This source also includes, but is not limited to, in-Lagoon erosion and scouring. Since this loading could not be estimated given the limited data, the Lagoon numeric target is set as the compliance point for meeting this Watershed Load Allocation. The sediment contributions from the Pacific Ocean are considered a background source and are presented as the Load Allocation from the Ocean (LA). Hence, the responsible parties were assigned the total WLA and are jointly responsible for meeting the wasteload reductions required in this TMDL project.

RESPONSIBLE PARTIES

Responsible parties include the following: Phase I Municipal Separate Storm Sewer Systems (MS4s) copermitees (the County of San Diego, City of San Diego, City of Del Mar, and City of Poway), Phase II MS4 permittees, Caltrans, general construction storm water NPDES permittees, and general industrial storm water NPDES permittees.

LINKAGE ANALYSIS

Reducing watershed sediment loads from the year 2000 levels to historic levels is a necessary component for restoring and providing long-term protection of the Lagoon's beneficial uses. Deposition of watershed sediment contributes to elevation increases within the Lagoon, leading to an increase in height relative to mean sea level. Elevation is a critical variable that determines the productivity, diversity, and stability of saltmarshes. The long-term existence of the saltmarsh depends on the success of the dominant plants, such as *Sarcocornia pacifica* (also referred to as *Salicornia virginica*) and *Frankenia salina*, and their close relationship to sediment supply, soil salinity, sea level change, and tidal range.

Reduced sediment loading consistent with the watershed numeric target will encourage the establishment of native vegetation in degraded areas. To represent the linkage between source contributions and receiving water response, models were developed to simulate source loadings and transport of sediment into the Lagoon. The models provide an important tool to evaluate year 2000 conditions, to evaluate historic conditions, and to calculate TMDL load reductions.

The Lagoon was capable of assimilating these historic sediment loads under historic Lagoon conditions. Because the Lagoon has evolved through time and accumulated over 40 years of watershed sediment loads, it cannot be assumed that the Lagoon, in the year 2010 conditions, can assimilate the same historic sediment loads. Evaluation of the extent of vegetation types in the Lagoon provides the necessary tool to assess how the Lagoon responds to watershed sediment load reductions and to establish a target Lagoon condition under which the Lagoon can again assimilate the historic sediment loads.

TMDL, ALLOCATIONS, AND LOAD REDUCTIONS

TMDL = 12,360 tons of sediment per year

The maximum load of sediment that Los Peñasquitos Lagoon can receive from all sources and still meet the sediment water quality objective is 12,360 tons per year.

Wasteload Allocations to Watershed = 2,580 tons/year

As the primary point source to the Lagoon, a wasteload allocation (WLA) of 2,580 tons/year was assigned to the responsible parties. A 67 percent sediment load reduction from the Year 2000 load to the historical (mid-1970s) load is required of the responsible parties.

Load Allocations to Ocean = 9,780 tons/year

The ocean is a nonpoint source of sediment to the Lagoon and was assigned a load allocation (LA) of 9,780 tons/year. Because the ocean is a natural background source, load reductions are not required of the ocean.

Watershed Load Allocations to Lagoon

Past historical watershed loading has led to accumulated sediment, erosion, and scouring in the Lagoon causing impairment to the Lagoon habitats. The Lagoon numeric target is set as the compliance for this LA: maintain at least 346 acres of tidal and non-tidal saltmarsh, represents 80 percent of the total acreage of tidal and non-tidal saltmarsh present in 1973.

Margin of Safety = Implicit

Conservative assumptions were used in selecting the TMDL numeric targets to provide an implicit margin of safety.

Critical Location

Due to the variability and dynamic nature of conditions within the Lagoon (e.g., mouth closures, tidal fluctuations, sediment fate and transport, etc.), the entire modeled Lagoon area was assessed as the critical location. Load reductions for sediment were based on achieving the numeric TMDL target across the Lagoon.

Critical Condition

The wet season that includes the 1993 El Niño storm events (October 1, 1992 April 10, 1993) was selected as the critical condition time period for TMDL development. This is one of the wettest periods on record over the past several decades. Because of the large amount of rainfall, sediment loads were significantly higher during this period than in other years with less rainfall.

Seasonal Considerations

Sources of sediment are similar for both dry and wet weather seasons (the two general seasons in the San Diego region). Despite the similarity of wet/dry sources, transport mechanisms can vary between the two seasons. Throughout the TMDL monitoring period, the greatest transport of sediment occurred during rainfall events. It is recognized that dry weather will contribute a de minimis discharge of sediment; however, model calibration and TMDL development focused on wet weather conditions as sediment transport is dramatically higher during wet weather.

MARGIN OF SAFETY (MOS)

An implicit MOS was incorporated through application of conservative assumptions.

IMPLEMENTATION PLAN

Actions San Diego Water Board May Take

The San Diego Water Board may exercise any of its authorities under the Water Code to compel responsible parties to comply with this TMDL.

Responsible Parties Identification

Under this TMDL, the responsible parties are collectively assigned a single WLA, which they are responsible for meeting. An aggregate WLA allows for flexibility in achieving the load reduction required to meet the TMDL and improve Lagoon conditions. Responsible parties include: Phase I MS4 copermittees (the County of San Diego, City of San Diego, City of Del Mar, and the City of Poway), Phase II MS4 permittees, Caltrans, and the General Construction and General Industrial Storm Water NPDES permittees.

The San Diego Water Board encourages cooperation among all the responsible parties. All the responsible parties in the Los Peñasquitos watershed must reduce their collective sediment load. Responsible parties include, but are not limited to, specific identification of General construction and industrial stormwater permittees, such as sand and gravel operation facilities in the watershed *that have capacity for long-term potential loadings into the watershed.*

The San Diego Water Board recommends all parties enter into a Memorandum of Understanding (MOU), or a similar formal joint effort, to collaboratively and more successfully implement the adaptive management framework.

All responsible entities identified must submit a Comprehensive Load Reduction Plan (CLRP) or SWPPP as appropriate and are strongly encouraged to jointly submit a CLRP to the San Diego Water Board within 18 months of the effective date of the TMDL.

The San Diego Water Board expects responsible parties to cooperate in TMDL implementation (e.g., load reduction, lagoon monitoring, lagoon restoration) as necessary to achieve compliance with this TMDL. Responsible Parties that have or are likely to cause or contribute to the CWA Section 303(d) listed impairment for sediment, and are not participating in TMDL implementation, shall be compelled to meet their compliance obligations through other regulatory authorities of the San Diego Water Board.

Any Responsible Party identified is required to develop pollutant reduction plan that includes description and schedule for implementing BMPs to reduce sediments from being discharged from their facility, property, etc. The plan must describe how the facility plans to meet the water quality objectives and pollutant reductions set forth in the TMDL.

Any Responsible Party as identified for this TMDL shall contribute information regarding the amount of sediments/sedimentation from their facility/entity. This may be produced from existing monitoring plans or by developing a monitoring plan for those entities that currently do not have any discharge monitoring on site. The TMDL has identified a "collective" wasteload allocation that includes several sources of sediments into the watershed. By developing individual site/permittee monitoring plans for flow and TSS discharges, it will be feasible to estimate individual site contributions in the future. Monitoring should address, at minimum, representative values of flow rates and TSS concentrations from the individual permittee's site(s) whenever long-term discharges occur.

Individual industrial facilities and construction sites are subject to regulation on two levels: (1) The San Diego Water Board is responsible for ensuring MS4 copermittees comply with the MS4 requirements in the MS4 storm water permit; and (2) each local municipality is responsible, under the MS4 storm water permit, for enforcing its own ordinances and permits (for violations of its ordinances/permits by an individual industrial facility or construction site within its jurisdiction). The San Diego Water Board is also responsible for enforcing the statewide General Industrial and Construction Storm Water NPDES Permits within its jurisdiction. The San Diego Water Board relies upon the municipality to enforce its ordinances/permits and then work with the municipality to coordinate information and actions to compel compliance.

Phased Implementation via the Adaptive Management Approach

A common problem in natural resource management involves a temporal sequence of decisions (or implementation actions), in which the best action at each decision point depends on the state of the managed system. Adaptive management is a structured iterative implementation process that offers flexibility for responsible parties to monitor implementation actions, determine the success of such actions and ultimately, base future management decisions upon the measured results of completed implementation actions and the current state of the system. This process enhances the understanding and estimation of predicted outcomes and ensures refinement of necessary activities to better guarantee desirable results. In this way, understanding of the resource can be enhanced over time, and management can be improved.

Adaptive management entails applying the scientific method to the TMDL. A National Research Council review of US EPA's TMDL program strongly suggests that the key to improving the application of science in the TMDL program is to apply the scientific method to TMDL implementation (NRC 2001). For a TMDL, applying the scientific method involves 1) taking immediate actions commensurate with available information, 2) defining and implementing a program for refining the information on which the immediate actions are based, and 3) modifying actions as necessary based on new information. This approach allows the Lagoon to make progress toward attaining water quality standards while regulators and stakeholders improve the understanding of the system through research and observation of how it responds to the immediate actions.

Implementation actions to achieve the required WLA and improve the specified numeric targets will be implemented via an iterative process, whereby the information collected at each step will be used to inform the implementation of the next phase. The project will be adjusted, as necessary, based on the latest information collected to optimize the efficiency of implementation efforts. Ultimately, the path moving forward is to create the physical conditions related to remediating sediment impacts associated with this TMDL. The implementation effort can be divided into three primary phases for this TMDL, as described below:

- Phase I Implementation includes elements to reduce the amount of sediment that is transported from the watershed to the Lagoon. An important component of Phase I will be to secure the relationships and agreements between cooperating parties and to develop a detailed scope of work with priorities.

Phase I includes the following elements:

- Incorporate interim limits into WDRs and NPDES permits;
- Implement structural and nonstructural BMPs throughout the watershed; and
- Develop and initiate a comprehensive monitoring program, which includes compliance monitoring and targeted special studies.

If appropriate, the TMDL will be reconsidered by the San Diego Water Board at the end of Phase I to consider completed special studies or policy.

- Phase II includes the implementation of additional watershed actions that are targeted to reducing sediment loads from high priority areas, as well as lagoon-specific actions that may be needed to facilitate recovery of beneficial uses that have been affected by various complex processes, including sedimentation, nuisance flows, reduced tidal circulation, and other factors. These actions may include Lagoon sediment remediation efforts, re-connecting the Lagoon's historic tidal channels, and maintenance of the Lagoon inlet in collaboration with State Parks, the San Diego Water Board, the Los Angeles-San Diego-San Luis Obispo (LOSSAN) Rail Corridor Agency, US EPA, and the watershed responsible parties. Phase II may also include additional upstream protections and BMP implementation to further reduce watershed sediment contributions. Responsible parties will develop, prioritize, and implement Phase II elements based on data from compliance monitoring and special studies.
- Phase III includes implementation of secondary and additional remediation actions, as necessary, to be in compliance with the required WLA allocation by the end of the compliance schedule.

Develop and Submit a Load Reduction Plan

Responsible parties are required to prepare and submit for San Diego Water Board review, comment, and revision, a Load Reduction Plan that demonstrates how they will comply with this TMDL. The San Diego Water Board expects that Load Reduction Plans will be developed collaboratively by the responsible parties within the watershed. The Load Reduction Plan shall be submitted to the San Diego Water Board within 18 months of the TMDL effective date, and reviewed by the San Diego Water Board Executive Officer within six months of submittal (this period will likely include a round of revisions by the responsible parties based on San Diego Water Board staff comments).

The Load Reduction Plan shall establish a watershed-wide, programmatic, adaptive management approach for implementation and include a detailed description of implementation actions, identified and planned by the responsible parties, to meet the requirements of this TMDL. Implementation actions identified by the Load Reduction Plan may include source control techniques, structural and/or non-structural storm water BMPs, and/or special studies that refine the understanding of sediment and pollutant sources within the watershed. The Load Reduction Plan shall include a description and objective of each implementation action, potential BMP locations, a timeline for project or BMP completion, and a monitoring plan to measure the effectiveness of implementation actions.

Storm Water Pollution Prevention Plans (SWPPPs) prepared by Phase II MS4s, Industrial Permittees, and Construction Permittees pursuant to their respective statewide general NPDES permits fulfill these entities responsibility to prepare a Load Reduction Plan. Permittees within the Los Peñasquitos watershed shall update their SWPPPs within 12 months of the TMDL effective date with any additional BMPs, monitoring, etc. to account for their site's potential to impact the receiving waterbody with respect to sediment. Sites identified through monitoring data or site inspections as posing an increased risk to the receiving water body may be directed to perform additional monitoring by the San Diego Water Board Executive Officer to quantify sediment load contributions to the receiving waterbody.

Comprehensive Approach

The comprehensive approach to the Load Reduction Plan requires that implementation efforts address all current TMDLs, current 303(d) listed waterbody/pollutant combinations, and other targeted impairments within the Los Peñasquitos watershed. A comprehensive approach to the Load Reduction Plan is consistent with implementation planning currently underway to address all of the impaired segments that were included in the approved bacteria TMDLs for San Diego Region Beaches and Creeks (San Diego Water Board, 2010).

The comprehensive approach to the Load Reduction Plan allows the responsible parties to proactively address other listed impairments within the watershed, which requires special studies to investigate sources and the water quality improvements needed to address these pollutants. Such special studies may significantly alter current understanding and refine the TMDL loading and/or allocations. This can impact the selection of subsequent implementation actions and how they are prioritized by responsible parties. A comprehensive approach to development of the Load Reduction Plan will provide a more cost effective and efficient approach for TMDL implementation and will have fewer potential environmental impacts associated with construction of structural BMPs (San Diego Water Board, 2010).

Load Reduction Plan Framework

With increased land development and inadequate management of runoff from impervious areas, increasing amounts of sediment are deposited into the Lagoon annually. To minimize the effects of runoff, proper sediment control can be achieved through the execution of implementation actions such as BMPs. Sediment implementation actions can be grouped into the four categories as summarized below.

1) *Preservation and Restoration*

Significant areas of land have been set aside for open space. Such land acquisition and preservation prevents natural areas from being developed and disturbed. Additionally, the restoration of riparian buffers and wetlands can include the stabilization of steep slopes with native riparian vegetation. This not only helps restore the habitat but also the natural function of the stream.

2) *Education & Outreach*

As a source control technique, education and outreach can function as pollution prevention to reduce or eliminate the amount of sediment generated at its source. Education and outreach can be targeted at specific land user groups and/or staff involved with site maintenance. As an example, implementation actions such as municipal incentives can be used to encourage proper irrigation and landscaping and can significantly reduce volumes of runoff.

3) *Retrofitting, New Development, & Site Management*

Land development (MS4 contribution) is the primary source of anthropogenic sediment contribution above historical conditions. Development can expose sediment and contribute excessive amounts of sediment to the Lagoon. Additionally, increased imperviousness associated with development can lead to increased storm water runoff and soil erosion or gulying within the MS4 and receiving waters. Appropriate site management can partially or fully mitigate the effects of development. The Load Reduction Plan must identify and prioritize BMPs based on an analysis of opportunities and cost/benefit considerations. Furthermore, the Load Reduction Plan must detail BMP projects and locations. Storm water BMPs can be implemented to reduce the effects of pollutant loading and increased storm water flows from development. Structural BMPs include incorporation of low impact development (LID) and storm flow hydrograph matching into new projects. The same structural BMPs can be utilized to retrofit existing sites or be applied as regional MS4 BMPs to treat pollutants and/or flows prior to discharge into receiving waters.

4) *Monitoring:*

A coordinated monitoring plan is needed to establish existing watershed conditions (baseline conditions) from which future changes and anticipated improvement in water quality can be measured. Additional monitoring could focus on sensitive species, areas of saltmarsh coverage, extent of invasive plant species, BMP effectiveness, and/or reduction in impervious coverage. Additionally, monitoring is crucial in the assessment of implementation actions to gain an understanding of performance for future adaptive management actions.

Load Reduction Plan Implementation

The Load Reduction Plan must be implemented within 90 days upon receipt of San Diego Water Board comments and recommendation, but in any event, no later than 6 months after submittal.

MONITORING

Monitoring is required to measure the progress of pollutant load reductions and improvements in water and saltmarsh habitat acreage. The information presented below is intended to be a brief overview of the goals of the monitoring. Special studies may be planned to improve understanding of key aspects related to achievement of WLAs and LAs, restore the beneficial uses, and to assist in the modification of structural and non-structural BMPs if necessary. The goals of monitoring include:

- 1) To determine compliance with the assigned wasteload and load allocations.
- 2) To monitor the effect of implementation actions proposed by responsible parties to improve water and saltmarsh habitat quality including proposed structural and non-structural BMPs to reduce storm water run-off and sediment loading, and remediation actions to remove sediment from the Lagoon.
- 3) To monitor the extent of vegetation habitat acreages in the Lagoon and determine if additional implementation action should be required.
- 4) To implement the monitoring in a manner consistent with other TMDL implementation plans and regulatory actions within the Los Peñasquitos watershed.

The proposed monitoring program shall be included in the Load Reduction Plan submitted to the San Diego Water Board Executive Officer for review.

Watershed Monitoring

Responsible parties must conduct suspended sediment, bedload, and flow monitoring to calculate total sediment loading to the Lagoon for each wet period (October 1 thru April 30) throughout the 20-year compliance period. The responsible parties must monitor enough storm events throughout to quantify sediment loading over each wet period. The compliance point for the WLA shall be the Lagoon as measured through the cumulative sediment loading from Los Peñasquitos, Carroll Canyon, and Carmel Creeks prior to entering the Lagoon. The responsible parties must monitor as many stations as necessary to quantify sediment loading to the Lagoon. Because of the natural variability in sediment delivery rates, sediment loading shall be evaluated using a 3-year, weighted rolling average. The first average must be calculated following the third critical wet period after the TMDL effective date.

Responsible parties are encouraged to collaborate or coordinate their efforts with other regional and local monitoring programs to avoid duplication and reduce associated costs.

Lagoon Monitoring

The responsible parties shall monitor the Lagoon annually in the Fall for changes in extent of the vegetation types. Aerial photos of the Lagoon must be acquired, digitized onscreen (at an approximate 1:2,500 scale), interpreted, and mapped into generalized classifications. Vegetation types must be classified as saltmarsh, non-tidal saltmarsh, freshwater marsh, non-tidal saltmarsh – *Lolium perrene* infested, freshwater marsh, southern willow scrub/mulefat scrub, herbaceous wetland, or upland land cover (urban, beach, dune, upland vegetation, etc.). Vegetation type classifications are described in the *Sediment TMDL for Los Peñasquitos Lagoon Staff Report*. Ground truthing may be performed after aerial photo interpretation to distinguish between vegetation types.

COMPLIANCE SCHEDULE

The implementation schedule for this TMDL follows the form of an adaptive management strategy, tracks implementation progress with established milestones or interim goals, and sets forth a final compliance date. It is impractical for land managers to actually measure sediment loading on a daily basis; thus, compliance with the TMDL is most appropriately expressed as an average annual load and should be evaluated as a long-term running average to account for natural fluctuations and inaccuracies in estimating sediment loads.

Pursuant to State Board Resolution No. 2000-015 and 2000-030 a TMDL compliance schedule must be as short as practicable, but in no case shall it exceed 20 years from the effective date of the Basin Plan amendment. This timeline in Table {Insert Table number} takes into consideration the planning needs of the responsible parties and other stakeholders to establish a Load Reduction Plan, time needed to address multiple impairments, and provides adequate time to measure temporal disparities between reductions in upland loading and the corresponding Lagoon water quality response. Current studies and other implementation actions or projects are underway to reduce sediment loading to the Lagoon and to gain a better understanding of source contributions. A variety of such projects will continue throughout the development of the Load Reduction Plan, ensuring there are no gaps in implementation efforts throughout the process.

At the end of the TMDL compliance schedule, as outlined in Table 7-57, waters must meet the Lagoon's sediment water quality standard and therefore, the Lagoon numeric target. The final lagoon numeric target requires the successful restoration of tidal and non-tidal salt marsh to achieve a lagoon total of 346 acres. This can either mean:

1. Successful restoration of 80 percent of the 1973 acreage of lagoon salt marsh habitat (346 acres); or
2. Demonstrate that implementation actions are active on and/or affecting 346 acres with continued monitoring to ensure 80 percent target achievement.

If at any point during the implementation plan, monitoring data or special studies indicate that WLAs or LAs will be attained but the Lagoon numeric target may not be achieved, the San Diego Water Board shall reconsider the TMDL to modify WLAs and LAs to ensure that the Lagoon numeric target is attained.

Table 7-57. Los Peñasquitos Lagoon Sediment TMDL Implementation Compliance Schedule

Item	Implementation Action	Responsible Party	Date
1	Obtain approval by OAL of Los Peñasquitos Lagoon Sediment TMDL = Establishes effective date of TMDL	San Diego Water Board, San Diego County, City of San Diego, City of Poway, City of Del Mar, Caltrans, General Storm Industrial and Construction permittees	Estimated June 2013
2a	Issue, reissue, or revise general WDRs and NPDES requirements for Phase I MS4s, including Caltrans, to incorporate requirements for complying with TMDL and WLAs	San Diego Water Board and State Water Board	Completed during permit renewal - within 5 years of applicable permit date, and every 5 years thereafter.
2b	Issue, reissue, or revise general WDRs and NPDES requirements for Construction and Industrial NPDES to incorporate requirements for complying with TMDL and WLAs	San Diego Water Board and State Water Board	Completed during permit renewal - within 5 years of applicable permit date, and every 5 years thereafter.

Item	Implementation Action	Responsible Party	Date
2c	Issue, reissue, or revise general WDRs and NPDES requirements for Phase II NPDES permittees to incorporate requirements for complying with TMDL and WLAs	San Diego Water Board and State Water Board	Completed during permit renewal - within 5 years of applicable permit date, and every 5 years thereafter.
3a	Completion of Load Reduction Plans	Phase 1 MS4s and Caltrans	Within 18 months of OAL effective date for sediment TMDL
3b	Approval of Load Reduction Plan	San Diego Water Board Executive Officer	Within 6 months of submittal
3c	Phased, adaptive implementation of Load Reduction Plan	Phase 1 MS4s and Caltrans	In accordance with Load Reduction Strategy – ongoing throughout the implementation
3d	Revision of SWPPPs	Construction, industrial, and Phase II Permittees	Within 12 months of OAL effective date for sediment TMDL
4a	Submit annual Progress Report to the San Diego Water Board due January 31 each year	Phase 1 MS4s	Annually after reissuance of NPDES WDR
4b	Submit annual Progress Report to the San Diego Water Board due April 1 each year	Caltrans	Annually after reissuance of NPDES WDR
5	Enforcement Actions	San Diego Water Board	As needed
6	Refine Load Reduction Plan	Phase 1 MS4s and Caltrans	As warranted by completion of special studies, additional monitoring and data compilation.
7	Reopen and reconsider TMDL	San Diego Water Board	As defensible through the collection of additional data and significant findings by the watershed stakeholders.
8	Meet Interim Milestone #1: Attain 20 percent required reduction in sediment loading (equivalent to 6691 tons of sediment per year) and/or show progress in improving Lagoon conditions consistent with the specified targets	MS4s and NPDES permittees	Within 5 years of approved TMDL
9	Meet Interim Milestone #2: Attain 40 percent required reduction in sediment loading (equivalent to 5663 tons of sediment per year) and/or show progress in improving Lagoon conditions consistent with the specified targets	MS4s and NPDES permittees	Within 9 years of approved TMDL

Item	Implementation Action	Responsible Party	Date
10	Meet Interim Milestone #3: Attain 60 percent required reduction in sediment loading (equivalent to 4636 tons of sediment per year) and/or show progress in improving Lagoon conditions consistent with the specified targets	MS4s and NPDES permittees	Within 13 years of approved TMDL
11	Meet Interim Milestone #4: Attain 80 percent required reduction in sediment loading (equivalent to 3608 tons of sediment per year) and/or show progress in improving Lagoon conditions consistent with the specified targets	MS4s and NPDES permittees	Within 15 years of approved TMDL
12	Meet Final Milestone: Achieve Lagoon numeric target: the successful restoration of tidal and non-tidal salt marsh to achieve a lagoon total of 346 acres. ⁷⁷	All Phase I, Phase II MS4s, Caltrans, and general construction and industrial NPDES enrollees, and other WDR and NPDES permittees in the watershed ⁷⁸	Within 20 years of approved TMDL

Note: TMDL implementation schedule may be altered due to TMDL reconsideration; additionally, enforcement actions by the San Diego Water Board will be taken as necessary.

⁷⁷ This can either mean:

1. Successful restoration of 80 percent of the 1973 acreage of lagoon salt marsh habitat (346 acres); or
2. Demonstrate that implementation actions are active on and/or affecting 346 acres with continued monitoring to ensure 80 percent target achievement.

⁷⁸ For general construction and industrial permittees and other NPDES/WDR permittees, this applies to those facilities that have potential for long-term loadings into the watershed.