

State Water Resources Control Board

Division of Drinking Water

November 3, 2015
System No.: 5400735

Ms. Diane Rodriguez-Cole
Rodriguez Labor Camp
P.O. Box 1270
Delano, CA 93216

RE: Compliance Order No. 03-24-15R-002
Violation of the Nitrate Maximum Contaminant Level

Dear Ms. Rodriguez-Cole:

Enclosed is a Compliance Order issued to the Rodriguez Labor Camp (Water System) public water system.

As directed in the enclosed Compliance Order, please provide recognition of receipt of this Compliance Order and the Water System's intent to comply with the Order to the Division of Drinking Water, Tulare District office by **November 30, 2015**.

If you have any questions regarding this letter or the enclosed Compliance Order, please contact the Tulare District office at (559) 447-3300.

Sincerely,



Chad Fischer, P.E.
Senior Sanitary Engineer, Tulare District
SOUTHERN CALIFORNIA BRANCH
DRINKING WATER FIELD OPERATIONS

CJF/MRC
Enclosures

cc: Tulare County Environmental Health Division
Tom Day, Contract Operator (P.O. Box 10642, Terra Bella, CA 93270)

1
2
3 **CALIFORNIA**
4 **STATE WATER RESOURCES CONTROL BOARD**
5 **DIVISION OF DRINKING WATER**
6

7 TO: Rodriguez Labor Camp
8 ATTN: Ms. Diane Rodriguez-Cole
9 P.O. Box 1270
10 Delano, CA 93216
11

12 **COMPLIANCE ORDER NO. 03-24-15R-002**
13 **FOR**
14 **VIOLATION OF HEALTH AND SAFETY CODE SECTION 116655 (a)(1)**
15 **AND THE PRIMARY DRINKING WATER STANDARD FOR NITRATE,**
16 **Dated November 3, 2015**

17 The State Water Resources Control Board (hereinafter "Board"), acting by and
18 through its Division of Drinking Water (hereinafter "Division") and the Deputy Director
19 for the Division (hereinafter "Deputy Director"), hereby issues this compliance order
20 (hereinafter "Order") pursuant to Section 116655 of the California Health and Safety
21 Code (hereinafter "CHSC") to Rodriguez Labor Camp for violation of CHSC section
22 116555(a)(1) and Title 22, California Code of Regulations (hereinafter "CCR"),
23 Section 64431.
24
25
26
27

1 **APPLICABLE AUTHORITIES**

2
3 **CHSC, Section 116555(a)(1) states in relevant part:**

- 4 (a) Any person who owns a public water system shall ensure that the system does
5 all of the following:
6 (1) Complies with primary and secondary drinking water standards.

7 **CHSC, Section 116655 states in relevant part:**

- 8 (a) Whenever the department determines that any person has violated or is violating
9 this chapter, or any permit, regulation, or standard issued or adopted pursuant
10 to this chapter, the director may issue an order doing any of the following:
11 (1) Directing compliance forthwith.
12 (2) Directing compliance in accordance with a time schedule set by the
13 department.
14 (3) Directing that appropriate preventive action be taken in the case of a
15 threatened violation.
16 (b) An order issued pursuant to this section may include, but shall not be limited to,
17 any or all of the following requirements:
18 (1) That the existing plant, works, or system be repaired, altered, or added to.
19 (2) That purification or treatment works be installed.
20 (3) That the source of the water supply be changed.
21 (4) That no additional service connection be made to the system.
22 (5) That the water supply, the plant, or the system be monitored.
23 (6) That a report on the condition and operation of the plant, works, system, or
24 water supply be submitted to the department.
25
26
27

19 **Title 22, CCR, Section 64431 (hereinafter “Section 64431”), states in relevant
20 part:**

21
22 Public water systems shall comply with the primary MCLs in table 64431-A as
23 specified in this article.
24
25
26
27

Table 64431-A
Maximum Contaminant Levels
Inorganic Chemicals

<i>Chemical</i>	<i>Maximum Contaminant Level, mg/L</i>
Aluminum	1.
Antimony	0.006
Nitrate	0.010
Asbestos	7 MFL*
Barium	1.
<i>Chemical</i>	<i>Maximum Contaminant Level, mg/L</i>
Beryllium	0.004
Cadmium	0.005
Chromium	0.05
Cyanide	0.15
Fluoride	2.0
Hexavalent chromium	0.010
Mercury	0.002
Nickel	0.1
Nitrate (as NO ₃)	45.
Nitrate+Nitrite (sum as	10.
Nitrite (as nitrogen)	1.
Perchlorate	0.006
Selenium	0.05
Thallium	0.002

* MFL=million fibers per liter; MCL for fibers exceeding 10 um in length.

Title 22, CCR Section 64432 (hereinafter "Section 64432") provides in relevant part:

Section 64432.1

(a) To determine compliance with the MCL for nitrate in Table 64431-A, all public water systems using groundwater and transient-noncommunity systems using approved surface water shall monitor annually, and all community and nontransient-noncommunity systems using approved surface water shall monitor quarterly.

(1) The water supplier shall require the laboratory to notify the supplier within 24 hours whenever the level of nitrate in a single sample exceeds the MCL, and shall ensure that a contact person is available to receive such analytical results 24-hours a day. The water supplier shall also require the laboratory to immediately notify the Division of any acute nitrate MCL exceedance if the laboratory cannot make direct contact with the designated contact person within 24 hours. Within 24 hours of notification, the water supplier shall:

(A) Collect another sample, and

1 (B) Analyze the new sample; if the average of the two nitrate sample results
2 exceeds the MCL, report the result to the Division within 24 hours. If the
3 average does not exceed the MCL, inform the Division of the results
4 within seven days from the receipt of the original analysis.

5 (C) If a system is unable to resample within 24 hours, it shall notify the
6 consumers by issuing a Tier 1 Public Notice pursuant to section 64463.1
7 and shall collect and analyze a confirmation sample within two weeks of
8 notification of the results of the first sample.

9 (2) For public water systems using groundwater, the repeat monitoring
10 frequency shall be quarterly for at least one year following any one sample
11 in which the concentration is greater than or equal to 50 percent of the MCL.
12 After four consecutive quarterly samples are less than the MCL, a system
13 may request that the Division reduce monitoring frequency to annual
14 sampling.

15 STATEMENT OF FACTS

16 Division is informed by the Water System and believes that the Rodriguez Labor
17 Camp water system (hereinafter "Water System") is a community water system
18 located in Tulare County that supplies water for domestic purposes to approximately
19 110 individuals through approximately 35 service connections. The Water System
20 operates under Domestic Water Supply Permit No. 03-24-15P-046 issued by the
21 Division. The Water System is a community public water system as defined in
22 CHSC, section 116275.

23 The Water System utilizes one groundwater well as its source of domestic water.
24 Title 22, CCR, Division 4, Chapter 15, Article 4, establishes primary drinking water
25 standards and monitoring and reporting requirements for inorganic constituents.
26 Community and nontransient noncommunity water systems must comply with the
27 maximum contaminant level for nitrate (as NO₃) of 45.0 mg/L, as established in Title
28 22 CCR Section 64431.

1 A sample collected from the Water System on August 23, 2015, showed a nitrate
 2 concentration of 113 mg/L in Well 01. Sample results from June 2005 to present are
 3 provided in Table 1 below:
 4

5 **Table 1: Well 01 Nitrate Monitoring Results**

Sample Date	Well 01
6/27/05	130 mg/L
7/21/06	130 mg/L
7/27/07	130 mg/L
10/20/09	121 mg/L
3/4/10	110 mg/L
7/24/11	126 mg/L
7/22/12	150 mg/L
7/21/13	120 mg/L
9/30/14	120 mg/L
5/6/15	138 mg/L
8/23/15	138 mg/L

6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17 Specifically, the Water System exceeded the nitrate MCL (45.0 mg/L as NO₃) by
 18 delivering water to the distribution system that was over the nitrate MCL. The last
 19 sample result collected on August 23, 2015 was 138 mg/L.

20
 21 By regulation, public notification is required on a quarterly basis as long as the well
 22 is being used. The Water System must also provide the Division with proof of public
 23 notification.
 24
 25
 26
 27

1 **DETERMINATIONS**

2 Based on the above Statement of Facts, the Division has determined that the Water
3 System has violated CHSC, Section 116555 and Section 64431 in that the water
4 produced by Well 01, exceeded the nitrate MCL as shown in Table 1 above, and
5 further has determined that said violation has continued from August 23, 2015 and
6 through the date of this Order.

7
8 **DIRECTIVES**

9 Water System is hereby directed to take the following actions:

- 10
- 11 1. On or before **December 1, 2018**, comply with Title 22, CCR, Section 64431
12 and remain in compliance.
 - 13
 - 14 2. On or before **November 30, 2015**, submit a written response to the Division
15 indicating the Water System's agreement to comply with the directives of this
16 Order and with the Corrective Action Plan addressed herein.
 - 17
 - 18 3. Commencing on the date of service of this Order, provide quarterly public
19 notification in accordance with Attachment A, hereto, of the Water System's
20 failure to meet the nitrate MCL (10.0 mg/L as N) during any calendar quarter
21 that the sample results exceeds the MCL.
 - 22
 - 23 4. Commencing on the date of service of this Order, submit proof of each public
24 notification conducted in compliance with Directive No. 3, herein above, within
25 10 days following each such notification, using the form provided as Attachment
26 B, hereto.
 - 27

- 1 5. Commencing on the date of service of this Order collect quarterly samples for
2 nitrate as N from Well 01, as required by Section 64432(g), and ensure that the
3 analytical results are reported to the Division electronically by the analyzing
4 laboratory no later than the 10th day following the month in which the analysis
5 was completed.
6
- 7 6. Prepare for Division approval a Corrective Action Plan identifying improvements
8 to the water system designed to correct the water quality problem (violation of
9 the nitrate MCL) and ensure that the Water System delivers water to
10 consumers that meets primary drinking water standards. The plan shall include
11 a time schedule for completion of each of the phases of the project such as
12 design, construction, and startup, and a date as of which the Water System will
13 be in compliance with the nitrate MCL, which date shall be no later than
14 December 1, 2018.
15
- 16 7. On or before **January 31, 2016**, present the Corrective Action Plan required
17 under Directive No. 6, above, to the Division in person at the Division's offices
18 located at 265 W. Bullard Avenue, Suite 101, Fresno, CA 93704.
19
- 20 8. Timely perform the Division approved Corrective Action Plan and each and
21 every element of said plan according to the time schedule set forth therein.
22
- 23 9. On or before **January 10, 2016**, and every three months thereafter, submit a
24 report to the Division in the form provided as Attachment C, hereto, showing
25 actions taken during the previous calendar three months to comply with the
26 Corrective Action Plan.
27

1 10. Not later than ten (10) days following the date of compliance with the nitrate
2 MCL, demonstrate to the Division that the water delivered by Water System
3 complies with the nitrate MCL.
4

5 11. Notify the Division in writing no later than five (5) days prior to the deadline for
6 performance of any Directive set forth herein if Water System anticipates it will
7 not timely meet such performance deadline.
8

9 All submittals required by this Order shall be addressed to:
10

11 Chad Fischer, P.E., Senior Sanitary Engineer
12 State Water Resources Control Board
13 Division of Drinking Water, Tulare District
14 265 W. Bullard Avenue, Suite 101
15 Fresno, CA 93704

16 As used in this Order, the date of issuance shall be the date of this Order; and the
17 date of service shall be the date of service of this Order, personal or by certified
18 mail, on the Water System.

19 The Division reserves the right to make such modifications to this Order and/or to
20 issue such further order(s) as it may deem necessary to protect public health and
21 safety. Such modifications may be issued as amendments to this Order and shall be
22 deemed effective upon issuance.
23

24 Nothing in this Order relieves Water System of its obligation to meet the
25 requirements of the California SDWA, or any regulation, standard, permit or order
26 issued thereunder.
27

1 **PARTIES BOUND**

2 This Order shall apply to and be binding upon Water System, its owners,
3 shareholders, officers, directors, agents, employees, contractors, successors, and
4 assignees.
5

6 **SEVERABILITY**

7 The Directives of this Order are severable, and Water System shall comply with
8 each and every provision hereof, notwithstanding the effectiveness of any other
9 provision.
10

11 **FURTHER ENFORCEMENT ACTION**

12 The California SDWA authorizes the Board to: issue a citation with assessment of
13 administrative penalties to a public water system for violation or continued violation
14 of the requirements of the California SDWA or any regulation, permit, standard,
15 citation, or order issued or adopted thereunder including, but not limited to, failure to
16 correct a violation identified in a citation or compliance order. The California SDWA
17 also authorizes the Board to take action to suspend or revoke a permit that has been
18 issued to a public water system if the public water system has violated applicable
19 law or regulations or has failed to comply with an order of the Board; and to petition
20 the superior court to take various enforcement measures against a public water
21 system that has failed to comply with an order of the Board. The Board does not
22 waive any further enforcement action by issuance of this Order.
23
24
25
26
27

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27



Carl Carlucci, P.E., Chief
Central California Section
State Water Resources Control Board
Division of Drinking Water

11-3-2015

Date

Certified Mail No. 7014 3490 0001 7868 7975



Attachments:

- Attachment A: Applicable Authorities
- Attachment B: Public Notification Form
- Attachment C: Proof of Notification Form
- Attachment D: Quarterly Progress Report Form

cc: County of Tulare, Department of Environmental Health (w/o attachments)
Tom Day, Contract Operator (P.O. Box 10642, Terra Bella, CA 93270)

Applicable AuthoritiesViolation of Maximum Contaminant Levels forNitrate

California Health and Safety Code, Section 116655, states in relevant part:

(a) Whenever the department determines that any person has violated or is violating this chapter, or any permit, regulation, or standard issued or adopted pursuant to this chapter, the director may issue an order doing any of the following:

- (1) Directing compliance forthwith.
- (2) Directing compliance in accordance with a time schedule set by the department.
- (3) Directing that appropriate preventive action be taken in the case of a threatened violation.

(b) An order issued pursuant to this section may include, but shall not be limited to, any or all of the following requirements:

- (1) That the existing plant, works, or system be repaired, altered, or added to.
- (2) That purification or treatment works be installed.
- (3) That the source of the water supply be changed.
- (4) That no additional service connection be made to the system.
- (5) That the water supply, the plant, or the system be monitored.
- (6) That a report on the condition and operation of the plant, works, system, or water supply be submitted to the department.

California Code of Regulations, Title 22, states in relevant part:

§64431. Maximum Contaminant Levels--Inorganic Chemicals.

Public water systems shall comply with the primary MCLs in table 64431-A as specified in this article.

Table 64431-A
Maximum Contaminant Levels
Inorganic Chemicals

<i>Chemical</i>	<i>Maximum Contaminant Level, mg/L</i>
Aluminum	1.
Antimony	0.006
Arsenic	0.010
Asbestos	7 MFL*
Barium	1.
Beryllium	0.004
Cadmium	0.005
Chromium	0.05
Cyanide	0.15
Fluoride	2.0
Hexavalent chromium	0.010
Mercury	0.002
Nickel	0.1
Nitrate (as NO ₃)	45.

Nitrate+Nitrite (sum as nitrogen)	10.
Nitrite (as nitrogen)	1.
Perchlorate	0.006
Selenium	0.05
Thallium	0.002

* MFL=million fibers per liter; MCL for fibers exceeding 10 um in length.

§64432. Monitoring and Compliance--Inorganic Chemicals.

(a) All public water systems shall monitor to determine compliance with the nitrate and nitrite MCLs in table 64431-A, pursuant to subsections (d) through (f) and Section 64432.1. All community and nontransient-noncommunity water systems shall monitor to determine compliance with the perchlorate MCL, pursuant to subsections (d), (e), (l), and section 64432.3. All community and nontransient-noncommunity water systems shall also monitor to determine compliance with the other MCLs in table 64431-A, pursuant to subsections (b) through (n) and, for asbestos, section 64432.2. Monitoring shall be conducted in the year designated by the Department of each compliance period beginning with the compliance period starting January 1, 1993.

(b) Unless directed otherwise by the Department, each community and nontransient-noncommunity water system shall initiate monitoring for an inorganic chemical within six months following the effective date of the regulation establishing the MCL for the chemical and the addition of the chemical to table 64431-A.

(1) If otherwise performed in accordance with this section, groundwater monitoring for an inorganic chemical performed no more than two years prior to the effective date of the regulation establishing the MCL may be used to satisfy the requirement for initiating monitoring within six months following such effective date.

(2) For routine monitoring required in subsection (c), chromium monitoring may be used in lieu of hexavalent chromium monitoring if the chromium results are less than the chromium DLR set forth in table 64432-A.

(c) Unless more frequent monitoring is required pursuant to this Chapter, the frequency of monitoring for the inorganic chemicals listed in table 64431-A, except for asbestos, nitrate/nitrite, and perchlorate, shall be as follows:

(1) Each compliance period, all community and nontransient-noncommunity systems using groundwater shall monitor once during the year designated by the Department. The Department will designate the year based on historical monitoring frequency and laboratory capacity. All community and nontransient-noncommunity systems using approved surface water shall monitor annually. All systems monitoring at distribution entry points which have combined surface and groundwater sources shall monitor annually.

(2) Quarterly samples shall be collected and analyzed for any chemical if analyses of such samples indicate a continuous or persistent trend toward higher levels of that chemical, based on an evaluation of previous data.

(d) For the purposes of sections 64432, 64432.1, 64432.2, and 64432.3, detection shall be defined by the detection limits for purposes of reporting (DLRs) in table 64432-A.

**Table 64432-A
Detection Limits for Purposes of Reporting (DLRs) for Regulated Inorganic Chemicals**

<i>Chemical</i>	<i>Detection Limit for Purposes of Reporting (DLR) (mg/L)</i>
Aluminum	0.05
Antimony	0.006
Arsenic	0.002
Asbestos	0.2 MFL>10um*
Barium	0.1
Beryllium	0.001
Cadmium	0.001
Chromium	0.01
Cyanide	0.1
Fluoride	0.1
Hexavalent chromium	0.001
Mercury	0.001
Nickel	0.01
Nitrate (as NO ₃)	2.
Nitrite (as nitrogen)	0.4
Perchlorate	0.004
Selenium	0.005
Thallium	0.001

* MFL=million fibers per liter; DLR for fibers exceeding 10 um in length.

(e) Samples shall be collected from each water source or a supplier may collect a minimum of one sample at every entry point to the distribution system which is representative of each source after treatment. The system shall collect each sample at the same sampling site, unless a change is approved by the Department.

(f) A water system may request approval from the Department to composite samples from up to five sampling sites, provided that the number of sites to be composited is less than the ratio of the MCL to the DLR. Approval will be based on a review of three years of historical data, well construction and aquifer information for groundwater, and intake location, similarity of sources, and watershed characteristics for surface water. Compositing shall be done in the laboratory.

(1) Systems serving more than 3,300 persons shall composite only from sampling sites within a single system. Systems serving 3,300 persons or less may composite among different systems up to the 5-sample limit.

(2) If any inorganic chemical is detected in the composite sample at a level equal to or greater than one fifth of the MCL, a follow-up sample shall be analyzed within 14 days from each sampling site included in the composite for the contaminants which exceeded the one-fifth-MCL level. If available, duplicates of the original sample taken from each sampling site used in the composite may be used instead of resampling; the analytical results shall be reported within 14 days. The water supplier may collect up to two additional samples each from one or more of the sources to confirm the result(s).

(3) Compliance for each site shall be determined on the basis of the individual follow-up samples, or on the average of the follow-up and confirmation sample(s) if the supplier collects confirmation sample(s) for each detection.

(g) If the level of any inorganic chemical, except for nitrate, nitrite, nitrate plus nitrite, or perchlorate, exceeds the MCL, the water supplier shall do one of the following:

- (1) Inform the Department within 48 hours and monitor quarterly beginning in the next quarter after the exceedance occurred; or
- (2) Inform the Department within seven days from the receipt of the analysis and, as confirmation, collect one additional sample within 14 days from receipt of the analysis. If the average of the two samples collected exceeds the MCL, this information shall be reported to the Department within 48 hours and the water supplier shall monitor quarterly beginning in the next quarter after the exceedance occurred.

(h) If the concentration of an inorganic chemical exceeds ten times the MCL, within 48 hours of receipt of the result the water supplier shall notify the Department and resample as confirmation. The water supplier shall notify the Department of the result(s) of the confirmation sample(s) within 24 hours of receipt of the confirmation result(s).

(1) If the average concentration of the original and confirmation sample(s) is less than or equal to ten times the MCL, the water supplier shall monitor quarterly beginning in the quarter following the quarter in which the exceedance occurred.

(2) If the average concentration of the original and confirmation sample(s) exceeds ten times the MCL, the water supplier shall, if directed by the Department;

(A) Immediately discontinue use of the contaminated water source; and

(B) Not return the source to service without written approval from the Department.

(i) Compliance with the MCLs shall be determined by a running annual average; if any one sample would cause the annual average to exceed the MCL, the system is immediately in violation. If a system takes more than one sample in a quarter, the average of all the results for that quarter shall be used when calculating the running annual average. If a system fails to complete four consecutive quarters of monitoring, the running annual average shall be based on an average of the available data.

(j) If a system using groundwater has collected a minimum of two quarterly samples or a system using approved surface water has collected a minimum of four quarterly samples and the sample results have been below the MCL, the system may apply to the Department for a reduction in monitoring frequency.

(k) Water quality data collected prior to January 1, 1990, and/or data collected in a manner inconsistent with this section shall not be used in the determination of compliance with the monitoring requirements for inorganic chemicals.

(l) Water quality data collected in compliance with the monitoring requirements of this section by a wholesaler providing water to a public water system shall be acceptable for use by that system for compliance with the monitoring requirements of this section.

(m) A water system may apply to the Department for a waiver from the monitoring frequencies specified in subsection (c)(1), if the system has conducted at least three rounds of monitoring (three periods for groundwater sources or three years for approved surface water sources) and all previous analytical results are less than the MCL. The water system shall specify the basis for its request. If granted a waiver, a system shall collect a minimum of one sample per source while the waiver is in effect and the term of the waiver shall not exceed one compliance cycle (i.e., nine years).

(n) A water system may be eligible for a waiver from the monitoring frequencies for cyanide specified in subsection (c)(1) without any prior monitoring if it is able to document that it is not vulnerable to cyanide contamination pursuant to the requirements in §64445(d)(1) or (d)(2).

(o) Transient-noncommunity water systems shall monitor for the inorganic chemicals in table 64431-A as follows:

- (1) All sources shall be monitored at least once for fluoride; and

(2) Surface water sources for parks and other facilities with an average daily population use of more than 1,000 people and/or which are determined to be subject to potential contamination based on a sanitary survey shall be monitored at the same frequency as community water systems.

§64463.4. Tier 2 Public Notice

(a) A water system shall give public notice pursuant to this section if any of the following occurs:

- (1) Any violation of the MCL, MRDL, and treatment technique requirements, except:
 - (A) Where a Tier 1 public notice is required under section 64463.1; or
 - (B) Where the Department determines that a Tier 1 public notice is required, based on potential health impacts and persistence of the violations;
- (2) All violations of the monitoring and testing procedure requirements in sections 64421 through 64426.1, article 3 (Primary Standards – Bacteriological Quality), for which the Department determines that a Tier 2 rather than a Tier 3 public notice is required, based on potential health impacts and persistence of the violations;
- (3) Other violations of the monitoring and testing procedure requirements in this chapter, and chapters 15.5, 17 and 17.5, for which the Department determines that a Tier 2 rather than a Tier 3 public notice is required, based on potential health impacts and persistence of the violations; or
- (4) Failure to comply with the terms and conditions of any variance or exemption in place.

(b) A water system shall give the notice as soon as possible within 30 days after it learns of a violation or occurrence specified in subsection (a), except that the water system may request an extension of up to 60 days for providing the notice. This extension would be subject to the Department's written approval based on the violation or occurrence having been resolved and the Department's determination that public health and welfare would in no way be adversely affected. In addition, the water system shall:

- (1) Maintain posted notices in place for as long as the violation or occurrence continues, but in no case less than seven days;
- (2) Repeat the notice every three months as long as the violation or occurrence continues. Subject to the Department's written approval based on its determination that public health would in no way be adversely affected, the water system may be allowed to notice less frequently but in no case less than once per year. No allowance for reduced frequency of notice shall be given in the case of a total coliform MCL violation or violation of a Chapter 17 treatment technique requirement; and
- (3) For turbidity violations pursuant to sections 64652.5(c)(2) and 64653(c), (d) and (f), as applicable, a water system shall consult with the Department as soon as possible within 24 hours after the water system learns of the violation to determine whether a Tier 1 public notice is required. If consultation does not take place within 24 hours, the water system shall give Tier 1 public notice within 48 hours after learning of the violation.

(c) A water system shall deliver the notice, in a manner designed to reach persons served, within the required time period as follows:

- (1) Unless otherwise directed by the Department in writing based on its assessment of the violation or occurrence and the potential for adverse effects on public health and welfare, community water systems shall give public notice by;

- (A) Mail or direct delivery to each customer receiving a bill including those that provide their drinking water to others (e.g., schools or school systems, apartment building owners, or large private employers), and other service connections to which water is delivered by the water system; and
 - (B) Use of one or more of the following methods to reach persons not likely to be reached by a mailing or direct delivery (renters, university students, nursing home patients, prison inmates, etc.):
 - 1. Publication in a local newspaper;
 - 2. Posting in conspicuous public places served by the water system, or on the Internet; or
 - 3. Delivery to community organizations.
- (2) Unless otherwise directed by the Department in writing based on its assessment of the violation or occurrence and the potential for adverse effects on public health and welfare, noncommunity water systems shall give the public notice by:
- (A) Posting in conspicuous locations throughout the area served by the water system; and
 - (B) Using one or more of the following methods to reach persons not likely to be reached by a public posting:
 - 1. Publication in a local newspaper or newsletter distributed to customers;
 - 2. E-mail message to employees or students;
 - 3. Posting on the Internet or intranet; or
 - 4. Direct delivery to each customer.

§64469 Reporting Requirements

- (d) Within 10 days of giving initial or repeat public notice pursuant to Article 18 of this Chapter, except for notice given under 64463.7(d), each water system shall submit a certification to the Department that it has done so, along with a representative copy of each type of public notice given.

Instructions for Tier 1 Nitrate Notice Template

Template Attached

Since exceeding the nitrate maximum contaminant level is a Tier 1 violation, you must provide public notice to persons served as soon as practical but within 24 hours after you learn of the violation [California Code of Regulations, Title 22, Chapter 15, Section 64463.1(b)]. **During this time period, you must also contact the Department. Each water system required to give public notice must submit the notice to the Department for approval prior to distribution or posting, unless otherwise directed by the Department [64463(b)].** You should also coordinate with your local health department.

Notification Methods

You must use one or more of the following methods to deliver the notice to consumers [64463.1(c)]:

- Radio or television
- Posting in conspicuous locations throughout the area served by the water system
- Hand delivery to persons served by the water system

You may need to use additional methods (e.g., newspaper, delivery of multiple copies to hospitals, clinics, or apartment buildings), since notice must be provided in a manner reasonably calculated to reach all persons served. If you post or hand-deliver, print your notice on letterhead, if available.

The notice attached is appropriate for hand delivery or a newspaper notice. However, you may wish to modify it before using it for radio, TV, or posting. If you do, you must still include all required elements and leave the health effects and notification language in italics unchanged. This language is mandatory [64465].

Multilingual Requirement

Spanish. Each public notice must contain information in Spanish regarding (1) the importance of the notice or (2) contain a telephone number or address where Spanish-speaking residents may contact the water system to obtain a translated copy of the public notice or assistance in Spanish.

Non-English Speaking Groups Other than Spanish-Speaking. For each group that exceeds 1,000 residents or 10% of the residents in the community served, whichever is less, the public notice must (1) contain information in the appropriate language(s) regarding the importance of the notice or (2) contain a telephone number or address where such residents may contact the water system to obtain a translated copy of the notice or assistance in the appropriate language.

Population Served

Make sure it is clear who is served by your water system -- you may need to list the areas you serve.

Alternative Sources of Water

If you are providing alternative sources of water for infants or pregnant women, your notice should say where to obtain it. If you choose to provide bottled water, remember that bottled water can also be contaminated or high in nitrates if the bottler uses water from your system. If you are providing bottled water, make sure it meets standards by contacting the bottler and asking for the most recent test results.

Corrective Action

In your notice, describe corrective actions you are taking. The bullet below describes one action commonly taken by water systems with nitrate/nitrite violations. Use this language, if appropriate, or develop your own:

- “We are investigating water treatment and other options. These may include drilling a new well, mixing the water with low-nitrate water from another source, or buying water from another water system.”

After Issuing the Notice

Send a copy of each type of notice and a certification that you have met all the public notice requirements to the Department within ten days after issuing the notice [64469(d)]. You should also issue a follow-up notice in addition to meeting any repeat notice requirements the Department sets.

It is recommended that you notify health professionals in the area of the violation. People may call their doctors with questions, and the doctors should have the information they need to respond appropriately. They also need to make sure the water is not provided to infants and pregnant women in their care.

It is a good idea to issue a “problem corrected” notice when the violation is resolved.

IMPORTANT INFORMATION ABOUT YOUR DRINKING WATER

Este informe contiene información muy importante sobre su agua potable.
Tradúzcalo o hable con alguien que lo entienda bien.

DRINKING WATER WARNING

Rodriguez Labor Camp water has high levels of nitrate

**DO NOT GIVE THE WATER TO
INFANTS UNDER 6 MONTHS OLD OR PREGNANT WOMEN
OR USE IT TO MAKE INFANT FORMULA**

Water sample results received [date] showed nitrate levels of [level and units]. This is above the nitrate standard, or maximum contaminant level (MCL), of 45 milligrams per liter. Nitrate in drinking water is a serious health concern for infants less than six months old.

What should I do?

- **DO NOT GIVE THE WATER TO INFANTS.** *Infants below the age of six months who drink water containing nitrate in excess of the MCL may quickly become seriously ill and, if untreated, may die because high nitrate levels can interfere with the capacity of the infant's blood to carry oxygen. Symptoms include shortness of breath and blueness of the skin. Symptoms in infants can develop rapidly, with health deteriorating over a period of days. If symptoms occur, seek medical attention immediately.*
- **PREGNANT WOMEN SHOULD NOT CONSUME THE WATER.** *High nitrate levels may also affect the oxygen-carrying ability of the blood of pregnant women.*
- Water, juice, and formula for children under six months of age should not be prepared with tap water. Bottled water or other water low in nitrates should be used for infants until further notice.
- **DO NOT BOIL THE WATER.** Boiling, freezing, filtering, or letting water stand does not reduce the nitrate level. Excessive boiling can make the nitrates more concentrated, because nitrates remain behind when the water evaporates.
- If you have other health issues concerning the consumption of this water, you may wish to consult your doctor.

What happened? What is being done?

Nitrate in drinking water can come from natural, industrial, or agricultural sources (including septic systems, storm water run-off, and fertilizers). Levels of nitrate in drinking water can vary throughout the year. We will let you know if the amount of nitrate is again below the limit.

[Describe corrective action, seasonal fluctuations, and when system expects to return to compliance.]

For more information, please contact [name of contact] at [phone number] or [mailing address].

Please share this information with all the other people who drink this water, especially those who may not have received this notice directly (for example, people in apartments, nursing homes, schools, and businesses). You can do this by posting this public notice in a public place or distributing copies by hand or mail.

Secondary Notification Requirements

Upon receipt of notification from a person operating a public water system, the following notification must be given within 10 days [Health and Safety Code Section 116450(g)]:

- **SCHOOLS:** Must notify school employees, students, and parents (if the students are minors).
- **RESIDENTIAL RENTAL PROPERTY OWNERS OR MANAGERS** (including nursing homes and care facilities): Must notify tenants.
- **BUSINESS PROPERTY OWNERS, MANAGERS, OR OPERATORS:** Must notify employees of businesses located on the property.

This notice is being sent to you by Rodriguez Labor Camp.

State Water System ID#: 5400735. Date distributed: _____.

POSITIVE TOTAL COLIFORM INVESTIGATION

This form is intended to assist public water systems in completing the investigation required by the California Department of Public Health (Section 64426(b) of Title 22, California Code of Regulations) and may be modified to take into account conditions unique to the system.

ADMINISTRATIVE INFORMATION

PWS Name:		PWSID NUMBER:	
	Name	Address	Telephone #
Operator in Responsible Charge (ORC)			
Person that collected TC samples if different than ORC			
Owner			
Certified Laboratory for Microbiological Analyses			
Date Investigation Completed:			
Month(s) of Total Coliform MCL Failure:			

INVESTIGATION DETAILS

SOURCE	WELL (name)	WELL (name)	WELL (name)	WELL (name)	COMMENTS
1. Inspect each well head for physical defects and report					
a. Is raw water sample tap upstream from point of disinfection?					
b. Is wellhead vent pipe screened?					
c. Is wellhead seal watertight?					
d. Is well head located in pit or is any piping from the wellhead submerged?					
e. Does the ground surface slope towards well head?					
f. Is there evidence of standing water near the wellhead?					
g. Are there any connections to the raw water piping that could be cross-connections? (describe all connections in comments)					
h. Is the wellhead secured to prevent unauthorized access?					
i. To what treatment plant (name) does this well pump?					
j. How often do you take a raw water total coliform (TC) test?					
k. Provide the date and result of the last TC test at this location					

TREATMENT

TREATMENT	PLANT (NAME)	PLANT (NAME)	PLANT (NAME)	COMMENTS
1. If you provide continuous chlorination treatment, was there any equipment failure? Did the distribution system maintain a chlorine residual?				
a. Was emergency chlorination initiated?				
b. If yes, for how long?				

POSITIVE TOTAL COLIFORM INVESTIGATION

TREATMENT	PLANT (NAME)	PLANT (NAME)	PLANT (NAME)	PLANT (NAME)	PLANT (NAME)	COMMENTS
2. Did the distribution system lose chlorine residual?						
3. If you do not provide routine chlorination, was emergency chlorination initiated? If Yes, when?						
4. Inspect each point where disinfectant is added and report						
a. For hypochlorinator systems						
1. Is the disinfectant feed pump feeding disinfectant?						
2. What is the feed rate of disinfectant in ml/minute						
3. What is the concentration of the disinfectant solution being fed? (percent, or mg/l of chlorine as HOCl)						
4. By what method was the concentration of solution determined? (ex: measured, manufacturer's literature)						
5. What is the age (days) of the disinfectant solution currently being used at this treatment location?						
6. What is the raw water flow rate at the point where disinfectant is added in gallons per minute?						
7. What is the total chlorine residual measured immediately downstream from the point of application?						
8. What is the free chlorine residual measured immediately downstream from the point of application?						
9. What is the contact time in minutes from the point of disinfectant application to the first customer?						

STORAGE	TANK (name)	TANK (name)	TANK (name)	TANK (name)	TANK (name)	COMMENTS
1. Is each tank locked to prevent unauthorized access?						
2. Are all vents of each tank screened down-turned to prevent dust and dirt from entering the tank?						
3. Is the overflow on each tank screened?						
4. Are there any unsealed openings in the tank such as access doors, water level indicators hatches, etc.?						
5. Is the roof/cover of the tank sealed and free of any leaks?						
6. Is the tank above ground or buried.						
a. If buried or partially buried, are there provisions to direct surface water away from the site.						
b. Has the interior of the tank been inspected to identify any sanitary defects, such as root intrusion?						
8. Does the tank "float" on the distribution system or are there separate inlet and outlet						

POSITIVE TOTAL COLIFORM INVESTIGATION

STORAGE	TANK (name)	TANK (name)	TANK (name)	TANK (name)	TANK (name)	COMMENTS
lines?						
9. What is the measured chlorine residual (total/free) of the water exiting the storage tank today ?						
10. What is the volume of the storage tank in gallons?						
11. Is the tank baffled?						
12. Prior to the TC+ or EC+, what was the previous date item #1-7 were checked and documented?						

DISTRIBUTION SYSTEM	SYSTEM RESPONSES
1. What is the minimum pressure you are maintaining in the distribution system?	
2. Did pressure in the distribution system drop to less than 5 psi prior to experiencing the TCR positive finding.	
3. Has the distribution system been worked on within the last week? (service taps, hydrant flushing, main breaks, main extensions, etc.) If yes, provide details.	
4. Are there any signs of excavations near your distribution system not under the direct control of your maintenance staff?	
5. Did you inspect your distribution system to check for mainline leaks? Do you or did you have a mainline leak?	
6. If there was a mainline leak, when was it repaired?	
7. On what date was the distribution system last flushed?	
8. Is there a written flushing procedure you can provide for our review?	
9. Do you have an active cross connection control program?	
10. What is name and phone number of your Cross-Connection Control Program Coordinator?	
11. Is the review and testing of backflow prevention devices current?	
12. On what date was the last physical survey of the system done to identify cross-connections?	

BOOSTER STATION	SYSTEM RESPONSES
1. Do you have a booster pump? How many?	
2. Do you have a standby booster pump if the main pump fails?	
3. Prior to bacteriological quality problems, did your booster pump fail?	
4. Do you notice standing water, leakage at the booster station?	

POSITIVE TOTAL COLIFORM INVESTIGATION

SAMPLE SITE EVALUATION (Complete for all TC+ or EC+ findings)	Routine Site TC+ or EC+	Upstream Site	Downstream Site	Sample 4 (specify)
1. What is the height of the sample tap above grade? (inches)				
2. Is the sample tap located in an exterior location or is it protected by an enclosure ?				
3. Is the sample tap threaded, have a swing arm (kitchen sink) or aerator (sinks)?				
4. Is the sample tap in good condition, free of leaks around the stem or packing?				
5. Can the sample tap be adjusted to the point where a good laminar flow can be achieved without excessive splash?				
6. Is the sample tap and area around the sample tap clean and dry (free of animal droppings, other contaminants or spray irrigation systems)				
7. Is the area around the sample tap free of excessive vegetation or other impediments to sample collection				
8. Describe how the tap was treated in preparation for sample collection (ran water, swabbed with disinfectant, flamed, etc.)				
9. Is this sample tap designated on the sampling plan submitted with this information request?				
10. What were the weather conditions at the time of the positive sample (rainy, windy, sunny),				

GENERAL OPERATIONS:	Response
1. Where there any power outages that affected water system facilities during the 30 days prior to the TC+ or EC + findings?	
2. Where there any main breaks, water outages, or low pressure reported in the service area where TC+ or EC+ samples were located.	
3. Does the system have backup power or elevated storage?	
4. During or soon after bacteriological quality problems, did you receive any complaints of any customers' illness suspected of being waterborne? How many?	
5. What were the symptoms of illness if you received complaints about customers being sick?	

POSITIVE TOTAL COLIFORM INVESTIGATION

Page 5 of 5

ADDITIONAL INFORMATION TO BE SUBMITTED WITH RESPONSES TO THE ABOVE QUESTIONS

1. **Sketch** of System showing all sources, treatment locations, storage tanks, microbiological sampling sites and general layout of the distribution system including the location of all hazardous connections such as the wastewater treatment facility.
2. A set of photographs of the well, pressure tanks, and storage tanks in the system may be submitted if they would show that the contamination is directly related and changes have been made since the last inspection by our Department
3. Name, certification level and certificate number of the Operator in Responsible Charge.
4. Copy of the last cross connection survey performed that identifies the location of all unprotected cross connections.

SUMMARY: BASED ON THE RESULTS OF YOUR INVESTIGATION AND ANY OTHER INFORMATION AT YOUR DISPOSAL, WHAT DO YOU BELIEVE TO BE THE CAUSE OF THE POSITIVE TOTAL COLIFORM SAMPLES FROM YOUR PUBLIC WATER SYSTEM?

CERTIFICATION: I CERTIFY THAT THE INFORMATION SUBMITTED IN RESPONSE TO THE QUESTIONS ABOVE IS ACCURATE TO THE BEST OF MY PROFESSIONAL KNOWLEDGE

NAME: _____ TITLE: _____ DATE: _____

AVISO SOBRE SU AGUA POTABLE

Agua del sistema Rodriguez Labor Camp tiene altos niveles de nitratos

NO DAR DE BEBER ESTA AGUA A BEBES MENORES DE 6 MESES DE EDAD NI USARLA PARA HACER LECHE DE FORMULA

Resultados de muestras de agua colectadas [date of sample(s)] _____ muestran concentraciones de nitratos en el agua de nuestra sistema de [level and units] _____. Este nivel excede el estandar de nitrato, o el nivel máximo de contaminación de 45 mg/L (miligramos por litro) como nitrato. Nitrato en agua potable puede generar problemas serias de salud para bebés menores de 6 meses de edad.

Que debo hacer?

- **NO LE DE ESTA AGUA A BEBES O A MUJERES EMBARAZADAS.** *Bebés menores de seis (6) meses que toman agua con nitrato en exceso del nivel máximo de contaminación se pueden enfermar seriamente y, sin tratamiento medico, pueden morir. Los síntomas incluyen dificultad en respirar y síndrome de bebé azul.* El síndrome de bebé azul se refiere al color azulado que toma la piel del bebé. Los síntomas en los bebes pueden desarrollarse con rapidez. Si los síntomas ocurren en infantes menores de seis (6) meses de edad, busque atención médica inmediatamente.
- **MUJERES EMBARAZADAS NO DEBEN BEBER ESTA AGUA.** Bebiendo agua con nitrato en exceso del nivel máximo de contaminación también puede afectar a mujeres embarazadas reduciendo la capacidad de la sangre para transportar oxígeno. Si usted está embarazada o tiene algún problema de salud en particular, puede optar por hacer una consulta con su médico.
- Agua, jugo o leche en polvo para bebés menores de seis (6) meses de edad no debe prepararse con agua del grifo. Deben usar agua embotellada o otra agua bajo el nitrato para los bebes hasta el próximo aviso.
- **NO HIERVA EL AGUA.** Hervir, congelar, filtrar o dejar el agua en reposo no reduce el nivel de nitrato. De hecho, al hervir el agua puede aumentar aún más la concentración de nitrato, debido a que el nitrato permanece cuando parte del agua se evapora.
- Sin embargo, si usted está embarazada o tiene algún problema de salud en particular, puede optar por hacer una consulta con su médico.

Qué pasó? Qué se está haciendo al respecto?

Nitrato en el agua puede provenir de fuentes naturales, industriales o de la agricultura (incluyendo descargas de tanques sépticos y lluvias). La concentración de nitrato en el agua potable puede variar a traves del año. Nosotros les avisaremos cuando el nivel de nitrato esté nuevamente debajo de el nivel máximo de contaminación.

[Describe corrective action, seasonal fluctuations, and when the system expects to return to compliance.]

Para mas información, favor de contactar a [name of contact] _____ al teléfono [phone number] _____ o escribiendo a [mailing address] _____.

Por favor comparta esta información con otros que pueden tomar de esta agua, colocando este aviso en lugares visibles, o remitiéndolo por correo, o entregandolo manualmente. Es de particular interés distribuir este aviso ampliamente si usted lo recibe representando un negocio, un hospital u hogar de infantes u hogar de ancianos o comunidad residencial.

Este aviso ha sido enviado a usted de parte de _____ Rodriguez Labor Camp.

Fecha [date]: _____

Certification of Completion of Public Notification

This form, when completed and returned to the Division of Drinking Water - Tulare District (265 W. Bullard Ave. #101, Fresno, CA 93704 or fax to 559-447-3304), serves as certification that public notification to water users was completed as required by Title 22, California Code of Regulations, Sections 64463-64465.

Public Water System Name: Rodriguez Labor Camp

Public Water System No.: 5400735

Public notification for **failure to comply with the** Nitrate MCL **for the** quarter **of 20** was performed by the following method(s) (check and complete those that apply):

- The notice was mailed to users on: _____
 A copy of the notice is attached.
- The notice was hand delivered to water customers on: _____
 A copy of the notice is attached.
- The notice was published in the local newspaper on: _____
 A copy of the newspaper notice is attached.
- The notice was published in conspicuous places on: _____
 A copy of the notice is attached.
 A list of locations the notice was posted is attached.
- The notice was delivered to community organizations on: _____
 A copy of the notice is attached.
 A list of community organizations the notice was delivered to is attached.

I hereby certify that the above information is factual.

 Printed Name

 Title

 Signature

 Date

Disclosure: Be advised that Section 116725 and 116730 of the California Health and Safety Code state that any person who knowingly makes any false statement on any report or document submitted for the purpose of compliance with the attached order may be liable for a civil penalty not to exceed five thousand dollars (\$5,000) for separate violation each day that the violation continues. In addition, the violators may be prosecuted in criminal court and, upon conviction, be punished by a fine of not more than \$25,000 for each day of violation, or be imprisoned in the county jail not to exceed one year, or by both the fine and imprisonment.

Due to the Division of Drinking Water within 10 days of issuance of notice to customers

System Number: 5400735

Enforcement Action No. 03-24-15R-002

Quarterly Progress Report

Water System: Rodriguez Labor Camp	Water System No.: 5400735
Compliance Order No.: 03-24-15R-002	Violation: Nitrate MCL
Calendar Quarter:	Date Prepared:

This form should be prepared and signed by Water System personnel with appropriate authority to implement the directives of the Compliance Order and the Corrective Action Plan. Please attach additional sheets as necessary. The quarterly progress report must be submitted by the 10th day of each subsequent quarter, to the Division of Drinking Water, Tulare District Office.

Summary of Compliance Plan:

Tasks completed in the reporting quarter:

Tasks remaining to complete:

Anticipate compliance date:

Name

Signature

Title

Date