

Lake Tahoe Watershed Modeling

Tahoe TMDL Symposium

December 9, 2004

Presented by:

John Riverson



TETRA TECH, INC.

Presentation Outline

- Project background & objectives
- Model setup and parameter selection
- Hydrology: Ward Creek example
 - Meteorological data
 - Model testing, calibration & validation
- Sediment and water quality
 - Methodology
 - TRG stormwater monitoring dataset
 - LTIMP monitoring dataset
- Next Steps



Why do we need a watershed model?

- Organize and integrate very detailed spatial and temporal data to identify/confirm trends
- No such model has ever been developed for Tahoe
- The need was identified by the TMDL Program
- Data compilation effort for modeling not only represents a beneficial contribution for the TMDL program, but also, for many other future efforts.
Examples include:

- Land use layer development
- Identifying potential disturbance factors
- Meteorological data compilation and dissemination
- Monitoring data compilation and dissemination



Watershed Modeling Goals


- Provide estimates for watershed loading of sediment and nutrients to Lake Tahoe
- Provide input to the Lake Clarity Model
- Evaluate management scenarios to meet loading targets
- Estimate TMDL allocation components

Integration of research results



TETRA TECH, INC

Relationship to Other Tasks



Evolution of the Watershed Model

Phase I

Model Scoping with D-Team Input
Data Compilation (historic, ongoing)
Preliminary Model Configuration and Calibration

Hydrology

Sediment

Nutrients

Preliminary TMDL Analysis

Phase II


Model Reconfiguration Using Research Results
Model Recalibration and Validation/Verification
Loading Alternative Evaluation

TMDL Analysis



Model Selection

- Apply EPA's Loading Simulation Program in C++ (LSPC), a dynamic watershed model, to simulate snow and hydrologic processes, erosion and sediment transport, and nutrient production/transport for the Tahoe Watershed



TMDL Modeling Toolbox:

<http://www.epa.gov/athens/wwqtsc/html/lspc.html>

Google: "LSPC Model" or "LSPC EPA"

LSPC Watershed Model

LSPC Model

File Edit View Help

Global Settings

- Simulation Options
- Temporal Settings
- Watershed Information
- Stream Information
- Snow
- Water Budget
- Sediment
- Water Quality Constituents
- Temperature
- TMDL Control Options
- Output

Model Components

- Snow
- Water Budget
- Sediment
- Water Quality Constituents
- Temperature
- pH
- Dissolved Oxygen

Model Run Conditions

- Baseline
- Calibration

Parameter Information

```

110 pvat-parm2
gid      parameter group id
lid      landuse id
lzm      lower zone nominal soil moisture storage (inches)
infiltr  index to the infiltration capacity of the soil (in/hr)
kvary    variable groundwater recession (1/inches)
agwrc    base groundwater recession (none)
    
```

Ready

OK Cancel

FTable


Layer	Depth(ft)	Area(ft2)	Wetted Perimeter(ft)	Volume(ft3)	Outflow(cfs)
1	0.000000	0.000000	0.000000	0.000000	0.000000
2	0.106532	0.177899	2.603549	1107.232472	0.710211
3	0.213064	0.495763	3.432406	3085.590360	3.259853
4	0.319596	0.914851	4.613846	5693.962065	7.430457
5	0.426127	1.485712	7.038050	9246.957839	12.581427
6	0.532659	2.393596	10.690288	14897.552768	21.081359
			12.142778	22499.392548	38.498097
			13.223832	30813.069184	61.426161
			14.094100	39784.222569	90.128031
			15.376596	49231.943327	121.302981
			17.520475	60069.422148	154.914414
			18.344315	71860.027244	202.540225
			18.816955	83966.174044	258.131510
			19.243244	96338.039603	319.774721
			19.627591	108914.130246	387.194371
			20.030460	121685.919832	459.522290
			20.590889	134720.739330	534.532386
			21.364516	148184.708754	611.284799
			22.231043	162175.031382	691.884201
			39.504561	182114.572735	572.149676
			58.157561	359225.078616	1371.640429
			60.241734	542073.778108	2659.902251
			62.325906	730660.671211	4276.749390
			64.410079	924985.757926	6198.536638
			66.494252	1125049.038252	8410.006586

Delete Row

LSPC Progress [93%]

Calculating: 11-15-2000
 Time elapsed: 00:00:29
 Time left: 00:00:01

Cancel




Watershed Modeling Outline

- Model Configuration
 - Locate monitoring locations
 - Determine watershed features, disturbance factors
 - Subwatershed delineation
 - Weather data
 - Model parameter selection based on physical data (landuse, slopes, soils)
- Model Testing, Calibration, Validation
- Model Production Runs & TMDL Scenarios




Subwatershed Delineation

- Lake Tahoe Basin was subdivided into 184 discrete subwatersheds
- Delineation based on:
 - elevation (topographic data)
 - stream connectivity
 - location of flow and water quality monitoring stations
- Each subwatershed is modeled with one representative stream
- Stream segments distinguished from intervening zones



Data Representation in LSPC



Each subwatershed:

- Landuse distribution
- Weather data
- Elevation (DEM)
- Representative soil behavior (NRCS Soils)

Each landuse (Physical):

- Average slope
- Average length of overland flow

Each landuse (Process):

- Hydrology
- Sediment yield (particle sizes)
- Pollutant load generation



Weather Data Application

Land

Reaches

Temp
Snow
Water
Sediment

Water
Heat
Gen. Qual.

● Required
▲ Optional


Precipitation	●	●	●	●		▲	▲	
Pot. ET			●	●		▲		
Air Temperature	●	●					●	
Wind Speed		●					●	●
Solar Radiation		●					●	
Dewpoint Temp.		●					●	
Cloud Cover		▲					●	▲




TETRA TECH, INC

Model Testing, Calibration, Validation

Legend



Example Calibration Points: TRG SWM Locations




Model Testing, Calibration, Validation

Legend



Example Validation Points: LTIMP Stations



Model Testing, Calibration, Validation



Modeling Sequence

- Hydrology
 - Process and parameters
 - Snow simulation
 - Stream hydraulics
- Sediment
 - Erosion & sediment yield
 - Instream settling and resuspension
- Water Quality
 - Dissolved nutrients
 - Sediment associated nutrients



Ward Creek Subwatershed

Focus Area



Snow at Elev. 6750 ft (SWS 8060)

Flow Calibration at USGS10336676

Ward Creek Model Configuration

- Site-specific meteorological data
- Snow simulation and model calibration
- Snowmelt, runoff, hydrologic response simulation and model calibration
- Hydrograph separation and baseflow/runoff analysis




Site-Specific Meteorology

- Hourly SNOTEL data (WRDC1):
 - Temperature and precipitation (10/1/1996 – Present)
- NCDC Composites:
 - Dewpoint & windspeed (SLT Airport & Reno Airport)
 - Cloud cover for solar radiation (SLT Airport, Blue Canyon, Reno, Sacramento)
- Computed Parameters:
 - Solar Radiation (Hamon Method)
 - Potential Evapotranspiration (Penman Method)
 - The method we select has a significant impact on model predictive behavior



What is potential evapotranspiration? Why is it important here?

Evaporation



+

Transpiration



by plants in their natural environment.



TETRA TECH, INC


What is potential evapotranspiration? Why is it important here?

- Typically computed empirically from other measurable parameters (i.e. temperature)
- Potential ET represents the MAXIMUM achievable ET that the model will predict
- Not all the Potential ET is necessarily actualized during the model run




Potential Evapotranspiration Methods

Ward Creek SNOTEL (WRDC1)



Potential Evapotranspiration Methods

Milwaukee Mitchell Field Airport




Potential Evapotranspiration Methods

- Hamon (1961)
 - Function of only temperature and latitude
 - Default method under-estimates PEVT in Tahoe Basin
- Jensen-Haise (1963)
 - Function of temperature, solar radiation, and mean watershed elevation
 - Default better than Hamon, but also under-estimate PEVT
- Penman (1948)
 - Function of temperature, solar radiation, dewpoint or relative humidity, and wind movement
 - Default vegetation factor of 0.75 converts Pan-ET to PEVT
 - Most representative estimate of PEVT in Tahoe



Potential Evapotranspiration Methods




Evapotranspiration in Tahoe Basin


- Relatively low dewpoints & low humidity leads to a higher temperature/dewpoint gradient and therefore higher evaporation potential
- Wind and Solar Radiation are also influential – Penman considers their added influence on PEVT
- In other regions of the country, the three methods may yield more similar PEVT predictions
- The Tahoe basin's weather patterns are distinct characteristics of the watershed that when factored together, tend to predict higher potential evapotranspiration



Modeled ET vs. PEVT Methods



Modeled vs. Historical Reference ET



* Historical average monthly reference crop evapotranspiration for Tahoe City, California
UC Davis Division of Agriculture and Natural Resources, Publication 21454

Snow Simulation Considerations

Two commonly used SNOW simulation algorithms:

- **Energy Balance**
 - COE, 1956; Anderson Crawford, 1964; Anderson, 1968
- Temperature Index or “Degree-day”
 - Rango and Martinec, 1995

LSPC uses Energy Balance (most comprehensive)




Snow Simulation Considerations

Weather Data	Energy Balance	Degree Day
Precipitation	Required	Required
Air Temperature	Required	Required
Solar Radiation	Required	Not Used
Dewpoint	Required	<i>optional</i>
Wind Speed	Required	Not Used
Cloud Cover	<i>optional</i>	Not Used



Snow Simulation Schematic




Evaluating LSPC Snow Simulation


- Locally monitored SNOTEL surface air temperature, precipitation, and snow-pack (**expressed as melted water equivalent depth**) was compared against model simulated counterparts.
- Selected a subwatershed with average elevation most similar to SNOTEL gage elevation to use for comparison (SWS 8060).
- All water volumes from model output were normalized by drainage area to unit-area depth basis for comparison with observed depths.



Snow Simulation (1996-2003)



Snow Simulation (Water Year 2002)




Temperature Lapse Rate in Tahoe

- Default model lapse rates (change in temperature per change in elevation) do not match observed trends in temperature and elevation data in Tahoe watershed.
- Four NCDC daily min/max temperature gages and six SNOTEL gages were used to estimate lapse rates using long-term average temperature and gage elevation for common time periods.
- Here is a comparison of lapse rates (Deg-F/ft):
 - Default lapse rates: 0.0035 to 0.0050
 - Tahoe lapse rates: 0.0015 to 0.0018
- This translates into a 35-40% reduction in the ELDAT parameter used in snow simulation.

Hydrologic Process & Parameters

- Hydrologic Components:

- Precipitation
- Interception
- Evapotranspiration
- Overland flow
- Infiltration
- Interflow
- Subsurface storage
- Groundwater flow
- Groundwater loss



Source: Stanford Watershed Model

Hydrology Calibration

Level of Effort




- Calibrate to Local Observed Data
- Analytical Considerations
 - Annual water balance
 - Seasonal / monthly distribution
 - Distribution of hydrograph components
 - Storm flow
 - Base flow
 - Snowfall / snowmelt influence



Hydrology Calibration Indicators


- Hourly/Daily/Monthly Time series
- Monthly Scatter/Balance Plots
- Seasonal Plots (Multi-Year Composites)
- Flow Duration Curves
- Flow Accumulation Curves
- Cumulative Error Statistics
- Hydrograph Components





January 1, 1997 Rain-on-snow event


Do you remember where you were when...



TETRA TECH, INC


Ward Creek (Monthly Average)

*January 1997: Extreme
Rain-on-snow event*





Ward Creek (NO Snow Simulation)

Snowfall/snowmelt results in a 3-month phase shift of peak flow





*With exception of the 1997 event, spring snowmelt peak is typically **higher** than if all precipitation had fallen as rain*

Ward Creek (Monthly Average)



Ward Creek (7-Year Composite)




Model Test for Seasonality



TETRA TECH, INC

Ward Creek (7-Year Composite)




Model Test for Seasonality



TETRA TECH, INC

— Observed Flow Duration (10/1/1996 to 9/30/2003)
— Modeled Flow Duration (10/1/1996 to 9/30/2003)



LSPC Simulated Flow

REACH OUTFLOW FROM SUBBASIN 8060

7-Year Analysis Period: 10/1/1996 - 9/30/2003
 Flow volumes are normalized, with total observed as 100

Observed Flow Gage

USGS 10336676 WARD C AT HWY 89 NR TAHOE PINES CA

Placer County, California
 Hydrologic Unit Code 16050101
 Latitude 39°07'56", Longitude 120°09'24" NAD27
 Drainage area 9.70 square miles

Total Simulated In-stream Flow:	110.06	Total Observed In-stream Flow:	100.00
Total of simulated highest 10% flows:	58.68	Total of Observed highest 10% flows:	53.74
Total of Simulated lowest 50% flows:	4.19	Total of Observed Lowest 50% flows:	4.45
Simulated Summer Flow Volume (months 7-9):	8.76	Observed Summer Flow Volume (7-9):	6.28
Simulated Fall Flow Volume (months 10-12):	7.11	Observed Fall Flow Volume (10-12):	5.60
Simulated Winter Flow Volume (months 1-3):	21.13	Observed Winter Flow Volume (1-3):	18.51
Simulated Spring Flow Volume (months 4-6):	73.06	Observed Spring Flow Volume (4-6):	69.61
Total Simulated Storm Volume:	6.88	Total Observed Storm Volume:	8.59
Simulated Summer Storm Volume (7-9):	0.59	Observed Summer Storm Volume (7-9):	0.41
<i>Errors (Simulated-Observed)</i>	<i>Error Statistics</i>	<i>Recommended Criteria</i>	
Error in total volume:	9.14	10	
Error in 50% lowest flows:	-6.04	10	
Error in 10% highest flows:	8.42	15	
Seasonal volume error - Summer:	28.30	30	
Seasonal volume error - Fall:	21.20	30	
Seasonal volume error - Winter:	12.41	30	
Seasonal volume error - Spring:	4.72	30	
Error in storm volumes:	-24.97	20	
Error in summer storm volumes:	30.49	50	


Hydrograph Separation Methods

USGS: *HYSEP*, Sloto & Cruise (1996)


- Separation interval ($2N^*$) is an odd-integer number of days (between 3 and 11) – *function of drainage area*
- Fixed Interval: assigns lowest discharge in an interval to all values in that interval (Step by $2N^*$)
- Sliding Interval: assigns lowest discharge in a sliding interval to a given point (Step by one day)
- Local Minimum: selects local minimums within a sliding interval and connects them with a straight line (Step by one day until next local minimum)



Fixed Interval Separation



Sliding Interval Separation




$| - 2N^* |$



TETRA TECH, INC

Local Minimum Separation




Model Hydrograph Components



Surface runoff -
overland flow


Interflow - flow
through surficial
layers of soil

Baseflow - groundwater
seepage from springs and
aquifers directly to the
stream channel



*Surface flow may actually
include all or some of Interflow*

Ward Creek (Oct 1996 – Sep 2003)




* Surface runoff interpreted as the sum of SURO and IFWO, Baseflow is AGWO

Lake Tahoe Reconstructed Weather

- 3-km by 3-km spatial resolution
- 142 grid cells cover Tahoe drainage area
- 42 years of hourly information at each grid
- Available information used include:
 - Precipitation
 - Temperature
 - Dew point
 - Wind speed
 - Solar radiation
- Potential evapotranspiration computed using Penman Method with 0.75 PEVT Coefficient
- LTRD information was spatially aggregated by subwatershed, resulting in 184 unique, spatially varied weather patterns throughout Tahoe Basin

Spatial Aggregation Method (Thiessen Polygon)



Subwatershed



3 km meteorological grid


Subbasin Area-Weighting

- Subbasin 1 =
 $0.4 c + 0.6 d$
- Subbasin 2 =
 $0.5a + 0.1b + 0.3c + 0.1d$
- Subbasin 3 =
 $0.7 b + 0.3 d$



TETRA TECH, INC


Reconstruction Grid Cells



- LTRD Grids
- Lake Boundary
- Subwatersheds

0 2 4 6 8 10 Kilometers


Subwatersheds



- LTRD Grids
- Lake Tahoe
- Subwatersheds

0 2 4 6 8 10 Kilometers


"Gage" Elevation



- Lake Boundary
- Subwatersheds
- Dew Point (C)
- 1904 - 2002
- 2002 - 2156
- 2156 - 2315
- 2315 - 2498
- 2498 - 2817

0 2 4 6 8 10 Kilometers



SWS "Gage" Elevation



- LTRD Grids
- Evapotranspiration (in)
- 1944 - 2090
- 2090 - 2210
- 2210 - 2345
- 2345 - 2522
- 2522 - 2734

0 2 4 6 8 10 Kilometers

Average Windspeed (m/s)





MM5 Meteorology in LSPC

- Precipitation
 - Good predictor of long-term totals and spatial variability
 - Underestimates water volume for snow events
- Temperature & Dewpoint
 - Excellent predictor for long-term and spatial variability
 - Sometimes over-predicts by a few degrees and misses snowfall events (snowfall simulation requires *precise* temperature data)
- Windspeed & Solar Radiation
 - Reasonable magnitude, though not enough observed data to validate



Ward Creek (10-Year Composite)



Model Test for Seasonality



TETRA TECH, INC


Model Testing, Calibration, Validation

Modeling Sequence

- Hydrology
 - Process and parameters
 - Snow simulation
 - Stream hydraulics
- Sediment
 - Erosion & sediment yield
 - Instream settling and resuspension
- Water Quality
 - Dissolved nutrients
 - Sediment associated nutrients



Sediment Processes




Sediment Budget and Transport

- Land Processes
 - Production and removal of sediment from land
 - Washoff of solids from impervious surfaces
 - Washoff of loose sediment from pervious surfaces
 - Scouring of soil matrix (pervious land)
- Stream Channel Processes
 - Transport, deposition and scour of sediment in the stream channels




TRG Stormwater Monitoring Dataset



LTIMP Reference Sites

General Creek



Unimpacted vegetated land,
some trails and campgrounds


Logan House Creek



Unimpacted vegetated land,
some trails

Function Table

- Area (surface) = Top width * length
- Volume = Cross sectional area * length
- Outflow can be withdrawal, spillway discharge or outflow at the downstream end of a reach
- Stream Flow = Cross sectional area * velocity



Depth	Area	Volume	Outflow
0.0	0.0	0.0	0.0
0.08	10.81	0.86	2.12
0.80	11.36	8.84	98.09
1.20	11.68	13.45	192.51




F-tables for Ungaged Streams

- General Creek and Logan House Creek were identified as reference streams with least stream channel erosion impact (Andrew Simon, 2004).
- Relationship between upstream drainage area and mean channel depth and width at downstream point established.
- Relationship factors, together with respective upstream drainage area, were applied to other streams to derive representative cross-sections and F-tables.



Sample General Creek Cross-Section*

GC35



* Provided by Andrew Simon



TETRA TECH, INC

Cross-section Methodology

- Average bank-full dimensions:
 - Depth: 1 m (3.2 ft)
 - Width: 8 m (26.2 ft)
- Derived Relationship:
 - Depth = a_1 (Upstream Area)^{b1}
 - Width = a_2 (Upstream Area)^{b2}

Typical Factors:

	<u>Exponent</u>	<u>Coefficient</u>
Depth	0.28	1.50
Width	0.40	14.49

Best-Fit Factors:



	<u>Exponent</u>	<u>Coefficient</u>
Depth	0.464	1.559
Width	0.395	14.490

Summary and Next Steps

- Continue sediment & nutrient calibration
 - LTIMP sediment & nutrient
 - Heyvaert & Thomas: SWM sediment & nutrient
 - Bob Coats: Landuse-Water Quality Relationships
- Integrate parallel research
 - Andrew Simon: Stream channel erosion (CONCEPTS)
 - Eric Strecker: BMP evaluations
 - Chad Praul & Tom Gavigan: BMP inventory



TMDL Analysis Considerations



Thank You
Questions?



TETRA TECH, INC