

**LATE REVISIONS
CITY OF BRENTWOOD
WASTEWATER TREATMENT PLANT
CONTRA COSTA COUNTY
NPDES Permit Renewal (NPDES No. CA0082660)
Regional Water Quality Control Board, Central Valley Region
Board Meeting – 26 July 2013
ITEM # 27b**

Late Revisions to the NPDES Permit to correct typographical errors and make a clarifying change.

1. Limitations and Discharge Requirements – Standard Provisions. Section VI.A.2.f

Modify section VI.A.2.f to make the following clarifying changes as shown in underline/strikeout format below:

f. The Discharger shall take all reasonable steps to minimize any adverse effects to waters of the State or users of those waters resulting from any discharge or sludge use or disposal in violation of this Order. Reasonable steps shall include such accelerated or additional monitoring as necessary to determine the nature and impact of the non-complying discharge or sludge use or disposal, and adequate public notification to ~~downstream~~ water agencies ~~or others who might contact the non-complying discharger~~ whose contact with the noncomplying discharge is reasonably foreseeable.

2. Attachment E – Monitoring and Reporting Program. Section IV.A.1. Table E-3 Monitoring Location EFF-001

Correct the typographical error in the footnote numbering for Nitrite Nitrogen, Total (as N), under the “Minimum Sampling Frequency” column, as shown in underline/strikeout format below:

Table E-3. Monitoring Location EFF-001

Parameter	Units	Sample Type	Minimum Sampling Frequency	Required Analytical Test Method
Nitrite Nitrogen, Total (as N)	mg/L	Grab	1/Quarter ¹² 10	¹

¹⁰ Monitoring for nitrite and nitrate shall be conducted concurrently.

¹² Samples for Total coliform organisms may be collected at any point following disinfection.

3. Attachment E – Monitoring and Reporting Program. Section VI.A.1. Table E-6 Land Discharge Monitoring Requirements

Correct the typographical error in the footnote numbering for pH, under the “Parameter” column, as shown in underline/strikeout format below:

Table E-6. Monitoring Location EFF-001

Parameter	Units	Sample Type	Minimum Sampling Frequency	Required Analytical Test Method
pH ¹	Standard Units	Grab	1/month	²

¹ Monitoring for dissolved oxygen and pH is not required when pond water depth is less than 1 foot.

4. Attachment E – Monitoring and Reporting Program. Section VIII.B.1.ii (a) Groundwater Monitoring Locations

Correct the typographical error in Section VIII.B.1.ii (a) as shown in underline/strikeout format below:

- ii. Monitoring locations BG-1, BG-2, BG-3, EB-5; MW-1 IN, and MW-2

- (a) Prior to sampling, the groundwater elevations shall be measured and the wells shall be purged of at least three well volumes until temperature, pH, and electrical conductivity have stabilized. Depth to groundwater shall be measured to the nearest 0.01 feet. Groundwater monitoring at Monitoring locations BG-1, BG-2, BG-3, ~~A-2~~, EB-5, MW-1 IN, and MW 2 shall include, at a minimum, the following in Table E 8.

5. Attachment F – Fact Sheet. Section IV.E. 2. Interim Chloride Effluent Limitation Calculation Summary

Correct the typographical error regarding the reference to Table F-16 in the last paragraph of Section IV.E.2 as shown in underline/strikeout format below:

A summary of the calculations of the interim effluent limitations for chloride is provided in Table ~~F-15~~ F-16 below: