SWPPP Amendment No. 2

Project Name: DOMINGUEZ LOOP ROAD

Project Number: 001-017

Qualified SWPPP Developer's Certification of the
Stormwater Pollution Prevention Plan Amendment

"This Stormwater Pollution Prevention Plan and attachments were prepared under my direction to meet the requirements of the California Construction General Permit (SWRCB Order No. 2009-009-DWQ as amended by 2010-0014-DWQ). I certify that I am a Qualified SWPPP Developer in good standing as of the date signed below."

E. Daniel Taylor
QSD's Signature

7/16/2013
Date

DANIEL TAYLOR
QSD Name

00324
QSD Certificate Number

RSC ENGINEERING
Title and Affiliation

916-788-2884
Telephone

2250 DOUGLAS BLVD. STE 150
ROSEVILLE, CA 95661
Address

d.taylor@rsc-engr.com
Email

Amendment Log

Project Name: *Doninguez Loop Road*

Amendment No.	Date	Brief Description of Amendment, include section and page number	Prepared and Approved By
1	12/17/12	ADDED TEMP BERM & PLUGGED OUT FALL PIPE. USE ATS ON ROCKLIN CROSSINGS (WDID 5531C364098)	Name: DANIEL TAYLOR QSD# 00324
2	07/16/13	INCREASED PROJECT AREA TO INCLUDE ROAD WIDENING TO SOUTH DOMINGUEZ & WEST OF SIERRA COLLEGE BLVD.	Name: DANIEL TAYLOR QSD# 00324
			Name: QSD#
			Name: QSD#
			Name: QSD#
			Name: QSD#
			Name: QSD#
			Name: QSD#
			Name: QSD#

2 AMENDMENT 2
INCREASED PROJECT AREA TO INCLUDE ROAD WIDENING TO SOUTH OF DOMINGUEZ LOOP ROAD AND ROAD IMPROVEMENTS ON WEST SIDE OF SIERRA COLLEGE BOULEVARD.

SCHRIBER WAY

SIERRA COLLEGE BOULEVARD

DOMINGUEZ LOOP ROAD

CONSTRUCTION TRAILER, MATERIAL STORAGE/STAGING, VEHICLE MAINTENANCE AND FUELING AND CONCRETE WASHOUT. LOCATION TO BE FIELD DETERMINED.

M

T

C

CONSTRUCTION ENTRANCE

PLACE SILT FENCE AT EDGE OF CONSTRUCTION

PLACE STRAW ROLL AT TOP AND TOE OF SLOPE AND EVERY 20' ALONG SLOPE.

PLACE SILT FENCE AT EDGE OF CONSTRUCTION

HYDROSEED NOTE:
ALL EXPOSED SOILS THAT ARE IN-ACTIVE FOR MORE THAN 14 DAYS ARE TO RECEIVE HYDROSEED, STRAW MULCH, AND TACKIFIER.

STRAW MULCH NOTE:
ALL EXPOSED SOILS SHALL RECIEVE STRAWMULCH AND TACKIFIER PRIOR TO ANY FORECAST RAIN EVENT.

PLACE HYDROSEED, STRAW MULCH AND TACKIFIER ON ALL EXPOSED SOILS ONCE GRADING IS COMPLETE.

LIMIT OF CONSTRUCTION TOTAL DISTURBED AREA = 4.1 AC. 2

PLACE DRAIN INLET PROTECTION

CONSTRUCT DOUBLE ROCK CHECK DAM

PLUG GRATED INLET

PLACE SILT FENCE AT EDGE OF CONSTRUCTION

PLACE STRAW ROLL AT TOP AND TOE OF SLOPE AND EVERY 20' ALONG SLOPE.

PLACE SILT FENCE AT EDGE OF CONSTRUCTION

PLACE HYDROSEED, STRAW MULCH AND TACKIFIER ON ALL EXPOSED SOILS ONCE GRADING IS COMPLETE.

PLACE DRAIN INLET PROTECTION (TYP.)

TEMPORARY BERM

D

INCOMING RUN-ON FROM NORTHWEST. IF RUNON IS ANTICIPATED TO CROSS AN AREA OF EXPOSED SOIL, PROVIDE A DIVERSION AROUND EXPOSED AREA OR PROVIDE A STABILIZED FLOW PATH OVER EXPOSED SOIL.

PLACE STRAW ROLL AT TOP AND TOE OF SLOPE AND EVERY 20' ALONG SLOPE.

CONSTRUCTION ENTRANCE

PLACE STRAW ROLL AT TOP AND TOE OF SLOPE AND EVERY 20' ALONG SLOPE.

PLACE GRAVEL BAG BERM ALONG SWALE AND AT EACH END OF CULVERT.

PLACE SILT FENCE AT EDGE OF CONSTRUCTION

DISCHARGE LOCATION AND SAMPLE POINT

PLACE STRAW ROLL AT TOP AND TOE OF SLOPE AND EVERY 20' ALONG SLOPE.

PLACE GRAVEL BAG BERM ALONG FACE OF CURB

PLUG INLET TO PROPOSED CULVERT AND PUMP ANY INCOMING FLOW INTO THE TEMPORARY HOLDING BASIN AT THE INLET NORTH OF DOMINGUEZ LOOP.

2

PLACE GRAVEL BAG BERM ALONG SWALE AND AT EACH END OF CULVERT.

PLACE SILT FENCE AT EDGE OF CONSTRUCTION

RSC ENGINEERING
2250 Douglas Blvd. Suite 150
Roseville, CA 95661
Ph: 916.788.2864 Fax: 916.788.4408

DOMINGUEZ LOOP ROAD
ROCKLIN, CA

FIGURE 3
POST-DEVELOPED SITE PLAN

PROJECT NO.: 001-017 | DATE: 07/16/2013 | SHEET NO. 2 OF 2

Date: 7/16/2013
RSC Proj. #: 001-017

Figure A.1
Dominguez Loop Road
Rainfall - Runoff Erosivity Factor (R) Calculations:

2250 Douglas Blvd.
Suite 150
Roseville CA 95661
Ph: 916-788-2884

Objective: Calculate the Rainfall - Runoff Erosivity Factor "R" per the methods described on the EPA publication: http://www.epa.gov/npdes/pubs/fact3-1.pdf. This Calculation is to be used in the RUSLE Equation as a part of the Risk Level Assesment for the project.

Erosivity Index Zone:	21	(Per Fig. 1 -Erosivity Index Map)
Project Start:	25-Jul-12	
Project Start EI%:	56.6%	Erosivity Index % based on July 14 and EI=21 (100-43.4)
Project Completion:	31-Dec-13	
Project End EI%:	100.0%	Erosivity Index % based on December 31 and EI=21
Total EI %:	157%	
I =	30	(Annual Isoerodent value Per Fig. 4 - Isoerodent Map of Ca.)
R =	46.98	Rainfall - Runoff Erosivity Factor (I x EI%)

	A	B	C
1	**Sediment Risk Factor Worksheet**		**Entry**
2	**A) R Factor**		
3	Analyses of data indicated that when factors other than rainfall are held constant, soil loss is directly proportional to a rainfall factor composed of total storm kinetic energy (E) times the maximum 30-min intensity (I30) (Wischmeier and Smith, 1958). The numerical value of R is the average annual sum of EI30 for storm events during a rainfall record of at least 22 years. "Isoerodent" maps were developed based on R values calculated for more than 1000 locations in the Western U.S. Refer to the link below to determine the R factor for the project site.		
4	http://cfpub.epa.gov/npdes/stormwater/LEW/lewCalculator.cfm		
5	**R Factor Value**		46.98
6	**B) K Factor (weighted average, by area, for all site soils)**		
7	The soil-erodibility factor K represents: (1) susceptibility of soil or surface material to erosion, (2) transportability of the sediment, and (3) the amount and rate of runoff given a particular rainfall input, as measured under a standard condition. Fine-textured soils that are high in clay have low K values (about 0.05 to 0.15) because the particles are resistant to detachment. Coarse-textured soils, such as sandy soils, also have low K values (about 0.05 to 0.2) because of high infiltration resulting in low runoff even though these particles are easily detached. Medium-textured soils, such as a silt loam, have moderate K values (about 0.25 to 0.45) because they are moderately susceptible to particle detachment and they produce runoff at moderate rates. Soils having a high silt content are especially susceptible to erosion and have high K values, which can exceed 0.45 and can be as large as 0.65. Silt-size particles are easily detached and tend to crust, producing high rates and large volumes of runoff. Use Site-specific data must be submitted.		
8	Site-specific K factor guidance		
9	**K Factor Value**		0.37
10	**C) LS Factor (weighted average, by area, for all slopes)**		
11	The effect of topography on erosion is accounted for by the LS factor, which combines the effects of a hillslope-length factor, L, and a hillslope-gradient factor, S. Generally speaking, as hillslope length and/or hillslope gradient increase, soil loss increases. As hillslope length increases, total soil loss and soil loss per unit area increase due to the progressive accumulation of runoff in the downslope direction. As the hillslope gradient increases, the velocity and erosivity of runoff increases. Use the LS table located in separate tab of this spreadsheet to determine LS factors. Estimate the weighted LS for the site prior to construction.		
12	LS Table		
13	**LS Factor Value**		0.28
14			
15	**Watershed Erosion Estimate (=RxKxLS) in tons/acre**		4.867128
16	**Site Sediment Risk Factor**		**Low**
17	Low Sediment Risk: < 15 tons/acre		
18	Medium Sediment Risk: >=15 and <75 tons/acre		
19	High Sediment Risk: >= 75 tons/acre		
20			

Receiving Water (RW) Risk Factor Worksheet	Entry	Score
A. Watershed Characteristics	**yes/no**	
A.1. Does the disturbed area discharge (either directly or indirectly) to a **303(d)-listed waterbody impaired by sediment** (For help with impaired waterbodies please visit the link below) or has a **USEPA approved TMDL implementation plan for sediment**?: http://www.waterboards.ca.gov/water_issues/programs/tmdl/integrated2010.shtml **OR**	**yes**	**High**
A.2. Does the disturbed area discharge to a waterbody with designated beneficial uses of SPAWN & COLD & MIGRATORY? (For help please review the appropriate Regional Board Basin Plan) http://www.waterboards.ca.gov/waterboards_map.shtml		
Region 1 Basin Plan Region 2 Basin Plan Region 3 Basin Plan Region 4 Basin Plan Region 5 Basin Plan Region 6 Basin Plan Region 7 Basin Plan Region 8 Basin Plan Region 9 Basin Plan		

Combined Risk Level Matrix



Project Sediment Risk: Low

Project RW Risk: High

Project Combined Risk: Level 2