

CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD  
CENTRAL VALLEY REGION

MONITORING AND REPORTING PROGRAM R5-2016-XXXX  
FOR  
CITY OF CLOVIS  
CITY OF CLOVIS MUNICIPAL SOLID WASTE LANDFILL  
CLASS III LANDFILL  
CONSTRUCTION, OPERATION,  
AND CORRECTIVE ACTION  
FRESNO COUNTY

This monitoring and reporting program (MRP) is issued pursuant to California Water Code section 13267 and incorporates requirements for groundwater, surface water, and unsaturated zone monitoring and reporting; facility monitoring, maintenance, and reporting; and financial assurances reporting contained in California Code of Regulations, title 27, section 20005, et seq. (hereafter Title 27), Waste Discharge Requirements (WDRs) Order R5-2016-XXXX, and the Standard Provisions and Reporting Requirements (SPRRs) dated December 2015. Compliance with this MRP is ordered by the WDRs and the Discharger shall not implement any changes to this MRP unless a revised MRP is issued by the Central Valley Water Board or the Executive Officer.

**A. MONITORING**

The Discharger shall comply with the detection monitoring program provisions of Title 27 for groundwater, surface water, and the unsaturated zone in accordance with Standard Monitoring Specifications in Section I of the SPRRs and the Monitoring Specifications in Section G of the WDRs. All monitoring shall be conducted in accordance with an approved *Sample Collection and Analysis Plan*, which includes quality assurance/quality control standards. A revised Monitoring Program Sampling and Water Quality Protection Standards Analysis Plan, dated April 2016, is currently under review. Once approved by Central Valley Water Board Staff, the Discharger shall comply with the approved document or any subsequent approved revisions thereto.

All compliance monitoring wells established for the detection monitoring program shall constitute the monitoring points for the groundwater Water Quality Protection Standard. All detection monitoring program groundwater monitoring wells, unsaturated zone monitoring devices, leachate, and surface water monitoring points shall be sampled and analyzed for monitoring parameters and constituents of concern (COCs) as indicated and listed in Tables I through VI.

The Discharger may use alternative analytical test methods, including new USEPA approved methods, provided the methods have method detection limits equal to or lower than the analytical methods specified in this Monitoring and Reporting Program, and are identified in the approved Sample Collection and Analysis Plan.

The monitoring program of this MRP includes:

<u>Section</u>	<u>Monitoring Program</u>
A.1	Groundwater Monitoring
A.2	Unsaturated Zone Monitoring
A.3	Leachate Monitoring, Seep Monitoring, and LCRS Testing
A.4	Surface Water Monitoring
A.5	Facility Monitoring
A.6	Corrective Action Monitoring

**1. Groundwater Monitoring**

The Discharger shall operate and maintain a groundwater detection monitoring system that complies with the applicable provisions of Title 27, sections 20415 and 20420. The detection monitoring system shall be certified by a California-licensed professional civil engineer or geologist as meeting the requirements of Title 27. A revised Monitoring Program and Water Quality Protection Standards Analysis Plan, dated April 2016, is currently under review. Once approved by Central Valley Water Board Staff, the Discharger shall comply with the approved document or any subsequent approved revisions thereto. The Discharger shall revise the groundwater detection monitoring system (after review and approval by Central Valley Water Board staff) as needed each time a new landfill cell or module is constructed.

The groundwater monitoring network consists of the following:

<u>Well</u>	<u>Status</u>	<u>Units Being Monitored</u>
GWMW-01	Evaluation	Reclaimed Area/Phase I/Phase II
GWMW-02	Background	
GWMW-04	Detection	Reclaimed Area
GWMW-05	Detection	
GWMW-06	Detection	Stage I
GWMW-07	Detection	Phase I/II
GWMW-10	Evaluation	Reclaimed Area
GWMW-11	Evaluation	Reclaimed Area
GWMW-12	Evaluation	Reclaimed Area
GWMW-13	Evaluation	Reclaimed Area
GWMW-14	Detection	Cell #1/#2
GWMW-15	Evaluation	Reclaimed Area
GWMW-16	Evaluation	Reclaimed Area
GWMW-17	Evaluation	Reclaimed Area
GWMW-18	Detection	Cell #4/5
GWMW-19	Evaluation	Reclaimed Area
GWMW-21	Detection	
GWMW-23	Background	
GWMW-24	Background	

<u>Well</u>	<u>Status</u>	<u>Units Being Monitored</u>
GWMW-205	Detection	Stage 1

Groundwater samples shall be collected from the background wells, detection monitoring wells, corrective action monitoring wells, and any additional wells added as part of the approved groundwater monitoring system. The collected samples shall be analyzed for the parameters and constituents listed in Table I in accordance with the specified methods and frequencies. The Discharger shall collect, preserve, and transport groundwater samples in accordance with the approved Sample Collection and Analysis Plan.

**Once per quarter**, the Discharger shall measure the groundwater elevation in each well, determine groundwater flow direction, and estimate groundwater flow rates in the uppermost aquifer and in any zones of perched water and in any additional portions of the zone of saturation monitored. The results shall be reported semiannually, including the times of expected highest and lowest elevations of the water levels in the wells, pursuant to Title 27, section 20415(e)(15).

Samples collected for the COC monitoring specified in Table I shall be collected and analyzed in accordance with the methods listed in Table VI every five years. Five-year COCs were last monitored in 2015 and shall be monitored again in **2020**. The results shall be reported in the Annual Monitoring Report for the year in which the samples were collected.

## 2. **Unsaturated Zone Monitoring**

The Discharger shall operate and maintain an unsaturated zone detection monitoring system that complies with the applicable provisions of Title 27, sections 20415 and 20420. The current unsaturated zone detection monitoring system meets the applicable requirements of Title 27. A revised Monitoring Program and Water Quality Protection Standards Analysis Plan, dated April 2016, is currently under review. Once approved by Central Valley Water Board Staff, the Discharger shall comply with the approved document or any subsequent approved revisions thereto. The Discharger shall install unsaturated zone monitoring devices (after review and approval by Central Valley Water Board staff) each time the landfill constructs a new cell or module.

The unsaturated zone monitoring network consists of:

<u>Mon Pt.</u>	<u>Status</u>
Phase II	Vadose Zone
Sump #1	Vadose Zone
Sump #2	Vadose Zone
Sump #4	Vadose Zone
MMW-128	Soil-Pore Gas

<u>Mon Pt.</u>	<u>Status</u>
MMW-129	Soil-Pore Gas
MMW-130	Soil-Pore Gas
MMW-131	Soil-Pore Gas
MMW-132	Soil-Pore Gas
MMW-133	Soil-Pore Gas
MMW-134	Soil-Pore Gas
MMW-135	Soil-Pore Gas
MMW-136	Soil-Pore Gas
MMW-137	Soil-Pore Gas
MMW-138	Soil-Pore Gas
MMW-139	Soil-Pore Gas
MMW-140	Soil-Pore Gas
MMW-141	Soil-Pore Gas

Unsaturated zone samples shall be collected from the monitoring network listed above and shall be analyzed for the parameters and constituents listed in Table II in accordance with the specified methods and frequencies (pan lysimeters need only be sampled when liquid is present). Pan lysimeters shall be inspected for the presence of liquid **quarterly**. If liquid is detected in a previously dry pan lysimeter, the Discharger shall verbally notify Central Valley Water Board staff within **seven days** and shall immediately sample and test the liquid for Field and Monitoring Parameters listed in Table II. Samples collected for the 5-year COC analyses specified in Table II shall be collected and analyzed in accordance with the methods listed in Table VI every five years, beginning again in **2020** (does not include soil-pore gas).

The Discharger shall collect, preserve, and transport samples in accordance with the quality assurance/quality control standards contained in the approved Sample Collection and Analysis Plan.

Monitoring results for the unsaturated zone shall be included in monitoring reports and shall include an evaluation of potential impacts of the facility on the unsaturated zone and compliance with the Water Quality Protection Standard.

### 3. **Leachate Monitoring, Seep Monitoring, and Annual LCRS Testing**

**Leachate Monitoring:** The Discharger shall operate and maintain leachate collection and removal system (LCRS) sumps, conduct monitoring of any detected leachate seeps, and conduct annual testing of each LCRS in accordance with Title 27 and this monitoring program.

The current LCRS leachate sump monitoring points are:

<u>Mon Pt.</u>	<u>Unit Where Sump is Located</u>
Phase II	Phase II

<u>Mon Pt.</u>	<u>Unit Where Sump is Located</u>
Sump #1	Cell 1
Sump #2	Cell 2
Sump #3	Cell 4
Sump #4	Stage I

All LCRS sumps shall be inspected monthly for the presence of leachate, and flow shall be recorded in accordance with Table III. If leachate is detected in a previously dry sump, the Discharger shall verbally notify Central Valley Water Board staff within **seven days** and shall immediately sample and test the leachate for Field and Monitoring Parameters listed in Table III. Leachate in the LCRS sump shall then be sampled for all parameters and constituents in accordance with the frequencies listed in Table III whenever liquid is present. All LCRS sump samples shall be analyzed for the 5-year COCs specified in Table III every five years, beginning again in **2020**.

**Seep Monitoring:** Leachate that seeps to the surface from a landfill unit shall be sampled and analyzed for the Field and Monitoring Parameters listed in Table III upon detection. The quantity of leachate shall be estimated and reported as Leachate Flow Rate (in gallons/day). Reporting for leachate seeps shall be conducted as required in Section B.3 of this MRP below.

**Annual LCRS Testing:** All LCRSs shall be tested annually pursuant to Title 27, section 20340(d) to demonstrate proper operation. The results of these tests shall be reported to the Central Valley Water Board in the Annual Monitoring Report and shall include comparisons with earlier tests made under comparable conditions.

#### 4. **Surface Water Monitoring**

The Discharger shall operate a surface water detection monitoring system for any landfill facility where runoff from landfill areas flows or could flow to waters of the United States. The monitoring system shall comply with the applicable provisions of Title 27, sections 20415 and 20420. The current surface water detection monitoring system meets the applicable requirements of Title 27. A revised Monitoring Program Sampling and Water Quality Protection Standards Analysis Plan, dated April 2016, is currently under review. Once approved by Central Valley Water Board Staff, the Discharger shall comply with the approved document or any subsequent approved revisions thereto.

The surface water monitoring points for the landfill are:

<u>Mon Pt.</u>	<u>Status</u>
Creek	Downstream
Creek	Upstream

For surface water detection monitoring, a sample shall be collected at each monitoring point location and analyzed for the monitoring parameters and constituents in accordance with the methods and frequency specified in Table IV. All surface water monitoring samples shall be collected and analyzed for the 5-year COCs specified in Table IV every five years, beginning again in **2020**.

## 5. Facility Monitoring

### a. Annual Facility Inspection

Annually, prior to the anticipated rainy season, but no later than **30 September**, the Discharger shall conduct an inspection of the facility. The inspection shall assess repair and maintenance needed for drainage control systems, cover systems, and groundwater monitoring wells; and shall assess preparedness for winter conditions (including but not limited to erosion and sedimentation control). The Discharger shall take photos of any problems areas before and after repairs. Any necessary construction, maintenance, or repairs shall be completed by **31 October**. Annual facility inspection reporting shall be submitted as required in Section B.4 of this MRP.

### b. Major Storm Events

The Discharger shall inspect all precipitation, diversion, and drainage facilities and all landfill side slopes for damage **within 7 days** following major storm events capable of causing damage or significant erosion. The Discharger shall take photos of any problems areas before and after repairs. Necessary repairs shall be completed **within 30 days** of the inspection. Notification and reporting requirements for major storm events shall be conducted as required in Section B.5 of this MRP.

### c. Five-Year Iso-Settlement Survey for Closed Units

For closed landfill units, the Discharger shall conduct a five-year iso-settlement survey and produce an iso-settlement map accurately depicting the estimated total change in elevation of each portion of the final cover's low-hydraulic-conductivity layer. For each portion of the landfill, this map shall show the total lowering of the surface elevation of the final cover, relative to the baseline topographic map [Title 27, section 21090(e)(1 & 2)]. Reporting shall be in accordance with Section B.6 of this MRP.

d. **Standard Observations**

The Discharger shall conduct Standard Observations at the landfill in accordance with this section of the MRP. Standard observations shall be conducted in accordance with the following schedule:

<u>Landfill Unit Type</u>	<u>Frequency</u>	<u>Season</u>
Active	Weekly	Wet: 1 October to 30 April
Active	Monthly	Dry: 1 May to 30 September
Inactive/Closed	Monthly	Wet: 1 October to 30 April
Inactive/Closed	Quarterly	Dry: 1 May to 30 September

The Standard Observations shall include:

- 1) For the landfill units:
  - a) Evidence of ponded water at any point on the landfill outside of any contact storm water/leachate diversions structures on the active face (show affected area on map); and
  - b) Evidence of erosion and/or of day-lighted refuse.
- 2) Along the perimeter of the landfill units:
  - a) Evidence of leachate seeps, estimated size of affected area, and flow rate (show affected area on map); and
  - b) Evidence of erosion and/or of day-lighted refuse.
- 3) For receiving waters:
  - a) Floating and suspended materials of waste origin - presence or absence, source, and size of affected area; and
  - b) Discoloration and turbidity - description of color, source, and size of affected area.

Results of Standard Observations shall be submitted in the semiannual monitoring reports required in Section B.1 of this MRP.

**6. Corrective Action Monitoring**

The Discharger shall conduct corrective action monitoring to demonstrate the effectiveness of corrective action in accordance with Title 27, section 20430 and this MRP. Groundwater monitoring wells and unsaturated zone monitoring points that are in a corrective action monitoring program shall be monitored in accordance with the groundwater and unsaturated zone monitoring requirements in parts A.1 and A.2 of this MRP, except as modified in this part of the MRP for any additional constituents or modified monitored frequencies.

## B. REPORTING

The Discharger shall submit the following reports in accordance with the required schedule:

### Reporting Schedule

<u>Section</u>	<u>Report</u>	<u>End of Reporting Period</u>	<u>Due Date</u>
B.1	Semiannual Monitoring Report	30 June, 31 December	<b>1 August, 1 February</b>
B.2	Annual Monitoring Report	31 December	<b>1 February</b>
B.3	Seep Reporting	Continuous	<b>Immediately &amp; 7 Days</b>
B.4	Annual Facility Inspection Report	31 October	<b>15 November</b>
B.5	Major Storm Event Reporting	Continuous	<b>7 days from damage discovery</b>
B.6	Survey and Iso-Settlement Map for Closed Landfills	Every Five Years	<b>At Closure Completion and Every Five Years</b>
B.7	Financial Assurances Report	31 December	<b>30 September</b>

### Reporting Requirements

The Discharger shall submit monitoring reports **semiannually** with the data and information as required in this Monitoring and Reporting Program and as required in WDRs Order R5-2016-XXX and the Standard Provisions and Reporting Requirements (particularly Section I: "Standard Monitoring Specifications" and Section J: "Response to a Release"). In reporting the monitoring data required by this program, the Discharger shall arrange the data in tabular form so that the date, the constituents, the concentrations, and the units are readily discernible. The data shall be summarized in such a manner so as to illustrate clearly the compliance with waste discharge requirements or the lack thereof. Data shall also be submitted in a digital format, such as a computer disk.

Field and laboratory tests shall be reported in each monitoring report. Semiannual and annual monitoring reports shall be submitted to the Central Valley Water Board in accordance with the above schedule for the calendar period in which samples were taken or observations made. In addition, the Discharger shall enter all monitoring data and monitoring reports into the online Geotracker database as required by Division 3 of Title 27 and Chapter 30, Division 3 of Title 23.

The results of **all monitoring** conducted at the site shall be reported to the Central Valley Water Board in accordance with the reporting schedule above for the calendar period in which samples were taken or observations made.

The Discharger shall retain records of all monitoring information, including all calibration and maintenance records, all original strip chart recordings of continuous monitoring instrumentation, copies of all reports required by this Order, and records of all data used to complete the application for this Order. Records shall be maintained throughout the life of the facility including the post-closure period. Such records shall be legible and shall show the following for each sample:

- a) Sample identification and the monitoring point or background monitoring point from which it was taken, along with the identity of the individual who obtained the sample;
- b) Date, time, and manner of sampling;
- c) Date and time that analyses were started and completed, and the name of the personnel and laboratory performing each analysis;
- d) Complete procedure used, including method of preserving the sample, and the identity and volumes of reagents used;
- e) Calculation of results; and
- f) Results of analyses, and the MDL and PQL for each analysis. All peaks shall be reported.

### Required Reports

1. **Semiannual Monitoring Report:** Monitoring reports shall be submitted semiannually and are due on **1 August** and **1 February**. Each semiannual monitoring report shall contain at least the following:
  - a) For each groundwater monitoring point addressed by the report, a description of:
    - 1) The time of water level measurement;
    - 2) The type of pump - or other device - used for purging and the elevation of the pump intake relative to the elevation of the screened interval;
    - 3) The method of purging used to stabilize water in the well bore before the sample is taken including the pumping rate; the equipment and methods used to monitor field pH, temperature, and conductivity during purging; results of pH, temperature, conductivity, and turbidity testing; and the method of disposing of the purge water;
    - 4) The type of pump - or other device - used for sampling, if different than the pump or device used for purging; and
    - 5) A statement that the sampling procedure was conducted in accordance with the approved Sample Collection and Analysis Plan.

- b) A map or aerial photograph showing the locations of observation stations, monitoring points, and background monitoring points.
  - c) The estimated quarterly groundwater flow rate and direction in the uppermost aquifer, in any zones of perched water, and in any additional zone of saturation monitored based upon water level elevations taken prior to the collection of the water quality data submitted in the report [Title 27, section 20415(e)(15)].
  - d) Cumulative tabulated monitoring data for all monitoring points and constituents for groundwater, unsaturated zone, leachate, and surface water. Concentrations below the laboratory reporting limit shall not be reported as "ND" unless the reporting limit is also given in the table. Otherwise they shall be reported "<" the reporting limit (e.g., <0.10). Units shall be as required in Tables I through IV unless specific justification is given to report in other units. Refer to the SPRRs Section I "Standard Monitoring Specifications" for requirements regarding MDLs and PQLs.
  - e) Laboratory statements of results of all analyses evaluating compliance with requirements.
  - f) An evaluation of the concentration of each monitoring parameter (or 5-year COC when five year COC sampling is conducted) as compared to the current concentration limits, and the results of any required verification testing for constituents exceeding a concentration limit . Report any actions taken under Section J: Response to a Release for verified exceedances of a concentration limit for wells/constituents not already in corrective action monitoring.
  - g) An evaluation of the effectiveness of the leachate monitoring and control facilities, and of the run-off/run-on control facilities. Include a summary of any instances where leachate depth on an MSW landfill liner system exceeded 30 cm (excluding the leachate sump), and information about the required notification and corrective action in Standard Facility Specification E.13 of the SPRRs.
  - h) A summary of all Standard Observations for the reporting period required in Section A.5.d of this MRP.
  - i) A summary of inspection, leak search, and repair of final covers on any closed landfill units in accordance with an approved final post-closure maintenance plan as required by Standard Closure and Post-Closure Maintenance Specifications G.26 through G.29 of the SPRRs.
2. **Annual Monitoring Report:** The Discharger shall submit an Annual Monitoring Report to the Central Valley Water Board by **1 February** covering the reporting period of the previous monitoring year. If desired, the Annual Monitoring Report may be combined with the second semiannual report, but if so, shall clearly state that it is both a semi-annual and annual monitoring report in its title. Each Annual Monitoring Report shall contain the following information:

- a) All monitoring parameters shall be graphed to show historical trends at each monitoring point and background monitoring point, for all samples taken within at least the previous five calendar years. If a 5-year COC event was performed, then these parameters shall also be graphically presented. Each such graph shall plot the concentration of one or more constituents for the period of record for a given monitoring point or background monitoring point, at a scale appropriate to show trends or variations in water quality. The graphs shall plot each datum, rather than plotting mean values. Graphical analysis of monitoring data may be used to provide significant evidence of a release.
  - b) An evaluation of the monitoring parameters with regards to the cation/anion balance, and a graphical presentation using a Stiff diagram, a Piper graph, or a Schoeller plot.
  - c) All historical monitoring data for which there are detectable results, including data for the previous year, shall be submitted in tabular form in a digital file format such as a computer disk. The Central Valley Water Board regards the submittal of data in hard copy and in digital format as "...the form necessary for..." statistical analysis [Title 27, section 20420(h)], that facilitates periodic review by the Central Valley Water Board.
  - d) Hydrographs of each well showing the elevation of groundwater with respect to the elevations of the top and bottom of the screened interval and the elevation of the pump intake. Hydrographs of each well shall be prepared quarterly and submitted annually.
  - e) A comprehensive discussion of the compliance record, and the result of any corrective actions taken or planned which may be needed to bring the Discharger into full compliance with the waste discharge requirements.
  - f) A map showing the area and elevations in which filling has been completed during the previous calendar year and a comparison to final closure design contours, and include a projection of the year in which each discrete landfill module will be filled.
  - g) A written summary of the monitoring results, indicating any changes made or observed since the previous Annual Monitoring Report.
  - h) The results of the annual testing of leachate collection and removal systems required under Standard Facility Specification E.14 of the SPRRs.
  - i) Updated concentration limits for each monitoring parameter at each monitoring well based on the new data set.
  - j) A comprehensive discussion of any Corrective Action Program required by this MRP under Section A.6.
3. **Seep Reporting:** The Discharger shall report by telephone any seepage from the disposal area **immediately** after it is discovered. A written report shall be filed with

the Central Valley Water Board **within seven days**, containing at least the following information:

- a) A map showing the location(s) of seepage;
  - b) An estimate of the flow rate;
  - c) A description of the nature of the discharge (e.g., all pertinent observations and analyses);
  - d) Verification that samples have been submitted for analyses of the Field Parameters and Monitoring Parameters listed in Table III of this MRP, and an estimated date that the results will be submitted to the Central Valley Water Board; and
  - e) Corrective measures underway or proposed, and corresponding time schedule.
4. **Annual Facility Inspection Reporting:** By **15 November** of each year, the Discharger shall submit a report describing the results of the inspection and the repair measures implemented, preparations for winter, and include photographs of any problem areas and the repairs. Refer to Section A.5.a of this MRP, above.
  5. **Major Storm Event Reporting:** Following major storm events capable of causing damage or significant erosion, the Discharger **immediately** shall notify Central Valley Water Board staff of any damage or significant erosion upon discovery and report subsequent repairs within **14 days** of completion of the repairs, including photographs of the problem and the repairs. Refer to Section A.5.b of this MRP, above.
  6. **Survey and Iso-Settlement Map for Closed Landfills:** The Discharger shall conduct a survey and submit an iso-settlement map for each closed area of the landfill every five years pursuant to Title 27, section 21090(e). Refer to Section A.5.c of this MRP, above.
  7. **Financial Assurances Report:** By **30 September** of each year, the Discharger shall submit a copy of the annual financial assurances report due to CalRecycle that updates the financial assurances for closure, post-closure maintenance, and corrective action. Refer to Financial Assurances Specifications F.1 through F.4 of the WDRs.

## **C. WATER QUALITY PROTECTION STANDARD AND COMPLIANCE PERIOD**

### **1. Water Quality Protection Standard Report**

For each waste management unit, the Water Quality Protection Standard shall consist of all COCs, the concentration limit for each constituent of concern, the verification retesting procedure to confirm measurably significant evidence of a

release, the point of compliance, and all water quality monitoring points for each monitored medium.

The Water Quality Protection Standard for naturally occurring waste constituents consists of the COCs, the concentration limits, and the point of compliance and all monitoring points. Any proposed changes to the Water Quality Protection Standard other than annual update of the concentration limits shall be submitted in a report for review and approval.

The report shall:

- a. Identify **all distinct bodies of surface and ground water** that could be affected in the event of a release from a waste management unit or portion of a unit. This list shall include at least the uppermost aquifer and any permanent or ephemeral zones of perched groundwater underlying the facility.
- b. Include a map showing the monitoring points and background monitoring points for the surface water monitoring program, groundwater monitoring program, and the unsaturated zone monitoring program. The map shall include the point of compliance in accordance with Title 27, section 20405.
- c. Evaluate the perennial direction(s) of groundwater movement within the uppermost groundwater zone(s).
- d. Include a proposed statistical method for calculating concentration limits for monitoring parameters and constituents of concern that are detected in 10% or greater of the background data (naturally-occurring constituents) using a statistical procedure from Title 27, section 20415(e)(8)(A-D)] or section 20415(e)(8)(E).
- e. Include a retesting procedure to confirm or deny measurably significant evidence of a release pursuant to Title 27, section 20415(e)(8)(E) and section 20420(j)(1-3).

The Water Quality Protection Standard shall be certified by a California-registered civil engineer or geologist as meeting the requirements of Title 27. If subsequent sampling of the background monitoring point(s) indicates significant water quality changes due to either seasonal fluctuations or other reasons unrelated to waste management activities at the site, the Discharger may request modification of the Water Quality Protection Standard.

The Water Quality Protection Standard shall be updated annually for each monitoring well using new and historical monitoring data. A revised Monitoring Program Sampling and Water Quality Protection Standards Analysis Plan,

dated April 2016, is currently under review. Once approved by Central Valley Water Board Staff, the Discharger shall comply with the approved document or any subsequent approved revisions thereto.

## **2. Monitoring Parameters**

Monitoring parameters are a select group of constituents that are monitored during each monitoring event that are the waste constituents, reaction products, hazardous constituents, and physical parameters that provide a reliable indication of a release from a waste management unit. The monitoring parameters for all waste management units are those listed in Tables I through V for the specified monitored medium.

## **3. Constituents of Concern (COCs)**

The COCs include a larger group of waste constituents, their reaction products, and hazardous constituents that are reasonably expected to be in or derived from waste contained in the waste management unit, and are required to be monitored every five years [Title 27, sections 20395 and 20420(g)]. The COCs for all waste management units at the facility are those listed in Tables I through IV for the specified monitored medium, and Table VI. The Discharger shall monitor all COCs every five years, or more frequently as required in accordance with a Corrective Action Program. The last 5-year COC report was submitted to the Central Valley Water Board in the 2015 *Annual Monitoring Report*, and 5-year COCs are due to be monitored again in **2020**.

## **4. Concentration Limits**

For a naturally occurring constituent of concern, the concentration limit for each constituent of concern shall be determined as follows:

- a. By calculation in accordance with a statistical method pursuant to Title 27, section 20415(e)(8); or
- b. By an alternate statistical method meeting the requirements of Title 27, section 20415(e)(8)(E).

## **5. Retesting Procedures for Confirming Evidence of a Release**

If monitoring results indicate measurably significant evidence of a release, as described in Standard Monitoring Specification I.45 of the SPRRs, then:

- a. For analytes that are detected in less than 10% of the background samples (such as non-naturally occurring constituents), the Discharger shall use the non-statistical retesting procedure required in Standard Monitoring Specification I.46 of the SPRRs.

- b. For analytes that are detected in 10% or greater of the background samples (naturally occurring constituents), the Discharger shall use one of the statistical retesting procedure as required in Standard Monitoring Specification I.47 of the SPRRs.

**6. Point of Compliance**

The point of compliance for the water standard at each waste management unit is a vertical surface located at the hydraulically downgradient limit of the Unit that extends through the uppermost aquifer underlying the unit.

**7. Compliance Period**

The compliance period for each waste management unit shall be the number of years equal to the active life of the unit plus the closure period. The compliance period is the minimum period during which the Discharger shall conduct a water quality monitoring program subsequent to a release from the waste management unit. The compliance period shall begin anew each time the Discharger initiates an evaluation monitoring program [Title 27, section 20410].

**8. Monitoring Points**

A monitoring point is a well, device, or location specified in the waste discharge requirements, which monitoring is conducted and at which the water quality protection standard applies. The monitoring points for each monitored medium are listed in Section A of this MRP.

**D. TRANSMITTAL LETTER FOR ALL REPORTS**

A transmittal letter explaining the essential points shall accompany each report. At a minimum, the transmittal letter shall identify any violations found since the last report was submitted, and if the violations were corrected. If no violations have occurred since the last submittal, this shall be stated in the transmittal letter. The transmittal letter shall also state that a discussion of any violations found since the last report was submitted, and a description of the actions taken or planned for correcting those violations, including any references to previously submitted time schedules, is contained in the accompanying report. The transmittal letter shall contain a statement by the discharger, or the discharger's authorized agent, under penalty of perjury, that to the best of the signer's knowledge the report is true, accurate, and complete.

The Discharger shall implement the above monitoring program on the effective date of this Program.

Ordered by: \_\_\_\_\_  
PAMELA C. CREEDON, Executive Officer

EAM

\_\_\_\_\_  
(Date)

**TABLE I**  
**GROUNDWATER DETECTION MONITORING PROGRAM**

<u>Parameter</u>	<u>Units</u>	<u>Sampling Frequency</u>	<u>Reporting Frequency</u>
<b>Field Parameters</b>			
Groundwater Elevation	Ft. & 100ths, M.S.L.	Quarterly	Semiannual
Temperature	°C	Semiannual	Semiannual
Electrical Conductivity	umhos/cm	Semiannual	Semiannual
pH	pH units	Semiannual	Semiannual
Turbidity	Turbidity units	Semiannual	Semiannual
<b>Monitoring Parameters</b>			
Total Dissolved Solids (TDS)	mg/L <sup>1</sup>	Semiannual	Semiannual
Chloride	mg/L	Semiannual	Semiannual
Carbonate	mg/L	Semiannual	Semiannual
Bicarbonate	mg/L	Semiannual	Semiannual
Nitrate - Nitrogen	mg/L	Semiannual	Semiannual
Sulfate	mg/L	Semiannual	Semiannual
Calcium	mg/L	Semiannual	Semiannual
Magnesium	mg/L	Semiannual	Semiannual
Potassium	mg/L	Semiannual	Semiannual
Sodium	mg/L	Semiannual	Semiannual
Volatile Organic Compounds (USEPA Method 8260B, short list, see Table V)	ug/L <sup>2</sup>	Semiannual	Semiannual
<b>5-Year Constituents of Concern (see Table VI)</b>			
Total Organic Carbon	mg/L	5 years	2020
Inorganics (dissolved)	mg/L	5 years	and every 5 years
Volatile Organic Compounds (USEPA Method 8260B, extended list)	ug/L	5 years	thereafter
Semi-Volatile Organic Compounds (USEPA Method 8270C or D)	ug/L	5 years	" "
Chlorophenoxy Herbicides (USEPA Method 8151A)	ug/L	5 years	" "
Organophosphorus Compounds (USEPA Method 8141B)	ug/L	5 years	" "

<sup>1</sup> Milligrams per liter

<sup>2</sup> Micrograms per liter

**TABLE II**  
**UNSATURATED ZONE DETECTION MONITORING PROGRAM**

**SOIL-PORE GAS<sup>1</sup>**

<u>Parameter</u>	<u>Units</u>	<u>Sampling Frequency</u>	<u>Reporting Frequency</u>
<b>Monitoring Parameters</b>			
Volatile Organic Compounds (USEPA Method TO-14)	ug/cm <sup>3</sup>	Semiannual	Semiannual
Methane	%	Semiannual	Semiannual

**PAN LYSIMETERS<sup>2</sup> (or other vadose zone monitoring device)**

<u>Parameter</u>	<u>Units</u>	<u>Sampling Frequency</u>	<u>Reporting Frequency</u>
<b>Field Parameters</b>			
Electrical Conductivity	umhos/cm	Semiannual	Semiannual
pH	pH units	Semiannual	Semiannual
Volume of liquid removed	gallons	Quarterly	Semiannual

**Monitoring Parameters**

Total Dissolved Solids (TDS)	mg/L	Semiannual	Semiannual
Chloride	mg/L	Semiannual	Semiannual
Carbonate	mg/L	Semiannual	Semiannual
Bicarbonate	mg/L	Semiannual	Semiannual
Nitrate - Nitrogen	mg/L	Semiannual	Semiannual
Sulfate	mg/L	Semiannual	Semiannual
Calcium	mg/L	Semiannual	Semiannual
Magnesium	mg/L	Semiannual	Semiannual
Potassium	mg/L	Semiannual	Semiannual
Sodium	mg/L	Semiannual	Semiannual
Volatile Organic Compounds (USEPA Method 8260B, short list, see Table V)	ug/L	Semiannual	Semiannual

**5-Year Constituents of Concern (see Table VI)**

Total Organic Carbon	mg/L	5 years	2020
Inorganics (dissolved)	mg/L	5 years	and every 5 years
Volatile Organic Compounds (USEPA Method 8260B, extended list)	ug/L	5 years	thereafter
Semi-Volatile Organic Compounds (USEPA Method 8270C or D)	ug/L	5 years	" "
Chlorophenoxy Herbicides (USEPA Method 8151A)	ug/L	5 years	" "
Organophosphorus Compounds (USEPA Method 8141B)	ug/L	5 years	" "

<sup>1</sup> Soil-pore gas samples collected from landfill gas probes are only subject to the VOC (USEPA Method TO-14) and methane sampling (not the other parameters listed for pan lysimeters).

<sup>2</sup> Pan lysimeters shall be inspected for the presence of liquid **monthly**. If liquid is detected in a previously dry pan lysimeter, the Discharger shall verbally notify Central Valley Water Board staff within **seven days** and shall immediately sample and test the liquid for Field and Monitoring Parameters listed in Table II.

**TABLE III**  
**LEACHATE MONITORING <sup>1</sup>, SEEP MONITORING <sup>2</sup>, AND LCRS TESTING <sup>3</sup>**

<u>Parameter</u>	<u>Units</u>	<u>Sampling Frequency</u>	<u>Reporting Frequency</u>
<b>Field Parameters</b>			
Total Flow	Gallons	Monthly	Semiannual
Flow Rate	Gallons/Day	Monthly	Semiannual
Electrical Conductivity	umhos/cm	Annually	Semiannual
pH	pH units	Annually	Semiannual
<b>Monitoring Parameters</b>			
Total Dissolved Solids (TDS)	mg/L	Annually	Annually
Chloride	mg/L	Annually	Annually
Carbonate	mg/L	Annually	Annually
Bicarbonate	mg/L	Annually	Annually
Nitrate - Nitrogen	mg/L	Annually	Annually
Sulfate	mg/L	Annually	Annually
Calcium	mg/L	Annually	Annually
Magnesium	mg/L	Annually	Annually
Potassium	mg/L	Annually	Annually
Sodium	mg/L	Annually	Annually
Volatile Organic Compounds (USEPA Method 8260B, short list, see Table V)	ug/L	Annually	Annually
<b>5-Year Constituents of Concern (see Table VI)</b>			
Total Organic Carbon	mg/L	5 years	2020
Inorganics (dissolved)	mg/L	5 years	and every 5 years
Volatile Organic Compounds (USEPA Method 8260B, extended list)	ug/L	5 years	thereafter
Semi-Volatile Organic Compounds (USEPA Method 8270C or D)	ug/L	5 years	" "
Chlorophenoxy Herbicides (USEPA Method 8151A)	ug/L	5 years	" "
Organophosphorus Compounds (USEPA Method 8141B)	ug/L	5 years	" "
<b>LCRS Testing <sup>3</sup></b>	---	Annually	Annually

<sup>1</sup> If leachate is detected in a previously dry sump, the Discharger shall verbally notify Central Valley Water Board staff within **seven days** and shall immediately sample and test the leachate for Field and Monitoring Parameters listed in Table III. Leachate in the LCRS sump shall then be sampled for all parameters and constituents in accordance with the frequencies listed in Table III whenever liquid is present.

<sup>2</sup> Leachate seeps shall be sampled and analyzed for the Field and Monitoring Parameters in this table upon detection. The quantity of leachate shall be estimated and reported in gallons/day. Also, refer to Section B.3

<sup>3</sup> The Discharger shall test each LCRS annually pursuant to Title 27, section 20340(d) to demonstrate proper operation. The results of the tests shall be compared with earlier tests made under comparable conditions.

**TABLE IV**  
**SURFACE WATER DETECTION MONITORING PROGRAM**

<u>Parameter</u>	<u>Units</u>	<u>Sampling Frequency</u> <sup>1</sup>	<u>Reporting Frequency</u>
<b>Field Parameters</b>			
Electrical Conductivity	umhos/cm	Semiannual	Semiannual
pH	pH units	Semiannual	Semiannual
Turbidity	Turbidity units	Semiannual	Semiannual
Flow to Waters of U.S.	Yes or No	Semiannual	Semiannual
<b>Monitoring Parameters</b>			
Total Dissolved Solids (TDS)	mg/L	Semiannual	Semiannual
Carbonate	mg/L	Semiannual	Semiannual
Bicarbonate	mg/L	Semiannual	Semiannual
Chloride	mg/L	Semiannual	Semiannual
Nitrate - Nitrogen	mg/L	Semiannual	Semiannual
Sulfate	mg/L	Semiannual	Semiannual
Calcium	mg/L	Semiannual	Semiannual
Magnesium	mg/L	Semiannual	Semiannual
Potassium	mg/L	Semiannual	Semiannual
Sodium	mg/L	Semiannual	Semiannual
Volatile Organic Compounds (USEPA Method 8260B, short list, see Table V)	ug/L	Semiannual	Semiannual
<b>5-Year Constituents of Concern (see Table VI)</b>			
Total Organic Carbon	mg/L	5 years	2020
Inorganics (dissolved)	mg/L	5 years	and every 5 years
Volatile Organic Compounds (USEPA Method 8260B, extended list)	ug/L	5 years	thereafter
Semi-Volatile Organic Compounds (USEPA Method 8270C or D)	ug/L	5 years	" "
Chlorophenoxy Herbicides (USEPA Method 8151A)	ug/L	5 years	" "
Organophosphorus Compounds (USEPA Method 8141B)	ug/L	5 years	" "

<sup>1</sup> Semiannual surface water monitoring is required twice per year when there is water present at the designated surface water monitoring point any time during the reporting period (1 January to 30 June or 1 July to 31 December). Reporting shall include whether there was flow from the facility to waters of the U.S. when the samples were collected.

## TABLE V

### MONITORING PARAMETERS FOR DETECTION MONITORING

#### Surrogates for Metallic Constituents:

pH  
Total Dissolved Solids  
Electrical Conductivity  
Chloride  
Sulfate  
Nitrate nitrogen

#### Volatile Organic Compounds, short list:

##### **USEPA Method 8260B**

Acetone  
Acrylonitrile  
Benzene  
Bromochloromethane  
Bromodichloromethane  
Bromoform (Tribromomethane)  
Carbon disulfide  
Carbon tetrachloride  
Chlorobenzene  
Chloroethane (Ethyl chloride)  
Chloroform (Trichloromethane)  
Dibromochloromethane (Chlorodibromomethane)  
1,2-Dibromo-3-chloropropane (DBCP)  
1,2-Dibromoethane (Ethylene dibromide; EDB)  
o-Dichlorobenzene (1,2-Dichlorobenzene)  
m-Dichlorobenzene (1,3-Dichlorobenzene)  
p-Dichlorobenzene (1,4-Dichlorobenzene)  
trans-1,4-Dichloro-2-butene  
Dichlorodifluoromethane (CFC-12)  
1,1-Dichloroethane (Ethylidene chloride)  
1,2-Dichloroethane (Ethylene dichloride)  
1,1 -Dichloroethylene (1,1 -Dichloroethene; Vinylidene chloride)  
cis- 1,2-Dichloroethylene (cis- 1,2-Dichloroethene)  
trans-1,2-Dichloroethylene (trans-1,2-Dichloroethene)  
1,2-Dichloropropane (Propylene dichloride)  
cis- 1,3-Dichloropropene  
trans- 1,3-Dichloropropene  
Di-isopropylether (DIPE)  
Ethanol  
Ethyltertiary butyl ether  
Ethylbenzene  
2-Hexanone (Methyl butyl ketone)  
Hexachlorobutadiene  
Methyl bromide (Bromomethene)  
Methyl chloride (Chloromethane)

**TABLE V**  
**MONITORING PARAMETERS FOR DETECTION MONITORING**

**Continued**

Methylene bromide (Dibromomethane)  
Methylene chloride (Dichloromethane)  
Methyl ethyl ketone (MEK: 2-Butanone)  
Methyl iodide (Iodomethane)  
Methyl t-butyl ether  
4-Methyl-2-pentanone (Methyl isobutylketone)  
Naphthalene  
Styrene  
Tertiary amyl methyl ether  
Tertiary butyl alcohol  
1,1,1,2-Tetrachloroethane  
1,1,2,2-Tetrachloroethane  
Tetrachloroethylene (Tetrachloroethene; Perchloroethylene)  
Toluene  
1,2,4-Trichlorobenzene  
1,1,1-Trichloroethane (Methylchloroform)  
1,1,2-Trichloroethane  
Trichloroethylene (Trichloroethene)  
Trichlorofluoromethane (CFC- 11)  
1,2,3-Trichloropropane  
Vinyl acetate  
Vinyl chloride  
Xylenes

**TABLE VI**  
**5-YEAR COCs & APPROVED USEPA ANALYTICAL METHODS**

<b><u>Inorganics (dissolved):</u></b>	<b><u>USEPA Method</u></b>
Aluminum	200.7
Antimony	200.8
Barium	200.7
Beryllium	200.8
Cadmium	200.7
Chromium	200.7
Cobalt	200.7
Copper	200.7
Silver	200.7
Tin	200.7
Vanadium	200.8
Zinc	200.7
Iron	200.7
Manganese	200.7
Arsenic	200.8
Lead	200.8
Mercury	200.8
Nickel	200.8
Selenium	SM 3114 B
Thallium	200.8
Cyanide	SM 4500-CN E
Sulfide	SM 4500-S E (18 <sup>th</sup> edition)

**Volatile Organic Compounds, extended list:**

**USEPA Method 8260B**

Acetone  
Acetonitrile (Methyl cyanide)  
Acrolein  
Acrylonitrile  
Allyl chloride (3-Chloropropene)  
Benzene  
Bromochloromethane (Chlorobromomethane)  
Bromodichloromethane (Dibromochloromethane)  
Bromoform (Tribromomethane)  
Carbon disulfide  
Carbon tetrachloride  
Chlorobenzene  
Chloroethane (Ethyl chloride)  
Chloroform (Trichloromethane)  
Chloroprene  
Dibromochloromethane (Chlorodibromomethane)  
1,2-Dibromo-3-chloropropane (DBCP)  
1,2-Dibromoethane (Ethylene dibromide; EDB)  
o-Dichlorobenzene (1,2-Dichlorobenzene)

## TABLE VI

### 5-YEAR COCs & APPROVED USEPA ANALYTICAL METHODS

#### Continued

m-Dichlorobenzene (1,3-Dichlorobenzene)  
p-Dichlorobenzene (1,4-Dichlorobenzene)  
trans- 1,4-Dichloro-2-butene  
Dichlorodifluoromethane (CFC 12)  
1,1 -Dichloroethane (Ethylidene chloride)  
1,2-Dichloroethane (Ethylene dichloride)  
1,1 -Dichloroethylene (1, 1-Dichloroethene; Vinylidene chloride)  
cis- 1,2-Dichloroethylene (cis- 1,2-Dichloroethene)  
trans- 1,2-Dichloroethylene (trans- 1,2-Dichloroethene)  
1,2-Dichloropropane (Propylene dichloride)  
1,3-Dichloropropane (Trimethylene dichloride)  
2,2-Dichloropropane (Isopropylidene chloride)  
1,1 -Dichloropropene  
cis- 1,3-Dichloropropene  
trans- 1,3-Dichloropropene  
Di-isopropylether (DIPE)  
Ethanol  
Ethyltertiary butyl ether  
Ethylbenzene  
Ethyl methacrylate  
Hexachlorobutadiene  
2-Hexanone (Methyl butyl ketone)  
Isobutyl alcohol  
Methacrylonitrile  
Methyl bromide (Bromomethane)  
Methyl chloride (Chloromethane)  
Methyl ethyl ketone (MEK; 2-Butanone)  
Methyl iodide (Iodomethane)  
Methyl t-butyl ether  
Methyl methacrylate  
4-Methyl-2-pentanone (Methyl isobutyl ketone)  
Methylene bromide (Dibromomethane)  
Methylene chloride (Dichloromethane)  
Naphthalene  
Propionitrile (Ethyl cyanide)  
Styrene  
Tertiary amyl methyl ether  
Tertiary butyl alcohol  
1,1,1,2-Tetrachloroethane  
1,1,1,2-Tetrachloroethane  
Tetrachloroethylene (Tetrachloroethene; Perchloroethylene; PCE)  
Toluene  
1,2,4-Trichlorobenzene  
1,1,1 -Trichloroethane (Methylchloroform)

**TABLE VI**

**5-YEAR COCs & APPROVED USEPA ANALYTICAL METHODS**

**Continued**

1,1,2-Trichloroethane  
Trichloroethylene (Trichloroethene; TCE)  
Trichlorofluoromethane (CFC- 11)  
1,2,3-Trichloropropane  
Vinyl acetate  
Vinyl chloride (Chloroethene)  
Xylene (total)

**Semi-Volatile Organic Compounds:**

**USEPA Method 8270C or D - base, neutral, & acid extractables**

Acenaphthene  
Acenaphthylene  
Acetophenone  
2-Acetylaminofluorene (2-AAF)  
Aldrin  
4-Aminobiphenyl  
Anthracene  
Benzo[a]anthracene (Benzanthracene)  
Benzo[b]fluoranthene  
Benzo[k]fluoranthene  
Benzo[g,h,i]perylene  
Benzo[a]pyrene  
Benzyl alcohol  
Bis(2-ethylhexyl) phthalate  
alpha-BHC  
beta-BHC  
delta-BHC  
gamma-BHC (Lindane)  
Bis(2-chloroethoxy)methane  
Bis(2-chloroethyl) ether (Dichloroethyl ether)  
Bis(2-chloro-1-methylethyl) ether (Bis(2-chloroisopropyl) ether; DCIP)  
4-Bromophenyl phenyl ether  
Butyl benzyl phthalate (Benzyl butyl phthalate)  
Chlordane  
p-Chloroaniline  
Chlorobenzilate  
p-Chloro-m-cresol (4-Chloro-3-methylphenol)  
2-Chloronaphthalene  
2-Chlorophenol  
4-Chlorophenyl phenyl ether  
Chrysene  
o-Cresol (2-methylphenol)  
m-Cresol (3-methylphenol)  
p-Cresol (4-methylphenol)  
4,4'-DDD

**TABLE VI**

**5-YEAR COCs & APPROVED USEPA ANALYTICAL METHODS**

**Continued**

4,4'-DDE  
4,4'-DDT  
Diallate  
Dibenz[a,h]anthracene  
Dibenzofuran  
Di-n-butyl phthalate  
3,3'-Dichlorobenzidine  
2,4-Dichlorophenol  
2,6-Dichlorophenol  
Dieldrin  
Diethyl phthalate  
p-(Dimethylamino)azobenzene  
7,12-Dimethylbenz[a]anthracene  
3,3'-Dimethylbenzidine  
2,4-Dimethylphenol (m-Xylenol)  
Dimethyl phthalate  
m-Dinitrobenzene  
4,6-Dinitro-o-cresol (4,6-Dinitro-2-methylphenol)  
2,4-Dinitrophenol  
2,4-Dinitrotoluene  
2,6-Dinitrotoluene  
Di-n-octyl phthalate  
Diphenylamine  
Endosulfan I  
Endosulfan II  
Endosulfan sulfate  
Endrin  
Endrin aldehyde  
Ethyl methanesulfonate  
Famphur  
Fluoranthene  
Fluorene  
Heptachlor  
Heptachlor epoxide  
Hexachlorobenzene  
Hexachlorocyclopentadiene  
Hexachloroethane  
Hexachloropropene  
Indeno(1,2,3-c,d)pyrene  
Isodrin  
Isophorone  
Isosafrole  
Kepone  
Methapyrilene  
Methoxychlor  
3-Methylcholanthrene  
Methyl methanesulfonate

**TABLE VI**

**5-YEAR COCs & APPROVED USEPA ANALYTICAL METHODS**

**Continued**

2-Methylnaphthalene  
1,4-Naphthoquinone  
1-Naphthylamine  
2-Naphthylamine  
o-Nitroaniline (2-Nitroaniline)  
m-Nitroaniline (3-Nitroaniline)  
p-Nitroaniline (4-Nitroaniline)  
Nitrobenzene  
o-Nitrophenol (2-Nitrophenol)  
p-Nitrophenol (4-Nitrophenol)  
N-Nitrosodi-n-butylamine (Di-n-butylnitrosamine)  
N-Nitrosodiethylamine (Diethylnitrosamine)  
N-Nitrosodimethylamine (Dimethylnitrosamine)  
N-Nitrosodiphenylamine (Diphenylnitrosamine)  
N-Nitrosodipropylamine (N-Nitroso-N-dipropylamine; Di-n-propylnitrosamine)  
N-Nitrosomethylethylamine (Methylethylnitrosamine)  
N-Nitrosopiperidine  
N-Nitrosopyrrolidine  
5-Nitro-o-toluidine  
Pentachlorobenzene  
Pentachloronitrobenzene (PCNB)  
Pentachlorophenol  
Phenacetin  
Phenanthrene  
Phenol  
p-Phenylenediamine  
Polychlorinated biphenyls (PCBs; Aroclors)  
Pronamide  
Pyrene  
Safrole  
1,2,4,5-Tetrachlorobenzene  
2,3,4,6-Tetrachlorophenol  
o-Toluidine  
Toxaphene  
2,4,5-Trichlorophenol  
0,0,0-Triethyl phosphorothioate  
sym-Trinitrobenzene

**TABLE VI**

**5-YEAR COCs & APPROVED USEPA ANALYTICAL METHODS**

**Continued**

**Chlorophenoxy Herbicides:**

**USEPA Method 8151A**

2,4-D (2,4-Dichlorophenoxyacetic acid)

Dinoseb (DNBP; 2-sec-Butyl-4,6-dinitrophenol)

Silvex (2,4,5-Trichlorophenoxypropionic acid; 2,4,5-TP)

2,4,5-T (2,4,5-Trichlorophenoxyacetic acid)

**Organophosphorus Compounds:**

**USEPA Method 8141B**

Atrazine

Chlorpyrifos

0,0-Diethyl 0-2-pyrazinyl phosphorothioate (Thionazin)

Diazinon

Dimethoate

Disulfoton

Methyl parathion (Parathion methyl)

Parathion

Phorate

Simazine