Proposed Permit Terms California WaterFix CSPA *et al.* July 9, 2018 (Not an exhaustive list)

No.	Title or Subject	Requirement	Compliance Point	Season or Frequency	Rationale with Exhibit(s) if Available
1	Fish screen approach velocity and sweeping velocity	.2 ft/sec max approach velocity .4 ft/sec or greater sweeping velocity	North Delta Diversions (NDD)	Velocities should apply always, on an instantaneous basis	Reduce mortality (DWR-1012)
2	Bypass criteria past NDD	Minimum NDD diversions (900 cfs) whenever bypass flows are less than 35,000 cfs	Immediately downstream of NDD	October– June Bypass requirements should apply on an instantaneous basis.	Avoid reverse flows at NDD; protect all species from entrainment, impingement, predation; 35,000 cfs identified as threshold in NMFS. BO for WaterFix, p. 772, Miller testimony (DWR- 1011), Rosenfield (NRDC-58), CSPA-204, CSPA- 500, CSPA-504
3	Bypass criteria past NDD	Minimum NDD diversions (900 cfs) whenever bypass flows are less than 7000 cfs	Immediately downstream of NDD	July- September	CSPA-500, NRDC-58
4	Salinity	Restrict NDD and South Delta Diversions (SDD) to minimum diversions (900 cfs NDD / 1500	Both Emmaton and Jersey Point	Extend to year round	Maintain LSZ in Suisun Bay to provide habitat for smelt; avoid entrainment at SDD.

		cfs NDD+SDD)			Should explicitly be
		when $EC > .50$			a fish and wildlife
		(average daily)			standard, not only
		Include salinity			an ag standard as in
		requirement as a			D-1641.
		measure to			
		protect fish and			From CSPA-204
		wildlife in			
		addition to			
		agriculture.		_	
5	Combined SDD	6000 cfs		June	Reinstate D-1485
	export limitations	9000 cfs		July	requirements whose
					elimination
					devastated Delta
					smelt and striped bass
					Uass
					Based on CSPA-
					500
6	Coordinated	Under balanced	As stated	Under	Avoid impacts to
	Operating	conditions, BOR	under current	balanced	upstream river
	Agreement (COA)	supplies 75% of	COA	conditions	reaches from
		water to meet in-			changes in reservoir
		basin uses, DWR			operations.
		supplies 25%.			
					DWR and BOR
					should not be
					allowed to
					renegotiate COA
					outside of
7	Joint Points Of	CVP should not	NDD	Alwayo	evidentiary process. CVP does not
/	Diversion (JPOD)	be permitted to		Always	appear to be a full
		exercise JPOD at			partner in the NDD
		the NDD.			facilities.
					identites.
		As an			JPOD should not
		alternative,			become a
		SWRCB must			permanent transfer
		set JPOD rules			workaround past
		for CVP at NDD			water rights.
		based on level of			
		Bureau			Maintain integrity
		participation in			of water rights that
		WaterFix.			are used as the
					basis for NDD

					diversions.
					D-1641 authorized JPOD without considering NDD, and some sources of JPOD water are Old River. CSPA-2 PCFFA-161
8	Carryover storage	1.6 MAF storage; operate to meet at least 1.6 MAF at end of December Both figures at 90% exceedance, with following year delivery penalty sufficient to deter failure.	Oroville Reservoir	End of September	CSPA analysis CSPA-202-errata
9	Carryover storage	 Wet: 3.2 MAF Above Normal: 3.2 MAF Below Normal: 2.8 MAF Dry: 2.2 MAF Critically dry: 1.9 MAF 	Shasta Reservoir	End of September	Consistent with proposed revision to Shasta RPA, NRDC-29, pdf. p. 214
10	Carryover storage	As proposed by American River Group in Part 2 case-in-chief.	Folsom Reservoir		ARWA-502
11	Carryover storage and export to Sacramento River	Interim Default carryover: • Ex Wet: 1.8 MAF • Wet: 1.8 MAF • Normal: 1.8 MAF • Dry: 1.4 MAF • Critically dry:	Trinity Reservoir	End of September	The goal of Trinity carryover storage levels is to meet NMFS 2000 Trinity River water temperature objectives. Interim numbers

			Т	
		1.2 MAF		based on review of
		• Except for Ex		PCFFA-126, esp.
		Wet, reduce		Table 1, p. 9:7.
		requirement by		
		.3 MAF per year		SWRCB should re-
		for up to 2		evaluate Trinity
		preceding Dry or		carryover storage as
		CD years		part of a hearing on
		CD years		Order WR 90-05
				(see #12 below).
		No more than		SWRCB should re-
		50% of total		evaluate Trinity
		release from		exports to
				Sacramento River
		Trinity Reservoir		
		exported to		as part of a hearing
		Sacramento		on Order WR 90-05
		River in any		(see #12 below)
		water year.		
				Issues with
		Flow volumes		Sacramento River
		for Trinity River		impacts of Trinity
		in Trinity River		River diversions
		ROD must be		raised in CSPA-220
		met.		
12	SWRCB			Operation of
	evidentiary hearing			Sacramento River
	to improve and			that is more
	make more			consistently
	consistent the			appropriate for fish
	fisheries benefits of			is gravely needed.
	upper Sacramento			
				NDD should not les
	River operations			NDD should partly
	within 5 years from			mitigate for re-
	decision on			operation of Shasta,
	WaterFix petitions.			Trinity and Sac
				River diversions
	In part, this hearing			once NDD is on
	will re-evaluate			line.
	Order WR 90-05.			
	It should also re-			Issues identified in
	evaluate Trinity			CSPA-204 and
	carryover storage			CSPA-500
h	•	•	1	



12	Dalta antflam	67 750/	Deservices	Establist and	Deced on the
13	Delta outflow	67-75%	December	Establish and	Based on the
1		unimpaired flow	through	implement a	Board's 2010
			February	real-time	public trust
1				measuring	recommendations
		67-75%	March	protocol for	of 75% of
		unimpaired flow	through June	Delta	unimpaired flow.
				outflow to	
				replace	The Board should
				NDOI	adopt these criteria
					that are protective
					of the public trust
		Delta outflow for	July-August	7100 cfs	as part of
		months other			"appropriate Delta
		than February -	September-	11,400 cfs in	flow criteria."
		June	November	Wet, AN yrs.	now enterna.
		5 4110		7400 cfs in	
				BN, Dry, CD	DFW ITP for
				-	WaterFix states a
				yrs.	
	Die Viete flam	10,000 of the	Die Wiste	T., 1., 41,	temporally and
	Rio Vista flow	10,000 cfs in	Rio Vista	July through	numerically
		Wet, AN yrs.		November	inadequate outflow
1		7,000 cfs in BN,			requirement whose
		Dry and CD yrs.			rationale is to
					maintain past levels
		Restrict NDD			of outflow in
		and South Delta			March-May
		Diversions			
		(SDD) to			CSPA 202-errata,
		<u>minimum</u>			CSPA 204, CSPA-
		diversions (900			500, NRDC-58
		cfs NDD / 1500			
		NDD+SDD)			
		when the values			
		shown above are			
		not met			
14	Conditions in BO's	Incorporated into		Hearing	SWRCB must have
	and ITP	permits; any		every 3 years	approval of changes
		changes must be		j 2 j 2	in BO's and ITP,
		subject to review			and exercise that
		by SWRCB in			approval in a public
		public			hearing.
		evidentiary			nouring.
		hearing.			CSPA 202-errata
15	Adaptive	Decisions and		Hearing	SWRCB must have
15	-	changes to		every 3 years	approval of changes
	management	-		every 5 years	in BO's and ITP,
L		permit terms,			III DO S alla ITP,

r	1	[_]		
		and evaluation of		and exercise that
		success of		approval in a public
		adaptive		hearing.
		management		
		subject to review		CSPA-200, CSPA-
		by SWRCB in		202-errata,
		•		CSPA-204
		public		CSPA-204
		evidentiary		
		hearing.		
		A. £C 1		
		Affected		
		stakeholders		
		need to be		
		engaged in		
		technical and		
		policy decisions		
		at public		
		meetings.		
16	Real-time decision	Affected		Operators and fish
10	making	stakeholders		agencies need
	maxing	need to be		technically
				-
		engaged in		competent, funded
		regular technical		chaperones.
		and policy		
		decisions at		CSPA -200, CSPA-
		public meetings.		202-errata, CSPA-
				204
17	OMR	The Board		To be addressed in
		should develop		Bay Delta Plan
		and include		The Board should
		explicit stand-		develop and include
		alone OMR		explicit OMR
		requirements in		requirements in the
		the update of the		WaterFix
		Bay-Delta Plan,		proceeding
		to be		proceeding
		incorporated into		
		÷		
		the permits for		
		the SWP and		
		CVP.		
		CSPA et al. have		
		no proposed		
		values at this		
		<u>time</u>		
18	Lower Feather	65° mouth of	May-Ju	1 0
	River flows	Yuba River; 68°		migration flows of
(

		mouth of Feather River			adequate temperature for upstream migration
19	Sacramento River at Wilkins Slough	7000 cfs bypass	Immediately downstream of Wilkins Slough	Always	Maintain adequate flow and water temperature in critical migration corridor. CSPA-500, CSPA- 504
20	Clifton Court ops	Constant rate of diversion into Clifton Court Forebay instead of "big gulp" on high tides	Entrance to Clifton Court Forebay	Always	Reduce entrainment and intra-daily effect of reverse flows
21	State of the art fish screens at Clifton Court Forebay and Jones pumping plant			Operating within 7 years from date petitions granted	Existing salvage facilities kill countless fish CSPA-200
22	Gaging and reporting	Hourly and 15 minute reporting of diversions and flow at and past NDD and SDD		NDD and SDD	CSPA-204
23	Biological monitoring and reporting	Fish entrained, impinged or salvaged at NDD and SDD Predatory fish at NDD		Daily At least monthly surveys of predatory fish near intakes	The public should have the ability to evaluate in real- time the efficacy of real-time operations in preventing entrainment of salvageable fish at SWP and CVP facilities CSPA-204
24	Preference for south Delta diversions	First 3000 cfs combined SWP and SVP export preferentially diverted at south Delta facilities		June-October	Maintain Delta water quality and Delta inflow in summer and early fall. Memorializes DWR

			representation made
			in Part 1.
25	Transfers through NDD and SDD facilities	Defined limitations, specifics to be determined	Limitations must be founded on publicly disclosed scientific evidence and be comprehensive. Any allowed transfers must demonstrate no harm to surface water, groundwater users, terrestrial habitat and dependent species AQUA-1-revised AQUA-5 AQUA-202 AQUA-202 AQUA-202 AQUA-227 CSPA-4-revised CSPA-204 CSPA-431
26	Indian trust assets	Permittees must consult with California Indian Water Commission on permit terms, operations, and any adaptive management changes	Permittees must explicitly recognize and fulfill obligations to protect native people's legal, biological, cultural, religious, sustenance, medicinal, water and other tribal resources AQUA-272
27	D-1641 Export- Inflow (E/I) ratio	E/I ratio should count inflow directly upstream of NDD as part of inflow for purposes of determining E/I ratio	Preserves protection for fish and water quality. PCFFA-126