CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD CENTRAL VALLEY REGION

Fresno Office 1685 "E" Street Fresno, CA 93706-2007

Sacramento Office (Main) 11020 Sun Center Drive #200 Rancho Cordova, CA 95670-6114

Redding Office 364 Knollcrest Drive #205 Redding, CA 96002

Regional Board Website (https://www.waterboards.ca.gov/centralvalley)

MONITORING & REPORTING PROGRAM (MRP) R5-2022-0044



ORDER INFORMATION

Order Type(s): Monitoring & Reporting Program (MRP)

Status: Adopted

Program: Title 27 Discharges to Land

Region 5 Office: Redding

Discharger(s): Plumas County

Facility: Gopher Hill Class III Municipal Solid Waste Landfill and

Class II Surface Impoundment

Address: Snake Lake Road County: Plumas County 113-010-002 WDID: 5A450303001 Prior Order(s): R5-2004-0062

	Officer, hereby certify that the following is a full, true, pted by the California Regional Water Quality Control			
Board, Central Valley Region, on 10 June 2022.				
	PATRICK PULUPA,			
	Executive Officer			

REGIONAL BOARD INFORMATION

Sacramento Office (Main)

Rancho Cordova, CA 95670-6114 11020 Sun Center Drive #200 Telephone: (916) 464-3291

Fresno Office

1685 "E" Street Fresno, CA 93706-2007 Telephone: (559) 445-5116

Redding Office

364 Knollcrest Drive #205 Redding, CA 96002 Telephone: (530) 224-4845

Regional Board Website

(https://www.waterboards.ca.gov/centralvalley)

PLUMAS COUNTY GOPHER HILL LANDFILL PLUMAS COUNTY

TABLE OF CONTENTS

TABL	ΕII	NDEX	iv
GLOS	SA	.RY	V
PREF	AC	E	8
MONI	то	RING & REPORTING PROGRAM	9
A.	Ge	eneral Provisions	9
	1.	Incorporation of Standard Provisions	9
	2.	Monitoring Provisions in WDRs Order	9
	3.	Compliance with Title 27	9
	4.	Sample Collection and Analysis Plan (SCAP)	9
В.	De	etection Monitoring Program (DMP)	10
	1.	Groundwater	10
		a. Required Network	10
		b. Sample Collection and Analysis	11
		c. Five-Year COCs	12
		d. Groundwater Conditions	13
	2.	Unsaturated Zone	14
		a. Required Network	14
		b. Soil Pore Gas (SPG) Monitoring	14
		c. Lysimeter Inspection	15
		d. Five-Year COCs	16
	3.	Surface Water	17
		a. Required Network	17

PLUMAS COUNTY GOPHER HILL LANDFILL

PLUMAS COUNTY

TABLE OF CONTENTS

		D.	Sample Collection and Analysis	18
		C.	Five-Year COCs	20
	4.	Su	mmary of Water Quality Protection Standard (WQPS) Components	20
		a.	Compliance Period	21
		b.	Monitoring Points	21
		C.	Point of Compliance (POC)	21
		d.	Constituents of Concern (COCs)	21
		e.	Monitoring Parameters	21
		f.	Five-Year COCs	22
		g.	Concentration Limits	22
		h.	Retesting Procedures	23
C.	Ac	dit	onal Facility Monitoring	23
	1.	Le	achate Impoundment (WMU-2)	23
		a.	Leachate Sampling	24
		b.	Five-Year COCs	25
	2.	Le	achate Seepage	26
	3.	Re	gular Visual Inspection	27
	4.	An	nual Facility Inspections	28
	5.	Ma	ijor Storm Events	28
	6.	Fiv	re-Year Iso-Settlement Surveys (Closed Landfills)	29
D.	Re	po	rting Requirements	29
	1.	Se	miannual Monitoring Reports (SMRs)	30
	2.	An	nual Monitoring Reports (AMRs)	32

TABLE OF CONTENTS

3. Lea	achate Seep Reporting	33
4. Ann	nual Facility Inspection Report	33
5. Maj	jor Storm Event Reports	33
6. Sur	vey and Iso-Settlement Map (Closed Landfill Units)	34
7. Fina	ancial Assurances Report	34
8. Wat	ter Quality Protection Standard Report	34
9. Ger	neral Reporting Provisions	35
a	Transmittal Letters	35
b. I	Monitoring Data and Reports	36
С. (Compliance with SPRRs	37
d. <i>i</i>	Additional Requirements for Monitoring Reports	37
E. Record	d Retention Requirements	37
ATTACHMEN	NT A—VOLATILE ORGANIC COMPOUNDS, SHORT LIST	39
ATTACHMEN	NT B—DISSOLVED INORGANICS (FIVE-YEAR COCS)	42
ATTACHMEN YEAR COCS)	NT C—VOLATILE ORGANIC COMPOUNDS, EXTENDED LIST (FIVE-	44
	NT D—SEMI-VOLATILE ORGANIC COMPOUNDS (FIVE-YEAR COCS)	
ATTACHMEN	NT E—CHLOROPHENOXY HERBICIDES (FIVE-YEAR COCS)	54
ATTACHMEN	NT F—ORGANOPHOSPHOROUS COMPOUNDS (FIVE YEAR COCS)	55

TABLE INDEX

Table 1—Groundwater Monitoring Network	. 10
Table 2—Groundwater Detection Monitoring, Physical Parameters	. 11
Table 3—Groundwater Detection Monitoring, Constituent Parameters	. 12
Table 4—Groundwater Detection Monitoring, Five-Year COCs	. 13
Table 5—Groundwater Detection Monitoring, Groundwater Conditions	. 14
Table 6—Unsaturated Zone Monitoring Network	. 14
Table 7—Unsaturated Zone Detection Monitoring Network	. 15
Table 8—Unsaturated Zone Detection Monitoring (Lysimeter), Physical Parameters	. 15
Table 9—Unsaturated Zone Detection Monitoring (Lysimeter), Constituent Parameter	
Table 10—Unsaturated Zone Detection Monitoring (Lysimeter), Five-Year COCs	
Table 11—Surface Water Detection Monitoring Network	. 18
Table 12—Surface Water Detection Monitoring, Physical Parameters	. 18
Table 13—Surface Water Detection Monitoring, Constituent Parameters	. 19
Table 14—Surface Water Detection Monitoring, Five-Year COCs	. 20
Table 15—LCRS Sump Monitoring, Parameters for Subsequent Monitoring	. 24
Table 16—LCRS Sump Monitoring, Five-Year COCs	. 25
Table 17—Leachate Seep Monitoring, Physical Parameters	. 26
Table 18—Leachate Seep Monitoring, Constituent Parameters	. 26
Table 19—Criteria for Regular Visual Inspections	. 27
Table 20—Regular Visual Inspection Schedule	. 28
Table 21—Summary of Required Reports	. 29

PLUMAS COUNTY GOPHER HILL LANDFILL PLUMAS COUNTY

GLOSSARY

AMR	Annual Monitoring Report
CalRecycle	California Department of Resources Recycling and Recovery
CAMP	Corrective Action Monitoring Program
C.F.R	Code of Federal Regulations
CIWQS	California Integrated Water Quality System Project
COCs	Constituents of Concern
DMP	Detection Monitoring Program
DWR	California Department of Water Resources
EC	Electrical Conductivity
ELAP	State Water Board's Environmental Laboratory Accreditation Program (formerly administered by California Department of Public Health)
EMP	Evaluation Monitoring Program
EW	Extraction Well
Five-Year COCs	Five-Year Constituents of Concern
GeoTracker	State Water Board's Data Management System for Sites with Potential Groundwater Impact
GP	Gas Probe
LCRS	Leachate Collection and Removal System
LF	Landfill
LFG	Landfill Gas
MDL	Method Detection Limit

PLUMAS COUNTY GOPHER HILL LANDFILL

PLUMAS COUNTY

GLOSSARY

Method TO-15 VOCs	Volatile Organic Compounds associated with USEPA Method TO-15
MRP	Monitoring and Reporting Program
MSW	Municipal Solid Waste
MSWLF	Municipal Solid Waste Landfill
N/A	Not Applicable
PID	Photo Ionization Detector
POC	Point of Compliance for Water Quality Protection Standard
QA/QC	Quality Assurance/Quality Control
Qualified Professional	Professional Civil Engineer or Geologist licensed by the State of California
RCRA	Resource Conservation and Recovery Act, 42 U.S.C. § 6901 et seq.
RL	Reporting Limit
ROWD / JTD	Report of Waste Discharge / Joint Technical Document
SCAP	Sample Collection and Analysis Plan
SGP	Soil Pore Gas
SI	Surface Impoundment
SMR	Semiannual Monitoring Report
SPRRs / Standard Provisions	Standard Provisions and Reporting Requirements for Nonhazardous Solid Waste Discharges Regulated by Subtitle D and/or Title 27 Municipal Solid Waste Facilities, December 2015 Edition

PLUMAS COUNTY GOPHER HILL LANDFILL

PLUMAS COUNTY

GLOSSARY

TDS	Total Dissolved Solids
Title 27	California Code of Regulations, Title 27
USEPA	United States Environmental Protection Agency
VOCs	Volatile Organic Compounds
WDRs	Waste Discharge Requirements
WMU	Waste Management Unit
WQPS	Water Quality Protection Standard
UNITS	
ft3 / min	Cubic Feet per Minute
°F	Degrees Fahrenheit
Gallons/Day	Gallons per Day
mg/L	Milligrams per Liter
μg/L	Micrograms per Liter
μmhos/cm	Microsiemens per Centimeter
μg/cm3	Micrograms per Cubic Centimeter
NTUs	Nephelometric Turbidity Units
% Vol	Percent by Volume
Inches Hg	Inches of Mercury (Barometric Pressure)
MM Hg Vacuum	Millimeters of Mercury (Barometric Pressure)

PLUMAS COUNTY

PREFACE

Adopted by the California Regional Water Quality Control Board, Central Valley Region (Central Valley Water Board) pursuant to Water Code section 13267, subdivision (b)(1), this Order establishes a Monitoring and Reporting Program (MRP) for Plumas County (Discharger), which owns and maintains the Gopher Hill Class III Municipal Solid Waste Landfill and Class II Surface Impoundments (Facility) in Plumas County. Additional information regarding the Facility is set forth in the enumerated findings of Waste Discharge Requirements Order R5-2022-0044 (WDRs Order). Except as otherwise provided in the following MRP, these findings are incorporated herein.

The MRP also contains supplemental findings related to monitoring and reporting activities, and/or Facility conditions. For the purposes of California Code of Regulations, title 27 (Title 27) (e.g., §§ 21720, 20380-20435), the findings and provisions of this Order are conversely incorporated as part of the WDRs Order as well.

Although adopted with the WDRs Order, this is a separate order subject to subsequent revision by the Executive Officer in accordance with delegated authority per Water Code section 13223. For the purposes of Title 27, such revisions shall be automatically incorporated as part of the WDRs Order.

MONITORING & REPORTING PROGRAM

IT IS HEREBY ORDERED, pursuant to Water Code section 13267: that all previously issued Monitoring and Reporting Program(s) for the discharge of solid waste at the Facility are rescinded (except for enforcement purposes); and that the Discharger, their agents, employees and successors shall comply with the following Monitoring and Reporting Program (MRP). The Discharger shall not implement any changes until a revised MRP is issued by the Central Valley Water Board or its Executive Officer.

A. General Provisions

PLUMAS COUNTY

1. Incorporation of Standard Provisions

The Discharger shall comply with all relevant provisions of the *Standard Provisions and Reporting Requirements for Nonhazardous Solid Waste Discharges Regulated by Subtitle D and/or Title 27 Municipal Solid Waste Facilities, December 2015 Edition* (SPRRs or Standard Provisions), which are incorporated herein. See, e.g., SPRRs section I (*Standard Monitoring Specifications*) and section J (*Response to Release*).

2. Monitoring Provisions in WDRs Order

The Discharger shall comply with all "Monitoring Provisions" in the Facility's operative Title 27 WDRs Order, which are also incorporated herein.

3. Compliance with Title 27

The Discharger shall comply with all of Title 27 provisions as they pertain to activities described in this MRP (including SPRRs).

4. Sample Collection and Analysis Plan (SCAP)

All samples shall be collected, preserved and transported in accordance with the approved Sample Collection and Analysis Plan (SCAP) and the Quality Assurance/Quality Control (QA/QC) standards specified therein. The Discharger may use alternative analytical test methods (including new USEPA-approved methods), provided that the alternative methods have method detection limits (MDLs) equal to or lower than the analytical methods specified in this MRP and are identified in the approved SCAP.

B. Detection Monitoring Program (DMP)

To detect a release at the earliest possible time (see Title 27, § 20420, subd. (b)), the Discharger shall implement a Detection Monitoring Program (DMP) for groundwater, surface water and the unsaturated zone in accordance with the provisions of Title 27, particularly sections 20415 and 20420.

Groundwater, unsaturated zone and surface water detection monitoring networks shall be revised (as needed) with the construction of each new landfill cell or module.

1. Groundwater

a. Required Network

The Facility's groundwater monitoring well network consists of the wells listed in **Table 1**. As of the date of this Order, the network meets the requirements of Title 27. (Title 27, § 20415, subd. (b).)

Table 1—Groundwater Monitoring Network

Well	Program	Monitored Unit	Zone	Status
GHL-3	Background	WMU-1	Shallow	Operational
GHL-5A	Detection	WMU-1	Shallow	Operational
GHL-6	Detection	WMU-1	Shallow	Operational
GHL-7	Detection	WMU-1	Shallow	Operational
GHL-8	Detection	WMU-1	Shallow	Operational
GHL-9	Detection	WMU-2	Shallow	Operational
GHL-10	Detection	WMU-1	Shallow	Operational
GHL-11	Detection	WMU-1	Shallow	Operational

¹ I.e., to the extent that surface water detection monitoring is required under this Order.

Well	Program	Monitored Unit	Zone	Status
GHL-12	Background	WMU-1	Shallow	Operational

PLUMAS COUNTY

b. Sample Collection and Analysis

Groundwater samples shall be collected from each well and analyzed for Monitoring Parameters listed in **Table 2** (Physical Parameters) and **Table 3** (Constituent Parameters), in accordance with the specified schedule for each parameter. (Title 27, § 20420, subds. (e)-(f).)

Table 2—Groundwater Detection Monitoring, Physical Parameters

Physical Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
Temperature	TEMP	°F	Semiannual	Semiannual
Electrical Conductivity	SC	µmhos/cm	Semiannual	Semiannual
рН	PH	pH Units	Semiannual	Semiannual
Turbidity	TURB	NTUs	Semiannual	Semiannual

See Glossary for definitions of terms and abbreviations in table.

^{*}Monitoring well monitored for groundwater depth only.

Table 3—Groundwater Detection Monitoring, Constituent Parameters

Constituent Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
TDS	TDS	mg/L	Semiannual	Semiannual
Chloride	CL	mg/L	Semiannual	Semiannual
Carbonate	CACO3	mg/L	Annual	Annual
Bicarbonate	BICACO3	mg/L	Annual	Annual
Sulfate	SO4	mg/L	Semiannual	Semiannual
Calcium	CA	mg/L	Annual	Annual
Magnesium	MG	mg/L	Annual	Annual
Potassium	K	mg/L	Annual	Annual
Sodium	NA	mg/L	Annual	Annual
Short List VOCs (Attachment A)	(various)	μg/L	Semiannual	Semiannual
1,2,3-Trichloropropane per Method SRL-524M-TCP	TCPR123	μg/L	Semiannual for two initial sampling events. If undetected, switch to five-year sampling.	Semiannual for two initial sampling events. If undetected, switch to five-year sampling.

c. Five-Year COCs

The Discharger shall analyze for groundwater samples from each well for the Five-Year Constituents of Concern (Five-Year COCs) listed in **Table 4**. Five-Year COCs were last monitored in 2020, and shall be analyzed again in 2025. (Title 27, § 20420, subd. (g).)

PLUMAS COUNTY

Table 4—Groundwater Detection Monitoring, Five-Year COCs

Five-Year Constituent	GeoTracker Code	Units	Sampling & Reporting Freq.
Total Organic Carbon	TOC	mg/L	Every 5 Years
Dissolved Inorganics (Attachment B)	(various)	μg/L	Every 5 Years
Extended List VOCs (Attachment C)	(various)	μg/L	Every 5 Years
Semi-Volatile Organic Compounds (Attachment D)	(various)	μg/L	Every 5 Years
Chlorophenoxy Herbicides (Attachment E)	(various)	μg/L	Every 5 Years
Organophosphorus Compounds (Attachment F)	(various)	μg/L	Every 5 Years

See Glossary for definitions of terms and abbreviations in table.

d. Groundwater Conditions

The Discharger shall monitor the Groundwater Conditions specified in **Table 5**, with the result of such monitoring being reported semiannually per **Section D.1**.² (Title 27, § 20415, subd. (b)(1).)

² To the extent feasible, this information shall be determined separately for: (1) the uppermost aquifer; (2) any zones of perched water; and (3) any additional zone of saturation monitored based upon water level elevations taken prior to the collection of

the water quality data submitted in the report. (Title 27, § 20415, subd. (e)(15).)

Table 5—Groundwater Detection Monitoring, Groundwater Conditions

Groundwater Condition	GeoTracker Code	Monitoring Freq.	Reporting Freq.
Elevation (Well-Specific)	ELEV	Semiannually	Semiannually
Gradient	(none)	Semiannually	Semiannually
Flow Rate	(none)	Semiannually	Semiannually

2. Unsaturated Zone

a. Required Network

The Facility's unsaturated zone monitoring network consists of the lysimeter monitoring point specified in **Table 6**. As of the date of this Order, the network meets the requirements of Title 27. (Title 27, § 20415, subd. (d).)

Table 6—Unsaturated Zone Monitoring Network

Monitoring Point	Program	Monitored Unit	Status
L-1	Detection	WMU-2	Active

See Glossary for definitions of terms and abbreviations in table.

b. Soil Pore Gas (SPG) Monitoring

Soil Pore Gas (SPG) has not been monitored at the site since closure was completed in 2005. The Facility has a passive gas venting system, consisting of two-500 foot lengths of polyvinyl chloride (PVC) pipe that cross at the top of the landfill with vent riser pipes, which was installed through the cap. The Facility's landfill WMU-1 was fully permitted and operating as of 1 July 1991. There are no dedicated unsaturated zone monitoring points at the Facility. Additionally, installation of unsaturated zone monitoring devices would require unreasonable dismantling or relocating of permanent structures at the Facility.

Table 7—Unsaturated Zone Detection Monitoring Network

Monitoring Point	Program	Monitored Unit	Status
Passive Gas Vents	Detection	WMU-1	Not currently sampled

c. Lysimeter Inspection

The pan lysimeter shall be inspected semiannually for the presence of liquid, which shall then be analyzed for the Monitoring Parameters in **Table 8** (Physical Parameters) and **Table 9** (Constituent Parameters). (Title 27, § 20420, subds. (e)-(f).) If liquid is detected in a previously dry pan lysimeter, the Discharger shall notify Central Valley Water Board staff within seven days of the detection. The pan lysimeter, L-1, has been dry since installation.

Table 8—Unsaturated Zone Detection Monitoring (Lysimeter),
Physical Parameters

Physical Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
Electrical Conductivity	SC	µmhos/cm	Semiannual	Semiannual
рН	PH	pH Units	Semiannual	Semiannual
Volume of Removed Liquid	(none)	Gallons	Semiannual	Semiannual

See Glossary for definitions of terms and abbreviations in table.

Table 9—Unsaturated Zone Detection Monitoring (Lysimeter),
Constituent Parameters

Constituent Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
TDS	TDS	mg/L	Semiannual	Semiannual
Chloride	CL	mg/L	Semiannual	Semiannual
Carbonate	CACO3	mg/L	Annual	Annual
Bicarbonate	BICACO3	mg/L	Annual	Annual
Sulfate	SO4	mg/L	Semiannual	Semiannual
Calcium	CA	mg/L	Annual	Annual
Magnesium	MG	mg/L	Annual	Annual
Potassium	K	mg/L	Annual	Annual
Sodium	NA	mg/L	Annual	Annual
Short List VOCs (Attachment A	(various)	μg/L	Semiannual	Semiannual
1,2,3-Trichloropropane per Method SRL-524M-TCP	TCPR123	μg/L	Semiannual for two initial sampling events. If undetected, switch to five- year sampling.	Semiannual for two initial sampling events. If undetected, switch to five-year sampling.

d. Five-Year COCs

Every five years, liquid from each pan lysimeter shall be analyzed for the Five-Year COCs listed below in **Table 10**. Five-Year COCs were last monitored in 2020, and shall be analyzed again in 2025. (Title 27, § 20420, subd. (g).)

Table 10—Unsaturated Zone Detection Monitoring (Lysimeter), Five-Year COCs

Five-Year Constituent	GeoTracker Code	Units	Sampling & Reporting Freq.
Total Organic Carbon	TOC	mg/L	Every 5 Years
Dissolved Inorganics (Attachment B)	(various)	μg/L	Every 5 Years
Extended List VOCs (Attachment C)	(various)	μg/L	Every 5 Years
Semi-Volatile Organic Compounds (Attachment D)	(various)	μg/L	Every 5 Years
Chlorophenoxy Herbicides (Attachment E)	(various)	μg/L	Every 5 Years
Organophosphorus Compounds (Attachment F)	(various)	μg/L	Every 5 Years

3. Surface Water

Runoff from the Facility is collected in a series of sedimentation basins, which periodically flow to Spanish Creek, which may be affected by a release. (See Title 27, § 20415, subd. (c)(1).) Two monitoring points exist at the Facility, monitoring point SP-1 is an intermittent spring located along the western toe of WMU-1, while TR-1 is an interceptor trench upgradient of the site intended to capture site run-on and direct it to WMU-2.

Additionally, the Facility is subject to NPDES Permit No. CAG995002. Surface water monitoring under the NPDES permit occurs at two points on Spanish Creek, RSW-1 and RSW-2.

a. Required Network

The Facility's surface water monitoring network consists of the monitoring points listed in **Table 11**. As of the date of this Order,

the network meets the requirements of Title 27. (See § 20415, subd. (c).)

Table 11—Surface Water Detection Monitoring Network

Monitoring Point	Program or Function	Monitored Unit	Location / Notes
SP-1	Detection	WMU-1	Western Toe of WMU-1
TR-1	Background	NA	Upgradient of WMU-1

See Glossary for definitions of terms and abbreviations in table.

b. Sample Collection and Analysis

When surface water is present at monitoring points in **Table 11** at any point during the monitoring period, samples shall be collected from each monitoring point and analyzed for the Monitoring Parameters in **Table 12** (Physical Parameters) and **Table 13** (Constituent Parameters), in accordance with the specified schedule. (Title 27, § 20420, subds. (e)-(f).)

Table 12—Surface Water Detection Monitoring, Physical Parameters

Physical Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
Electrical Conductivity	SC	µmhos/cm	Semiannual	Semiannual
pH	PH	Std. Units	Semiannual	Semiannual
Turbidity	TURB	NTUs	Semiannual	Semiannual
Hardness	HARD	mg / L	Semiannual	Semiannual

See Glossary for definitions of terms and abbreviations in table.

Table 13—Surface Water Detection Monitoring, Constituent Parameters

Constituent Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
TSS	TSS	mg/L	Semiannual	Semiannual
Chloride	CL	mg/L	Annual	Annual
Carbonate	CACO3	mg/L	Annual	Annual
Bicarbonate	BICACO3	mg/L	Semiannual	Semiannual
Nitrate as Nitrogen	NO3N	mg/L	Annual	Annual
Sulfate	SO4	mg/L	Annual	Annual
Calcium	CA	mg/L	Annual	Annual
Magnesium	MG	mg/L	Annual	Annual
Potassium	K	mg/L	Semiannual	Semiannual
Sodium	NA	mg/L	Annual	Annual
Short List VOCs (Attachment A)	(various)	μg/L	Semiannual	Semiannual
1,2,3-Trichloropropane per Method SRL-524M-TCP	TCPR123	μg/L	Semiannual for two initial sampling events. If undetected, switch to five-year sampling.	Semiannual for two initial sampling events. If undetected, switch to five-year sampling.

c. Five-Year COCs

The Discharger shall analyze surface water samples for the Five-Year COCs listed in **Table 14** Five-Year COCs were last monitored in 2020, and shall be analyzed again in 2025. (Title 27, § 20420, subd. (g).)

Table 14—Surface Water Detection Monitoring, Five-Year COCs

Five-Year Constituent	GeoTracker Code	Units	Sampling & Reporting Freq.
Total Organic Carbon	TOC	mg/L	Every 5 Years
Dissolved Inorganics (Attachment B)	(various)	μg/L	Every 5 Years
Extended List VOCs (Attachment C)	(various)	μg/L	Every 5 Years
Semi-Volatile Organic Compounds (Attachment D)	(various)	μg/L	Every 5 Years
Chlorophenoxy Herbicides (Attachment E)	(various)	μg/L	Every 5 Years
Organophosphorus Compounds (Attachment F)	(various)	μg/L	Every 5 Years

See Glossary for definitions of terms and abbreviations in table.

4. Summary of Water Quality Protection Standard (WQPS) Components

The Water Quality Protection Standard (WQPS) is the Title 27 analytical framework through which an individual WMU is monitored for releases and impacts to water quality, i.e., the Detection Monitoring Program (DMP). (See Title 27, § 20390, subd. (a).) As explained in further detail below, for the duration of the Compliance Period, the Monitoring Points situated at a WMU's Point of Compliance are sampled and analyzed for Monitoring Parameters indicative of a release. If concentrations of Constituents of Concern exceed Concentration Limits, the results are confirmed through Retesting Procedures.

a. Compliance Period

The "compliance period" is the minimum time for which a water quality monitoring will be required—i.e., equal to the sum of active years and the closure period. (Title 27, § 20410.) The period restarts each time an Evaluation Monitoring Program (EMP) is initiated for a given WMU. (Id., §§ 20410(a), 20415, 20425.) If a WMU is in corrective action, the period continues until it is demonstrated that the WMU has been in continuous compliance with its WQPS for at least three years. (Id., § 20410, subd. (c).)

b. Monitoring Points

For WQPS purposes, a "monitoring point" is any well, device, or location where monitoring is conducted, and is specified in the Facility's WDRs and subject to the WQPS. (Title 27, § 20164.) Monitoring Points are listed in **Section B** (Detection Monitoring Program)—specifically **Table 1** (Groundwater), **Table 6** (Unsaturated Zone) and **Table 11** (Surface Water).

c. Point of Compliance (POC)

The Point of Compliance (POC) is a vertical plane at the WMU's hydraulically downgradient limit, extending through the uppermost underlying aquifer. (Title 27, §§ 10164, 20405(a).) The Facility's POC monitoring wells are all downgradient monitoring wells.

d. Constituents of Concern (COCs)

Constituents of Concern (COCs) are waste constituents, reaction products, and hazardous constituents that are reasonably expected to be in or derived from waste contained in a WMU. (Title 27, §§ 20164, 20395.)

e. Monitoring Parameters

Monitoring Parameters are a predetermined set of COCs and measurable physical characteristics (e.g., temp., electrical conductivity, pH), which serve as reliable indicators of a WMU release, and for which samples will therefore be routinely analyzed. (Title 27, §§ 20164, 20395(a), 20420(e)-(f).) For the purposes of this MRP, the Monitoring Parameters are:

- i. For Surface Water, those in Table 12 and Table 13;
- ii. For **Groundwater**, those in **Table 2** and **Table 3**; and
- iii. For the Unsaturated Zone, those in **Table 8** and **Table 9**.

f. Five-Year COCs

PLUMAS COUNTY

In addition to the Monitoring Parameters described above, this Order requires the quinquennial analysis of samples for a larger range of constituents that are reasonably expected to be found in, or derived from, the waste contained within each unit at the Facility. (Title 27, §§ 20395, 20420(g).) Analytical results for Five-Year COCs were last submitted to the Central Valley Water Board as part of the 2020 Annual Monitoring Report and are due again in 2025. For the purposes of this MRP, the Five-Year COCs are listed in:

- i. Attachment B (Dissolved Inorganics);
- ii. Attachment C (Extended List VOCs);
- iii. Attachment D (Semi-Volatile Organic Compounds);
- iv. Attachment E (Chlorophenoxy Herbicides);
- v. Attachment F (Organophosphorus Compounds); and
- vi. Any other COCs listed in **Table 14** (*Surface Water*), **Table 4** (*Groundwater*) and **Table 10** (*Unsaturated Zone*)

g. Concentration Limits

The Concentration Limit for each COC is the "background concentration," as determined by the statistical methods outlined in subdivision (e)(8) of Title 27, section 20415. (Title 27, § 20400,

³ Concentration Limits are initially proposed by the discharger, then reviewed and approved by the Central Valley Water Board (subject to any necessary revisions). The limits specified herein are approved and incorporated as part of the Facility's WDRs.

subds. (a), (b).) Methods for calculating Concentration Limits were proposed in the April 2014 WQPS Report. The approved methods use a non-parametric prediction limit evaluation comparing the background monitoring wells GHL-3 and GHL-12 with downgradient compliance monitoring wells GHL-5A, GHL-6, GHL-7, GHL-8, and GHL-9. to generate interwell concentration limits at 95 percent confidence and 95 percent coverage.

Concentration Limits shall be proposed and/or updated by the Discharger on an annual basis, in the Annual Monitoring Report (AMR) submitted per **Section D.2** here.

If the Discharger fails to submit periodically updated concentration limits, as provided in this MRP, the existing concentration limits shall remain operative, provided that, where appropriate, the Executive Officer may revert to lower concentrations where warranted based on existing monitoring data.

h. Retesting Procedures

If monitoring results indicate measurably significant evidence of a release, as described in Section I.45 of the SPRRs (Standard Monitoring Specifications), the Discharger shall apply the following:

- vii. **Non-Statistical Retesting Procedures (SPRRs, § I.46)** for analytes detected in less than 10 percent of background samples (e.g., non-naturally occurring COCs); and
- viii. Statistical Retesting Procedures (SPRRs, § I.46) for analytes detected in at least 10 percent of background samples (e.g., naturally occurring COCs).

C. Additional Facility Monitoring

1. Leachate Impoundment (WMU-2)

The Discharger shall operate and maintain leachate impoundment WMU-2, and conduct monitoring of any detected leachate seeps in accordance with Title 27 and the following provisions.

a. Leachate Sampling

When leachate is discharging from the leachate discharge pipe into the surface impoundment, the leachate shall be sampled and analyzed for the same parameters, and in accordance with the specified sampling and reporting schedule in **Table 15**.

Table 15—LCRS Sump Monitoring, Parameters for Subsequent Monitoring

Constituent Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
Electrical Conductivity	SC	µmhos/cm	Semiannual	Semiannual
pH	PH	pH Units	Semiannual	Semiannual
TDS	TDS	mg/L	Semiannual	Semiannual
Chloride	CL	mg/L	Semiannual	Semiannual
Carbonate	CACO3	mg/L	Semiannual	Semiannual
Bicarbonate	BICACO3	mg/L	Semiannual	Semiannual
Nitrate (as Nitrogen)	NO3N	mg/L	Semiannual	Semiannual
Sulfate	SO4	mg/L	Semiannual	Semiannual
Calcium	CA	mg/L	Semiannual	Semiannual
Magnesium	MG	mg/L	Semiannual	Semiannual
Potassium	K	mg/L	Semiannual	Semiannual
Sodium	NA	mg/L	Semiannual	Semiannual
Short List VOCs (Attachment A)	(various)	μg/L	Semiannual	Semiannual

Constituent Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
1,2,3-Trichloropropane per Method SRL-524M- TCP	TCPR123	μg/L	Semiannual for two initial sampling events. If undetected, switch to five- year sampling.	Semiannual for two initial sampling events. If undetected, switch to five-year sampling.

b. Five-Year COCs

At least once every five years, the Discharger shall sample and analyze any leachate present in the sump for the Five-Year COCs listed in **Table 16**. Five-Year COCs were last monitored in 2020, and shall be analyzed again in 2025.

Table 16—LCRS Sump Monitoring, Five-Year COCs

Parameter	GeoTracker Code	Units	Sampling & Reporting Freq.
Total Organic Carbon	TOC	mg/L	Every 5 Years
Dissolved Inorganics (Attachment B)	(various)	μg/L	Every 5 Years
Extended List VOCs (Attachment C)	(various)	μg/L	Every 5 Years
Semi-Volatile Organic Compounds (Attachment D)	(various)	μg/L	Every 5 Years
Chlorophenoxy Herbicides (Attachment E)	(various)	μg/L	Every 5 Years
Organophosphorus Compounds (Attachment F)	(various)	μg/L	Every 5 Years

See Glossary for definitions of terms and abbreviations in table.

2. Leachate Seepage

Leachate that seeps to the surface from WMU-1 shall, immediately upon detection, be sampled and analyzed for the Monitoring Parameters in **Table 17** (Physical Parameters) and **Table 18** (Constituent Parameters). See **Section D.3** for Reporting Requirements.) In the event of a reported leachate seep, Central Valley Water Board staff may direct additional sampling and analysis pursuant to Water Code section 13267, subdivision (b)(1).

Table 17—Leachate Seep Monitoring, Physical Parameters

Physical Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
Total Flow	(none)	Gallons	Upon Detection	See MRP, § D.3
Flow Rate	FLOW	Gallons/Day	(same)	(same)
Electrical Conductivity	SC	µmhos/cm	(same)	(same)
pН	PH	pH Units	(same)	(same)

See Glossary for definitions of terms and abbreviations in table.

Table 18—Leachate Seep Monitoring, Constituent Parameters

Constituent Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
TDS	TDS	mg/L	Upon Detection	See MRP, § D.3
Chloride	CL	mg/L	(same)	(same)
Carbonate	CACO3	mg/L	(same)	(same)
Bicarbonate	BICACO3	mg/L	(same)	(same)
Nitrate as N	NO3N	mg/L	(same)	(same)
Sulfate	SO4	mg/L	(same)	(same)

Constituent Parameter	GeoTracker Code	Units	Sampling Freq.	Reporting Freq.
Calcium	CA	mg/L	(same)	(same)
Magnesium	MG	mg/L	(same)	(same)
Potassium	K	mg/L	(same)	(same)
Sodium	NA	mg/L	(same)	(same)
Short List VOCs (Attachment A)	(various)	μg/L	(same)	(same)
1,2,3-Trichloropropane per Method SRL-524M-TCP	TCPR123	μg/L	(same)	(same)

3. Regular Visual Inspection

The Discharger shall perform regular visual inspections at the Facility in accordance with **Table 19** (Criteria) and **Table 20** (Schedule). Results of these regular visual inspections shall be included in Semiannual Monitoring Reports per **Section D.1**.

Table 19—Criteria for Regular Visual Inspections

Category	Criteria
Within Unit	 Evidence of ponded water at any point on unit outside of any contact storm water/leachate diversions structures on the active face of unit (record affected areas on map). Evidence of erosion and/or of day-lighted refuse.
Unit Perimeter	 Evidence of leachate seep. Estimated size of affected area (record on map) and flow rate. Evidence of erosion and/or of day-lighted refuse.

Category	Criteria
Receiving Waters	 Floating and suspended materials of waste origin—presence or absence, source and size of affected areas. Discoloration and turbidity—description of color, source and size of affected areas.

Table 20—Regular Visual Inspection Schedule

Category	Wet Season (1 Oct. to 30 April)	Dry Season (1 May to 30 Sept.)
Active Unit WMU-2	Monthly, unless snow accumulation limits Facility access and/or visual assessment of the Facility conditions	Quarterly
Closed Unit WMU-1	Monthly, unless snow accumulation limits Facility access and/or visual assessment of the Facility conditions	Quarterly

4. Annual Facility Inspections

Prior to 30 September of each year, the Discharger shall inspect the Facility to assess repair and maintenance needs for drainage control systems, cover systems and groundwater monitoring wells; and preparedness for winter conditions (e.g., erosion and sedimentation control). If repairs are made as result of the annual inspection, problem areas shall be photographed before and after repairs. Any necessary construction, maintenance, or repairs shall be completed by 31 October. See **Section D.4** for Reporting Requirements.

5. Major Storm Events

Within seven days of any storm event capable of causing damage or significant erosion (Major Storm Event), the Discharger shall inspect the Facility for damage to any precipitation, diversion and drainage facilities, and all landfill side slopes. Necessary repairs shall be completed within 30

days of the inspection. The Discharger shall take photos of any problem areas before and after repairs. See **Section D.5** for Reporting Requirements.

6. Five-Year Iso-Settlement Surveys (Closed Landfills)

The Discharger shall conduct an iso-settlement survey of the WMU-1 landfill unit and produce an iso-settlement map accurately depicting the estimated total change in elevation of each portion of the final cover's low-hydraulic-conductivity layer. This shall be performed if visual inspection yields signs of settling such as ponding or development of fissures along the final cover. For each portion of WMU-1, this map shall show the total lowering of the surface elevation of the final cover, relative to the baseline topographic map. (Title 27, § 21090, subd. (e)(1)-(2).) See **Section E.6** for Reporting Requirements.

D. Reporting Requirements

Table 21—Summary of Required Reports

Section	Report	Deadline
§ 0	Semiannual Monitoring Reports (SMRs)	1 August (1 January to 30 June)
		1 February (1 July to 31 December)
§ 0	Annual Monitoring Reports (AMRs)	1 February
§ D.3	Leachate Seep Reporting	Immediately upon Discovery of Seepage (staff notification)
		Within 7 Days (written report)
§ 0	Annual Facility Inspection Reports	15 November

Section	Report	Deadline
§ 0	Major Storm Reporting	Immediately after Damage Discovery (staff notification)
		Within 14 Days of Completing Repairs (written report, photos)
§ 0	Survey and Iso-Settlement Mapping	As needed and indicated by visual inspection
§ 0	Financial Assurances Reports	1 June
§ 0	Water Quality Protection Standard Reports	Proposed Revisions (excluding Concentration Limits)

1. Semiannual Monitoring Reports (SMRs)

The Discharger shall submit Semiannual Monitoring Reports (SMRs) on 1 August (1 Jan. to 30 June) and 1 February (1 July to 31 Dec.). SMRs shall contain the following materials and information:

- A statement affirming that all sampling activities referenced in the report were conducted in accordance with the approved SCAP (see § A.4).
- b. Map(s)/aerial photograph(s) depicting locations of all observation stations, monitoring points referenced in the report.
- c. In tabulated format, all monitoring data required to be reported on a semiannual basis, including Groundwater Conditions and Monitoring Parameters. (See **Section D.9.b** for additional requirements.)
- d. For each groundwater monitoring point referenced in the SMR:
 - i. The times each water level measurement was taken;
 - ii. The type of pump or other device used to purge and elevate pump intake level relative to screening interval;

PLUMAS COUNTY

- iii. The purging methods used to stabilize water in the well bore before sampling (including pumping rate);
- iv. The equipment and methods used for monitoring pH, temperature and electrical conductivity (EC) during purging activity, and the results of such monitoring;
- v. Methods for disposing of purged water; and
- vi. The type of device used for sampling, if different than the one used for purging.
- e. Evaluation of concentrations for all Constituent Parameters and Five-Year COCs (when analyzed), comparison to current Concentration Limits, and results of any Retesting Procedures per **Section B.4.h**.
- f. In the event of a verified exceedance of Concentration Limit(s), any actions taken per Section J of the SPRRs (*Response to Release*) for wells and/or constituents not already specifically addressed in Corrective Action Monitoring under this MRP.
- g. Evaluation as to effectiveness of existing leachate monitoring and control facilities, and runoff/run-on control facilities.
- h. Summaries of all Regular Visual Inspections conducted per **Section D3** during the reporting period.
- For closed landfill unit WMU-1, summaries of inspections, leak searches and final cover repairs conducted in accordance with an approved Post-Closure Maintenance Plan per Standard Provisions G.26-29 (Standard Closure and Post-Closure Maintenance Specifications).
- Laboratory statements of results of all analyses evaluating compliance with the WDRs.

2. Annual Monitoring Reports (AMRs)

On 1 February of each year,⁴ the Discharger shall submit an Annual Monitoring Report (AMR) containing following materials and information:

- a. In tabulated format, all monitoring data for which annual reporting is required under this MRP. (See **Section D.9.b** for additional requirements for monitoring reports.)
- b. Graphs of historical trends for all Monitoring Parameters and Five-Year COCs (if such analyses were performed) with respect to each monitoring point over the five prior calendar years.⁵
- An evaluation of Monitoring Parameters with regard to the cation/anion balance, and graphical presentation of same in a Stiff diagram, Piper graph or Schoeller plot.
- d. All historical monitoring data for which there are detectable results, including data for the previous year, shall be submitted in tabular form in a digital file.
- e. For each groundwater well, hydrographs showing the elevation of groundwater with respect to the top and bottom of the screened interval, and the elevation of the pump intake,
- f. A comprehensive discussion of the Facility's compliance record, and the result of any corrective actions taken or planned which may be needed to attain full compliance with the WDRs.
- g. For WMU-1, a map showing the areas and elevations of each unit where filling was completed during the previous calendar year;

⁴ The Annual Monitoring Report may be combined with the Semiannual Monitoring Report for 1 July through 31 December of the same year, provided that the combination is clearly indicated in the title.

⁵ Each graph shall contain individual data points (not mean values) and be appropriately scaled to accurately depict statistically significant trends or variations in water quality.

comparison to final closure design contours; and projected years in which each discrete module are expected to be filled.

- h. A summary of the monitoring results, indicating any changes made or observed since the previous AMR.
- Annual updates to the Concentration Limits for all Monitoring Parameters and WQPS Monitoring Points, in accordance with Section B.4.g of this Order.

3. Leachate Seep Reporting

PLUMAS COUNTY

Upon discovery of seepage from any disposal area within the Facility, the Discharger shall immediately notify the Central Valley Water Board via telephone or email; and within seven days, submit a written report with the following information:

- a. Map(s) depicting the location(s) of seepage;
- b. Estimated flow rate(s);
- c. A description of the nature of the discharge (e.g., all pertinent observations and analyses);
- Verification that samples have been submitted for analyses of the Monitoring Parameters in Table 17 (*Physical Parameters*) and Table 18 (*Constituent Parameters*), and an estimated date that the results will be submitted to the Central Valley Water Board; and
- e. Corrective measures underway or proposed, and corresponding time schedule.

4. Annual Facility Inspection Report

By 15 November, the Discharger shall submit a report with results of the Annual Facility Inspection per **Section C.4**. The report shall discuss any repair measures implemented, any preparations for winter, and include photographs of any problem areas and repairs.

5. Major Storm Event Reports

Immediately following each post-storm inspection described in **Section C.5**, the Discharger shall notify Central Valley Water Board staff of any damage or significant erosion (upon discovery). Subsequent repairs shall be

reported to the Central Valley Water Board (together with before and after photos of the repaired areas) within 14 days of completion.

6. Survey and Iso-Settlement Map (Closed Landfill Units)

The Discharger shall submit all iso settlement maps prepared in accordance with **Section D.6**. (Title 27, § 21090, subd. (e).)

7. Financial Assurances Report

PLUMAS COUNTY

By 1 June of each year, the Discharger shall submit a copy of the annual financial assurances report due to the California Department of Resources Recycling and Recovery (CalRecycle) that updates the financial assurances for post-closure maintenance, and corrective action. (See WDRs Order.)

8. Water Quality Protection Standard Report

Any proposed changes⁶ to the Water Quality Protection Standard (WQPS) components (§ B.4), other than periodic update of the Concentration Limits (§ B.4.g), shall be submitted in a WQPS Report for review and approval. The report shall be certified by a "Qualified Professional" (§ B), and contain the following:

a. Potentially Affected Waterbodies—An identification of all distinct bodies of surface water and groundwater potentially affected by a WMU release (including, but not limited to, the uppermost aquifer and any permanent or ephemeral zones of perched groundwater underlying the Facility);

⁶ If subsequent sampling of the background monitoring point(s) indicates significant water quality changes due to either seasonal fluctuations or other reasons unrelated to onsite waste management activities, the [DISCHARGERS] may request modification of the WQPS.

- b. *Map of Monitoring Points*—A map of all groundwater, surface water⁷ and unsaturated zone monitoring points (including all background/upgradient and Point of Compliance monitoring points);
- c. *Groundwater Movement*—An evaluation of perennial direction(s) of groundwater movement within the uppermost zone(s);
- d. Statistical Method for Concentration Limits—A proposed statistical method for calculating Concentration Limits for Monitoring Parameters and Five-Year COCs (see § 0) detected in at least 10 percent of the background data (naturally-occurring constituents) using a statistical procedure from subdivisions (e)(8)(A)-(D) or (e)(8)(E) of Title 27, section 20415; and
- e. Retesting Procedure—A retesting procedure to confirm or deny measurably significant evidence of a release (Title 27, §§ 20415(e)(8)(E), 20420(j)(1)-(3)).

9. General Reporting Provisions

a. Transmittal Letters

Each report submitted under this MRP shall be accompanied by a Transmittal Letter providing a brief overview of the enclosed report, as well as the following:

- Any violations found since the last report was submitted, a
 description of all actions undertaken to correct the violation
 (referencing any previously submitted time schedules for
 compliance), and whether the violations were corrected; and
- ii. A statement from the submitting party, or its authorized agent, signed under penalty of perjury, certifying that, to the best of the signer's knowledge, the contents of the enclosed report are true, accurate and complete.

⁷ To the extent that surface water monitoring is included in the Detection Monitoring Program.

b. Monitoring Data and Reports

i. Electronic Submission via GeoTracker

All reports with monitoring data (e.g., SMRs and AMRs) shall be submitted electronically via the State Water Board's Geotracker Database

(https://geotracker.waterboards.ca.gov). After uploading a report, the Discharger shall notify Central Valley Water Board staff via email at

CentralValleyRedding@WaterBoards.ca.gov. The following information shall be included in the body of the email:

Attention: WDR Unit

Report Title: [Title of Report]

GeoTracker Upload ID: [Number

Facility Name: [Gopher Hill Class III Municipal

Solid Waste Landfill and Class II

Surface Impoundment]

County: Plumas County

CIWQS Place ID: 227632

ii. Data Presentation and Formatting

In reporting monitoring data, the Discharger shall arrange the data in tabular form so that the date, the constituents, the concentrations, and the units are readily discernible. Additionally, data shall be summarized in a manner that clearly illustrates compliance/noncompliance with WDRs.

iii. Non-Detections / Reporting Limits

Unless the reporting limits (RL) are specified in the same table or adjacent to the table, non-detections and sub-RL concentrations shall be reported as "< [limit]" (e.g., "< $5 \mu g/L$ ").

iv. Units

Absent specific justification, all monitoring data shall be reported in the units specified herein.

c. Compliance with SPRRs

All reports submitted under this MRP shall comply with applicable provisions of the SPRRs, including those in Section I (Standard Monitoring Specifications) and Section J (Response to Release).

d. Additional Requirements for Monitoring Reports

Every monitoring report submitted under this MRP (e.g., SMRs [§ D.1], AMRs [§ D.2]) shall include a discussion of relevant field and laboratory tests, and the results of all monitoring conducted at the site shall be reported to the Central Valley Water Board in accordance with the reporting schedule above for the calendar period in which samples were taken or observations made.

E. Record Retention Requirements

PLUMAS COUNTY

The Discharger shall maintain permanent records of all monitoring information, including without limitation: calibration and maintenance records; original strip chart recordings of continuous monitoring instrumentation; copies of all reports required by this MRP; and records of all data used to complete the application for WDRs. Such records shall be legible, and show the following for each sample:

- 1. Sample identification and the monitoring point or background monitoring point from which it was taken, along with the identity of the individual who obtained the sample;
- 2. Date, time and manner of sampling;
- 3. Date and time that analyses were started and completed, and the name of the personnel and laboratory performing each analysis;
- 4. A complete list of procedures used (including method of preserving the sample, and the identity and volumes of reagents used);
- 5. A calculation of results: and
- 6. The results of all analyses, as well as the MDL and PQL for each analysis (all peaks shall be reported).

LIST OF ATTACHMENTS

Attachment A—Volatile Organic Compounds, Short List

PLUMAS COUNTY

Attachment B—Dissolved Inorganics (Five-Year COCs)

Attachment C—Volatile Organic Compounds, Extended List (Five-Year COCs)

Attachment D—Semi-Volatile Organic Compounds (Five-Year COCs)

Attachment E—Chlorophenoxy Herbicides (Five-Year COCs)

Attachment F—Organophosphorous Compounds (Five Year COCs)

ENFORCEMENT

If, in the opinion of the Executive Officer, the Discharger fail to comply with the provisions of this Order, the Executive Officer may refer this matter to the Attorney General for judicial enforcement, may issue a complaint for administrative civil liability, or may take other enforcement actions. Failure to comply with this Order may result in the assessment of Administrative Civil Liability of up to \$10,000 per violation, per day, depending on the violation, pursuant to the Water Code, including sections 13268, 13350 and 13385. The Central Valley Water Board reserves its right to take any enforcement actions authorized by law.

ADMINISTRATIVE REVIEW

Any person aggrieved by this Central Valley Water Board action may petition the State Water Board for review in accordance with Water Code section 13320 and California Code of Regulations, title 23, section 2050 et seq. To be timely, the petition must be received by the State Water Board by 5:00 pm on the 30th day after the date of this Order; if the 30th day falls on a Saturday, Sunday or state holiday, the petition must be received by the State Water Board by 5:00 pm on the next business day. The law and regulations applicable to filing petitions are available on the State Water Board website (http://www.waterboards.ca.gov/public_notices/petitions/water_quality). Copies will also be provided upon request.

ATTACHMENT A—VOLATILE ORGANIC COMPOUNDS, SHORT LIST

USEPA Method 8260B, Short List

Constituent	Geotracker Code
Acetone	ACE
Acrylonitrile	ACRAMD
Benzene	BZ
Bromochloromethane	BRCLME
Bromodichloromethane	BDCME
Bromoform (Tribromomethane)	TBME
Carbon disulfide	CDS
Carbon tetrachloride	CTCL
Chlorobenzene	CLBZ
Chloroethane (Ethyl chloride)	CLEA
Chloroform (Trichloromethane)	TCLME
Dibromochloromethane (Chlorodibromomethane)	DBCME
1,2 Dibromo 3 chloropropane (DBCP)	DBCP
1,2 Dibromoethane (Ethylene dibromide; EDB)	EDB
o Dichlorobenzene (1,2 Dichlorobenzene)	DCBZ12
m Dichlorobenzene (1,3 Dichlorobenzene)	DCBZ13
p Dichlorobenzene (1,4 Dichlorobenzene)	DCBZ14
trans I ,4 Dichloro 2 butene	DCBE14T
Dichlorodifluoromethane (CFC-12)	FC12

ATTACHMENT A—VOLATILE ORGANIC COMPOUNDS, SHORT LIST

Constituent	Geotracker Code
1,1 Dichloroethane (Ethylidene chloride)	DCA11
1,2 Dichloroethane (Ethylene dichloride)	DCA12
1,1 Dichloroethylene (1,1 Dichloroethene; Vinylidene chloride)	DCE11
cis 1,2 Dichloroethylene (cis 1,2 Dichloroethene)	DCE12C
trans 1,2 Dichloroethylene (trans 1,2 Dichloroethene)	DCE12T
1,2 Dichloropropane (Propylene dichloride)	DCPA12
cis 1,3 Dichloropropene	DCP13C
trans 1,3 Dichloropropene	DCP13T
Di-isopropylether (DIPE)	DIPE
Ethanol	ETHANOL
Ethyltertiary butyl ether	ETBE
Ethylbenzene	EBZ
2 Hexanone (Methyl butyl ketone)	HXO2
Hexachlorobutadiene	HCBU
Methyl bromide (Bromomethene)	BRME
Methyl chloride (Chloromethane)	CLME
Methylene bromide (Dibromomethane)	DBMA
Methylene chloride (Dichloromethane)	DCMA
Methyl ethyl ketone (MEK: 2 Butanone)	MEK
Methyl iodide (lodomethane)	IME
Methyl t-butyl ether	MTBE

ATTACHMENT A—VOLATILE ORGANIC COMPOUNDS, SHORT LIST

Constituent	Geotracker Code
4-Methyl 2 pentanone (Methyl isobutylketone)	MIBK
Naphthalene	NAPH
Styrene	STY
Tertiary amyl methyl ether	TAME
Tertiary butyl alcohol	ТВА
1,1,1,2 Tetrachloroethane	TC1112
1,1.2,2 Tetrachloroethane	PCA
Tetrachloroethylene (Tetrachloroethene; Perchloroethylene)	PCE
Toluene	BZME
1,2,4-Trichlorobenzene	TCB124
1,1,1 Trichloroethane (Methylchloroform)	TCA111
1,1,2 Trichloroethane	TCA112
Trichloroethylene (Trichloroethene)	TCE
Trichlorofluoromethane (CFC 11)	FC11
1,2,3 Trichloropropane	TCPR123
Vinyl acetate	VA
Vinyl chloride	VC
Xylenes	XYLENES

ATTACHMENT B—DISSOLVED INORGANICS (FIVE-YEAR COCS)

Dissolved Inorganics List

Constituent	Analytical Method	Geotracker Code
Aluminum	USEPA Method 6010	AL
Antimony	USEPA Method 7041	SB
Arsenic	USEPA Method 7062	AS
Barium	USEPA Method 6010	ВА
Beryllium	USEPA Method 6010	BE
Cadmium	USEPA Method 7131A	CD
Chromium	USEPA Method 6010	CR
Cobalt	USEPA Method 6010	СО
Copper	USEPA Method 6010	CU
Cyanide	USEPA Method 9010C	CN
Iron	USEPA Method 6010	FE
Lead	USEPA Method 7421	РВ
Manganese	USEPA Method 6010	MN
Mercury	USEPA Method 7470A	HG
Nickel	USEPA Method 7521	NI
Selenium	USEPA Method 7742	SE
Silver	USEPA Method 6010	AG
Sulfide	USEPA Method 9030Bx	S
Thallium	USEPA Method 7841	TL

PLUMAS COUNTY GOPHER HILL LANDFILL PLUMAS COUNTY

ATTACHMENT B—DISSOLVED INORGANICS (FIVE-YEAR COCS)

Constituent	Analytical Method	Geotracker Code
Tin	USEPA Method 6010	SN
Vanadium	USEPA Method 6010	V
Zinc	USEPA Method 6010	ZN

ATTACHMENT C—VOLATILE ORGANIC COMPOUNDS, EXTENDED LIST (FIVE-YEAR COCS)

USEPA Method 8260, Extended List

Volatile Organic Compound	Geotracker Code
Acetone	ACE
Acetonitrile (Methyl cyanide)	ACCN
Acrolein	ACRL
Acrylonitrile	ACRAMD
Allyl chloride (3 Chloropropene)	CLPE3
Benzene	BZ
Bromochloromethane (Chlorobromomethane)	BRCLME
Bromodichloromethane (Dibromochloromethane)	DBCME
Bromoform (Tribromomethane)	ТВМЕ
Carbon disulfide	CDS
Carbon tetrachloride	CTCL
Chlorobenzene	CLBZ
Chloroethane (Ethyl chloride)	CLEA
Chloroform (Trichloromethane)	TCLME
Chloroprene	CHLOROPRENE
Dibromochloromethane (Chlorodibromomethane)	DBCME
1,2 Dibromo 3 chloropropane (DBCP)	DBCP
1,2 Dibromoethane (Ethylene dibromide; EDB)	EDB

GOPHER HILL LANDFILL PLUMAS COUNTY

ATTACHMENT C—VOLATILE ORGANIC COMPOUNDS, EXTENDED LIST, (FIVEYEAR COCS)

Volatile Organic Compound	Geotracker Code
o Dichlorobenzene (1,2 Dichlorobenzene)	DCBZ12
m Dichlorobenzene(1,3 Dichlorobenzene)	DCBZ13
p Dichlorobenzene (1,4 Dichlorobenzene)	DCBZ14
trans 1,4 Dichloro 2 butene	DCBE14T
Dichlorodifluoromethane (CFC 12)	FC12
1,1 Dichloroethane (Ethylidene chloride)	DCA11
1,2 Dichloroethane (Ethylene dichloride)	DCA12
1,1 Dichloroethylene (1, I Dichloroethene; Vinylidene chloride)	DCE11
cis I ,2 Dichloroethylene (cis 1,2 Dichloroethene)	DCE12C
trans I ,2 Dichloroethylene (trans 1,2 Dichloroethene)	DCE12T
1,2 Dichloropropane (Propylene dichloride)	DCPA12
1,3 Dichloropropane (Trimethylene dichloride)	DCPA13
2,2 Dichloropropane (Isopropylidene chloride)	DCPA22
1,1 Dichloropropene	DCP11
cis 1,3 Dichloropropene	DCP13C
trans I ,3 Dichloropropene	DCP13T
Di-isopropylether (DIPE)	DIPE
Ethanol	ETHANOL
Ethyltertiary butyl ether	ETBE
Ethylbenzene	EBZ

PLUMAS COUNTY GOPHER HILL LANDFILL PLUMAS COUNTY

ATTACHMENT C—VOLATILE ORGANIC COMPOUNDS, EXTENDED LIST, (FIVEYEAR COCS)

Volatile Organic Compound	Geotracker Code
Ethyl methacrylate	EMETHACRY
Hexachlorobutadiene	HCBU
2 Hexanone (Methyl butyl ketone)	HXO2
Isobutyl alcohol	ISOBTOH
Methacrylonitrile	METHACRN
Methyl bromide (Bromomethane)	BRME
Methyl chloride (Chloromethane)	CLME
Methyl ethyl ketone (MEK; 2 Butanone)	MEK
Methyl iodide (lodomethane)	IME
Methyl t-butyl ether	MTBE
Methyl methacrylate	MMTHACRY
4 Methyl 2 pentanone (Methyl isobutyl ketone)	MIBK
Methylene bromide (Dibromomethane)	DBMA
Methylene chloride (Dichloromethane)	DCMA
Naphthalene	NAPH
Propionitrile (Ethyl cyanide)	PACN
Styrene	STY
Tertiary amyl methyl ether	TAME
Tertiary butyl alcohol	TBA
1,1,1,2 Tetrachloroethane	TC1112

PLUMAS COUNTY GOPHER HILL LANDFILL PLUMAS COUNTY

ATTACHMENT C—VOLATILE ORGANIC COMPOUNDS, EXTENDED LIST, (FIVEYEAR COCS)

Volatile Organic Compound	Geotracker Code
1,1,2,2 Tetrachloroethane	PCA
Tetrachloroethylene (Tetrachloroethene; Perchloroethylene; PCE)	PCE
Toluene	BZME
1,2,4 Trichlorobenzene	TCB124
1,1,1 Trichloroethane (Methylchloroform)	TCA111
1,1,2 Trichloroethane	TCA112
Trichloroethylene (Trichloroethene; TCE)	TCE
Trichlorofluoromethane (CFC 11)	FC11
1,2,3 Trichloropropane	TCPR123
Vinyl acetate	VA
Vinyl chloride (Chloroethene)	VC
Xylene (total)	XYLENES

ATTACHMENT D—SEMI-VOLATILE ORGANIC COMPOUNDS (FIVE-YEAR COCS)

USEPA Methods 8270C or 8270D Base, Neutral & Acids Extractables List

Constituent	Geotracker Code
Acenaphthene	ACNP
Acenaphthylene	ACNPY
Acetophenone	ACPHN
2 Acetylaminofluorene (2 AAF)	ACAMFL2
Aldrin	ALDRIN
4 Aminobiphenyl	AMINOBPH4
Anthracene	ANTH
Benzo[a]anthracene (Benzanthracene)	BZAA
Benzo[b]fluoranthene	BZBF
Benzo[k]fluoranthene	BZKF
Benzo[g,h,i]perylene	BZGHIP
Benzo[a]pyrene	BZAP
Benzyl alcohol	BZLAL
Bis(2 ethylhexyl) phthalate	BIS2EHP
alpha BHC	BHCALPHA
beta BHC	BHCBETA
delta BHC	BHCDELTA
gamma BHC (Lindane)	BHCGAMMA

Constituent	Geotracker Code
Bis(2 chloroethoxy) methane	BECEM
Bis(2 chloroethyl) ether (Dichloroethyl ether)	BIS2CEE
Bis(2 chloro 1 methyethyl) ether (Bis(2 chloroisopropyl) ether; DCIP)	BIS2CIE
4 Bromophenyl phenyl ether	BPPE4
Butyl benzyl phthalate (Benzyl butyl phthalate)	BBP
Chlordane	CHLORDANE
p Chloroaniline	CLANIL4
Chlorobenzilate	CLBZLATE
p Chloro m cresol (4 Chloro 3 methylphenol)	C4M3PH
2 Chloronaphthalene	CNPH2
2 Chlorophenol	CLPH2
4 Chlorophenyl phenyl ether	CPPE4
Chrysene	CHRYSENE
o Cresol (2 methylphenol)	MEPH2
m Cresol (3 methylphenol)	MEPH3
p Cresol (4 methylphenol)	MEPH4
4,4' DDD	DDD44
4,4' DDE	DDE44
4,4' DDT	DDT44
Diallate	DIALLATE

Constituent	Geotracker Code
Dibenz[a,h]anthracene	DBAHA
Dibenzofuran	DBF
Di n butyl phthalate	DNBP
3,3' Dichlorobenzidine	DBZD33
2,4 Dichlorophenol	DCP24
2,6 Dichlorophenol	DCP26
Dieldrin	DIELDRIN
Diethyl phthalate	DEPH
p (Dimethylamino) azobenzene	PDMAABZ
7,12 Dimethylbenz[a]anthracene	DMBZA712
3,3' Dimethylbenzidine	DMBZD33
2,4 Dimehtylphenol (m Xylenol)	DMP24
Dimethyl phthalate	DMPH
m Dinitrobenzene	DNB13
4,6 Dinitro o cresol (4,6 Dinitro 2 methylphenol)	DN46M
2,4 Dinitrophenol	DNP24
2,4 Dinitrotoluene	DNT24
2,6 Dinitrotoluene	DNT26
Di n octyl phthalate	DNOP
Diphenylamine	DPA
Endosulfan I	ENDOSULFANA

GOPHER HILL LANDFILL PLUMAS COUNTY

Constituent	Geotracker Code
Endosulfan II	ENDOSULFANB
Endosulfan sulfate	ENDOSULFANS
Endrin	ENDRIN
Endrin aldehyde	ENDRINALD
Ethyl methanesulfonate	EMSULFN
Famphur	FAMPHUR
Fluoranthene	FLA
Fluorene	FL
Heptachlor	HEPTACHLOR
Heptachlor epoxide	HEPT-EPOX
Hexachlorobenzene	HCLBZ
Hexachlorocyclopentadiene	НССР
Hexachloroethane	HCLEA
Hexachloropropene	HCPR
Indeno(1,2,3 c,d) pyrene	INP123
Isodrin	ISODRIN
Isophorone	ISOP
Isosafrole	ISOSAFR
Kepone	KEP
Methapyrilene	MTPYRLN
Methoxychlor	MTXYCL

Constituent	Geotracker Code
3 Methylcholanthrene	MECHLAN3
Methyl methanesulfonate	MMSULFN
2 Methylnaphthalene	MTNPH2
1,4 Naphthoquinone	NAPHQ14
1 Naphthylamine	AMINONAPH1
2 Naphthylamine	AMINONAPH2
o Nitroaniline (2 Nitroaniline)	NO2ANIL2
m Nitroaniline (3 Nitroaniline)	NO2ANIL3
p Nitroaniline (4 Nitroaniline)	NO2ANIL4
Nitrobenzene	NO2BZ
o Nitrophenol (2 Nitrophenol)	NTPH2
p Nitrophenol (4 Nitrophenol)	NTPH4
N Nitrosodi n butylamine (Di n butylnitrosamine)	NNSBU
N Nitrosodiethylamine (Diethylnitrosamine)	NNSE
N Nitrosodimethylamine (Dimethylnitrosamine)	NNSM
N Nitrosodiphenylamine (Diphenylnitrosamine)	NNSPH
N Nitrosodipropylamine (N Nitroso N dipropylamine; Di n propylnitrosamine)	NNSPR
N Nitrosomethylethylamine (Methylethylnitrosamine)	NNSME
N Nitrosopiperidine	NNSPPRD
N Nitrosospyrrolidine	NNSPYRL

Constituent	Geotracker Code
5 Nitro o toluidine	TLDNONT5
Pentachlorobenzene	PECLBZ
Pentachloronitrobenzene (PCNB)	PECLNO2BZ
Pentachlorophenol	PCP
Phenacetin	PHNACTN
Phenanthrene	PHAN
Phenol	PHENOL
p Phenylenediamine	ANLNAM4
Polychlorinated biphenyls (PCBs; Aroclors)	PCBS
Pronamide	PRONAMD
Pyrene	PYR
Safrole	SAFROLE
1,2,4,5 Tetrachlorobenzene	C4BZ1245
2,3,4,6 Tetrachlorophenol	TCP2346
o Toluidine	TLDNO
Toxaphene	TOXAP
2,4,5 Trichlorophenol	TCP245
0,0,0 Triethyl phosphorothioate	TEPTH
sym Trinitrobenzene	TNB135

ATTACHMENT E—CHLOROPHENOXY HERBICIDES (FIVE-YEAR COCS)

USPEA Method 8151A List

Constituent	GeoTracker Code
2,4 D (2,4 Dichlorophenoxyacetic acid)	24D
Dinoseb (DNBP; 2 sec Butyl 4,6 dinitrophenol)	DINOSEB
Silvex (2,4,5 Trichlorophenoxypropionic acid; 2,4,5 TP)	SILVEX
2,4,5 T (2,4,5 Trichlorophenoxyacetic acid)	245T

ATTACHMENT F—ORGANOPHOSPHOROUS COMPOUNDS (FIVE YEAR COCS)

USEPA Method 8141B List

Constituent	GeoTracker Code
Atrazine	ATRAZINE
Chlorpyrifos	CLPYRIFOS
0,0-Diethyl 0-2-pyrazinyl phosphorothioate (Thionazin)	ZINOPHOS
Diazinon	DIAZ
Dimethoate	DIMETHAT
Disulfoton	DISUL
Methyl parathion (Parathion methyl)	PARAM
Parathion	PARAE
Phorate	PHORATE
Simazine	SIMAZINE