# CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD COLORADO RIVER BASIN REGION

ORDER NO. 90-023

WASTE DISCHARGE REQUIREMENTS
FOR
PIMA GRO SYSTEMS, INC.
Colorado Hydrologic Unit - Riverside County

1 h

The California Regional Water Quality Control Board, Colorado River Basin Region, finds that:

- 1. Pima Gro Systems, Inc. (hereinafter also referred to as the discharger), 2305 Ruthrauff Road, Tucson, Arizona 85705, submitted a Report of Waste Discharge, dated March 25, 1988, to operate a program for beneficial agricultural use of sewage sludge. On June 30, 1988 the Regional Board issued Board Order No. 88-083, prescribing waste discharge requirements for the discharger. The Regional Board has, on its own motion, reviewed Board Order No. 88-083, and is now revising that Order.
- 2. The discharger proposes to utilize stabilized wastewater treatment plant sludge through agricultural land application at agronomic rates. The discharger has formulated a plan of operation to meet requirements of this Regional Water Quality Control Board and guidelines contained in the California Department of Health Services Manual of Good Practice for Land Spreading of Sewage Sludge.
- 3. Air dried sludge and mechanically de-watered digested (stabilized) sludge would be handled as a bulk material using dump trucks and loaders. Sludge would be transported to designated land application sites and stock-piled for spreading. Field stockpiling would be restricted to limited time durations to prevent nuisances and water pollution. Sludge would be distributed on the application sites with a box-type spreader. Following distribution of sludge on a field, applied material would be soil incorporated within 24 hours with tillage equipment. Incorporation would be done directly by the discharger.
- 4. The discharger states that sludge transportation would be achieved with semi-dump trailers. These units would be in good condition and would be equipped with water-tight end gates. A manifest system would be maintained whereby the date, time, quantity, source and destination of each load would be recorded. Such records would provide one of the bases for the monitoring program.
- 5. The crops under consideration for sludge application would include bermuda grass, small grain, sugar beets, alfalfa and cotton. Produce crops such as lettuce would be avoided due to California and Federal food chain crop restrictions, where resting periods are mandated when a crop in direct contact with the soil is consumed raw.

Superseded by: Board Oil. # 97-027 5/28/97

- 6. The discharger's original report of waste discharge was for both the Imperial and Riverside County portion of the Colorado Hydrologic Unit. However, upon request of the County of Imperial, this Board Order applies only to the Riverside County portion of the Colorado Hydrologic Unit.
- 7. The Water Quality Control Plan for the Colorado River Basin Region of California designates the beneficial uses of ground and surface waters in this Region.
- 8. The beneficial uses of ground waters in the Colorado Hydrologic Unit are:
  - a. Municipal supply (MUN)
  - b. Industrial supply (IND)
  - c. Agricultural supply (AGR)
- 9. The Board has notified the discharger and all known interested agencies and persons of its intent to update waste discharge requirements for this discharge.
- 10. The Board in a public meeting heard and considered all comments pertaining to this discharge.
- 11. In accordance with the California Environmental Quality Act (CEQA), the Regional Board, acting as lead agency, processed and approved Negative Declaration SCH # 89031307 for sludge applications for the Riverside County portion of the Colorado Hydrologic Unit that includes this project area.

IT IS HEREBY ORDERED, the discharger shall comply with the following:

### A. Discharge Specifications

- 1. The discharge operations shall not create pollution or a nuisance as defined in Division 7 of the California Water Code.
- 2. Land application of the sludges shall be done at agronomic rates and be limited to agricultural sites in the Riverside County portion of the Colorado Hydrologic Unit. Land application shall be restricted to only those sources of sludge(s) receiving prior written approval by the Executive Officer of this Regional Board. The following factors will be used by the discharger to determine land application suitability:
  - a. Single application and lifetime limits of all constituents as described in both 40 CFR Part 257, Criteria for Classification of Solid Waste Disposal Facilities and Practices, U.S.E.P.A., September 1979, and "Manual of Good Practice for Landspreading of Sewage Sludge", California Department of Health Services, Sanitary Engineering Branch, April 1983.
  - b. Soil Cation Exchange Rate
  - c. Soil pH
  - d. Nitrogen Loading Rates
  - e. Phytotoxicity

Also, the land application suitability will be continually reviewed as new data is received.

- 3. Sludge request forms signed by both the farm operator and the land owner shall be submitted to the Regional Board as an informational item stating the crops intended to be grown on the subject acreage (the enforcement of this lies with applicable state and county agencies), in accordance with the "Manual of Good Practice for Landspreading of the Sewage Sludge", California Department of Health Services Sanitary Engineering Branch, April 1983.
- 4. All landspreading practices shall be in compliance with 40 CFR Part 257, Criteria for Classification of Solid Waste Disposal Facilities and Practices, U.S.E.P.A., September 1979, and the "Manual of Good Practice for Landspreading of Sewage Sludge", Department of Health Services, Sanitary Engineering Branch, April 1983 (responsibility for enforcement of those provisions not related to water quality control lies with the applicable agency).
- 5. Sludge shall be landspread and incorporated within 24 hours of arrival on the site.
- 6. Sludge shall not be applied on areas exceeding 4 percent in slope.
- 7. Sludge stockpiles will be limited to approved sites in accordance with Department of Health Services guidelines, and shall be located at least:
  - a. 25 feet away from property lines unless permission is obtained from the adjacent landowner.
  - b. 500 feet away from drinking water wells.
  - c. 50 feet away from public roads.
- 8. The discharger shall submit to the Regional Board an annual screening test which shall include all metals and organics that are prescribed by the California Assessment Manual (CAM) on all sludges which the discharger intends to use as soil amendments. In addition, the discharger shall submit to the Regional Board monthly results of analyses of sludge tested at the wastewater treatment plant, showing the following (documented treatment plant results may be permitted):

	<u>Determination</u>	<u>Unit</u>
а	Arsenic	mg/kg
	Chromium	mg/kg
c.	Cadmium	mg/kg
đ.	Lead	mg/kg
e.	Zinc	mg/kg
f.	Copper	mg/kg
g.	Nickel	mg/kg
h.	Mercury	mg/kg
i.	Selenium	mg/kg
j.	Total Nitrogen	-
k.	Available Nitrogen	lbs/dry ton
	for Plant Uptake	
1.	Solids	8

- 9. The discharger shall report to the Regional Board (informational purposes only), for a period of 3 years after the last sludge application to a particular field, what crops are being grown on the field.
- 10. This Board Order does not authorize any violations of laws and regulations of any federal, state, or local agencies.
- 11. Sampling techniques for CAM testing shall be done in accordance with Section 1 of "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods" SW-846, 2nd Edition, U.S.E.P.A., 1982.
- 12. No tailwater shall be discharged off any field where sludge has been spread, nor shall sludge be spread on any field which has a pipe, conduit, or channel in place for the conveyance of tailwater off the field, without written permission from the Executive Officer.

#### B. Provisions

- 1. The discharger shall comply with "Monitoring and Reporting Program No. 90-023", and future revisions thereto, as specified by the Executive Officer.
- 2. Prior to any material modifications in any aspect of the sludge management plan, the discharger shall report in writing to the Regional Board allowing sufficient time for Board consideration and action.
- 3. This waste discharge requirement shall immediately be subject to Regional Board's review and applicable revision when the U.S. Environmental Protection Agency issues any technical criteria, regulations or guidance affecting sludge disposal currently being developed under authorities provided under Section 405(d) of the Federal Clean Water Act.

IT IS FURTHER ORDERED that Board Order No. 88-083 be superseded by this Order.

I, Philip A. Gruenberg, Executive Officer, do hereby certify the foregoing is a full, true and correct copy of an Order adopted by the California Regional Water Quality Control Board, Colorado River Basin Region, on May 16, 1990.

Executive Officer

## CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD COLORADO RIVER BASIN REGION

MONITORING AND REPORTING PROGRAM NO. 90-023 FOR

PIMA GRO SYSTEMS, INC. Colorado Hydrologic Unit - Riverside County

### **MONITORING**

- I. The discharger shall submit to the Regional Board monthly reports as follows:
  - A. Soil samples shall be collected prior to each sludge application and analyzed for:

1.	pН	-
2.	Cation Exchange Capacity	meg/100 grams
3.	Lead	mg/kg
4.	Cadmium	mg/kg
5.	Copper	mg/kg
6.	Zinc	mg/kg
7.	Nickel	mg/kg
8.	Selenium	mg/kg
9.	Total Nitrogen	-
10.	Chromium	mg/kg
11.	Silver	mg/kg
12.	Mercury	mg/kg

- B. Samples shall be collected monthly from the sludge applied to each field and the following shall be reported monthly to the Regional Board.
  - 1. Number of tons applied that month, number of tons of sludge applied to the field total and crop to be grown.
  - Pounds per acre of copper, zinc, cadmium, nickel and lead that has been applied that month, pounds per acre that have been applied of each metal in the lifetime of the field and theoretical maximum amounts described by 40CFR, Part 257, U.S.E.P.A., September 1979.
  - 3. Total Kjeldahl nitrogen, ammonia-nitrogen, nitrate-nitrogen from a composite of the sludge being applied.
  - 4. Total percent solids from a composite of the sludge being applied.
- II. The discharger shall submit to the Regional Board an annual screening test of sludge samples to be collected at the wastewater treatment plant, which shall include all metals and organics that are prescribed by the California Assessment Manual on all sludge sources which the discharger intends to use as soil amendments.

III. The discharger shall submit to the Regional Board monthly results of analyses of sludge tested at the wastewater treatment plant, showing the following:

<u>Determination</u>	<u>Unit</u>
0.000.000	71
a. Arsenic	mg/kg
b. Chromium	mg/kg
c. Cadmium	mg/kg
d. Lead	mg/kg
e. Zinc	mg/kg
f. Copper	mg/kg
g. Nickel	mg/kg
h. Mercury	mg/kg
i. Selenium	mg/kg
j. Total Nitrogen	-
k. Available Nitrogen for Plant Uptake	lbs/dry ton
l. Solids	8

IV. For a period of 3 years after the last sludge application, the discharger shall submit to the Regional Board an annual report stating which crops are being grown on each field. This report shall include a certification that all resting periods required by E.P.A., 40 CFR, Part 257 and the "Manual of Good Practice for Landspreading of Sewage Sludge", Department of Health Services, Sanitary Engineering Branch, April 1983 are maintained.

### REPORTING

Monthly reports shall be submitted to the Regional Board by the 15th day of the following month. Annual reports shall be submitted to the Regional Board by January 15th of the following year. Copies of the reports submitted to the Board pursuant to this Monitoring and Reporting Program shall be maintained at the operations site, and shall be made available to staff of the Regional Board upon request.

Mail reports to:

California Regional Water Quality Control Board Colorado River Basin Region 73-271 Highway 111, Suite 21 Palm Desert, CA 92260

ORDERED BY:

May 16, 1990

Date