



## Performance Data Sheet Mirage Filtered Water Pitcher

**Model Series: WFPT200**

Hoja de datos de funcionamiento  
Jarra de agua filtrada Mirage  
**Modelo serie WFPT200**

**IMPORTANT NOTICE:** Read this Performance Data Sheet and compare the capabilities of this unit with your actual water treatment needs. It is recommended that before purchasing a water treatment unit, you have your water supply tested to determine your actual water treatment needs.

**AVISO IMPORTANTE:** Lea esta hoja de datos de rendimiento y compare las capacidades de esta unidad con su necesidad reales de tratamiento del agua. Se recomienda que antes de adquirir una unidad de tratamiento de agua, haga examinar el suministro de agua para determinar sus necesidades reales de tratamiento del agua.



*The miracles of science™*



© 2014 Protect Plus. All rights reserved. The DuPont Oval Logo, DuPont™, and The miracles of science™, are registered trademarks or trademarks of E. I. du Pont de Nemours and Company and are used under license by Protect Plus, LLC.

© 2014 Protect Plus. Todos los derechos reservados. El logotipo ovalado de DuPont, DuPont™ y The miracles of science™ son marcas comerciales o marcas comerciales registradas de E. I. du Pont de Nemours and Company y se utilizan bajo licencia por Protect Plus, LLC.

# Performance Data Sheet

## DuPont™ Mirage Filtered Water Pitcher Series WFPT200 with DuPont™ Universal Fit Pitcher Cartridge WFPTC100

This filtration system has been tested and certified according to NSF/ANSI Standards 42 and 53 by WQA for the reduction of the substances listed below, as verified and substantiated by test data. The concentration of the indicated substances in the water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standards 42 and 53. Tested and certified by Water Quality Association against NSF/ANSI 372 for low lead compliance. Please see warranty insert for manufacturer's limited warranty. Please see installation instructions for internal operation and maintenance requirements.

### NSF/ANSI Standard 42 Aesthetic Effects

Substance	Influent Challenge Concentration	Required Minimum % Reduction	Actual Minimum Percent Reduction	Actual Average Percent Reduction
Taste & Odor, Aesthetic Chlorine	2mg/L	50%	95.0%	98.0%
Particulate Class III (5 µm to < 15 µm)	>10,000 particles per ml	85%	94.0%	97.5%

### NSF/ANSI Standard 53 Health Effects

Substance	Influent Challenge Concentration	US EPA Maximum Permissible Water Concentration / Required Minimum % Reduction		Actual Minimum Percent Reduction	Actual Average Percent Reduction
		US EPA Maximum Permissible Water Concentration	Required Minimum % Reduction		
Cadmium (pH 6.5)	0.03 mg/L	0.005 mg/L	83%	96.4%	98.5%
Cadmium (pH 8.5)	0.03 mg/L	0.005 mg/L	83%	83.2%	95.5%
Lead (pH 6.5)	0.150 mg/L	0.010 mg/L	93%	95.5%	98.7%
Lead (pH 8.5)	0.150 mg/L	0.010 mg/L	93%	95.0%	97.4%
Mercury (pH 6.5)	0.006 mg/L	0.002 mg/L	67%	95.7%	96.5%
Mercury (pH 8.5)	0.006 mg/L	0.002 mg/L	67%	96.7%	96.7%
VOC (Surrogate)*	0.3 mg/L	0.015 mg/L	95%	95.7%	99.4%

Operating Requirements: Filter System capacity 40 gallons / 151 liters or approximately 2 months.

Operating Temperature: Min 35°F / 2°C - Max 85°F / 29°C

Laboratory Test Conditions: pH: 6.5 – 8.5, Water Temperature: 72°F / 23°C - 75°F / 24°C Actual performance may vary with local water conditions. Do not use with water that is microbiologically unsafe or of unknown water quality without adequate disinfection before or after the system.

The replacement cartridges referenced above generally retail for \$6.99 each.

**\* Table 17 - Performance data sheet reduction claims for organic chemicals included by surrogate testing**

Substance	Influent Challenge Concentration (mg/liter)	Maximum permissible product water concentration (mg/liter)
alachlor	0.050	0.001
atrazine	0.100	0.003
benzene	0.081	0.001
carbofuran	0.190	0.001
carbon tetrachloride	0.078	0.0018
chlorobenzene	0.077	0.001
chloropicrin	0.015	0.0002
2, 4-D	0.110	0.0017
dibromochloropropane (DBCP)	0.052	0.00002
o-dichlorobenzene	0.080	0.001
p-dichlorobenzene	0.040	0.001
1, 2-dichloroethane	0.088	0.0048
1, 1-dichloroethylene	0.083	0.001
cis-1, 2-dichloroethylene	0.170	0.0005
trans-1, 2-dichloroethylene	0.086	0.001
1, 2-dichloropropane	0.080	0.001
cis-1, 3-dichloropropylene	0.079	0.001
dinoseb	0.170	0.0002
endrin	0.053	0.00059
ethylbenzene	0.088	0.001
ethylene dibromide (EDB)	0.044	0.00002
haloacetonitriles (HAN):		
bromochloroacetonitrile	0.022	0.0005
dibromoacetonitrile	0.024	0.0006
dichloroacetonitrile	0.0096	0.0002
trichloroacetonitrile	0.015	0.0003
haloketones (HK):		
1, 1-dichloro-2-propanone	0.0072	0.0001
1,1,1-trichloro2-2propanone	0.0082	0.0003
heptachlor	0.025	0.00001
heptachlor epoxide	0.0107	0.0002
hexachlorobutadiene	0.044	0.001
hexachlorocyclopentadiene	0.060	0.000002

Table 17 - Performance data sheet reduction claims for organic chemicals included by surrogate testing (continued)

Substance	Influent Challenge Concentration (mg/liter)	Maximum permissible product water concentration (mg/liter)
lindane	0.055	0.00001
methoxychlor	0.050	0.0001
pentachlorophenol	0.096	0.001
simazine	0.120	0.004
styrene	0.150	0.0005
1,1,2,2-tetrachloroethane	0.081	0.001
tetrachloroethylene	0.081	0.001
toluene	0.078	0.001
2,4,5-TP (silvex)	0.270	0.0016
tribromoacetic acid	0.042	0.001
1,2,4-trichlorobenzene	0.160	0.0005
1,1,1-trichloroethane	0.084	0.0046
1,1,2-trichloroethane	0.150	0.0005
trichloroethylene	0.180	0.0010
trihalomethanes (includes): chloroform (surrogate chemical) bromoform bromodichloromethane chlorodibromomethane	0.300	0.015
xylenes (total)	0.070	0.001

[http://www2.dupont.com/Water\\_Filtration/en\\_US/index.html](http://www2.dupont.com/Water_Filtration/en_US/index.html)

Protect Plus, LLC

PO Box 9181, Hickory, NC 28603

(828) 449-1040

To maintain product certification and ensure uniform performance, the product is retested on a consistent basis.