

**State of California**  
**CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD**  
**LOS ANGELES REGION**  
**320 West 4th Street, Suite 200, Los Angeles**  
**FACT SHEET**  
**WASTE DISCHARGE REQUIREMENTS**  
**FOR**  
**331 NORTH MAPLE LLC.**  
**NPDES NO. CAG994004**  
**CI-7738**

**PROJECT LOCATION**

331 N. Maple Drive  
 Beverly Hills, CA 90210

**FACILITY MAILING ADDRESS**

3130 Wilshire Boulevard, 2<sup>nd</sup> Floor  
 Santa Monica, CA 90403

**PROJECT DESCRIPTION**

331 North Maple LLC. operates a groundwater dewatering system at the office building located at 331 N. Maple Drive, Beverly Hills. The dewatering is necessary to protect the integrity of the building structure from rising groundwater. Discharge from the site is regulated under general NPDES Permit CAG994001 (Order No. 97-045) which was issued on November 26, 1997. On October 17, 2003, WRC submitted a Notice of Intent (NOI) form, and analytical results of groundwater samples to continue enrollment under the General NPDES Permit No. CAG994004, Order No. R4-2003-0111, adopted by this Board on August 7, 2003.

**VOLUME AND DESCRIPTION OF DISCHARGE**

Up to 990,000 gallons per day of groundwater is discharged to a storm drain located at Latitude 34°02'57", Longitude 118°23'33", thence to Ballona Creek, a water of the United States. The site location map is shown as Figure 1.

**APPLICABLE EFFLUENT LIMITATIONS**

Based on the information provided in the NPDES Application Supplemental Requirements, the following constituents listed in the table below have been determined to show reasonable potential to exist in the discharge. The discharge of groundwater flows into Ballona Creek which is designated as MUN (Potential) beneficial use. Therefore, the discharge limitations under the "Other Water" column apply to the discharge.

This table lists the specific constituents and effluent limitations applicable to the discharge.

Constituents	Units	Discharge Limitations	
		Daily Maximum	Monthly Average
Total Suspended Solids	mg/L	150	50
Turbidity	NTU	150	50

Constituents	Units	Discharge Limitations	
		Daily Maximum	Monthly Average
BOD <sub>5</sub> 20°C	mg/L	30	20
Oil and Grease	mg/L	15	10
Settleable Solids	ml/L	0.3	0.1
Sulfides	mg/L	1.0	---
Phenols	mg/L	1.0	---
Residual Chlorine	mg/L	0.1	---
Methylene Blue Active Substances (MBAS)	mg/L	0.5	---

### **FREQUENCY OF DISCHARGE**

The discharge will be continuous and is expected to last throughout the life of the building.

### **REUSE OF WATER**

Due to lack of landscaped area at the site, there are no feasible reuse options for the discharge; therefore, the treated groundwater is discharged to storm drain.

