State of California CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION

MONITORING AND REPORTING PROGRAM NO. <u>CI-8032</u> for

HONEYWELL INTERNATIONAL, INC. (Former Honeywell Sepulveda Faclity) (NPDES NO. CAG914001)

I. REPORTING REQUIREMENTS

A. The discharger shall implement this monitoring program on the effective date of coverage under this permit. The discharger shall submit monitoring reports to this Regional Board by the dates in the following schedule:

Reporting Period
January – March
April – June
August 15
July – September
October – December
Annual Summary Report

Report Due
May 15
August 15
November 15
February 15
March 15

- B. The first monitoring report under this Program is due by May 15, 2003. The annual summary report shall contain a discussion of the previous year's effluent monitoring data, as well as graphical and tabular summaries of the data. If there is no discharge during any reporting period, the report shall so state.
- C. All monitoring reports shall include discharge limitations in the Order, tabulated analytical data, the chain of custody form, the analytical laboratory report (including, but not limited to: date and time of sampling, date of analyses, method of analysis, and detection limits), and discharge certification statement.
- D. Before commencing a new discharge, a representative sample of the effluent shall be collected and analyzed for all the constituents listed in Section F.1. of Order No. R4-2002-0107. The test results must meet all applicable discharge limitations. (This requirement does not apply to existing discharge)

II. SAMPLE COLLECTION REQUIREMENTS

- A. Daily samples shall be collected each day.
- B. Weekly samples shall be collected on a representative day of each week.
- C. Monthly samples shall be collected on a representative day of each month.
- D. Quarterly samples shall be collected in February, May, August, and November.
- E. Semi-annual samples shall be collected in May and November.
- F. Annual samples shall be collected in November.

III. EFFLUENT MONITORING REQUIREMENTS

- A. Sampling station(s) shall be established for each point of discharge and shall be located where representative samples of that effluent can be obtained. The discharger shall notify this Regional Board in writing of the location(s) of the sampling stations once established. Provisions shall be made to enable visual inspection before discharge. If oil sheen, debris, and/or other objectionable materials or odors are present, discharge shall not be commenced before compliance with the requirements is demonstrated. All visual observations shall be included in the monitoring report.
- B. If monitoring results indicate an exceedance of a limit contained in Order R4-2002-0107, the discharge shall be terminated and shall only be resumed after remedial measures have been implemented and full compliance with the requirements has been ascertained.
- C. In addition, as applicable, following an effluent limit exceedance, the discharger shall implement the following accelerated monitoring program:
 - 1. Monthly monitoring shall be increased to weekly monitoring.
 - 2. Quarterly monitoring shall be increased to monthly monitoring, and
 - 3. Semi-annually monitoring shall be increased to guarterly.
 - 4. Annually monitoring shall be increased to semi-annually.

If three consecutive accelerated monitoring events demonstrate full compliance with effluent limits, then, the discharger may return to regular monitoring frequency, with the approval of the Executive Officer of the Regional Board.

D. The following shall constitute the discharge monitoring program:

Constituent	<u>Unit</u>	Type of Sample	Minimum Frequency of Analysis
Total Waste Flow Temperature pH Total Suspended Solids	gal/day °F pH units mg/L	totalizer grab grab grab	continuously quarterly quarterly quarterly
Turbidity BOD ₅ @ 20° Settleable Solids Sulfides Oil and Grease	mg/L mg/L ml/L mg/L mg/L	grab grab grab grab grab	quarterly quarterly quarterly quarterly quarterly

1	er Honeywell Sepulveda Facility)			Minimum
	Constituent	<u>Unit</u>	Type of Sample	Frequency of Analysis
	1,1-Dichloroethane	μg/L	grab	monthly
	1,2-Dichloroethane	μg/L	grab	monthly
	1,1-Dichloroethylene	μg/L monthly	grab	
	Carbon Tetrachloride	μg/L monthly	grab	
	1,1,2,2-Tetrachloroethane	μg/L	grab	monthly
	Tetrachloroethylene	μg/L monthly	grab	
	1,2-trans-Dichloroethylene	μg/L	grab	monthly
	1,1,1-Trichloroethane	μg/L	grab	monthly
	1,1,2-Trichloroethane	μg/L	grab	monthly
	Trichloroethylene	μg/L	grab	monthly
	Vinyl chloride	μg/L monthly	grab	·
	1,4-Dioxane	μg/L monthly	grab	
	Benzene	μg/L annually	grab	
	Ethylbenzene	μg/L annually	grab	
	Ethylene dibromide	μg/L aunually	grab	
	Methyl Tertiary Butyl Ether (MTBE)	μg/L annually	grab	
	Toluene	µg/L	grab	annually
	Xylenes	μg/L annually	grab	,
	Total Petroleum Hydrocarbons	μg/L annually	grab	
	Tertiary butyl alcohol (TBA)	μg/L annually	grab	
	N-Nitrosodimethyl amine (NDMA)	μg/L annually	grab	
	Chloroethane	µg/L	grab	annually
	Chloroform	μg/L	grab	annually
	Acetone	μg/L annually	grab	,
	Acrolein	μg/L annually	grab	
	Acrylonitrile	µg/L	grab	

Mr. Benny DeHghi Honeywell International, Inc. (Former Honeywell Sepulveda Facility) CI-8032

annually		
μg/L	grab	annually
	µg/L µg/L µg/L µg/L µg/L	µg/L grab µg/L grab µg/L grab µg/L grab µg/L grab

Constituent	<u>Unit</u>	Type of <u>Sample</u>	Minimum Frequency of Analysis
Methyl bromide	μg/L	grab	annually
Methyl chloride	μg/L	grab	annually
Methylene chloride	μg/L	grab	annually
Methyl ethyl ketone	μg/L	grab	annually
Di-isopropyl ether (DIPE)	μg/L	grab	annually
Napthalene	μg/L	grab	annually
Residual Chlorine	mg/L	grab	annually
Phenols	mg/L	grab	
	annually		
Perchlorate	μg/L annually	grab	
Acute Toxicity	%survival	grab	annually

IV. EFFLUENT TOXICITY TESTING

- A. The discharger shall conduct acute toxicity tests on 100% effluent grab samples by methods specified in 40 CFR Part 136 which cites USEPA's *Methods for Measuring the Acute Toxicity of Effluents to Freshwater and Marine Organisms*. August 1993, (EPA/600/4-90/027F) or a more recent edition. Submission of bioassay results should include the information noted on pages 71-74 of the EPA/600/4-90/027F document.
- B. The fathead minnow, *Pimephales promelas*, shall be used as the test species for fresh water discharges and the topsmelt, *Atherinops affinis*, shall be used as the test species for brackish discharges. The method for topsmelt is found in

Mr. Benny DeHghi CI-8032

Honeywell International, Inc.

(Former Honeywell Sepulveda Facility)

USEPA's Short Term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to West Coast Marine and Estuarine Organisms, First Edition, August 1995 (EPA/600/R-95/136).

C. If the results of the toxicity test yields a survival of less than 90%, then the frequency of analyses shall increase to monthly until at least three test results have been obtained and full compliance with effluent limitations has been demonstrated, after which the frequency of analyses shall revert to annually. Results of toxicity tests shall be included in the first monitoring report following sampling.

V. GENERAL PROVISIONS FOR REPORTING

- A. The discharger shall inform this Regional Board 24 hours before the start of the discharge.
- B. All chemical, bacteriological, and toxicity analyses shall be conducted at a laboratory certified for such analyses by the California Department of Health Services Environmental laboratory Accreditation Program (ELAP) or approved by the Executive Officer. A copy of the laboratory certification shall be provided with the first monitoring report and each time a new and/or renewal is obtained from ELAP.
- C. Samples must be analyzed within allowable holding times as specified in 40 CFR Part 136.3. Proper chain of custody procedures must be followed and a copy shall be submitted with the report.
- D. As required in part I.4 of Order No. R4-2002-0107, the monitoring report shall specify the USEPA analytical method used, the method detection limit, and the minimum level for each pollutant.

VI. NOTIFICATION

- A. The discharger shall notify the Executive Officer in writing prior to discharge of any chemical that may be toxic to aquatic life. Such notification shall include:
 - 1. Name and general composition of the chemical,
 - 2. Frequency of use,
 - 3. Quantities to be used,

Mr. Benny DeHghi CI-8032

Honeywell International, Inc.

(Former Honeywell Sepulveda Facility)

- 4. Proposed discharge concentrations, and
- 5. EPA registration number, if applicable.

No discharge of such chemical shall be made prior to obtaining the Executive Officer's approval.

B. The discharger shall notify the Regional Board via telephone and/or fax within 24 hours of noticing an exceedance above the effluent limits in Order No. R4-2002-0107. The discharger shall provide to the Regional Board within 14 days of observing the exceedance a detailed statement of the actions undertaken or proposed that will bring the discharge into full compliance with the requirements and submit a timetable for correction.

VII. MONITORING FREQUENCIES

Monitoring frequencies may be adjusted by the Executive Officer to a less frequent basis if the Discharger requests same and the request is backed by statistical trends of monitoring data submitted.

Ordered by:	
,	Dennis A. Dickerson
	Executive Officer

Date: February 3, 2003

Jt/