State of California CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION

MONITORING AND REPORTING PROGRAM NO. 8066 for COUNTY OF LOS ANGELES, DEPARTMENT OF PUBLIC WORKS (ALAMITOS BARRIER PROJECT) (NPDES NO. CAG994005)

I. REPORTING REQUIREMENTS

A. The Discharger shall implement this monitoring program on the effective date of coverage under this permit. The Discharger shall submit monitoring reports to this Regional Board by the dates in the following schedule:

Reporting Period
January – March
April – June
August 15
July – September
October – December
Annual Summary Report

Report Due
May 15
August 15
November 15
February 15
March 15

- B. The first monitoring report under this Program is due by February 15, 2004. If there is no discharge during any reporting period, the report shall so state. The annual summary report shall contain a discussion of the previous year's effluent monitoring data, as well as graphical and tabular summaries of the data, and must be received by March 15, of each year.
- C. Each monitoring report shall contain a separate section titled "Summary of Non-Compliance" which discusses the compliance record and corrective actions taken or planned that may be needed to bring the discharge into full compliance with waste discharge requirements. This section shall clearly list all non-compliance with waste discharge requirements, as well as all excursions of effluent limitations.
- D. All monitoring reports shall include discharge limitations in the Order, tabulated analytical data, the chain of custody form, the analytical laboratory report (including, but not limited to: date and time of sampling, date of analyses, method of analysis, and detection limits), and discharge certification statement.
- E. Before commencing a new discharge, a representative sample of the effluent shall be obtained and analyzed for toxicity, and all the constituents listed on Part E.1. and E.2. of Order No. R4-2003-0108. The test results must meet all applicable discharge limitations. [This requirement does not apply to existing discharge.]

T-1

Revised: April 26, 2004

November 14, 2003

II. SAMPLE COLLECTION REQUIREMENTS (AS APPROPRIATE)

- A. Daily samples shall be collected each day.
- B. Weekly samples shall be collected on a representative day of each week.
- C. Monthly samples shall be collected on a representative day of each month.
- D. Quarterly samples shall be collected in February, May, August, and November.
- E. Semi-annual samples shall be collected in May and November.
- F. Annual samples shall be collected in November.

III. EFFLUENT MONITORING REQUIREMENTS

- A. Sampling stations shall be established for each point of discharge and shall be located where representative samples of that effluent can be obtained. The discharger shall notify this Regional Board in writing of the location(s) of the sampling stations once established. Provisions shall be made to enable visual inspection before discharge. If oil sheen, debris, and/or other objectionable materials or odors are present, discharge shall not be commenced before compliance with the requirements is demonstrated. All visual observations shall be included in the monitoring report.
- B. If monitoring result indicates an exceedance of a limit contained in R4-2003-0108, the discharge shall be terminated and shall only be resumed after remedial measures have been implemented and full compliance with the requirements has been ascertained.
- C. In addition, as applicable, following the effluent limit exceedance, the discharger shall implement the following accelerated monitoring program:
 - 1. Monthly monitoring shall be increased to weekly monitoring;
 - 2. Quarterly monitoring shall be increased to monthly monitoring; and
 - 3. Semi-annually monitoring shall be increased to guarterly.
 - 4. Annually monitoring shall be increased to semi-annually.

If three consecutive accelerated monitoring events demonstrate full compliance with effluent limits, then the discharger may return to the regular monitoring frequency, with the approval of the Executive Officer of the Regional Board.

D. The following shall constitute the discharge monitoring program for both the extraction and injection wells.

1. Extraction Wells

Constituent	Unit	Type of	Minimum Frequency of						
		<u>Sample</u>	<u>Analysis</u>						
Total Waste Flow	gal/day	recorder	continuously						
рН	pH units	grab	monthly						
Temperature	°F	grab	monthly						
Total Suspended Solids	mg/L	grab	monthly						
Turbidity	NTU	grab	monthly						
BOD ₅ 20°C	mg/L	grab	monthly						
Settleable Solids	ml/L	grab	monthly						
Residual Chlorine	mg/L	grab	monthly						
Copper	μg/L	grab	annually						
Lead	μg/L	grab	annually						
Total Chromium	μg/L	grab	annually						
1,1-Dichloroethane	μg/L	grab	annually						
1,1-Dichloroethylene	μg/L	grab	annually						
1,1,1-Trichloroethane	μg/L	grab	annually						
1,1,2-Trichloroethane	μg/L	grab	annually						
1,1,2,2-Tetrachloroethane	μg/L	grab	annually						
1,2-Dichloroethane	μg/L	grab	annually						
1,2-Trans Dichloroethylene	μg/L	grab	annually						
Tetrachloroethylene	μg/L	grab	annually						
Trichloroethylene	μg/L	grab	annually						
Carbon Tetrachloride	μg/L	grab	annually						
Vinyl Chloride	μg/L	grab	annually						
Total Trihalomethanes	μg/L	grab	annually						
Benzene	μg/L	grab	annually						
Methyl tertiary butyl ether	μg/L	grab	annually						
Perchlorate	μg/L	grab	annually						
N-Nitrosodimethyl amine	μg/L	grab	annually						
1,4-Dioxane	μg/L	grab	annually						
Acute Toxicity	%	grab	annually						
	survival								

2: <u>Intermittent Injection Wells (Frequency of Analysis):</u>

		Type of	33	34	34	34	34	34	34	34	34	34	35	34	34	35	35	35	34	34	35	35
Constituent	<u>Unit</u>	<u>Sample</u>	Ζ	D	G	J	L	S	V	F	Н	Z	G	Ε	G2	F	H1	H2	F1	H5	J1	K1
Total Waste Flow	gal/day	recorder	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
рН	pH units	grab	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Temperature	°F	grab	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Total Suspended Solids	mg/L	grab	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Turbidity	NTU	grab	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Settleable Solids	ml/L	grab	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
BOD ₅ @ 20°C	mg/L	grab							•						•		•					
Residual Chlorine	mg/L	grab							•						•		•					
Copper	μg/L	grab							•						•		•					
Lead	μg/L	grab							•						•		•					
Total Chromium	μg/L	grab							•						•		•					
1,1-Dichloroethane	μg/L	grab							•						•		•					
1,1-Dichloroethylene	μg/L	grab							•						•		•					
1,1,1-Trichloroethane	μg/L	grab							•						•		•					
1,1,2-Trichloroethane	μg/L	grab							•						•		•					
1,1,2,2,-Tetrachloroethane	μg/L	grab							•						•		•					
1,2-Dichloroethane	μg/L	grab							•						•		•					
1,2-Trans Dichloroethylene	μg/L	grab							•						•		•					
Tetrachloroethylene	μg/L	grab							•						•		•					
Trichloroethylene	μg/L	grab							•						•		•					
Carbon Tetrachloride	μg/L	grab							•						•		•					
Vinyl Chloride	μg/L	grab							•						•		•				<u> </u>	
Total Trihalomethanes	μg/L	grab							•						•		•					
Benzene	μg/L	grab							•						•		•					
Methyl Tertiary Butyl Ether	μg/L	grab							•						•		•					
Perchlorate	μg/L	grab							•						•		•					
N-Nitrosodimethyl amine	μg/L	grab							•						•		•					
1,4-Dioxane	μg/L	grab							•						•		•					
Acute Toxicity	% survival	grab							•						•		•					

^{• =} Once per discharge event

IV. EFFLUENT TOXICITY TESTING

- A. The discharger shall conduct acute toxicity testing tests on 100% effluent grab samples by methods specified in 40 CFR Part 136 which cites USEPA's Methods for Measuring the Acute Toxicity of Effluents and Receiving Water to Freshwater and Marine Organisms, October 2002, (EPA/821-R-02-012) or a more recent edition. Submission of bioassay results should include the information noted on pages 109-113 of the EPA/821-R-02-012 document.
- B. The fathead minnow, Pimephales promelas, shall be used as the test species for fresh water discharges and the topsmelt, Atherinops affinis, shall be used as the test species for brackish discharges. The method for topsmelt is found in USEPA's Short-term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Marine and Estuarine Organisms, Third Edition, October 2002, (EPA/821-R-02-014).
- C. If the results of the toxicity test yields a survival of less than 90%, then the frequency of analyses shall increase to monthly until at least three test results have been obtained and full compliance with effluent limitations has been demonstrated, after which the frequency of analyses shall revert to annually. Results of toxicity tests shall be included in the first monitoring report following sampling.

V. GENERAL PROVISIONS FOR REPORTING

- A. The Discharger shall inform this Regional Board 24 hours before the start of the discharge.
- B. All chemical, bacteriological, and toxicity analyses shall be conducted at a laboratory certified for such analyses by the California Department of Health Services Environmental Laboratory Accreditation Program (ELAP) or approved by the Executive Officer. A copy of the laboratory certification shall be provided with the first monitoring report and each time a new and/or renewal is obtained from ELAP.
- C. Samples must be analyzed within allowable holding time as specified in 40 CFR Part 136.3. Proper chain of custody procedures must be followed and a copy shall be submitted with the report.
- D. As required in part H.4 of Order No. R4-2003-0108, the monitoring report shall specify the USEPA analytical method used, the method detection limit, and the minimum level for each pollutant as applicable.

VI. COMPLIANCE DETERMINATION (AS APPLICABLE)

- A. Compliance with single constituent effluent limitation If the concentration of the pollutant in the monitoring sample is greater than the effluent limitation and greater than or equal to the reported Minimum Level (see Monitoring and Reporting Requirement Section H.4 of Order No. R4-2003-0108), then the Discharger is out of compliance.
- B. Compliance with monthly average limitations In determining compliance with monthly average limitations, the following provisions shall apply to all constituents:
 - If the analytical result of a single sample, monitored monthly, quarterly, semiannually, or annually, does not exceed the monthly average limit for that constituent, the Discharger has demonstrated compliance with the monthly average limit for that month.
 - 2. If the analytical result of a single sample, monitored monthly, quarterly, semiannually, or annually, exceeds the monthly average limit for any constituent, the Discharger shall collect four additional samples at approximately equal intervals during the month. All five analytical results shall be reported in the monitoring report for that month, or 45 days after results for the additional samples were received, whichever is later.

When all sample results are greater than or equal to the reported Minimum Level (see Monitoring and Reporting Requirement Section H.4 of Order No. R4-2003-0108), the numerical average of the analytical results of these five samples will be used for compliance determination.

When one or more sample results are reported as "Not-Detected (ND)" or "Detected, but Not Quantified (DNQ see Monitoring and Reporting Requirement Section H.4 of Order No. R4-2003-0108), the median value of these four samples shall be used for compliance determination. If one or both of the middle values is ND or DNQ, the median shall be the lower of the two middle values.

- 3. In the event of noncompliance with a monthly average effluent limitation, the sampling frequency for that constituent shall be increased to weekly and shall continue at this level until compliance with the monthly average effluent limitation has been demonstrated.
- 4. If only one sample was obtained for the month or more than a monthly period and the result exceed the monthly average, then the Discharger is in violation of the monthly average limit.

- C. Compliance with effluent limitations expressed as a sum of several constituents If the sum of the individual pollutant concentrations is greater than the effluent limitation, then the Discharger is out of compliance. In calculating the sum of the concentrations of a group of pollutants, consider constituents reported as ND or DNQ to have concentrations equal to zero, provided that the applicable ML is used.
- D. Compliance with effluent limitations expressed as a median in determining compliance with a median limitation, the analytical results in a set of data will be arranged in order of magnitude (either increasing or decreasing order); and
 - 1. If the number of measurements (n) is odd, then the median will be calculated as = $X_{(n+1)/2}$, or
 - 2. If the number of measurements (n) is even, then the median will be calculated as = $[X_{n/2} + X_{(n/2)+1}]$, i.e. the midpoint between the n/2 and n/2+1 data points.
- E. In calculating mass emission rates from the monthly average concentrations, use one half of the method detection limit for "Not Detected" (ND) and the estimated concentration for "Detected, but Not Quantified" (DNQ) for the calculation of the monthly average concentration. To be consistent with section VI.B.3., if all pollutants belonging to the same group are reported as ND or DNQ, the sum of the individual pollutant concentrations should be considered as zero for the calculation of the monthly average concentration.

VII. NOTIFICATION

- A. The Discharger shall notify the Executive Officer in writing prior to discharge of any chemical that may be toxic to aquatic life. Such notification shall include:
 - 1. Name and general composition of the chemical,
 - 2. Frequency of use,
 - 3. Quantities to be used.
 - 4. Proposed discharge concentrations, and
 - 5. EPA registration number, if applicable.

No discharge of such chemical shall be made prior to obtaining the Executive Officer's approval.

B. The Discharger shall notify the Regional Board via telephone and/or fax within 24 hours of noticing an exceedance above the effluent limits in Order No. R4-2003-0108. The Discharger shall provide to the Regional Board within 14 days of observing the exceedance a detailed statement of the actions undertaken or

County of Los Angeles, Department of Public Works (Alamitos Barrier Project)
Monitoring and Reporting Program

CI-8066

proposed that will bring the discharge into full compliance with the requirements and submit a timetable for correction.

VIII. MONITORING FREQUENCIES

Monitoring frequencies may be adjusted by the Executive Officer to a less frequent basis if the Discharger requests same and the request is backed by statistical trends of monitoring data submitted.

Ordered by:		Date: April 26, 2004
·	Dennis A. Dickerson	•
	Executive Officer	

/ttw