

**STATE OF CALIFORNIA  
CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD  
LOS ANGELES REGION  
320 West 4<sup>th</sup> Street, Suite 200, Los Angeles, California 90013**

**FACT SHEET  
WASTE DISCHARGE REQUIREMENTS  
FOR  
GATX TANK STORAGE TERMINALS CORPORATION  
(TANK 23570, CARSON TERMINAL)  
HYDROSTATIC TESTING**

**NPDES NO. CAG674001  
CI-8224**

**FACILITY ADDRESS**

2000 E. Sepulveda Blvd.  
Carson, CA 90810

**FACILITY MAILING ADDRESS**

2000 E. Sepulveda Blvd.  
Carson, CA 90810

**PROJECT DESCRIPTION:**

GATX Tank Storage Terminals Corporation (GATX) proposes to discharge hydrostatic test water from Outfall 001 into Dominguez Channel. GATX is in the process of refurbishing Tank 23570 that includes pressure washing with cold water. No chemicals will be used or added during the cleaning process. After washing, all rinsate will be collected in a tank for further treatment. The treated water will be discharged into the sewer. The hydrostatic testing of the tank will only commence after all the rinsate has been evacuated and the tank is clean. Potable domestic water will be used for the hydrostatic test.

**VOLUME AND DESCRIPTION OF DISCHARGE:**

Up to 950,000 gallons (total volume) of hydrostatic water will be discharged into Dominguez Channel (Latitude: 33° 48' 40", Longitude: 118° 13' 30"), a water of the United States above the estuary.

**FREQUENCY OF DISCHARGE:**

The discharge will be intermittent.

**REUSE OF WATER:**

There is no feasible reuse option for the hydrostatic water at the site.