State of California CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION

MONITORING AND REPORTING PROGRAM NO. <u>CI-8303</u> for

Reyes Construction, Inc. (Santa Paula Creek Improvement, Reach 3 Project) (NPDES NO. CAG994001)

I. REPORTING REQUIREMENTS

A. The Discharger shall implement this monitoring program on the effective date of coverage under this permit. The discharger shall submit monitoring reports to this Regional Board by the dates in the following schedule:

Reporting Period	Report Due
January – March	April 15
April – June	July 15
July – September	October 15
October – December	January 15
Annual Summary Report	March 15

- B. The first monitoring report under this Program is due by October 15, 2001. The annual summary report shall contain a discussion of the previous year's effluent monitoring data, as well as graphical and tabular summaries of the data. If there is no discharge during any reporting period, the report shall so state.
- C. All monitoring reports shall include discharge limitations in the Order, tabulated analytical data, the chain of custody form, the analytical laboratory report (including, but not limited to, date and time of sampling, date of analyses, method of analysis, and detection limits), and discharge certification statement.
- D. Before commencing a new discharge, a representative sample shall be analyzed, and test results must meet all discharge limitations in Part E and Attachment A.3.f. of Order No. 97-045.

II. SAMPLE COLLECTION REQUIREMENTS

- A. Daily samples shall be collected each day.
- B. Weekly samples shall be collected on a representative day of each week.
- C. Monthly samples shall be collected on a representative day of each month.
- D. Quarterly samples shall be collected in February, May, August, and November.
- E. Semi-annual samples shall be collected in May and November.
- F. Annual samples shall be collected in November.

CI-8303

III. EFFLUENT MONITORING REQUIREMENTS

- A. Sampling station(s) shall be established for each point of discharge and shall be located where representative samples of that effluent can be obtained. Provisions shall be made to enable visual inspection before discharge. In the event of presence of oil sheen, debris, and/or other objectionable materials or odors, discharge shall not commence until compliance with the requirements is demonstrated. All visual observations shall be included in the monitoring report.
- B. If any constituent exceeds the limit in Order No. 97-045 during any monitoring event, the Discharger shall implement remedial measures to assume full compliance with the requirements. In addition, an effluent limit exceedance, the Discharger shall implement the following accelerated monitoring program, as applicable:
 - 1. Monthly monitoring shall be increased to weekly monitoring.
 - 2. Quarterly monitoring shall be increased to monthly monitoring, and
 - 3. Semi-annually monitoring shall be increased to quarterly.

If three consecutive accelerated monitoring events show full compliance with effluent limits, then, the Discharger may return to regular monitoring frequency, with the approval of the Executive Officer of the Regional Board.

C. The following shall constitute the discharge monitoring program:

Constituent	<u>Unit</u>	Type of Sample	Minimum Frequency of Analysis
Total Waste Flow Temperature pH Total Suspended Solids Turbidity BOD ₅ @ 20° Settleable Solids Sulfides Total Dissolved Solids Sulfate Chloride Nitrogen Phenols Phenolic Compounds (chlorinated)	gal/day °F pH units mg/L mg/L mg/L mg/L mg/L mg/L mg/L mg/L	totalizer grab grab grab grab grab grab grab gra	continuously monthly annually annually

CI-8303

		Type of	Minimum Frequency
Constituent	<u>Unit</u>	Sample Sample	of Analysis
Residual Chlorine	mg/L	grab	annually
Detergents as Methylene Blue			
Active Substances (MBAS)	mg/L	grab	annually
Total Petroleum Hydrocarbons	μg/L	grab	annually
Benzene	μg/L	grab	annually
Toluene	μg/L	grab	annually
Ethylbenzene	μg/L	grab	annually
Xylene	μg/L	grab	annually
Ethylene Dibromide	μg/L	grab	annually
Methyl Tertiary Butyl Ether (MTBE)	μg/L	grab	annually
Carbon tetrachloride	µg/L	grab	annually
Tetrachloroethylene	µg/L	grab	annually
Trichloroethylene	μg/L	grab	annually
1,4-dichlorobenzene	μg/L	grab	annually
1,1-dichloroethane	μg/L	grab	annually
1,2-dichloroethane	μg/L	grab	annually
1,1-dichloroethylene	μg/L	grab	annually
Vinyl chloride	μg/L	grab	annually
Arsenic	μg/L	grab	annually
Cadmium	μg/L	grab	annually
Chromium	μg/L	grab	annually
Copper	μg/L	grab	annually
Lead	μg/L	grab	annually
Mercury	μg/L	grab	annually
Selenium	μg/L	grab	annually
Silver	μg/L	grab	annually
Acute Toxicity	% surviva	al grab	annually

IV. Acute Toxicity shall be conducted by the method specified in "Method for Measuring the Acute Toxicity of Effluents to Freshwater and Marine Organisms" – September 1991, (EPA/600/4-90/027). Submission of bioassay results should include the information noted on pages 70-73 of the "Methods". The fathead minnow (Pimephales promelas) shall be used as the test species. If the results of the toxicity test yields a survival of less than 90%, then the frequency of analyses shall increase to monthly until at least three test results have been obtained and full compliance with effluent limitations has been demonstrated, after which the frequency of analyses shall revert to annually. Results of toxicity tests shall be included in the first monitoring report following sampling.

Mr. Ricardo Jimenez
Reyes Construction, Inc.
(Santa Paula Creek Improvements, Reach 3 Project)
V. GENERAL PROVISIONS FOR REPORTING

CI-8303

- A. The Discharger shall inform this Regional Board 24 hours before the start of the discharge.
- B. All chemical, bacteriological, and toxicity analyses shall be conducted at a laboratory certified for such analyses by the California Department of Health Services Environmental laboratory Accreditation Program (ELAP) or approved by the Executive Officer. A copy of the laboratory certification shall be provided with the first monitoring report and each time a new and/or renewal is obtained from ELAP.
- C. Samples must be analyzed within allowable holding time as specified in 40 CFR Part 136.3. All Quality Assurance/Quality Control (QA/QC) analyses should be performed on the same dates when samples are actually analyzed and documentation shall accompany the laboratory reports.
- D. The monitoring report shall specify the USEPA analytical method used, the Method Detection Limit (MDL) and the Minimum Level⁽¹⁾ (ML) for each pollutant. For the purpose of reporting compliance with numerical limitations, performance goals, and receiving water limitations, analytical data shall be reported with one of the following methods, as the case may be:
 - An actual laboratory measured value for sample results greater than or equal to the ML; or
 - 2. "Detected, but Not Quantified (DNQ)" if results are greater than or equal to the laboratory's MDL but less than the ML. The estimated chemical concentration (2) of the sample shall also be reported; or
 - 3. "Not-Detected (ND)" for sample results less than the laboratory's MDL with the MDL indicated for the analytical method used.

The ML employed for an effluent analysis shall be lower than the permit limit established for a given parameter, unless the Discharger can demonstrate that a particular ML is not attainable and obtains approval for a higher ML from the Executive Officer. At least once a year, the Discharger shall submit a list of the analytical methods employed for each test and associated laboratory QA/QC procedures.

⁽¹⁾ The minimum levels are those published by the State Water Quality Control Board in the Policy for the implementation of Toxic Standards for Inland Surface Water, Enclosed Bays, and Estuaries of California, March 2, 2000. See attached Appendix A.

⁽²⁾ Estimated chemical concentration is the estimated chemical concentration that results from the confirmed detection of the substance by the analytical method below the ML value.

Mr. Ricardo Jimenez Reyes Construction, Inc. (Santa Paula Creek Improvements, Reach 3 Project) CI-8303

VI. NOTIFICATION

- A. The Discharger shall notify the Executive Officer in writing prior to discharge of any chemical that may be toxic to aquatic life. Such notification shall include:
- 1. Name and general composition of the chemical,
- 2. Frequency of use,
- 3. Quantities to be used,
- 4. Proposed discharge concentrations, and
- 5. EPA registration number, if applicable.

No discharge of such chemical shall be made prior to obtaining the Executive Officer's approval.

B. The Discharger shall notify the Regional Board via telephone and/or fax within 24 hours of noticing an exceedance above the effluent limits in Order No. 97-045. The Discharger shall provide to the Regional Board within 14 days of observing the exceedance a detailed statement of the actions undertaken or proposed that will bring the discharge into full compliance with the requirements and submit a timetable for correction.

VII. MONITORING FREQUENCIES

Monitoring frequencies may be adjusted by the Executive Officer to a less frequent basis if the Discharger requests same and the request is backed by statistical trends of monitoring data submitted.

Ordered by:	
ا	Dennis A. Dickerson Executive Officer

Date: <u>August 9, 2001</u>

Jt/