State of California CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION

MONITORING AND REPORTING PROGRAM NO. 8331 for HARRY'S AUTO BODY INC. (NPDES NO. CAG994002)

I. REPORTING REQUIREMENTS

A. The Discharger shall implement this monitoring program on the effective date of coverage under this permit. The Discharger shall submit monitoring reports to this Regional Board by the dates in the following schedule:

Reporting Period	Report Due
January – March	April 15
April – June	July 15
July – September	October 15
October – December	January 15
Annual Summary Report	March 15

- B. The first monitoring report under this Program is due by January 15, 2001. If there is no discharge during any reporting period, the report shall so state. The annual summary report shall contain a discussion of the previous year's effluent monitoring data, as well as graphical and tabular summaries of the data, and must be received by March 15, of each year.
- C. All monitoring reports shall include discharge limitations in the Order, tabulated analytical data, the chain of custody form, the analytical laboratory report (including, but not limited to, date and time of sampling, date of analyses, method of analysis, and detection limits), and discharge certification statement.
- D. Before commencing any discharge, a representative sample shall be analyzed, and the test results must meet all discharge limitations stated in Part E of Order No. 97-043.

II. SAMPLE COLLECTION REQUIREMENTS

- A. Daily samples shall be collected each day.
- B. Weekly samples shall be collected on a representative day of each week.
- C. Monthly samples shall be collected on a representative day of each month.
- D. Quarterly samples shall be collected in February, May, August, and November.
- E. Semi-annual samples shall be collected in May and November.
- F. Annual samples shall be collected in November.

Harry's Auto Body Inc. Monitoring and Reporting Program

III. EFFLUENT MONITORING REQUIREMENTS

- A. Sampling stations shall be established for each point of discharge and shall be located where representative samples of that effluent can be obtained. The discharger shall notify this Regional Board in writing of the location(s) of the sampling stations once established. Provisions shall be made to enable visual inspection before discharge. If oil sheen, debris, and/or other objectionable materials or odors are present, discharge shall not be commenced before compliance with the requirements is demonstrated. All visual observations shall be included in the monitoring report.
- B. If monitoring result indicates an exceedance of a limit contained in Order 97-043, the discharge shall be terminated and shall only be resumed after remedial measures have been implemented and full compliance with the requirements has been ascertained.
- C. In addition, as applicable, following the effluent limit exceedance, the discharger shall implement the following accelerated monitoring program:
 - 1. Monthly monitoring shall be increased to weekly monitoring;
 - 2. Quarterly monitoring shall be increased to monthly monitoring; and
 - 3. Semi-annually monitoring shall be increased to quarterly.

If three consecutive accelerated monitoring events demonstrate full compliance with effluent limits, then the discharger may return to the regular monitoring frequency, with the approval of the Executive Officer of the Regional Board.

D. The following shall constitute the discharge monitoring program:

Constituent	<u>Unit</u>	Type of <u>Sample</u>	Minimum Frequency of <u>Analysis</u>
Total Waste Flow Temperature pH Total Suspended Solids Turbidity BOD₅ 20°C Oil and Grease Settleable Solids Sulfides Phenols	gal/day °F pH units mg/L mg/L mg/L ml/L mg/L mg/L	recorder grab grab grab grab grab grab grab gra	continuously monthly monthly monthly monthly monthly monthly monthly annually
Phenolic Compounds (chlorinated)	μg/L	grab	annually
Residual Chlorine	mg/L	grab	monthly

Harry's Auto Body Inc. Monitoring and Reporting Program

Constituent	<u>Unit</u>	Type of <u>Sample</u>	Minimum Frequency of <u>Analysis</u>
Detergent as Methylene Blue Active Substances	mg/l	grab	monthly
Benzene	µg/L	grab	monthly
Toluene	µg/L	grab	monthly
Ethylbenzene	µg/L	grab	monthly
Xylene	µg/L	grab	monthly
Ethylene Dibromide	µg/L	grab	monthly
Carbon Tetrachloride	µg/L	grab	monthly
Tetrachloroethylene	µg/L	grab	monthly
Trichloroethylene	µg/L	grab	monthly
1,4-dichlorobenzene	µg/L	grab	monthly
1,1-dichloroethene	µg/L	grab	monthly
1,2-dichloroethane	µg/L	grab	monthly
1,1-dichloroethylene	µg/L	grab	monthly
Vinyl Chloride	µg/L	grab	monthly
Methyl Tertiary Butyl Ether	µg/L	grab	monthly
Total Petroleum Hydrocarbons	µg/L	grab	monthly
Arsenic	µg/L	grab	annually
Cadmium	µg/L	grab	annually
Chromium	µg/L	grab	annually
Copper	µg/L	grab	annually
Lead	µg/L	grab	annually
Mercury	µg/L	grab	annually
Selenium	µg/L	grab	annually
Silver	µg/L	grab	annually

IV. GENERAL PROVISIONS FOR REPORTING

- A. The Discharger shall inform this Regional Board 24 hours before the start of the discharge.
- B. Each monitoring report must affirm in writing that: "All analyses were conducted at a laboratory certified for such analyses by the California Department of Health Services, and in accordance with current U.S. EPA guideline procedures or as specified in this Monitoring Program."
- C. Samples must be analyzed within allowable holding time as specified in 40 CFR Part 136.3. All Quality Assurance/Quality Control (QA/QC) analyses should be performed on the same dates when samples are actually analyzed and documentation shall accompany the laboratory reports.

- D. The monitoring report shall specify the USEPA analytical method used, the Method Detection Limit (MDL) and the Minimum Level (ML)⁽²⁾ (Refer to Appendix I) for each pollutant. For the purpose of reporting compliance with numerical limitations, performance goals, and receiving water limitations, analytical data shall be reported with one of the following methods, as the case may be:
 - 1. An actual laboratory measured value for sample results greater than or equal to the ML; or
 - 2. "Detected, but Not Quantified (DNQ)" if results are greater than or equal to the laboratory's MDL but less than the ML. The estimated⁽³⁾ chemical concentration of the sample shall also be reported; or
 - 3. "Not-Detected (ND)" for sample results less than the laboratory's MDL with the MDL indicated for the analytical method used.

The ML employed for an effluent analysis shall be lower than the permit limit established for a given parameter, unless the Discharger can demonstrate that a particular ML is not attainable and obtains approval for a higher ML from the Executive Officer. At least once a year, the Discharger shall submit a list of the analytical methods employed for each test and associated laboratory QA/QC procedures.

V. NOTIFICATION

- A. The Discharger shall notify the Executive Officer in writing prior to discharge of any chemical that may be toxic to aquatic life. Such notification shall include:
 - 1. Name and general composition of the chemical,
 - 2. Frequency of use,
 - 3. Quantities to be used,
 - 4. Proposed discharge concentrations, and
 - 5. EPA registration number, if applicable.

No discharge of such chemical shall be made prior to obtaining the Executive Officer's approval.

⁽²⁾ The minimum levels are those published by the State Water Quality Control Board in the Policy for the Implementation of Toxic Standards for Inland Surface Water, Enclosed Bays, and Estuaries of California, March 2, 2000. See attached Appendix I.

⁽³⁾ Estimated chemical concentration is the estimated chemical concentration that results from the confirmed detection of the substance by the analytical method below the ML value.

Harry's Auto Body Inc. Monitoring and Reporting Program

B.

- The discharger shall notify the Regional Board via telephone and/or fax within 24 hours of noticing an exceedance above the effluent limits in Order No. 97-043. The discharger shall provide to the Regional Board within 14 days of observing the
- discharger shall provide to the Regional Board within 14 days of observing the exceedance a detailed statement of the actions undertaken or proposed that will bring the discharge into full compliance with the requirements and submit a timetable for correction.

VI. MONITORING FREQUENCIES

Monitoring frequencies may be adjusted by the Executive Officer to a less frequent basis if the Discharger requests same and the request is backed by statistical trends of monitoring data submitted.

Ordered by:

Date: November 28, 2001

Dennis A. Dickerson Executive Officer