State of California CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION 320 West 4th Street, Suite 200, Los Angeles

FACT SHEET
WASTE DISCHARGE REQUIREMENTS
FOR
SOUTHERN CALIFORNIA GAS COMPANY
NPDES NO. CAG674001
CI-8406

PROJECT LOCATION

Natural Gas Pipeline Slauson Avenue and Rio Hondo Channel Pico Rivera, CA 90660

FACILITY MAILING ADDRESS

P.O. Box 2300 Chatsworth, CA 91313 Contact: Mr. Edward A. Wiegman

PROJECT DESCRIPTION

Southern California Gas Company proposes to perform hydrostatic testing of a new natural gas distribution pipeline located at Slauson Avenue and Rio Hondo Channel in Pico Rivera. The installation of the pipeline started in April 2002 and the hydrostatic testing will be conducted after the installation. The hydrostatic testing will be performed using municipal water from the City of Pico Rivera.

VOLUME AND DESCRIPTION OF DISCHARGE

Southern California Gas Company proposes to discharge up to 15,000 gallons of wastewater during the hydrostatic testing. The wastewater will be collected in baker tanks and tested prior to discharge to Rio Hondo Channel (Outfall No. 001) located on site (Latitude 33° 58' 32", Longitude 118° 07' 9"). The discharge will flow directly to Rio Hondo River (Los Angeles River Watershed), a water of the United States. See Figure 1, site location map.

FREQUENCY OF DISCHARGE

The discharge will last for approximately one week. The maximum discharge flow rate will not exceed one million gallons per day. The discharge is proposed to begin in May 2002.

REUSE OF WATER

Some of the wastewater from the hydrostatic testing will be used for dust control at the site and the remainder will be discharged to the Rio Hondo River.