

**STATE OF CALIFORNIA
CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
LOS ANGELES REGION**

**MONITORING AND REPORTING PROGRAM NO. CI-8984
FOR
PNEUMO ABEX CORPORATION SITE
3151 WEST FIFTH STREET
OXNARD, CALIFORNIA**

**ORDER NO. R4-2005-0030 (Series No. 030)
FILE NO. 02-150, Site ID NO. 2043600**

I. Monitoring and Reporting Requirements

- A. The Pneumo Abex Corporation (hereinafter Discharger) shall implement this monitoring program on the effective date of this enrollment (December 12, 2005) under Regional Board Order No. R4-2002-0030. Prior to the initiation of quarterly monitoring, monitoring reports shall be submitted monthly by the 15th of the following month, with the first report due January 15, 2006, for the first month of this remediation program. Following that, the first quarterly monitoring report under this program, for January – March 2006, shall be received at the Regional Board by April 15, 2006. Subsequent monitoring reports shall be received at the Regional Board according to the following schedule:

<u>Monitoring Period</u>	<u>Report Due</u>
January – March	April 15
April – June	July 15
July – September	October 15
October – December	January 15
Annual Summary Report	March 1 of each year beginning in 2006

- B. If there is no discharge or injection, during any reporting period, the report shall so state. Monitoring reports must be addressed to the Regional Board, Attention: Information Technology Unit.
- C. By March 1 of each year, starting in 2006, the Discharger shall submit an annual summary report to the Regional Board. The report shall contain both tabular and graphical summaries of the monitoring data obtained during the previous calendar year. In addition, the Discharger shall discuss the compliance record and the corrective actions taken or planned, which may be needed to bring the discharge into full compliance with the waste discharge requirements.
- D. The Discharger shall comply with requirements contained in Section G. of Order No. R4-2002-0030 “*Monitoring and Reporting Requirements*” in addition to the aforementioned requirements.

II. Discharge Monitoring

Seventeen wells will be used to collect groundwater samples for analyses and to determine the groundwater gradient to monitor the migration of injected materials and compounds generated insitu (MW-4A, MW-6A, MW-6B, MW-7A, MW-7B, MW-14A, MW-14B, MW-15A, MW-15B, MW-16A, MW-16B, MW-17B, MW-24A, MW-24B, MW-25A, MW-25B, and a new well [MW-26], to be installed within 30 days of injection, approximately 100 feet downgradient of the former degreaser area, figure 2).

The Discharger shall sample from the following 16 groundwater monitoring wells for baseline groundwater parameters prior to the start of the remediation project (MW-4A, MW-6A, MW-6B, MW-7A, MW-7B, MW-14A, MW-14B, MW-15A, MW-15B, MW-16A, MW-16B, MW-17B, MW-24A, MW-24B, MW-25A, and MW-25B). Monitoring of the Hydrogen Release Compound remediation project shall consist of samples collected from one monitoring well upgradient of the project area (MW-17B), and 16 monitoring wells within and down gradient of the areas of injection (MW-4A, MW-6A, MW-6B, MW-7A, MW-7B, MW-14A, MW-14B, MW-15A, MW-15B, MW-16A, MW-16B, MW-24A, MW-24B, MW-25A, MW-25B, and a new well [MW-26], to be installed within 30 days of injection, approximately 100 feet downgradient of the former degreaser area). Following the collection of baseline groundwater data all of these wells shall be monitored in accordance with the following discharge monitoring program:

<u>CONSTITUENT</u>	<u>UNITS</u>	<u>TYPE OF SAMPLE</u>	<u>MINIMUM FREQUENCY OF ANALYSIS</u>
Total daily injection waste flow	liters/day	In situ	Daily during injection
Chlorinated Volatile Organic Compounds (EPA Method 8260B)	µg/l	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Total Organic Carbon (EPA Method 9060 Modified)	µg/l	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Total dissolved solids and total suspended solids	mg/l	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Specific Conductivity	µmhos/cm	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Turbidity	NTU	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter

PH	pH units	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Oxidation-reduction potential	Millivolts	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Temperature	°F	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Groundwater Elevation	Feet, mean see level (msl) and below ground surface (bgs)	In situ	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Dissolved Oxygen	µg/l	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Major Anions (bromide, chloride, sulfate, nitrate, nitrite, O-phosphate, and sulfide)	µg/l	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Major Cations (barium, calcium, magnesium, potassium and sodium)	µg/l	Grab	<ul style="list-style-type: none"> • Weekly first month • Monthly second and third months • Quarterly thereafter
Metals in priority pollutant scan*	µg/L	Grab	<ul style="list-style-type: none"> • Initial background sample only unless significant concentrations of these analytes are detected

*Priority Pollutants are listed in Attachment A

All groundwater monitoring reports must include, at minimum, the following:

- a. Well identification, date and time of sampling;
- b. Sampler identification, and laboratory identification;
- c. Quarterly observation of groundwater levels, recorded to 0.01 feet mean sea level and groundwater flow direction.

III. CERTIFICATION STATEMENT

Each report shall contain the following completed declaration:

"I certify under penalty of law that this document, including all attachments and supplemental information, was prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of a fine and imprisonment.

Executed on the _____ day of _____

at _____

_____(Signature)

_____(Title)"

IV. MONITORING FREQUENCIES

Specifications in this monitoring program are subject to periodic revisions. Monitoring requirements may be modified or revised by the Executive Officer based on review of monitoring data submitted pursuant to this Order. Monitoring frequencies may be adjusted to a less frequent basis or parameters and locations dropped by the Executive Officer if the Discharger makes a request and the request is backed by statistical trends of monitoring data submitted.

All records and reports submitted in compliance with this Order are public documents and will be made available for inspection during business hours at the office of the California Regional Water Quality Control Board, Los Angeles Region, upon request by interested parties. Only proprietary information, and only at the request of the Discharger will be treated as confidential.

Ordered by: _____
Jonathan Bishop
Executive Officer

Date: December 12, 2005