STATE OF CALIFORNIA CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION

MONITORING AND REPORTING PROGRAM NO. <u>CI-9214</u> FOR

FORMER INFINITY OF VENTURA ENROLLMENT UNDER REGIONAL BOARD ORDER NO. R4-2005-0030: SERIES NO. 066 (VCEHD# C03050)

I. REPORTING REQUIREMENTS

A. Mr. Jack Weber (hereinafter Discharger) shall implement this monitoring program on the effective date (January 4, 2007) under Regional Board Order No. R4-2005-0030. The first monitoring report under this Program is due by April 15, 2007.

Monitoring reports shall be received by the dates according to the following schedule:

Reporting Period	Report Due
January – March	April 15
April – June	July 15
July – September	October 15
October – December	January 15

- B. If there is no discharge or injection during any reporting period, the report shall so state. Monitoring reports must be addressed to the Regional Board, Attention: Information Technology Unit.
- C. By March 1st of each year, the Discharger shall submit an annual summary report to the Regional Board. The report shall contain both tabular and graphical summaries of the monitoring data obtained during the previous calendar year. In addition, the Discharger shall explain the compliance record and the corrective actions taken, or planned, which may be needed to bring the discharge into full compliance with the waste discharge requirements (WDRs).
- D. Each monitoring report shall contain a separate section titled "Summary of Non-Compliance" which discusses the compliance record and the corrective actions taken or planned that may be needed to bring the discharge into full compliance with WDRs. This section shall be located at the front of the report and shall clearly list all non-compliance with discharge requirements, as well as all excursions of effluent limitations.
- E. The Discharger shall comply with requirements contained in Section G of Order No. R4-2005-0030 "Monitoring and Reporting Requirements" in addition to the aforementioned requirements.

II. FENTON'S REAGENT INJECTION MONITORING REQUIREMENTS

The quarterly reports shall contain the following information regarding injection activities:

- 1. Location Map showing injection point(s) of Fenton's Reagent used during the reporting period.
- 2. Boring log with groundwater depth of each injection point or vertical cross-section diagram of injection point(s) indicating the placement of the Fenton's Reagent during the reporting period.
- 3. Written summary including, but not limited to:
 - Depth of injection point(s);
 - Days on which the injection system has been operating;
 - Quantity of Fenton's Reagent injected at each point; and
 - Total amount of Fenton's Reagent injected.

III. GROUNDWATER MONITORING PROGRAM

Groundwater monitoring wells shall not be used as injection wells. Injection wells IW-1 through IW-6 shall be installed. The Discharger shall sample upgradient well (MW-3), source wells (MW-1, MW-2, MW-5, MW-6, and MW-8) and downgradient well (MW-9), to provide groundwater quality information prior to and after the Fenton's Reagent injection. Groundwater from the wells noted above shall be monitored for the duration of the remediation in accordance with the following discharge monitoring program:

CONSTITUENT	UNITS	TYPE OF SAMPLE	MINIMUM FREQUENCY OF ANALYSIS
Total petroleum hydrocarbons as gasoline (TPHg) and as diesel (TPHd)	μg/L ¹	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter
Benzene, Toluene, Ehylbenzene, Xylenes (BTEX)	μg/L	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter

CONSTITUENT		TYPE OF	MINIMUM FREQUENCY OF
OONOTTOENT	UNITS	SAMPLE	ANALYSIS
Benzene, Toluene, Ehylbenzene, Xylenes (BTEX)	μg/L	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter
Methyl tertiary butyl ether (MTBE), Tertiary butyl alcohol (TBA), Tertiary amyl methyl ether (TAME), Di-isopropyl ether (DIPE), Ethyl tertiary butyl ether (ETBE)	μg/L	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter
Ethanol Formaldehyde Acetone	μg/L	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter
Total dissolved solids Chloride Sulfate	mg/L	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter
Oxidation-reduction potential	Milivolts	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter
Dissolved Oxygen	μg/L	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter

CONSTITUENT	UNITS	TYPE OF SAMPLE	MINIMUM FREQUENCY OF ANALYSIS
Total Chromium and Chromium VI ²	μg/L	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter
PH	pH units	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter
Temperature	°F/°C	Grab	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter
Groundwater Elevation	Feet, mean sea level and below ground surface	In situ	 1 week before injection Bi-weekly for the first month following injection Monthly for the next 3 months Quarterly thereafter

μg/l - micrograms per liter

All groundwater monitoring reports must include, at a minimum, the following:

- a. Well identification, date and time of sampling;
- b. Sampler identification, and laboratory identification;
- c. Quarterly observation of groundwater levels, recorded to 0.01 feet mean sea level and groundwater flow direction.

The Discharger is required to monitor for total chromium and chromium six if total chromium is detected in the baseline samples. The monitoring is required only for the well(s) that the total chromium was detected.

Date: January 4, 2007

Mr. Jack Weber Order No. R4-2005-0030 (Series No. 066) Monitoring and Reporting Program No. CI #9214

IV. MONITORING FREQUENCIES

Specifications in this monitoring program are subject to periodic revisions. Monitoring requirements may be modified or revised by the Executive Officer based on review of monitoring data submitted pursuant to this Order. Monitoring frequencies may be adjusted to a less frequent basis or parameters and locations dropped by the Executive Officer if the Discharger makes a request and the request is backed by statistical trends of monitoring data submitted.

V. CERTIFICATION STATEMENT

VI.

Ordered by:

Original signed by

Jonathan S. Bishop Executive Officer

Each report shall contain the following completed declaration:

"I certify under penalty of law that this document, including all attachments and supplemental information, was prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of a fine and imprisonment.

Executed on theday of	at	·
		(Signature)
		(Title)"
PUBLIC DOCUMENTS		
These records and reports are public dinspection during normal business hours a Quality Control Board, Los Angeles Region.		