

California Regional Water Quality Control Board

Los Angeles Region

Recipient of the 2001 Environmental Leadership Award from Keep California Beautiful

Linda S. Adams
Agency Secretary

320 W. 4th Street, Suite 200, Los Angeles, California 90013
Phone (213) 576-6600 FAX (213) 576-6640 - Internet Address: http://www.waterboards.ca.gov/losangeles



March 10, 2009

CERTIFIED MAIL No. 7005 0390 0000 4141 4457 RETURN RECEIPT REQUESTED

Mr. Vince Damasse Santa Clarita Water Division 22722 Soledad Canyon Road Santa Clarita, CA 91350

Dear Mr. Damasse:

REVISON OF COVERAGE UNDER GENERAL NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM AND WASTE DISCHARGE REQUIREMENTS—SANTA CLARITA WATER DIVISION, BOUQUET WELL AND CENTRAL PARK WELL #1, ALONG BOUQUET CANYON ROAD, SANTA CLARITA, CALIFORNIA (NPDES NO. CAG994005, CI-9371)

We received and reviewed the letter from your office dated February 9, 2009, requesting to incorporate discharge from Central Park Well #1 into your existing coverage under the subject General NPDES Permit. You have indicated that Central Park Well #1 is located less than one mile from the Bouquet Well, which is covered under your existing NPDES permit coverage, and the two wells share the same aguifer and have the similar water quality.

Based on the information provided, we have no objections to your request. The proposed discharge of groundwater meets the conditions to be regulated under Order No. R4-2003-0108, General National Pollutant Discharge Elimination System and Waste Discharge Requirements for Discharges of Groundwater from Potable Water Supply Wells to Surface Waters in Coastal Watersheds of Los Angeles and Ventura Counties, adopted by this Board on August 7, 2003.

Enclosed are your Waste Discharge Requirements, which also serve as your NPDES permit, consisting of Order No. R4-2003-0108 and Monitoring and Reporting Program No. CI-9371. The discharge limitations in Part E.1 of Order No. R4-2003-0108 are applicable to your discharge. Discharge from the project drains to the Santa Clara River between West Pier Highway 99 and Blue Cut gaging station; therefore, the discharge limitations in Attachment B.3.d. are applicable to your discharge. Prior to starting discharge, a representative sample of the effluent shall be obtained and analyzed to determine compliance with the discharge limitations.

The Monitoring and Reporting Program requires you to implement the monitoring program on the effective date of coverage under this permit. All monitoring reports should be sent to the Regional Board, <u>ATTN: Information Technology Unit.</u> When submitting monitoring or technical reports to the Regional Board per these requirements, please include a reference to "Compliance File No. CI-9371 and NPDES No. CAG994005", which will assure that the reports are directed to the

California Environmental Protection Agency

Mr. Vince Damasse Santa Clarita Water Division

appropriate file and staff. Also, please do not combine other reports with your monitoring reports. Submit each type of report as a separate document.

-2-

To avoid future annual fees, please submit written notification when the project has been completed and the permit is no longer needed. Be aware that the annual fee covers the fiscal year billing period beginning July 1 and ending June 30, the following year. You will pay full annual fee if your request for termination is made after the beginning of new fiscal year beginning July 1.

We are sending a copy of Order No. R4-2003-0108 only to the applicant. For those on the mailing list, please refer to the Board Order previously sent to you. A copy of the Order will be furnished to anyone who requests it, or it can be obtained at our web site address: http://www.waterboards.ca.gov/losangeles/board_decisions/adopted_orders/.

If you have any questions, please contact Gensen Kai at (213) 576-6651.

Sincerely,

Tracy J. Egoscue La Executive Officer

Enclosures:

Order No. R4-2003-0108 Monitoring and Reporting Program No. CI-9371 Fact Sheet

cc: Environmental Protection Agency, Region 9, Permit Section (WTR-5)

U.S. Army Corps of Engineers

U.S. Fish and Wildlife Services, Division of Ecological Services

NOAA, National Marine Fisheries Service

California Department of Fish and Game, Marine Resources, Region 5

Gary H. Yamamoto, California Department of Public Health, Division of Drinking Water and Environmental Management

Philip Isorena, SWRCB, NPDES Unit

Stephanie Trotter, State Water Resource Control Board

Los Angeles County, Department of Public Works, Waste Management Division

Los Angeles County, Department of Health Services

City Manager, City of Santa Clarita

Jae Kim, Tetratech

STATE OF CALIFORNIA CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION 320 West 4th Street, Suite 200, Los Angeles, California 90013

REVISE FACT SHEET WASTE DISCHARGE REQUIREMENTS FOR SANTA CLARITA WATER DIVISION (BOUQUET WELL & CENTRAL PARK WELL #1)

NPDES NO. CAG994005, SERIES NO. 087 CI-9371

FACILITY ADDRESS

FACILITY MAILING ADDRESS

Along Bouquet Canyon Road Santa Clarita, CA

22722 Soledad Canyon Road Santa Clarita, CA 91350

PROJECT DESCRIPTION:

The Santa Clarita Division (Discharger) operates an agricultural well, Central Park Well #1, located on the northeast corner of Bouquet Canyon Road and the north entrance to Central Park (see Figure 1). The Discharger plans to re-develop and convert the Central Park Well #1 to a drinking water well. The Discharger requests the Regional Board to revise its existing coverage under the subject General NPDES Permit for its Bouquet Well to include the Central Park Well #1.

VOLUME AND DESCRIPTION OF DISCHARGE:

Up to 2.2 million gallons per day (mgd) of groundwater will be discharged during pumping and aquifer tests for a period of about 7 days. Discharge from Bouquet Well flows to the outfall located at Latitude: 34° 25′ 53″, Longitude: 118° 32′ 01″. Discharge from Central Park Well #1 flows to the outfall located at Latitude: 34° 26′ 08″, Longitude: 118° 31′ 15″. Discharges from both wells drain to Santa Clara River, a water of the United States. The high rate of discharge is necessary to properly develop the well during the short-term tests. The discharger will need up to eight months to complete the project.

APPLICABLE EFFLUENT LIMITATIONS

Based on the information provided, the analytical data did not show reasonable potential for toxics to exist in the groundwater above the Screening Levels for Potential Pollutants of Concern in potable groundwater in Attachment A. Therefore, the effluent limits for toxic compounds in Section E.2 are not applicable to your discharge. The discharge flows to Santa Clara River (between Bouquet Canyon Road Bridge and West Pier Highway 99). Therefore, the discharge limitations in Attachment B.3.c. are applicable to the discharge.

This Table lists the specific constituents and effluent limitations applicable to the discharge.


Constituents	Units	Discharge Limitations	
Constituents		Daily Maximum	Monthly Average
Total Suspended Solids	mg/L	150	50
Turbidity	NTU	150	50
BOD₅ 20°C	mg/L	30	20
Settleable Solids	ml/L	0.3	0.1
Residual Chlorine	mg/L	0.1	,
TDS	mg/L	1000	
Sulfate	mg/L	300	.~
Chloride	mg/L	100	
Boron	mg/L	1.5	
Nitrate-nitrogen plus nitrite-nitrogen	mg/L	1.0	

FREQUENCY OF DISCHARGE:

The discharge from the facility will be intermittent.

REUSE OF WATER:

Offsite disposal of treated wastewater is not feasible due to the high cost of disposal. Discharge to the sewer is not feasible. The property and the immediate vicinity have no landscaped areas that require irrigation. Since there are no feasible reuse options, the groundwater will be discharged to the surface water in accordance with the attached Order.



STATE OF CALIFORNIA CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION

REVISED MONITORING AND REPORTING PROGRAM NO. CI-9371 FOR

SANTA CLARITA WATER DIVISION (BOUQUET WELL & CENTRAL PARK WELL #1) (NPDES NO. CAG994005, SERIES NO. 087)

I. REPORTING REQUIREMENTS

A. The discharger shall implement this monitoring program on the effective date of this permit. The discharger shall submit monitoring reports to the Regional Board by the dates in the following schedule:

Reporting Period	Report Due
January - March	May 15
April - June	August 15
July - September	November 15
October - December	February 15

- B. The first monitoring report under this Program is due by May 15, 2009. If there is no discharge during any reporting period, the report shall so state.
- C. All monitoring reports shall include the discharge limitations in the Order, tabulated analytical data, the chain of custody form, and the laboratory report (including but not limited to date and time of sampling, date of analyses, method of analysis and detection limits).
- D. Each monitoring report shall contain a separate section titled "Summary of Non-compliance" which discusses the compliance record and corrective action taken or planned that may be needed to bring the discharge into full compliance with waste discharge requirements. This section shall clearly list all non-compliance with waste discharge requirements, as well as all excursions of effluent limitations.
- E. Before commencing a new discharge, a representative sample of the effluent shall be collected and analyzed for all the constituents listed in the Fact Sheet and the test results must meet all applicable limitations of Order No. R4-2003-0108.

II. SAMPLE COLLECTION REQUIREMENTS (AS APPROPRIATE)

- A. Daily samples shall be collected each day.
- B. Weekly samples shall be collected on a representative day of each week.
- C. Monthly samples shall be collected on a representative day of each month.
- D. Quarterly samples shall be collected in February, May, August, and November.
- E. Semi-annual samples shall be collected in May and November.
- F. Annual samples shall be collected in November.

III. EFFLUENT MONITORING REQUIREMENTS

- A. Sampling station(s) shall be established at the discharge point and shall be located where representative samples of the effluent can be obtained. Provisions shall be made to enable visual inspections before discharge. In the event of presence of oil sheen, debris, and/or other objectionable materials or odors, discharge shall not commence until compliance with the requirements is demonstrated. All visual observations shall be included in the monitoring report.
- B. If monitoring result indicate an exceedance of a limit contained in Order R4-2003-0108, the discharge shall be terminated and shall only be resumed after remedial measures have been implemented and full compliance with the requirements has been ascertained.
- C. In addition, as applicable, following an effluent limit exceedance, the discharger shall implement the following accelerated monitoring program:
 - 1. Monthly monitoring shall be increased to weekly monitoring,
 - 2. Quarterly monitoring shall be increased to monthly monitoring,
 - 3. Semi-annually monitoring shall be increased to quarterly, and
 - 4. Annual monitoring shall be increased to semi-annually.

If three consecutive accelerated monitoring events demonstrate full compliance with effluent limits, the discharger may return to the regular monitoring frequency, with the approval of the Executive Officer of the Regional Board.

D. The following shall constitute the discharge monitoring program:

Constituent	Unit	Sample Type	Minimum Frequency of Analysis
Flow	gal/day	totalizer	Continuously*
pН	pH units	grab	once per discharge event**
Temperature	°F	grab	once per discharge event**
Total Suspended Solids	mg/L	grab	once per discharge event**
Turbidity	NTU	grab	once per discharge event**
BOD₅20°C	mg/L	grab	once per discharge event**
Settleable Solids	ml/L	grab	once per discharge event**
Residual Chlorine	mg/L	grab	once per discharge event**
TDS	mg/L	grab	once per discharge event**
Sulfate	mg/L	grab	once per discharge event**
Chloride	mg/L	grab	once per discharge event**
Boron	mg/L	grab	once per discharge event**
Nitrogen	mg/L	grab	once per discharge event**
Perchlorate	μg/L	grab	annually
1-4 Dioxane	μg/L	grab	annually
N-Nitrosodimethylamine	μg/L	grab	annually
Acute Toxicity	% survival	grab	annually

- * Record the monthly total flow and report the calculated daily average flow and monthly flow in the quarterly and annual reports, as appropriate.
- ** If the discharge event for a well or site is continuous or intermittent for more than 30 days, the minimum frequency of analysis becomes monthly.

IV. EFFLUENT TOXICITY TESTING

- A. The discharger shall conduct acute toxicity testing tests on 100% effluent grab samples by methods specified in 40 CFR Part 136 which cites USEPA's *Methods for Measuring the Acute Toxicity of Effluents and Receiving Water to Freshwater and Marine Organisms*, October 2002, (EPA/821-R-02-012) or a more recent edition. Submission of bioassay results should include the information noted on pages 109-113 of the EPA/821-R-02-012 document.
- B. The fathead minnow, *Pimephales promelas*, shall be used as the test species for fresh water discharges and the topsmelt, *Atherinops affinis*, shall be used as the test species for brackish discharges. The method for topsmelt is found in USEPA's *Short-term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to West Coast Marine and Estuarine Organisms*, First Edition, August 1995, (EPA/600-R-95-136).

C. If the results of the toxicity test yields a survival of less than 90%, then the frequency of analyses shall increase to monthly until at least three test results have been obtained and full compliance with effluent limitations has been demonstrated, after which the frequency of analyses shall revert to annually. Results of toxicity tests shall be included in the first monitoring report following sampling.

V. GENERAL PROVISIONS FOR REPORTING

- A. The discharger shall inform this Regional Board 24 hours before the start of the discharge.
- B. All chemical, bacteriological, and toxicity analyses shall be conducted at a laboratory certified for such analyses by the California Department of Public Health Environmental Laboratory Accreditation Program (ELAP) or approved by the Executive Officer. A copy of the laboratory certification shall be provided with the first monitoring report and each time a new and/or renewal is obtained from ELAP.
- C. Samples must be analyzed within allowable holding time limits as specified in 40 CFR Part 136.3. Proper chain of custody procedures must be followed and a copy shall be submitted with the report.
- D. As required in part H of Order No. R4-2003-0108, the monitoring report shall specify the USEPA analytical method used, the Method Detection Limit and the Minimum Level for each pollutant.

VI. COMPLIANCE DETERMINATION (AS APPLICABLE)

- A. Compliance with single constituent effluent limitation If the concentration of the pollutant in the monitoring sample is greater than the effluent limitation and greater than or equal to the reported Minimum Level (see Monitoring and Reporting Requirements Section H.4. of Order R4-2003-0108), then the Discharger is out of compliance.
- B. Compliance with monthly average limitations In determining compliance with monthly average limitations, the following provisions shall apply to all constituents:
 - a. If the analytical result of a single sample, monitored monthly, quarterly, semi-annually, or annually, does not exceed the monthly average limit for that constituent, the Discharger has demonstrated compliance with the monthly average limit for that month.
 - b. If the analytical result of a single sample, monitored monthly, quarterly, semi-annually, or annually, exceeds the monthly average limit for any constituent, the Discharger shall collect four additional samples at approximately equal intervals during the month. All five analytical results shall be reported in the monitoring report for that

month, or 45 days after results for the additional samples were received, whichever is later.

When all sample results are greater than or equal to the reported Minimum Level (see Monitoring and Reporting Requirements Section H.4. of Order R4-2003-0108), the numerical average of the analytical results of these five samples will be used for compliance determination.

When one or more sample results are reported as "Not-Detected (ND)" or "Detected, but Not Quantified (DNQ)" (see Monitoring and Reporting Requirements Section H.4. of Order R4-2003-0108), the median value of these four samples shall be used for compliance determination. If one or both of the middle values is ND or DNQ, the median shall be the lower of the two middle values.

- c. In the event of noncompliance with a monthly average effluent limitation, the sampling frequency for that constituent shall be increased to weekly and shall continue at this level until compliance with the monthly average effluent limitation has been demonstrated.
- d. If only one sample was obtained for the month or more than a monthly period and the result exceed the monthly average, then the Discharger is in violation of the monthly average limit.
- C. Compliance with effluent limitations expressed as a sum of several constituents If the sum of the individual pollutant concentrations is greater than the effluent limitation, then the Discharger is out of compliance. In calculating the sum of the concentrations of a group of pollutants, consider constituents reported as ND or DNQ to have concentrations equal to zero, provided that the applicable ML is used.
- D. Compliance with effluent limitations expressed as a median in determining compliance with a median limitation, the analytical results in a set of data will be arranged in order of magnitude (either increasing or decreasing order); and
 - a. If the number of measurements (n) is odd, then the median will be calculated as = $X_{(n+1)/2}$, or
 - b. If the number of measurements (n) is even, then the median will be calculated as = $[X_{n/2} + X_{(n/2)+1}]$, i.e. the midpoint between the n/2 and n/2+1 data points.
- E. In calculating mass emission rates from the monthly average concentrations, use one half of the method detection limit for "Not Detected" (ND) and the estimated concentration for "Detected, but Not Quantified" (DNQ) for the calculation of the monthly average concentration. To be consistent with section VI.C., if all pollutants belonging to the same

group are reported as ND or DNQ, the sum of the individual pollutant concentrations should be considered as zero for the calculation of the monthly average concentration.

VII. NOTIFICATION

- A. The discharger shall notify the Executive Officer in writing prior to discharge of any chemical which may be toxic to aquatic life. Such notification shall include:
 - 1. Name and general composition of the chemical,
 - 2. Frequency of use,
 - 3. Quantities to be used,
 - 4. Proposed discharge concentrations and,
 - 5. EPA registration number, if applicable.

No discharge of such chemical shall be made prior to obtaining the Executive Officer's approval.

B. The discharger shall notify the Regional Board via telephone and/or fax within 24 hours of noticing an exceedance above the effluent limits in Order No. R4-2003-0108. The discharger shall provide to the Regional Board within 14 days of observing the exceedance a detailed statement of the actions undertaken or proposed that will bring the discharge into full compliance with the requirements and submit a timetable for correction.

VIII. MONITORING FREQUENCIES

Monitoring frequencies may be adjusted by the Executive Officer to a less frequent basis if the discharger makes a request and the request is justified by statistical trends of monitoring data submitted. However, monitoring frequency may also increase based on site-specific conditions.

Ordered by:

Tracy J. Egoscue

Executive Officer

Date:

March 10, 2009