

STATE OF CALIFORNIA
CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
LOS ANGELES REGION
MONITORING AND REPORTING PROGRAM NO. CI-9381
FOR
NIX AUTOMOTIVE
ENROLLMENT UNDER REGIONAL BOARD
ORDER NO. R4-2007-0019
SERIES NO. 050

I. REPORTING REQUIREMENTS

- A. Nix Automotive (hereinafter Discharger) shall implement this monitoring program on the effective date of this enrollment under Regional Board Order No. R4-2007-0019.

Monitoring reports shall be received by the due dates in the following schedule:

<u>Reporting Period</u>	<u>Report Due</u>
January – March	April 15
April – June	July 15
July – September	October 15
October – December	January 15

The first monitoring report under this monitoring program is due by April 15, 2008.

- B. If there is no discharge or injection during any reporting period, the report shall so state. Monitoring reports must be addressed to the Regional Board, Attention: Information Technology Unit.
- C. By January 30 of each year, beginning January 30, 2008, the Discharger shall submit an annual summary report to the Regional Board. The report shall contain both tabular and graphical summaries of the monitoring data obtained during the previous calendar year. In addition, the Discharger shall explain the compliance record and the corrective actions taken or planned, which may be needed to bring the discharge into full compliance with the waste discharge requirements (WDR).
- D. Each monitoring report shall contain a separate section titled "Summary of Non-Compliance" which discusses the compliance record and the corrective actions taken or planned that may be needed to bring the discharge into full compliance with the WDR. This section shall be located at the front of the report and shall clearly list all non-compliance with discharge requirements, as well as all excursions of effluent limitations.

E. In addition to the aforementioned requirements, the Discharger shall comply with requirements contained in Section G of Order No. R4-2007-0019 "Monitoring and Reporting Requirements".

II. DISCHARGE MONITORING REQUIREMENTS

The quarterly reports shall contain the following information regarding the injection activities. If there is no injection during any reporting period, the report shall so state:

1. Location map showing injection points.
2. Written summary defining:
 - Depth of injection points;
 - Quantity of the hydrogen peroxide injected at each injection point; and
 - Total amount of hydrogen peroxide injected at the site.
3. Quarterly visual inspection at each injection well shall be conducted to evaluate the well casing integrity after each injection. The quarterly report shall include a summary of the visual inspection.
4. To avoid groundwater monitoring network reduction, data bias, and well screen clogging or alteration, no groundwater monitoring wells shall be used as injection points during the proposed injection. Separate injection points/wells must be installed at the Site for the proposed injection.

III. GROUNDWATER MONITORING PROGRAM

A groundwater-monitoring program shall be designed to detect and evaluate impacts associated with the injection activities. The monitoring well network must include MW-1 and MW-9 as background wells; MW-10 and MW-8 as source wells; and MW-3 and MW-4 as downgradient wells. These sampling stations shall not be changed and any proposed change of monitoring locations shall be identified and approved by the Regional Board Executive Officer (Executive Officer) prior to their use. The Discharger shall conduct a baseline sampling from all wells onsite one or two weeks prior to the proposed injection and regular sampling with the required frequencies from all the monitoring wells in the monitoring network for the following constituents:

<u>CONSTITUENT</u>	<u>UNITS</u> ¹	<u>TYPE OF SAMPLE</u>	<u>MINIMUM FREQUENCY OF ANALYSIS</u>
pH ²	pH units	grab	Quarterly
Temperature ²	°F	grab	Quarterly
Oxidation-reduction potential ²	Millivolts	grab	Quarterly

Specific conductivity ²	µmhos/cm	grab	Quarterly
Ferrous iron	µg/L	grab	Quarterly
Dissolved Oxygen ²	µg/L	grab	Quarterly
Total Petroleum Hydrocarbons (as gasoline)	µg/L	grab	Quarterly
Benzene	µg/L	grab	Quarterly
Ethylbenzene	µg/L	grab	Quarterly
Toluene	µg/L	grab	Quarterly
Total xylenes	µg/L	grab	Quarterly
MTBE	µg/L	grab	Quarterly
TBA	µg/L	grab	Quarterly
TAME	µg/L	grab	Quarterly
DIPE	µg/L	grab	Quarterly
ETBE	µg/L	grab	Quarterly
Ethanol	µg/L	grab	Quarterly
Methane	µg/L	grab	Quarterly
Formaldehyde	µg/L	grab	Quarterly
Acetates	µg/L	grab	Quarterly
Total organic carbon	µg/L	grab	Quarterly
Total dissolved solids	mg/l	grab	Quarterly
Arsenic	mg/L	grab	Quarterly
Bromide	mg/L	grab	Quarterly
Sulfate	mg/L	grab	Quarterly
Chloride	mg/L	grab	Quarterly
Boron	mg/L	grab	Quarterly
Sodium	mg/L	grab	Quarterly
Carbon dioxide	mg/L	grab	Quarterly
Manganese	µg/L	grab	Quarterly
Total iron	µg/L	grab	Quarterly

Alkalinity	µg/L	grab	Quarterly
Total chromium ³	µg/L	grab	Quarterly
Chromium six ³	µg/L	grab	Quarterly

¹ mg/L: milligrams per liter; µg/L: micrograms per liter; µmhos/cm: microohms per centimeter; °F: degree Fahrenheit.

² Field instrument may be used to measure this parameter.

³ The Discharger is required to monitor for total chromium and chromium six in the baseline, second and fourth quarterly sampling. If detected at any of these sampling events, the total chromium and chromium six must be monitored quarterly thereafter.

All groundwater monitoring reports must include, at a minimum, the following:

- a. Well identification, date and time of sampling;
- b. Sampler identification, and laboratory identification;
- c. Quarterly observation of groundwater levels, recorded to 0.01 feet mean sea level and groundwater flow direction.

IV. MONITORING FREQUENCIES

Specifications in this monitoring program are subject to periodic revisions. Monitoring requirements may be modified or revised by the Executive Officer based on review of monitoring data submitted pursuant to this Order. Monitoring frequencies may be adjusted to a less frequent basis or parameters and locations dropped by the Executive Officer if the Discharger makes a request and the request is backed by statistical trends of monitoring data submitted.

V. CERTIFICATION STATEMENT

Each report shall contain the following completed declaration:

"I certify under penalty of law that this document, including all attachments and supplemental information, was prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of a fine and imprisonment.

Executed on the _____ day of _____ at _____.

_____ (Signature)

_____ (Title)"

Nix Automotive
Monitoring and Reporting Program No. CI-9381

UST File No. 913640516
Order No. R4-2007-0019

All records and reports submitted in compliance with this Order are public documents and will be made available for inspection during business hours at the office of the California Regional Water Quality Control Board, Los Angeles Region, upon request by interested parties. Only proprietary information, and only at the request of the Discharger, will be treated as confidential.

Ordered by:



Tracy J. Egoscue
Executive Officer

Date: February 25, 2008