

California Regional Water Quality Control Board Los Angeles Region

. Matthew Rodriquez Secretary for Environmental Protection 320 West Fourth Street, Suite 200, Los Angeles, California 90013 (213) 576-6600 • Fax (213) 576-6640 http://www.waterboards.ca.gov/losangeles



Edmund G. Brown Jr. Governor

January 20, 2012

Mr. James B. Glancy City of Lakewood Department of Water Resources 5050 Clark Avenue Lakewood, CA 90712 Certified Mail Return Receipt Requested Claim No. 7004 1160 0002 8028 1871

COVERAGE UNDER GENERAL NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM AND WASTE DISCHARGE REQUIREMENTS—CITY OF LAKEWOOD-DEPARTMENT OF WATER RESOURCES, WELL NO. 22, 3310 CANDLEWOOD STREET, LAKEWOOD, CALIFORNIA (NPDES NO. CAG994005, CI—9786)

Dear Mr. Glancy:

We have completed our review of your application for a permit to discharge wastewater under the National Pollutant Discharge Elimination System (NPDES).

Based on the information provided, the proposed discharge of groundwater meets the conditions to be regulated under Order No. R4-2003-0108, *General National Pollutant Discharge Elimination System and Waste Discharge Requirements for Discharges of Groundwater from Potable Water Supply Wells to Surface Waters in Coastal Watersheds of Los Angeles and Ventura Counties*, adopted by this Board on August 7, 2003.

Enclosed are your Waste Discharge Requirements, which also serve as your NPDES permit, consisting of Order No. R4-2003-0108 and Monitoring and Reporting Program No. CI-9786. Since the groundwater analytical data provided meets the screening criteria, full enrollment under this general permit is authorized and the discharge limitations in Part E.1. of Order No. R4-2003-0108 are applicable to your discharge. The wastewater discharge flows into Los Cerritos Channel, thence to the Alamitos Bay. Therefore, the discharge limitations in Attachment B of Order No. R4-2003-0108 are not applicable to your discharge.

The Monitoring and Reporting Program requires you to implement the monitoring program on the effective date of coverage under this permit. All monitoring reports should be sent to the Regional Board, <u>ATTN: Information Technology Unit.</u> When submitting monitoring or technical reports to the Regional Board per these requirements, please include a reference to "Compliance File No. CI-9786 and NPDES No. CAG994005", which will assure that the reports are directed to the appropriate file and staff. Also, please do not combine other reports with your monitoring reports. Submit each type of report as a separate document.

California Environmental Protection Agency

Our mission is to preserve and enhance the quality of California's water resources for the benefit of present and future generations.

Mr. James B. Glancy -2-City of Lakewood-Department of Water Resources (Well No. 22) CI-9786

To avoid paying future annual fees, please submit written request for termination of your enrollment under the general permit in a separate letter, when your project has been completed and the permit is no longer needed.

We are sending a copy of Order No. R4-2003-0108 only to the applicant. For those on the mailing list, please refer to the Board Order sent to you previously. A copy of the Order will be furnished to anyone who requests it, or it can be obtained at our website address at *http://www.waterboards.ca.gov/losangeles/board decisions/adopted orders/*

If you have any questions, please contact Vilma Correa at (213) 576-6794.

Sincerely,

Samuel Orion Samuel Unger, P.E.

Executive Officer

Enclosures:

General NPDES No. CAG994005, Order No. R4-2003-0108 Fact Sheet Monitoring and Reporting Program No. CI-9786

CC:

Environmental Protection Agency, Region 9, Permit Section (WTR-5) State Water Resources Control Board, NPDES_Wastewater@waterboard.ca.gov U.S. Army Corps of Engineers

U.S. Fish and Wildlife Services, Division of Ecological Services NOAA, National Marine Fisheries Service

California Department of Fish and Game, Marine Resources, Region 5 Leah Walker, California Department of Public Health,

Division of Drinking Water and Environmental Management Los Angeles County, Department of Public Works, Environmental Program Division Los Angeles County, Department of Public Works, Flood Control Division Los Angeles County, Department of Health Services Jae Kim, Tetratech

Leon delos Reyes, City of Lakewood, Department of Water Resources

/vbc

California Environmental Protection Agency

🗳 Recycled Paper

Our mission is to preserve and enhance the quality of California's water resources for the benefit of present and future generations.

STATE OF CALIFORNIA CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION 320 West 4th Street, Suite 200, Los Angeles, California 90013

FACT SHEET WASTE DISCHARGE REQUIREMENTS FOR CITY OF LAKEWOOD-DEPARTMENT OF WATER RESOURCES (WELL NO. 22)

(ORDER NO. R4-2003-0108, SERIES NO. 122) NPDES NO. CAG994005

CI-9786

FACILITY ADDRESS

3310 Candlewood Street Lakewood, CA 92712

FACILITY MAILING ADDRESS

5050 Clark Avenue Lakewood, CA 90712

PROJECT DESCRIPTION:

City of Lakewood, Department of Water Resources (City of Lakewood), proposes to discharge groundwater associated with well redevelopment and pumping tests from Well No. 22, located at 3310 Candlewood Street, Lakewood. A desilting tank will be installed to allow sediment to settle out from the groundwater before discharging. The well redevelopment and aquifer tests will be completed within three weeks.

VOLUME AND DESCRIPTION OF DISCHARGE:

Approximately 960,000 gallons per day (gpd) of groundwater will be discharged to the stormdrain located along Downey Avenue (Latitude: 33° 51' 154", Longitude: 118° 09' 60"). The discharge from the stormdrain flows into Los Cerritos Channel, thence into the Alamitos Bay, waters of the United States. The site location map is shown in Figure 1.

APPLICABLE EFFLUENT LIMITATIONS

Based on the information provided in the NPDES Application Supplemental Requirements, the following constituents listed in the Table below have been determined to show reasonable potential to exist in your discharge. The discharge of groundwater flows into Los Cerritos Channel, thence into the Alamitos Bay. (between Firestone Boulevard and San Gabriel River Estuary). Therefore, the discharge limitations in Attachment B of Order No. R4-2003-0108 is not applicable to your discharge.

January 20, 2012

This table below lists the specific constituents and effluent limitations applicable to the discharge.


| | | Discharge Limitations | | |
|------------------------|-------|-----------------------|-----------------|--|
| Constituents | Units | Daily Maximum | Monthly Average | |
| Total Suspended Solids | mg/L | 150 | 50 | |
| Turbidity | NTU | 150 | 50 | |
| BOD₅ 20°C | mg/L | 30 | 20 | |
| Settleable Solids | ml/L | 0.3 | 0.1 | |
| Residual Chlorine | mg/L | 0.1 | | |

FREQUENCY OF DISCHARGE:

The discharge will be intermittent and will last approximately three weeks.

REUSE OF WATER:

Due to lack of landscaping area at the site for irrigation use and the inability to economically transport the water offsite for reuse, an alternative method of disposal is not feasible. Therefore, the groundwater will be discharged to the Los Cerritos Channel in compliance with the requirements of the attached order.



CI-9786

CITY OF LAKEWOOD-DEPARTMENT OF WATER RESOURCES (WELL NO. 22)

STATE OF CALIFORNIA CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD LOS ANGELES REGION

MONITORING AND REPORTING PROGRAM NO. CI-9786 FOR CITY OF LAKEWOOD-DEPARTMENT OF WATER RESOURCES (WELL NO. 22)

(ORDER NO. R4-2003-0108, SERIES NO. 122) (NPDES NO. CAG994005)

REPORTING REQUIREMENTS

A. The discharger shall implement this monitoring program on the effective date of this permit. The discharger shall submit monitoring reports to the Regional Board by the dates in the following schedule:

Reporting Period

Report Due

January - March April - June July - September October - December May 15 August 15 November 15 February 15

- B. The first monitoring report under this Program is due by May 15, 2012. If there is no discharge during any reporting period, the report shall so state.
- C. All monitoring reports shall include the discharge limitations in the Order, tabulated analytical data, the chain of custody form, and the laboratory report (including but not limited to date and time of sampling, date of analyses, method of analysis and detection limits).
- D. Each monitoring report shall contain a separate section titled "Summary of Non-compliance" which discusses the compliance record and corrective action taken or planned that may be needed to bring the discharge into full compliance with waste discharge requirements. This section shall clearly list all non-compliance with waste discharge requirements, as well as all excursions of effluent limitations.
- E. Before commencing a new discharge, a representative sample of the effluent shall be collected and analyzed for all the constituents listed in the Fact Sheet and the test results must meet all applicable limitations of Order No. R4-2003-0108.

January 20, 2012

CAG994005

II. SAMPLE COLLECTION REQUIREMENTS (AS APPROPRIATE)

- A. Daily samples shall be collected each day.
- B. Weekly samples shall be collected on a representative day of each week.
- C. Monthly samples shall be collected on a representative day of each month.
- D. Quarterly samples shall be collected in February, May, August, and November.
- E. Semi-annual samples shall be collected in May and November.
- F. Annual samples shall be collected in November.

III. EFFLUENT MONITORING REQUIREMENTS

- A. Sampling station(s) shall be established at the discharge point and shall be located where representative samples of the effluent can be obtained. Provisions shall be made to enable visual inspections before discharge. In the event of presence of oil sheen, debris, and/or other objectionable materials or odors, discharge shall not commence until compliance with the requirements is demonstrated. All visual observations shall be included in the monitoring report.
- B. If monitoring results indicate an exceedance of a limit contained in Order R4-2003-0108, the discharge shall be terminated and shall only be resumed after remedial measures have been implemented and full compliance with the requirements has been ascertained.
 - In addition, as applicable, following an effluent limit exceedance, the discharger shall implement the following accelerated monitoring program:
 - 1. Monthly monitoring shall be increased to weekly monitoring,
 - 2. Quarterly monitoring shall be increased to monthly monitoring,
 - 3. Semi-annually monitoring shall be increased to quarterly, and
 - 4. Annual monitoring shall be increased to semi-annually.

If three consecutive accelerated monitoring events demonstrate full compliance with effluent limits, the discharger may return to the regular monitoring frequency, with the approval of the Executive Officer of the Regional Board.

D. The following shall constitute the discharge monitoring program:

| Constituent | Units | | Minimum Frequency of Analysis |
|-------------|----------|-----------|----------------------------------|
| Flow | gal/day | totalizer | continuously ¹ |
| рН | pH units | grab | monthly |

1

C.

Record the monthly total flow and report the calculated daily average flow and monthly flow in the quarterly and annual reports, as appropriate.

City of Lakewood-Department of Water Resources (Well No. 22)

| Monitoring and | Reporting | Program No. | CI-9786 |
|----------------|-----------|-------------|---------|
|----------------|-----------|-------------|---------|

| Constituent | Units | Type of Sample | Minimum Frequency of Analysis |
|------------------------|----------|-------------------|----------------------------------|
| Temperature | °F | grab | monthly |
| Total Suspended Solids | mg/L | grab | monthly |
| Turbidity | NTU | grab | monthly |
| BOD₅20°C | mg/L | grab | monthly |
| Settleable Solids | · ml/L | grab | monthly |
| Residual Chlorine | mg/L | grab | monthly |
| Acute Toxicity | . % | grab | annually |
| | survival | | |

EFFLUENT TOXICITY TESTING

IV.

- A. The discharger shall conduct acute toxicity testing tests on 100% of the effluent grab samples by methods specified in 40 CFR Part 136 which cites USEPA's *Methods for Measuring the Acute Toxicity of Effluents and Receiving Water to Freshwater and Marine Organisms*, October 2002, (EPA/821-R-02-012) or a more recent edition. Submission of bioassay results should include the information noted on pages 109-113 of the EPA/821-R-02-012 document.
- B. The fathead minnow, *Pimephales promelas*, shall be used as the test species for fresh water discharges and the topsmelt, Atherinops affinis, shall be used as the test species for brackish discharges. The method for topsmelt is found in USEPA's *Short-term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Marine and Estuarine Organisms*, Third Edition, October 2002, (EPA/821-R-02-014).
- C. If the results of the toxicity test yields a survival of less than 90%, then the frequency of analyses shall increase to monthly until at least three test results have been obtained and full compliance with effluent limitations has been demonstrated, after which the frequency of analyses shall revert to annually. Results of toxicity tests shall be included in the first monitoring report following sampling.

V. GENERAL PROVISIONS FOR REPORTING

- A. The discharger shall inform this Regional Board 24 hours before the start of the discharge.
- B. All chemical, bacteriological, and toxicity analyses shall be conducted at a laboratory certified for such analyses by the California Department of Health Services Environmental Laboratory Accreditation Program (ELAP) or approved by the Executive Officer. A copy of the laboratory certification shall be provided with the first monitoring report and each time a new certification and/or renewal is obtained from ELAP.

City of Lakewood-Department of Water Resources (Well No. 22) Monitoring and Reporting Program No. CI-9786

- C. Samples must be analyzed within allowable holding time limits as specified in 40 CFR Part 136.3. Proper chain of custody procedures must be followed and a copy shall be submitted with the report.
- D. As required in part H.4. of Order No. R4-2003-0108, the monitoring report shall specify the USEPA analytical method used, the Method Detection Limit and the Minimum Level for each pollutant.

VI. COMPLIANCE DETERMINATION (AS APPLICABLE)

Α.

- Compliance with single constituent effluent limitation If the concentration of the pollutant in the monitoring sample is greater than the effluent limitation and greater than or equal to the reported Minimum Level (see Monitoring and Reporting Requirements Section H.4. of Order R4-2003-0108), then the Discharger is out of compliance.
- B. Compliance with monthly average limitations In determining compliance with monthly average limitations, the following provisions shall apply to all constituents:
 - a. If the analytical result of a single sample, monitored monthly, quarterly, semiannually, or annually, does not exceed the monthly average limit for that constituent, the Discharger has demonstrated compliance with the monthly average limit for that month.
 - b. If the analytical result of a single sample, monitored monthly, quarterly, semiannually, or annually, exceeds the monthly average limit for any constituent, the Discharger shall collect four additional samples at approximately equal intervals during the month. All five analytical results shall be reported in the monitoring report for that month, or 45 days after results for the additional samples were received, whichever is later.

When all sample results are greater than or equal to the reported Minimum Level (see Monitoring and Reporting Requirements Section H.4. of Order R4-2003-0108), the numerical average of the analytical results of these five samples will be used for compliance determination.

When one or more sample results are reported as "Not-Detected (ND)" or "Detected, but Not Quantified (DNQ)" (see Monitoring and Reporting Requirements Section H.4. of Order R4-2003-0108), the median value of these four samples shall be used for compliance determination. If one or both of the middle values is ND or DNQ, the median shall be the lower of the two middle values.

CAG994005

City of Lakewood-Department of Water Resources (Well No. 22) Monitoring and Reporting Program No. CI-9786

- c. In the event of noncompliance with a monthly average effluent limitation, the sampling frequency for that constituent shall be increased to weekly and shall continue at this level until compliance with the monthly average effluent limitation has been demonstrated.
- d. If only one sample was obtained for the month or more than a monthly period and the result exceed the monthly average, then the Discharger is in violation of the monthly average limit.
- C. Compliance with effluent limitations expressed as a sum of several constituents If the sum of the individual pollutant concentrations is greater than the effluent limitation, then the Discharger is out of compliance. In calculating the sum of the concentrations of a group of pollutants, consider constituents reported as ND or DNQ to have concentrations equal to zero, provided that the applicable ML is used.
- D. Compliance with effluent limitations expressed as a median in determining compliance with a median limitation, the analytical results in a set of data will be arranged in order of magnitude (either increasing or decreasing order); and
 - a. If the number of measurements (n) is odd, then the median will be calculated as = $X_{(n+1)/2}$, or
 - b. If the number of measurements (n) is even, then the median will be calculated as = $[X_{n/2} + X_{(n/2)+1}]/2$, i.e. the midpoint between the n/2 and n/2+1 data points.
- Ε.
- In calculating mass emission rates from the monthly average concentrations, use one half of the method detection limit for "Not Detected" (ND) and the estimated concentration for "Detected, but Not Quantified" (DNQ) for the calculation of the monthly average concentration. To be consistent with section VI.C., if all pollutants belonging to the same group are reported as ND or DNQ, the sum of the individual pollutant concentrations should be considered as zero for the calculation of the monthly average concentration.

VII. NOTIFICATION

- A. The discharger shall notify the Executive Officer in writing prior to discharge of any chemical which may be toxic to aquatic life. Such notification shall include:
 - 1. Name and general composition of the chemical,
 - 2. Frequency of use,
 - 3. Quantities to be used,
 - 4. Proposed discharge concentrations and,

City of Lakewood-Department of Water Resources (Well No. 22)

Monitoring and Reporting Program No. CI-9786

5. EPA registration number, if applicable.

No discharge of such chemical shall be made prior to obtaining the Executive Officer's approval.

B. The discharger shall notify the Regional Board via telephone and/or fax within 24 hours of noticing an exceedance above the effluent limits in Order No. R4-2003-0108. The discharger shall provide to the Regional Board within 14 days of observing the exceedance a detailed statement of the actions undertaken or proposed that will bring the discharge into full compliance with the requirements and submit a timetable for correction.

VIII. MONITORING FREQUENCIES

Monitoring frequencies may be adjusted by the Executive Officer to a less frequent basis if the discharger makes a request and the request is justified by statistical trends of monitoring data submitted. However, monitoring frequency may also increase based on site-specific conditions.

Ordered by:

Dame. Samuel Unger, P.E.

Executive Officer

Date:

January 20, 2012

/vbc