

Draft Staff Report

Amendment to the *Water Quality Control Plan for the Los Angeles Region* to Suspend the Recreational Beneficial Uses in Engineered Channels during Unsafe Wet Weather Conditions



**Prepared by
California Regional Water Quality Control Board, Los Angeles Region**

May 15, 2003

Photo on cover of Ballona Creek storm conditions on March 15, 2003
(Courtesy of Culver City)

Table of Contents

	Page
I. Introduction	1
II. Background	2
A. Designation of Beneficial Uses	2
B. Recreational Use Designations in the Los Angeles Region	2
C. Historical Basis for Recreational Use Designations in the Los Angeles Region	3
D. Regional and National Developments Regarding Recreational Use Designations	4
III. Proposed Actions	5
A. Water Bodies Covered by Amendment	5
B. Conditions Triggering Suspension of REC Use(s)	6
IV. Legal Justification for Suspension of REC Use(s)	9
A. Legal Requirements for Removal of Designated Uses	9
B. Legal Justification for Suspension of REC Use(s) during Defined Rain Events	11
V. Discussion of Alternatives	14
A. To Which Recreational Uses Should the Suspension Apply?	14
B. Which Trigger Should Be Used to Initiate Suspension?	15
C. To Which Water Quality Objective Should the Suspension Apply?	16
D. No Action	16
VI. Other Considerations	17
A. Protection of Downstream Recreational Uses	17
B. Antidegradation Requirements	17
C. Anti-Backsliding Requirements	18
D. Future Uses	18
VII. Recommended Alternative	19
VIII. Implementation Provisions	21

I. INTRODUCTION

The Regional Board is proposing to amend its Basin Plan to acknowledge the inherent danger of recreating in engineered flood control channels during unsafe conditions characterized by high velocities and deep water. Specifically, the Regional Board proposes to suspend the recreational beneficial use(s) in engineered flood control channels where access can be restricted during and immediately following significant storm events to address the physically unsafe conditions in these channels. At present, the recreational beneficial uses (Water Contact Recreation or REC-1 and Non-contact Water Recreation or REC-2) assigned to these channels apply at all times, regardless of weather conditions or any other condition that could make recreational activities unsafe or infeasible. The proposed amendment would revise the recreational beneficial use designations (REC uses) for these engineered channels to reflect recreational use(s) that are temporarily suspended during and immediately following defined storm events.

Engineered flood control channels are constructed to reduce the incidence of flooding in urbanized areas by conveying stormwater runoff to the ocean or other discharge point as efficiently as possible. To accomplish this, the channels are usually lined, on the sides and/or bottom, with rip-rap or concrete. This modification creates “swiftwater” conditions during and immediately following storm events (see Exhibit 1, Photo 1). The vertical walls or steep-sided slopes of these channels in conjunction with restrictive fencing limit direct access to channelized creeks and streams for the purpose of recreational use (see Exhibit 1, Photos 2, 3, and 4).

The inherent danger of recreating in these channels during and immediately following storm events is widely recognized and is already addressed by Los Angeles and Ventura Counties through county policies. In Los Angeles County, protocols for locking access gates to flood control channels and preparing for possible swift-water rescues in these channels during defined storm events have been set by the Los Angeles County, California Multi-Agency Swift Water Rescue Committee. In Ventura County, access gates to these channels are kept locked at all times.

Since the suspension of the REC use(s) during defined storm events reduces the level of protection for the water body, the USEPA requires the Regional Board to conduct a use attainability analysis (UAA) for each water body to which the suspension would apply (USEPA, 2002, 1998, 1994). To meet these requirements, the Regional Board has developed this categorical UAA for all engineered flood control channels during defined storm events.

II. BACKGROUND

A. Designation of Beneficial Uses

According to 40 C.F.R. § 131.3(f), designated uses are those uses specified in water quality standards for each water body or segment whether or not they are being attained. Section 101(a)(2) of the federal Clean Water Act (CWA) says, “it is the national goal that wherever attainable, an interim goal of water quality which provides for the protection and propagation of fish, shellfish, and wildlife and provides for recreation in and on the water be achieved by July 1, 1983.”

40 C.F.R. §131.10 directs States on the designation of uses:

(a) Each State must specify appropriate water uses to be achieved and protected. The classification of the waters of the State must take into consideration the use and value of water for public water supplies, protection and propagation of fish, shellfish and wildlife, recreation in and on the water, agricultural, industrial and other purposes including navigation. In no case shall a State adopt waste transport or waste assimilation as a designated use for any waters of the United States.

(b) In designating uses of a water body and the appropriate criteria for those uses, the State shall take into consideration the water quality standards of downstream waters and shall provide for the attainment and maintenance of the water quality standards of downstream waters.

(c) States may adopt sub-categories of a use and set the appropriate criteria to reflect varying needs of such sub-categories of uses, for instance, to differentiate between cold water and warm water fisheries.

(d) At a minimum, uses are deemed attainable if they can be achieved by the imposition of effluent limits required under sections 301(b) and 306 of the Act and cost-effective and reasonable best management practices for nonpoint source pollution.

B. Recreational Use Designations in the Los Angeles Region

Existing and potential uses of inland surface waters in the region are listed in Table 2-1 of the Basin Plan (CRWQCB, 1994). The Basin Plan defines recreational uses as follows:

Water Contact Recreation (REC-1): “Uses of water for recreational activities involving body contact with water, where ingestion of water is reasonably possible. These uses include, but are not limited to, swimming, wading, water-skiing, skin and scuba diving, surfing, white water activities, fishing, or use of natural hot springs.” (CRWQCB, 1994, p. 2-2)

Non-contact Water Recreation (REC-2): “Uses of water for recreational activities involving proximity to water, but not normally involving body contact with water, where ingestion of water is reasonably possible. These uses include, but are not limited to, picnicking, sunbathing, hiking, beachcombing, camping, boating, tidepool and marine life study, hunting, sightseeing, or aesthetic enjoyment in conjunction with the above activities.” (CRWQCB, 1994, p. 2-2)

Per 40 C.F.R. 131.3(f), existing beneficial uses refer to those beneficial uses that have been attained for a water body on, or after, November 28, 1975. Potential use designations are based on a number of factors, including:

- a) plans to put the water to such future use,
- b) potential to put the water to such future use,
- c) designation of a use by the Regional Board as a regional water quality goal, or
- d) public desire to put the water to such future use (CRWQCB, 1994).

C. Historical Basis for Recreational Use Designations in the Los Angeles Region

As stated earlier, section 101(a)(2) of the federal Clean Water Act (CWA) states that, “it is the national goal that wherever attainable, an interim goal of water quality which provides for the protection and propagation of fish, shellfish, and wildlife and provides for recreation in and on the water will be achieved by July 1, 1983.” This formed a broad basis for the beneficial use designations for surface waters of the State.

In addition to this consideration, a comprehensive review of existing data and solicited input from stakeholders was conducted in the early 1970s to determine the existing and potential beneficial uses for the waters of the Los Angeles Region. These were the bases for the beneficial uses as designated in the 1975 Water Quality Control Plans for the Los Angeles River Basin and Santa Clara River Basin (Basin Plans). Data and reports for this assessment were obtained from the California Departments of Health, Fish and Game, Conservation, and Water Resources, as well as the Southern California Association of Governments, County of Los Angeles, Los Angeles County Flood Control District, and various regional and local water agencies. Comments received from public agencies, public utilities, industrial organizations, water companies and private citizens were also considered (CRWQCB, 1975). Beneficial uses identified included existing or potential water contact recreation (REC-1) for virtually all waters in the region, and non-contact water recreation (REC-2) for most waters in the region.

Prior to the 1994 update of the Basin Plans, researchers at California State University, Fullerton conducted a comprehensive review of the Region’s beneficial uses under a contract with the Regional Board (Saint, Prem K., *et al.*, 1993). The review included an evaluation of existing data, detailed field investigations and surveys of agencies and interest groups. Over 350 sites were surveyed as part of the field investigations and 50 agencies and interest groups were contacted and asked to provide input to the study. Based on the study results, the researchers recommended the addition of 126 rivers, 44 lakes and reservoirs, 45 groundwater basins, 9 coastal features and 108 wetlands and

accompanying beneficial uses to the revised Basin Plan. On the basis of field surveys and interviews, “existing”, “intermittent” or “potential” REC-1 and REC-2 uses were proposed for many of these newly included water bodies.

D. Regional and National Developments Regarding Recreational Use Designations

The 1994 Basin Plan preserved these recreational beneficial uses. Recently, however, the validity and appropriateness of the REC use(s) assigned to engineered flood control channels where access is restricted or prohibited due to public safety concerns has been questioned by public agencies such as the Los Angeles County Department of Public Works (LACDPW) (County of Los Angeles DPW, 2001, 2002a, 2002b, 2002c). In light of these concerns and similar concerns expressed by the State Water Resources Control Board (State Board), the Regional Board submitted a letter to the State Board outlining possible alternatives for re-evaluating the REC beneficial use(s) assigned to these engineered channels (LARWQCB, 2002).¹ One of these alternatives was to conduct a categorical UAA for the REC use(s) of all engineered flood control channels with restricted or prohibited access during defined storm events corresponding to physically unsafe conditions.

The USEPA has also recently recognized potential circumstances where REC use(s) may be inappropriate due to high wet weather flows that result in dangerous conditions physically precluding recreation (USEPA, 2002). Specifically, USEPA states in its Implementation Guidance for Ambient Water Quality Criteria for Bacteria, May 2002 Draft, that “an intermittent REC-1 use may be appropriate when the water quality criteria [referred to in State terminology as “objectives”] associated with REC-1 are not attainable for all wet weather events” (p. 32). One example used by USEPA is high wet weather flows that result in dangerous conditions physically precluding recreation such as arroyo washes in the arid west. In light of this type of situation, USEPA suggests that meeting the REC-1 bacteriological objectives may be suspended during defined periods of time, usually after a specified hydrologic or climatic event, or for a specified number of events or days per year.

¹ Most recently, during a public hearing to consider approval of a Basin Plan amendment updating the Region’s bacteria objectives set to protect the REC-1 use, State Board expressed concerns about the appropriateness of assigning recreational beneficial uses to engineered flood control channels where access is restricted or prohibited (see State Board Resolution No. 2002-0142).

III. PROPOSED ACTION

The Regional Board proposes to suspend the REC use(s) assigned to engineered flood control channels during and immediately after defined storm events where access to the channel can be restricted during the defined conditions. The rationale for this suspension is, first, that these storm events result in high flows/velocities that create physically unsafe conditions that cannot be remedied. Second, during these storm events, it is the policy of Los Angeles County to lock the access gates to these channels due to the inherent danger of recreating in these channels during wet weather, thus preventing individuals from engaging in recreational activities in the channel. The policy of Ventura County is to keep access gates to these flood control channels locked at all times.

A. Water Bodies Covered by Amendment

Staff evaluated whether to conduct water body-by-water body UAAs or a categorical UAA covering all water bodies meeting certain criteria. For this limited circumstance, staff proposes a regional approach, since all water bodies subject to the suspension of REC use(s) have similar features that justify it. Specifically, water bodies to which the suspension of the REC use(s) would apply during the defined conditions include those meeting all of the following criteria:

- a) inland water bodies
- b) flowing water bodies
- c) engineered channels
- d) water bodies where access can be restricted or prohibited (through fencing/signs)

See Appendix 1 for a list and map of the 61 inland, flowing water body segments in Los Angeles and Ventura Counties to which the suspension would apply.²

Comment [JR1]: Need to document start and end points, and construction dates. Okay.

A categorical suspension of REC use(s) during and immediately following defined storm events for inland, flowing engineered channels where access is restricted or prohibited is a practical approach and does not reduce public health protection in these channels, since the recreational use(s) do not exist under the proposed conditions for the suspension.³ Furthermore, as discussed in section VI.A, downstream REC uses must continue to be protected. As described earlier, engineered channels are designed to convey water rapidly out to a discharge point, making conditions unusually unsafe for recreational activities during high flows/velocities associated with storm events. While not sufficient alone to

² These water bodies were selected using a two-step approach. First, staff identified all inland, flowing water bodies listed in Table 2-1 of the Basin Plan where the REC use(s) were qualified due to restricted or prohibited access. Second, staff circulated this list internally among staff knowledgeable about the proposed water bodies to confirm that each of the water bodies met the criteria for inclusion in the proposed amendment. Staff will follow-up with field surveys of the candidate water bodies where necessary to confirm physical characteristics and access restrictions.

³ The recreational uses do not exist because (1) during the defined wet weather conditions, the velocity and depth of the water in these channels renders them unsafe for recreation and (2) under the defined wet weather conditions, Los Angeles County routinely locks all access gates to these flood control channels and Ventura County keeps access gates to flood control channels locked at all times.

trigger a suspension of the REC uses, restricted or prohibited access to these channels is also proposed as a complementary prerequisite for the suspension to ensure that people cannot access a water body during the defined wet weather periods.⁴

Staff evaluated, but does not recommend applying the suspension of REC use(s) to all inland water bodies for the following reasons.⁵ Inland water bodies include those that would not be subject to the high flows/velocities that occur in engineered channels. For example, lakes obviously are not characterized by high flows/velocities during storm events that would result in unsafe conditions. As for other inland, flowing water bodies, they may have neither (1) conditions of an engineered channel that would make recreation unsafe during storm events nor (2) restricted or prohibited access.

B. Condition Triggering Suspension of REC Use(s)

Staff evaluated several possible triggers for the suspension of REC use(s) in engineered channels with restricted or prohibited access. These included:

- a) flow and velocity (e.g., "swiftwater" conditions),
- b) depth (e.g., outside of low flow channel), and
- c) rainfall (e.g., total daily rainfall).

A summary of staff's evaluation regarding the feasibility and appropriateness of using each of these triggers is provided in Appendix 2.

Based on this evaluation, staff concludes that rainfall is the most appropriate trigger. The reason for this is three-fold. First, the Los Angeles County, California Multi-Agency Swift Water Rescue Committee uses rainfall prediction as the basis for routinely locking access gates to County flood control channels and putting swiftwater rescue personnel on alert. Written guidance for County personnel and other involved agencies is provided by the Committee in the "Operational Standards and Guidelines Document" (dated December 10, 1999). This document outlines the protocols used by the City of Los Angeles Fire Department, County of Los Angeles Fire Department, Sheriff's Department, Lifeguards and Department of Public Works to prepare for and provide swift-water rescues. Under the "Water Rescue Pre-Deployment Section" (Sec. 6.00, p. 13), three storm levels are defined (Levels 1-3) based on storm warnings with an 80% prediction of specified levels (e.g., ½ inch, 1 inch, 1½ inches) of rain over 24 hours.⁶ The following are the three alert levels:

⁴ USEPA states, "For states and authorized tribes using this [high-flow cutoff] approach, EPA encourages the development of a plan to communicate to the public the conditions under which recreation should not occur" (USEPA, 2002, p. 34).

⁵ Furthermore, staff evaluated, but does not recommend applying the suspension to coastal water bodies, since there is use during and immediately following storm events (e.g. surfing) and access is not restricted.

⁶ According to LA County Flood Control, these protocols are implemented in the following way. There are 12 superintendents who are responsible for closing gates to flood control channels in LA County when they deem appropriate. Each superintendent looks at Doppler information generally and estimates for their geographic region whether they should close the gates.

Level 1	1 inch of rain (if unsaturated ground) or ½ inch (if saturated ground)
Level 2	1 ½ inch of rain (if unsaturated ground) or 1 inch (if saturated ground)
Level 3	Rainfall/saturation levels exceeding those listed for Level 2 Generalized flash floods, urban flooding and/or mud and debris flows Urban flooding with possible life hazards.

Other factors that the agencies consider when determining deployment levels include:

- 1) The effect of major wildland and interface burn areas. Large burn areas result in increased runoff and high potential for mud and debris flows and flash floods.
- 2) Flood watches and flood warnings.
- 3) Real time effects of the storm, which may differ from weather forecasts, resulting in severe conditions in particular geographic areas.
- 4) Releases in the flood control channels.

At the Level 1 Alert threshold, County personnel routinely lock all access gates to flood control channels. Access gates are kept locked for at least 24 hours after the storm event (Burke, J., 2003, personal communication).

The second reason that rainfall is selected as the most appropriate trigger is because there are numerous rain gages throughout Los Angeles and Ventura Counties making precipitation data readily available whereas flow, velocity and depth data are not available for all candidate channels (see Appendix 2 for more details). Third, rainfall is an adequate proxy for high flows/velocities resulting in unsafe conditions, given the reliance on rainfall prediction by the Multi-Agency Swift Water Rescue Committee. To confirm this, staff used five years of data (water years 1998-2002) to match days above the Level 1 Alert rainfall thresholds of ½ inch or 1 inch with corresponding flow, velocity and depth data in several local channels and compared this data to swift-water rescue data from these same channels as well as other agencies' protocols for evaluating when conditions in these channels are unsafe. Specifically, staff relied upon a protocol used by the USGS and the County of Orange in which in-stream conditions are evaluated using the following calculation to determine whether it is safe for monitoring personnel to be in a stream or channel. The calculation is the peak depth (in feet) multiplied by the peak velocity (in feet/second). If the result is greater than or equal to 10, then it is considered unsafe (Caldwell, A., 2003, personal communication; County of Orange, 2001).

The results of this analysis demonstrate that a significant percentage (63% on average and as much as 83%) of unsafe days (as determined using the USGS protocol described above) occur on days where the preceding day's rainfall was greater than ½ inch, regardless of whether ground conditions were saturated or unsaturated.⁷ See Appendix 3, Table 1. (The counterpoint to this is that on average 37% of unsafe days occur on days

⁷ In the data analysis, staff compared the preceding day's rainfall to conditions on the target day. Staff chose this approach due to the lag time associated with storm flows. See Appendix 3, Figures 1 to 3, for an example of this lag time. Had staff compared both the preceding day's rainfall as well as rainfall on the target day to conditions on the target day, the percentages above may have been slightly higher.

outside of the defined wet weather conditions.) Additionally, 36 percent of documented swift-water rescues from 2001 to 2002 occurred on days with rainfall greater than or equal to ½ inch, while 71% occurred on days considered “unsafe”.⁸ See Appendix 3, Table 2. Finally, our analysis shows that, on average, 82% of days and as high as 100% of days where the preceding day’s rainfall was greater than ½ inch were considered unsafe per the USGS protocol, regardless of whether the ground was saturated. See Appendix 3, Table 1. (Again, the counterpoint to this is that on average 18% of days where the preceding day’s rainfall was greater than ½ inch were *not* considered unsafe.) The results of this analysis show that using days with greater than ½ inch of rainfall and the following day will provide protection by suspending the use during 63% of unsafe days. Additionally, this trigger appears appropriate and justifiable based on this analysis, since on average 82% of days where the preceding day’s rainfall was greater than ½ inch were considered unsafe. See Appendix 3 for a more detailed discussion and presentation of this analysis.

On the basis of the detailed data analysis described above and in Appendix 3, staff proposes to use the Level 1 Alert (with saturated conditions) threshold [rainfall greater than or equal to ½ inch as measured at the closest rain gage] as the trigger for suspension of the REC use(s) assigned to a particular engineered channel.⁹ Staff proposes to use the Level 1 Alert (with saturated conditions) threshold because rainfall in Southern California tends to be concentrated over a short “wet season” during November to March and, in particular, from January to March, leading to a greater likelihood of saturated conditions as compared to unsaturated conditions. Furthermore, staff’s analysis indicates that days deemed “unsafe” based on other agencies’ protocols are more likely to occur on days where the preceding day’s rainfall is between ½ to 1 inch than on days where the preceding day’s rainfall is greater than 1 inch, regardless of ground conditions (i.e. saturated vs. unsaturated).¹⁰ See Appendix 3, Table 1. Therefore, it is more protective of public safety to use the ½ inch rain threshold than the 1 inch rain threshold (i.e., the recreational use(s) will be suspended on a greater number of unsafe days if the ½ inch threshold is used as compared to the 1 inch threshold). In addition, due to the lag time associated with storm flows, staff proposes to apply the suspension for 24 hours after the specified rain event. (See Appendix 3, Figures 1 to 3.) This comports with the policy of Los Angeles County to keep all access gates locked for a minimum of 24 hours following the specified rain event (Burke, J., 2003, personal communication).

⁸ Eighty-two percent of swift-water rescues from 2001 to 2002 occurred on days with rainfall greater than 0.1 inch or days following rainfall of greater than 0.1 inch.

⁹ Staff evaluated several methods for identifying the precipitation corresponding to a particular engineered channel. These included using one centralized rain gage per county, one gage per watershed, or the closest gage to the engineered channel. Due to the variability in rainfall in the region, as confirmed by our analysis of these different methods, staff concluded that the closest rain gage to the engineered channel should be used. Consideration should be given to the completeness and quality of the data from that gage. If the data are incomplete or of poor quality, the next closest gage should be used.

¹⁰ This can be explained by the fact that there tend to be more days with rainfall between ½ to 1 inch than days with rainfall greater than 1 inch. However, it is also insightful that the percentage of unsafe days where the preceding day’s rainfall was between ½ inch and 1 inch (32%) is similar to the percentage of unsafe days where the preceding day’s rainfall was greater than 1 inch (26%).

IV. LEGAL JUSTIFICATION FOR SUSPENSION OF REC USE(S)

A. Legal Requirements for Removal of Designated Uses

Per 40 C.F.R. § 131.10(g), States may remove a designated use that is not an existing use, as defined in 40 C.F.R. § 131.3, or establish subcategories of use if the State can demonstrate that attaining the designated use is not feasible for one or more of the following reasons:

1. Naturally occurring pollutant concentrations prevent the attainment of the use,
2. Natural, ephemeral, intermittent or low flow conditions or water levels prevent the attainment of the use, unless these conditions may be compensated for by the discharge of sufficient volume of effluent discharges without violating State water conservation requirements to enable uses to be met;
3. Human caused conditions or sources of pollution prevent the attainment of the use and cannot be remedied or would cause more environmental damage to correct than to leave in place;
4. Dams, diversions or other types of hydrologic modifications preclude the attainment of the use, and it is not feasible to restore the water body to its original condition or to operate such modification in a way that would result in the attainment of the use;
5. Physical conditions related to the natural features of the water body, such as the lack of a proper substrate, cover, flow, depth, pools, riffles, and the like, unrelated to water quality, preclude attainment of aquatic life protection uses; or
6. Controls more stringent than those required by sections 301(b) [Effluent Limitations] and 306 [National Standards of Performance] of the Act would result in substantial and widespread economic and social impact.

1. Restrictions on Removal of Use: 40 C.F.R. § 131.10

Federal regulations restrict States from removing designated beneficial uses. Specifically 40 C.F.R. § 131.10 (h) prohibits States from removing designated uses if:

1. They are existing uses, as defined in 40 C.F.R. § 131.3, unless a use requiring more stringent criteria is added; or
2. Such uses will be attained by implementing effluent limits required under sections 301(b) and 306 of the Act and by implementing cost-effective and reasonable best management practices.

Furthermore, 40 C.F.R. § 131.10(i) states that where existing water quality standards specify designated uses less than those which are presently being attained, the State shall revise its standards to reflect the uses actually being attained.

2. *Use Attainability Analyses: 40 C.F.R. § 131.3(g)*

40 C.F.R. § 131.3(g) defines a use attainability analysis (UAA) as a structured scientific assessment of the factors affecting the attainment of the use which may include physical, chemical, biological, and economic factors as described in § 131.10(g).

Under section 40 C.F.R. § 131.10(j) of the Water Quality Standards Regulation, States are required to conduct a UAA whenever a State wishes to remove a designated use that is specified in section 101(a)(2) of the Act or adopt subcategories of uses specified in section 101(a)(2) that require less stringent criteria.

USEPA (2002) provides guidance on conducting UAAs for recreational uses and provides the following factors that may be addressed:

- a) physical analyses considering the actual use (as of November 28, 1975), public access to the water body, facilities promoting the use of recreation, proximity to residential areas, safety considerations, and substrate, depth, width, etc. of a water body;
- b) chemical analyses of existing water quality ;
- c) potential for water quality improvements including an assessment of nutrients and bacteriological contaminants; and
- d) economic/affordability analyses.

This reaffirms previous USEPA guidance in which USEPA suggested that, when evaluating recreational uses, States look at a suite of factors such as whether the water body is actually being used for primary contact recreation, existing water quality, water quality potential, access, recreational facilities, location, proximity to residential areas, safety considerations, and physical conditions of the water body in making any use attainability decision (USEPA, 1994).

On the subject of physical analyses, USEPA has previously stated that, “physical factors, which are important in determining attainability of aquatic life uses, may not be used as the basis for removing or not designating a recreational use consistent with the CWA section 101(a)(2) goal” (US EPA, 1994). This precludes States from relying upon either factor 2 (low flows) or factor 5 (physical factors in general) as the *sole* basis for determining attainability of recreational uses. The reason for this preclusion is that States and USEPA have an obligation to do as much as possible to protect the health of the public. In certain instances, people will use whatever water bodies are available for recreation, regardless of the physical conditions (USEPA, 1994).

USEPA is in the process of considering whether the regulation or Agency guidance should be amended to allow consideration of physical factors, alone, as the basis for removing, or not designating primary contact recreational uses (USEPA, 1998). As part of this process, USEPA has convened a national workgroup to discuss recreational use designations. A key topic being vetted by the workgroup is Use Attainability Analyses for recreational uses.

B. Legal Justification for Suspension of REC Use(s) during Defined Rain Events

Suspension of REC use(s) in engineered channels with restricted or prohibited access during rainfall of greater than or equal to ½ inch and the 24 hours following the rain event is legally justified for three reasons. These are:

- (1) During the defined wet weather events, recreation is not an existing use in engineered channels,
- (2) Under the defined wet weather conditions during which the suspension would apply, recreational uses in these channels are not attainable through effluent limitations under CWA section 301(b)(1)(A) and (B) and section 306 or through cost effective and reasonable best management practices, and
- (3) These water bodies meet two of the six conditions listed in 40 C.F.R. 131.10(g) during the defined wet weather conditions.

The logic underlying each of these reasons is discussed in detail below.

1. During the defined wet weather events, recreation is not an existing use in engineered channels.

During the defined wet weather conditions, recreation is not an existing use in engineered flood control channels with restricted access, for two related reasons.¹¹ First, during the defined wet weather conditions, the rate of flow, velocity and depth of the water in engineered channels renders them unsafe for individuals to engage in recreational activities. This is particularly true for REC-1 activities because REC-1 involves body contact recreation. As presented earlier, the definition of REC-1 is:

“Uses of water for recreational activities involving body contact with water, where ingestion of water is reasonably possible. These uses include, but are not limited to, swimming, wading, water-skiing, skin and scuba diving, surfing, white water activities, fishing or use of natural hot springs.” (CRWQCB, 1994, p. 2-2)

While REC-2 does not normally involve body contact with water, it does involve recreational activities in close proximity to water. As a result, REC-2 activities may result in accidental contact with water. Due to the extreme danger associated with recreation in or near these channels during the defined wet weather conditions, REC-2 activities, which may involve accidental contact with the water, are also unsafe. This is because if someone recreating near the water body fell into the water, they could be quickly swept downstream due to the high velocities, flow rates, and depths characterizing the defined

¹¹ Note that while some of the water bodies proposed for inclusion in this amendment have “existing” REC uses assigned to them, these uses have never been “existing” during the defined wet weather conditions for the reasons discussed below.

wet weather conditions. Furthermore, the geometry of these flood control channels (i.e. vertical or steeply sloped sides) makes it extremely difficult to get out of the channel during these conditions. See section III.B and Appendix 3 for a detailed analysis of unsafe conditions. (See Exhibit 1, Photos 4 and 5.)

Second, under the defined wet weather conditions including the 24 hours after the rain event, Los Angeles County routinely locks all access gates to these flood control channels per the protocols outlined in the “Operational Standards and Guidelines Document” (December 10, 1999) prepared by the Multi-Agency Swift Water Rescue Committee. Access gates to engineered flood control channels in Ventura County are always locked. Therefore, recreational activities are prohibited in these channels under the defined wet weather conditions. (See Exhibit 1, Photos 6 and 7.)

2. Under the defined wet weather conditions during which the suspension would apply, recreational uses are not attainable through effluent limitations under CWA section 301(B)(1)(A) and (B) and section 306 or through cost effective and reasonable best management practices.

Due to the design of the engineered flood control channels, recreational uses are not attainable during the defined wet weather conditions that would trigger the suspension even if water quality was adequate to support the uses. In other words, it is not water quality that ultimately precludes attainment of the REC uses, but rather the physical conditions during the defined wet weather conditions in hydrologically modified (engineered) channels. This is because, as described earlier, engineered flood control channels are constructed to reduce the incidence of flooding in urbanized areas by conveying stormwater runoff to the ocean or other discharge point as efficiently as possible. To accomplish this, the channels are usually lined, on the bottom and sides, with rip-rap or concrete. Furthermore, the channel sides are usually vertical or steeply sloped. These modifications, necessary for flood control, create “swiftwater” conditions during and immediately following storm events. Due to the need for flood control during storm events, these channels cannot be modified to eliminate the physical danger associated with recreation in or near these channels during wet weather conditions.

3. These water bodies meet two of the six conditions listed in 40 C.F.R. 131.10(g).

As described earlier, there are six factors that may be used to justify removal of a designated use that is not an existing use or the establishment of sub-categories of a use. Federal regulation (40 C.F.R. 131.10(g)) requires that at least one of these six factors be met. These six factors are as follows:

1. Naturally occurring pollutant concentrations prevent the attainment of the use;
or
2. Natural, ephemeral, intermittent or low flow conditions or water levels prevent the attainment of the use, unless these conditions may be compensated

- for by the discharge of sufficient volume of effluent discharges without violating State water conservation requirements to enable uses to be met; or
3. Human caused conditions or sources of pollution prevent the attainment of the use and cannot be remedied or would cause more environmental damage to correct than to leave in place; or
 4. Dams, diversions or other types of hydrologic modifications preclude the attainment of the use, and it is not feasible to restore the water body to its original condition or to operate such modification in a way that would result in the attainment of the use; or
 5. Physical conditions related to the natural features of the water body, such as the lack of a proper substrate, cover, flow, depth, pools, riffles, and the like, unrelated to water quality, preclude attainment of aquatic life protection uses; or
 6. Controls more stringent than those required by sections 301(b) and 306 of the Act would result in substantial and widespread economic and social impact.

The suspension of the REC use(s) in engineered flood control channels with restricted access is justified by factors 2 and 4 above. Regarding factor 2, southern California streams are naturally flashy systems due to the predominantly dry climate and short, concentrated wet season. These natural flashy conditions result in intermittent dangerous flow volumes and velocities after rain events that prevent the attainment of the use during and for the 24 hours after a ½-inch rain event.¹²

In addition, the natural conditions in the factor 2 analysis are further exacerbated in engineered flood control channels, which are designed to contain and convey water rapidly to a discharge point. This results in the use being unattainable under factor 4 as well. These hydrologic modifications, made for the purpose of flood control, in combination with natural conditions (i.e., characteristically flashy systems during wet weather) physically preclude the attainment of the recreational use during and immediately following a ½-inch or greater storm event. Further, it is not feasible to restore the water body to its original condition or operate the modifications in such a way as to attain the use during the defined wet-weather events.

¹² Furthermore, regarding factor 2, because the natural conditions of concern are high flow/velocity conditions, these conditions cannot be compensated for by the discharge of sufficient volume of effluent discharges to enable uses to be met.

V. DISCUSSION OF ALTERNATIVES

Below staff presents four sets of alternatives, including (1) which recreational uses to suspend, (2) which trigger to use to identify periods subject to the suspension, (3) which associated water quality objectives to suspend, and (4) a “no action” alternative. Alternatives within each set are mutually exclusive, but alternatives between sets 1, 2 and 3 are intended to be considered in combination.

A. To Which Recreational Uses Should the Suspension Apply?

1. REC-1 Use Only

Due to the inherent danger of recreating in the water during high flow, velocity and depth conditions associated with storm events and the fact that the access gates are locked during these conditions, there is little likelihood that REC-1 uses could occur in these circumstances. Under this recommendation, the REC-2 use and the associated objectives set to protect the REC-2 use would still apply during periods when the REC-1 use was suspended.

2. REC-1 and REC-2 Uses

Suspending both REC-1 and REC-2 uses is reasonable and can be justified by the inability of the channels to support REC-2 activities under the defined conditions. To examine whether REC-2 uses are supported under these conditions, it is useful to examine again the definition of REC-2.

Uses of water for recreational activities involving proximity to water, but not normally involving body contact with water, where ingestion of water is reasonably possible. These uses include, but are not limited to picnicking, sunbathing, hiking, beachcombing, camping, boating, tidepool and marine life study, hunting, sightseeing, or aesthetic enjoyment in conjunction with the above activities. (CRWQCB, 1994, p. 2-2)

The REC-2 use involves activities in proximity to water bodies and, therefore, may involve accidental contact with water, which under the defined wet weather conditions is unsafe. As discussed earlier, this is because if someone recreating near the water body fell into the water, they could be quickly swept downstream due to the high velocities, flow rates, and depths characterizing the defined wet weather conditions. Furthermore, the geometry of these flood control channels (i.e. vertical or steeply sloped sides) makes it extremely difficult to get out of the channel during these conditions. See section III.B and Appendix 3 for a detailed analysis of unsafe conditions. Furthermore, it is unlikely that any of the REC-2 activities are possible where access to the water is barred by fencing and locked access gates during the defined wet weather conditions. On the other hand, where access is prohibited, individuals could come in proximity to a channel (i.e., as close as the fencing would allow). This proximity may result in the incidental

ingestion of water (e.g., from splashing). It is the incidental/accidental ingestion of water that is being protected against with the REC-2 use.

B. Which Trigger Should Be Used to Initiate the Suspension?

1. Days of Rainfall greater than or equal to ½ inch plus the 24 Hours Following the Rain Event (Level 1 Alert threshold).

Analysis showing that a trigger of greater than or equal to ½ inch of rainfall, including the 24 hours following the rain event, will capture 63% of “unsafe days” supports this alternative. From another standpoint, analysis showing that 82% of days with rainfall greater than ½ inch were followed by “unsafe” days also supports this alternative. Due to the lag time associated with storm flows, continuing to apply the suspension for 24 hours after the specified rain event is reasonable and justified. This also comports with the Level 1 Alert threshold used by Los Angeles County and its policy to keep all access gates locked for a minimum of 24 hours following the specified rain event.

Under this alternative, the suspension would typically apply 16 to 22 days per year (or 4 to 6% of the year) based on an evaluation of historical rainfall data from LAX and three representative rain gages in Ventura County.¹³ See Appendix 3, Table 4.

2. Days of Rainfall greater than 1 inch plus the 24 Hours Following the Rain Event (Level 1 Alert threshold with antecedent unsaturated conditions).

This approach is less conservative from the public safety standpoint than Alternative B.1 in that the recreational use(s) would still apply on a number of days with rainfall of ½ inch to 1 inch when conditions would be deemed “unsafe.” (It is, however, more conservative from a water body protection standpoint.) As discussed earlier, the average percentage of unsafe days occurring on days where rainfall of ½ to 1 inch fell on the preceding day (32%) was nearly the same as the average percentage of unsafe days where rainfall of greater than 1 inch fell on the preceding day (26%). Using the more conservative ½ inch trigger captures 63% of unsafe days, on average, while using the less conservative 1 inch trigger only captures 29% of unsafe days, on average. Furthermore, looking at the data from another standpoint, the majority (69%) of days where rainfall of ½ to 1 inch fell the preceding day were deemed unsafe.

Under this alternative, the suspension would typically apply 6 to 12 days per year (or 2 to 3% of the year) based on an evaluation of historical rainfall data from LAX and three representative rain gages in Ventura County.¹⁴ See Appendix 3, Table 5.

¹³ This may be an overestimate because staff has assumed that no day with rainfall greater than or equal to ½ inch was followed by a second consecutive day of rainfall greater than or equal to ½ inch. If one or more days of rainfall greater than or equal to ½ inch were followed consecutively by a day(s) of rainfall greater than or equal to ½ inch, these numbers would be smaller.

¹⁴ This may be an overestimate because staff has assumed that no day with rainfall greater than or equal to 1 inch was followed by a second consecutive day of rainfall greater than or equal to 1 inch. If one or more

C. To Which Water Quality Objectives [Set to Protect Recreational Uses] Should the Suspension Apply?

Under either Alternative A.1 or A.2, the associated objectives set to protect the REC use(s) that should be concurrently suspended should only include those that satisfy the following conditions:

- 1) The constituents should degrade over a relatively short period of time; conversely, those that are stable or bioaccumulate should not be exempted due to the potential for extended and cumulative downstream impacts beyond the period of the suspension.
- 2) High levels of these constituents should be of concern to those partaking in only those recreational activities where ingestion of water is possible, for these are the uses that are precluded by the defined wet weather events. Conversely, constituents that could have an effect on other beneficial uses that still occur during wet weather events, should not be suspended, e.g. fish consumption.
- 3) High levels of these constituents should not in any way affect the non-proximal aesthetic enjoyment of the water body.

Therefore, the bacteria objectives set to protect the REC use(s) are the only objectives that should be concurrently suspended along with the REC use(s). This comports with USEPA guidance, which only envisioned applying a “high flow/velocity” exemption to recreational uses and the associated bacteriological criteria (USEPA, 2002).

D. No Action

Another alternative would be to do nothing and, as such, continue to apply the REC use(s) to all water bodies at all times. Recreational uses would be fully protected; however, the beneficial use designations will not reflect the actual or potential use of these channels under the defined wet weather conditions. Some stakeholders may view this alternative as unreasonably protective.

days of rainfall greater than or equal to 1 inch were followed consecutively by a day(s) of rainfall greater than or equal to 1 inch, these numbers would be smaller.

VI. OTHER CONSIDERATIONS

A. Protection of Downstream Recreational Uses

40 C.F.R. Part 131.10(b) states that “in designating uses of a water body and the appropriate criteria for those uses, the State shall take into consideration the water quality standards of downstream waters and shall provide for the attainment and maintenance of the water quality standards of downstream waters.” Many of the candidate channels in this proposed amendment flow directly, or indirectly as tributaries to other water bodies, to coastal water bodies and beaches. Many of these coastal water bodies (e.g. beaches) are currently listed as impaired due to bacteria. The Regional Board must ensure that the downstream coastal recreational uses are protected during wet weather events (subject to any other pertinent implementation procedures for the bacteria objectives) and that the recreational uses of the candidate channels are protected when normal/safe conditions return.

On the coast, in Santa Monica Bay, a reference system approach¹⁵ is employed as the regulatory mechanism to protect the REC-1 use of the Bay’s beaches. Tables 4 and 5 in Appendix 3 provide estimates of the number of days on which a suspension of the REC use(s) would apply. Because the number of allowable exceedance days under the reference system approach will be re-evaluated in four years based on data from the wave wash (the point of compliance for the TMDL), staff cannot draw definitive conclusions as to whether the recommendations here conflict with the reference system approach. It appears that Alternative A.1 to suspend the REC-1 use only would not be in conflict with the reference system approach under most conditions. It is not clear whether Alternative A.2 to suspend both the REC-1 and REC-2 uses would be in conflict with the downstream reference system approach or not. To assess this, staff would need better information on bacterial degradation rates and transport times from each of the engineered channels to which the suspension would apply.

B. Antidegradation Requirements

Per the State Anti-degradation Policy (State Board Resolution 68-16), there may be no lowering of water quality from that currently attained. The policy states, “Whenever the existing quality of water is better than the quality established in policies as of the date on which such policies become effective, such existing high quality shall be maintained until it has been demonstrated to the State that any change will be consistent with maximum benefit to the people of the State, will not unreasonably affect present and anticipated beneficial use of such water and will not result in water quality less than that prescribed

¹⁵ Under this approach, a reference system is selected on the coast, which is influenced less than any other area in the watershed by human activities. The number of exceedances for that coastal area is considered to be a result of natural or background conditions. That number is then set as the allowable exceedance days for the rest of the coast unless a particular location has fewer exceedance days than the reference site, in which case antidegradation provisions apply.

in the policies” (SWRCB, 1968). In other words, existing water quality must be maintained even after the effective date of the proposed amendment.

C. Anti-backsliding Requirements

When the Regional Board reissues NPDES permits, the effluent limitations generally must be as stringent as the prior permit. This concept is known as anti-backsliding and it is codified in federal Clean Water Act section 402(o) and separately in 40 C.F.R. § 122.44(l). There are several exceptions to the anti-backsliding provisions of Federal law. In general, the relaxation water quality objectives, as permitted by the proposed Basin Plan amendment, does not exempt a discharger from the anti-backsliding provisions of the federal Clean Water Act. The Regional Board must evaluate NPDES permits on a case-by-case basis when the permits are reissued to determine whether an applicable anti-backsliding exception applies.

D. Future Uses

Suspending the recreational use(s) of the candidate engineered channels does not preclude a lifting of this suspension should conditions within these channels change in the future. While such changes seem unlikely in most cases due to the necessary use of these channels for flood control, none of the alternatives would preclude a return to fully protecting all recreational uses at all times, if warranted.

VII. RECOMMENDED ALTERNATIVE

The Regional Board recommends suspending the water contact recreational activities associated with the swimmable goal as expressed in the federal Clean Water Act section 101(a)(2) and regulated under the REC-1 use, non-contact water recreation involving incidental water contact regulated under the REC-2 use, and the associated bacteriological objectives set to protect those activities, using as a trigger days of rainfall greater than or equal to ½ inch and the 24 hours following the rain event, which comports with the Los Angeles County Level 1 Alert threshold with antecedent saturated conditions. This alternative is justified by the unsafe conditions in engineered flood control channels during storm events of greater than or equal to ½ inch, regardless of ground conditions (i.e. saturated or unsaturated). Furthermore, the candidate channels are routinely locked by Los Angeles County under these conditions, while Ventura County keeps its access gates locked at all times, preventing individuals from engaging in recreational activities in these channels during these conditions.¹⁶ The suspension would apply to inland, flowing, engineered channels where it is possible to restrict access during the defined conditions. Water quality objectives set to protect (1) other recreational uses associated with the fishable goal as expressed in the federal Clean Water Act section 101(a)(2) and regulated under the REC-1 use and (2) other REC-2 uses (e.g., uses involving the aesthetic aspects of water) shall still remain in effect.

In making this recommendation, staff has considered all factors set forth in §13241 of the Porter Cologne Water Quality Control Act:

- a) Past, present and probable future beneficial uses of the candidate engineered channels have been, are and will be limited by the hydrologic modifications and other physical factors (i.e. natural conditions).
- b) Bacteriological water quality objectives set to protect recreational uses are not being met in 62 percent of the assessed candidate water bodies, however, TMDLs will rectify this in the future, taking into account any suspension of the recreational uses per this amendment.
- c) Stormwater is the primary source of bacterial contamination in these channels, particularly during the wet weather conditions under which the suspension would apply. Historically, stormwater has been difficult to control, particularly during wet weather conditions. Furthermore, given the role these channels serve for flood control, it will be particularly difficult to control flows during and immediately following large storm events.
- d) With regard to economic considerations, the recommended alternative is not expected to impose any additional cost and will likely reduce future costs by

¹⁶ Regional Board staff recognizes a potential gap between current Los Angeles County policies and the proposed amendment on days with between ½ inch and 1 inch of rainfall where there are unsaturated ground conditions. On these days, current Los Angeles County policies would not require locking access gates, though our analysis shows conditions to be unsafe on the majority of these days. Ways of addressing this gap are discussed in section VIII “Implementation Provisions”.

suspending the recreational uses and associated bacteria objectives during some wet weather events.

- e) The recommended alternative will have no impact on the need for developing housing within the region.
- f) The need to develop and use recycled water will not be affected by the proposed modifications and, in fact, the ability to reuse stormwater may be facilitated by this amendment by providing flexibility as to where stormwater controls must be implemented.

VIII. IMPLEMENTATION PROVISIONS

The Regional Board is proposing to suspend REC-1 and REC-2 uses in engineered channels on days of greater than or equal to ½ inch of rain and the 24 hours following in acknowledgement of the inherent danger of recreating in these channels during these periods. Staff's recommendation is based on analysis presented in section III.B and Appendix 3, which shows that in general rainfall greater than ½ inch results in unsafe conditions (based on velocity and depth considerations) regardless of whether there are saturated or unsaturated conditions.

The current protocols used in Los Angeles County for locking access gates to engineered channels during storm events provide an effective mechanism for preventing access to these channels when conditions are unsafe. However, staff recognizes a potential gap between current County policies and the proposed amendment on days with between ½ inch and 1 inch of rainfall where there are unsaturated ground conditions. On these days, current County policies would not require locking access gates, though our analysis shows conditions to be unsafe on the majority of these days.

To address this gap, the Regional Board proposes to work in coordination with Los Angeles County Flood Control as well as the Multi-Agency Swift-Water Rescue Committee to identify a mechanism for letting the public know that conditions in these channels are unsafe on days of greater than or equal to ½ inch of rain and the 24 hours following and, therefore, recreational use of these channels is being suspended in the interest of public safety. Potential mechanisms may include permanent signage, press releases, and public outreach in coordination with other public education programs (e.g., the municipal storm water permit public outreach program).

IX. REFERENCES

1. Burke Jerry, Staff of the Los Angeles County Flood Maintenance Division. Personal communication. 2003.
2. California Regional Water Quality Control Board, Los Angeles Region (CRWQCB-LA), Letter from Dennis Dickerson to Art Baggett, Chair of State Water Board, dated July 10, 2002.
3. California Regional Water Quality Control Board, Los Angeles Region (CRWQCB-LA) Total Maximum Daily Load to Reduce Bacterial Indicator Densities during Dry Weather at Santa Monica Bay Beaches. January, 2002.
4. California Regional Water Quality Control Board, Los Angeles Region, 1996 California Water Quality Assessment - 305(b) Report, Supporting Documentation for Los Angeles Region.
5. California Regional Water Quality Control Board (CRWQCB). Basin Plan for the Coastal Watersheds of Los Angeles and Ventura Counties. 1994.
6. California Regional Water Quality Control Board (CRWQCB). Water Quality Control Plan Report. Los Angeles River Basin (4A). Part I. March 1975.
7. California Regional Water Quality Control Board (CRWQCB). Water Quality Control Plan Report. Los Angeles River Basin (4B). Parts I, II, III, IV, V. March 1975.
8. County of Los Angeles, Department of Public Works. Letter to the California State Water Resources Control Board dated April 29, 2002.
9. County of Los Angeles, Department of Public Works. Letter to the California State Water Resources Control Board dated May 13, 2002.
10. County of Los Angeles, Department of Public Works. Letter to the California State Water Resources Control Board dated July 15, 2002.
11. County of Los Angeles, Department of Public Works. Letter to the California Regional Water Quality Control Board dated September 18, 2001.
12. County of Orange, Public Facilities and Resources Department. Program Development Division. Environmental Resources Section. Water Quality Unit. "Water Quality Sampling Manual for the NPDES Stormwater Permit Program." Revised March 6, 2001.

13. Los Angeles County Department of Public Works, Water Resources Division (Records), hydrologic and meteorological data.
14. Los Angeles County Fire Department, National Fire Incident Reporting System Unit, Information Management Division. Swift Water Rescue Data.
15. Los Angeles County Multi-Agency Swift Water Rescue Committee (LACMSWRC) Operational Standards & Guidelines. December 10, 1999.
16. Saint, Prem K., Hanes, Ted L., Lloyd, William J., Waterbodies, Wetlands, and their Beneficial Uses in the Los Angeles Region (4). Volume 1. Waterbodies and their Beneficial Uses. California State University, Fullerton. July 1993.
17. State Water Resources Control Board, State Board Resolution 68-16, Statement of Policy With Respect to Maintaining High Quality Waters in California. October 28, 1968.
18. United States Environmental Protection Agency (USEPA) “Ambient Water Quality Criteria for Bacteria – 1986”. Report No. EPA 330/5-84-002. January 1986.
19. United States Environmental Protection Agency (USEPA). “Water Quality Standards Handbook: Second Edition”. Report No. EPA-823-8-94-005a. August 1994.
20. United States Environmental Protection Agency (USEPA). Federal Register, 40 CFR Part 131. “Water Quality Standards Regulation; Proposed Rules”. Tuesday, July 7, 1998.
21. United States Environmental Protection Agency (USEPA). EPA-833-R-01-002. “Guidance: Coordinating CSO Long Term Planning with Water Quality Standards Reviews.” July 31, 2001.
22. United States Environmental Protection Agency (USEPA) “Implementation Guidance for Ambient Water Quality Criteria for Bacteria”. May 2002 Draft.