DESIGN EXAMPLES—SECTION 4

CONTENTS

Section	Page DE-
4.0 CASE STUDY—ROCK CREEK	50
Figures for Section 4	
Figure 1—Flor Storage Facility Plan View	53
Figure 2—Typical Pond Edge Adjacent to Community Ditch	54
Figure 3—Typical Embankment Crest	54
Figure 4—Typical Pond Edge Adjacent to Filing No. 13	55
Figure 5—Typical Clay Cutoff Trench	55
Figure 6—Profile Pond Outlet Works	56
Figure 7—Plan Drop Box	56
Figure 8—Section Drop Box	57
Figure 9—Plan 78" RCP Outlet	58
Figure 10—Section 78" RCP Outlet	58
Figure 11—Rock Creek Flor Storage and Landscape Plan	59
Figure 12—Landscape Plan Construction Notes and Plant Legend	60
Figure 13—Planting and Trail Details	61
Figure 14—Grouted Boulder Drop Structures	64
Figure 15— LB3 Channel Profile	65
Figure 16—Typical Drop Structure	65
Figure 17—Grout Cutoff Section	66
Figure 18—Drop Structure Profile	66
Figure 19—Typical Drop Basin Section and Sill	67
Figure 20—Typical Drop Face Section	67
Figure 21—Drop Structure Measurement Table	68
Figure 22—LB3 Channel Plan	72
Figure 23—Typical Wetland Channel Section and LB3 Channel Profile	72
Figure 24—Check Structure Plan	
Figure 25—Check Structure Profile	73
Figure 26—Check Structure Layout Table	74
Figure 27—Check Structure Details	
Figure 28—Stream Stabilization Plan	
Figure 29—Grouted Boulder Check Structure with Low-Water Crossing Site Pla	
Figure 30—Typical Stream Stabilization Detail	
Figure 31—Stream Stabilization Site Plan	

4.0 CASE STUDY—ROCK CREEK

The purpose of this case study is to demonstrate the following features:

- Detention facility
- Grouted boulder drop structure
- Grouted boulder check structures and wetland bottom channels
- Stream bank stabilization including grouted boulder check structure with low-water crossing,
 slope flattening and revegetation

McLaughlin Water Engineers, Ltd. (MWE) and the Norris/Dullea Company (both based in Denver) prepared the attached drawings. Photographs are provided for each of the facilities featured in this case study.

The formal names of these projects are:

- 1. Tributary LB-3 Channel and Flor Storage Facility
- 2. Rock Creek Stabilization, Tributary RB-3 Outfall Pipe, and Community Pond East

The client for MWE and Norris/Dullea Company was Superior Metropolitan District No. 1 and the relevant drawings were prepared in 1994 and 1997.

Public reaction to the facilities shown on the attached pages and to the overall drainage plan has been extremely positive due to the aesthetic nature of the facilities, the fact that they nicely integrate into the community, their environmentally-sensitive nature and multi-purpose benefits. There is no question that the drainage system in Rock Creek substantially enhances community character and the value of residential properties.

DE-50





Detention Facility—Flor Storage Facility





Detention Facility—Flor Storage Facility and Interpretive Sign




Figure 1—Flor Storage Facility Plan View




Figure 2—Typical Pond Edge Adjacent to Community Ditch




Figure 3—Typical Embankment Crest




Figure 4—Typical Pond Edge Adjacent to Filing No. 13




Figure 5—Typical Clay Cutoff Trench




Figure 6—Profile Pond Outlet Works




Figure 7—Plan Drop Box




Figure 8—Section Drop Box




Figure 9—Plan 78" RCP Outlet




Figure 10—Section 78" RCP Outlet




Figure 11—Rock Creek Flor Storage and Landscape Plan

Construction Notes


- 1. All plant material, trial surface material, and site furniture will be provided and delivered to project area by the district. Installation of these items shall be by the Boulder County Youth group.
- 2. Trail cutting by district contractor. Trail surface installation by Boulder Co. Youth. Minimize disturbance to grades and vegetation by removing cut material from the site. Do not pile soil on existing vegetation adjacent to the trial. Seed disturbed areas with native seed.
- 3. Notify The Norris Dullea Company for Trial, Plant, and Site Furniture locations prior to installation.
- 4. Trees and shrubs to be planted per detail. Install plant material in general locations shown on plan. Adjust location relative to moisture conditions for each species. Refer to Plant Legend for optimal moisture conditions for each species.
- 5. Water all planted material every 2 days for the first 30 days after planting. Reduce watering to every 4 days from 31 days to 90 days after planting. fully saturate soil within planting saucer with pond water. Minimize disturbance to the pond bank while obtaining water. Suspend watering schedule if pond floods. Resume watering after water levels reaches normal pool level.
- 6. Compact crusher fines in 2" lifts with sod roller. Maintain crusher fine material within the 6' cut area. Mound crusher fines 1" above edges in center of trail.

Plant Legend

Sym.	Plant Name	Size/Condition	Planting Instructions
PC	Plains Cottonwood	1 1/2" Cal. B&B	1'-2' above water table no water in planting pit not in water quality zone
PLW	Peach Leaf Willow	1 1/2" Cal. B4B	1'-2' above water table no water in planting pit not in water quality zone
CB	Common Boxelder	1 1/2" Cal. B&B	.5'-1.5' above water table no water in planting pit
TLA	Thin-Leaf Alder	5 Gal.	.5'-1.5' above water table no water in planting pit
NC	Natíve Chokecherry	5 Gal.	2'-3' above water table no water in planting pit not in water quality zone
SW	Sandbar Willow	5 Gal.	.5'-1' above water table no water in planting pit
RD	Redosier Dogwood	5 Gal.	.5'-1' above water table no water in planting pit
WR	Woods Rose	5 Gal.	2'-4' above water table no water in planting pit not in water quality zone


Figure 12—Landscape Plan Construction Notes and Plant Legend

DE-60 06/2001




Shrub Planting Detail

Tree Planting Detail



Wetland Planting Section




Trail Construction Section

Figure 13—Planting and Trail Details





Grouted Boulder Drop Structures on Tributary LB-3 Channel



Grouted Boulder Drop Structures on Tributary LB-3 Channel




Figure 14—Grouted Boulder Drop Structures




Figure 15— LB3 Channel Profile




Figure 16—Typical Drop Structure




Figure 17—Grout Cutoff Section




Figure 18—Drop Structure Profile




Figure 19—Typical Drop Basin Section and Sill




Figure 20—Typical Drop Face Section

(ALL DIMENSIONS ARE IN FEET)	REMARKS	54.5 51.3 & 60.0 FLCY T = 7.3.7 AT UPSTREAM END	AND DOWNSTREAM		
	ELEV.	51.3 & 60.0		70.4	
	ELEV. U	54.5		73.7	
	ELEV.	73.0		81.5	
	ELEV.	50.5		9.69	
	ELEV.	49.0		68.7	
ABLE	ELEV.	0.69		77.5	
⊢ ⊢ Z	۵	1.5		1.0	
EME	z	18.5		10 6.5 7.9 1.0	
ASUF	>	00		6.5	
	٦	5		10	
URE	¥	25		25	
RUCI	7	6.75			
STI	I	7 83.25 6.75 25		31.2	
ROF	9	7		9	
	R.	91		16	
	FL	91		16	
	ER FL	91		91	
	EL	9		16	
	D R	ω		7.5	
	۵ ا	ω		7.5	
	C R	۵		ы	
	CL	۵		33	
	B R	ω		2	
	В	۵		5	
	A R	6.7		=	
	A _L	6.7		=	
	STATION OF DROP	2+15		3+97	

Figure 21—Drop Structure Measurement Table





Grouted Boulder Check Structures And Wetland Bottom Channels





Grouted Boulder Check Structures And Wetland Bottom Channels



Wetland Bottom Channel




Figure 22—LB3 Channel Plan




Figure 23—Typical Wetland Channel Section and LB3 Channel Profile

DE-72




Figure 24—Check Structure Plan




Figure 25—Check Structure Profile

CHECK STRUCTURE DESIGNATION	STA.	STA.	STA.
	7+00	8+40	10+50
SILL LENGTH	_ 3'	3'	3'
BASIN LENGTH	_ 10'	10'	10'
FACE LENGTH	_ 12'	12'	12'
APPROACH LENGTH	_ 8'	8'	8'
NOTCH WIDTH	_ 4'	4'	4'
BANK WIDTH	_ 18' L/18' R	18' L/18' R	18' L/18' R
WING EXTENSION	_ 0' L/0' R	0' L/0' R	0' L/0' R
OVERALL WIDTH	40'	40'	40'
BASIN WIDTH	_ 6'	6'	6'
1/2 UPSTREAM GROUT WIDTH	_ 13' L/13' R	13' L/13' R	13' L/13' R
MINIMUM BOULDER SIZE	_ 2'	2'	2'
RIPRAP TYPE FOR BASIN AND APPROACH	_ н	Н	Н
COORDINATES AT CREST			
NORTHING	_ 16,333	16,427.5	16,628
EASTING	_ 19,849	19,747	19,729
COORDINATES AT SILL			
NORTHING	_ 16,313	16,411	16,603.5
EASTING	_ 19,864	19,766	19,723
BASIN ELEVATION	_ 79.2	83.5	88.5
NOTCH ELEVATIONS/ROW ELEVATIONS			
ROW 1	_ 80.4/80.4	84.7/84.7	89.7/89.7
ROW 2	_ 80.4/80.9	84.7/85.2	89.7/90.2
ROW 3	_ 81.0/81.6	85.3/85.9	90.3/90.9
ROW 4	_ 81.7/82.3	86.0/86.6	91.0/91.6
ROW 5	_ 82.4/83.0	86.7/87.3	91.7/92.3
ROW 6	_ 83.1/83.7	87.4/88.0	92.4/93.0
CREST ROW	_ 83.4/84.4	87.7/88.7	92.7/93.7
BOULDER WING ELEVATIONS			
ELEVATION A	_ 84.7	89.0	94.0
ELEVATION B	_ NA	NA	NA
ELEVATION C	_ NA	NA	NA
CUTOFF DEPTH	5'	5'	5'
ANGLE L (in degrees)	- 45°	45°	45°
ANGLE R (in degrees)	- 45°	45°	45°
WEEP DRAIN OUTLET-ELEVATION D			

^{*} IF NA APPEARS IN TABLE, THEN THAT PARTICULAR ROW OR ELEVATION IS NOT REQUIRED IN THE CHECK STRUCTURE.

Figure 26—Check Structure Layout Table




Figure 27—Check Structure Details






Stream Bank Stabilization Including Grouted Boulder Check Structure With Low-Water Crossing, Slope Flattening, And Revegetation





Stream Bank Stabilization Including Grouted Boulder Check Structure With Low-Water Crossing, Slope Flattening, And Revegetation





Stream Bank Stabilization Including Grouted Boulder Check Structure With Low-Water Crossing, Slope Flattening, And Revegetation




Figure 28—Stream Stabilization Plan




Figure 29—Grouted Boulder Check Structure with Low-Water Crossing Site Plan




Figure 30—Typical Stream Stabilization Detail




Figure 31—Stream Stabilization Site Plan