ATTACHMENT E

Determination of Erosion Potential

 E_p is determined as follows- The *total effective work* done on the channel boundary is derived and used as a metric to predict the likelihood of channel adjustment given watershed and stream hydrologic and geomorphic variables. The index under urbanized conditions is compared to the index under pre-urban conditions expressed as a ratio (E_p) . The effective work index (W) is computed as the excess shear stress that exceeds a critical value for streambed mobility or bank material erosion integrated over time and represents the total work done on the channel boundary:

$$W = \sum_{i=1}^{n} \left(\tau_i - \tau_c \right)^{1.5} \cdot V \cdot \Delta t_i \tag{1}$$

Where τ_c = critical shear stress that initiates bed mobility or erodes the weakest bank layer, τ_i = applied hydraulic shear stress, Δt = duration of flows (in hours), and n = length of flow record. The effective work index for presumed stable stream channels under pre-urban conditions is compared to stable and unstable channels under current urbanized conditions. The comparison, expressed as a ratio, is defined as the Erosion Potential (Ep)¹ (McRae (1992, 1996).

$$Ep = \frac{W_{post}}{W_{pre}} \tag{2}$$

where:

 W_{post} = work index estimated for the post-urban condition W_{pre} = work index estimated for the pre-urban condition

MacRae, C.R. 1992. The Role of Moderate Flow Events and Bank Structure in the Determination of Channel Response to Urbanization. Resolving conflicts and uncertainty in water management: Proceedings of the 45th Annual Conference of the Canadian Water Resources Association. Shrubsole, D, ed. 1992, pg. 12.1-12.21; MacRae, C.R. 1996. Experience from Morphological Research on Canadian Streams: Is Control of the Two-Year Frequency Runoff Event the Best Basis for Stream Channel Protection. Effects of Watershed Development and Management on Aquatic Ecosystems, ASCE Engineering Foundation Conference, Snowbird, Utah, pg. 144-162