

**STATE OF CALIFORNIA
CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
LOS ANGELES REGION**

**MONITORING AND REPORTING PROGRAM NO. CI-8498
FOR
SKYWORKS SOLUTIONS, INC.**

**ENROLLMENT UNDER REGIONAL BOARD
ORDER NO. R4-2002-0030 (Series No. 016)
SLIC FILE NO. 423**

I. MONITORING AND REPORTING REQUIREMENTS

- A. Skyworks Solutions, Inc. (hereinafter Discharger) shall implement this monitoring program on the effective date of this enrollment (June 16, 2003) under Regional Board Order No. R4-2002-0030. The first monitoring report under this program, for the monitoring period July – September 2003, shall be received at the Regional Board by October 15, 2003. Subsequent monitoring reports shall be received at the Regional Board according to the following schedule:

<u>Monitoring Period</u>	<u>Report Due</u>
January – March	April 15
April – June	July 15
July – September	October 15
October – December	January 15
Annual Summary Report	March 1 of each year

- B. If there is no discharge during any reporting period, the report shall so state. Monitoring reports must be addressed to this Regional Board, Attention: Information Technology Unit.
- C. By March 1 of each year, the Discharger shall submit an annual summary report to the Regional Board. The report shall contain both tabular and graphical summaries of the monitoring data obtained during the previous calendar year. In addition, the Discharger shall discuss the compliance record and the corrective actions taken or planned, which may be needed to bring the discharge into full compliance with the Requirements.
- D. Each monitoring report shall contain a separate section titled “Summary of Non-Compliance” which discusses the compliance record and the corrective actions taken or planned that may be needed to bring the discharge into full compliance with waste discharge requirements. This section shall be located at the front of the report and shall clearly list all non-compliance with discharge requirements, as well as all excursions of effluent limitations.

June 16, 2003

- E. The Discharger shall comply with requirements contained in Section G. of Order No. R4-2002-0030 “*Monitoring and Reporting Requirements*” in addition to the aforementioned requirements.

II. WATER QUALITY MONITORING

A. Influent Monitoring

Representative samples of groundwater shall be obtained from the trench and de-watering system (French drain de-watering system), prior to any treatment. This sampling station shall not be changed and any proposed change of sampling location shall be identified and approved by the Executive Officer prior to their use.

The following shall constitute the influent-monitoring program for the groundwater extraction wells:

<u>Constituents</u>	<u>Units</u>	<u>Type of Sample</u>	<u>Minimum Frequency of Analysis</u>
pH	pH units	grab	Semi-annual
Temperature	°F	grab	Semi-annual
Benzene	µg/L	grab	Semi-annual
Toluene	µg/L	grab	Semi-annual
Ethylbenzene	µg/L	grab	Semi-annual
Total Xylenes	µg/L	grab	Semi-annual
Methyl Tertiary Butyl Ether	µg/L	grab	Semi-annual
Carbon tetrachloride	µg/L	grab	Semi-annual
1,1-dichloroethylene	µg/L	grab	Semi-annual
1,4-Dioxane	µg/L	grab	Semi-annual
1,1-dichloroethane	µg/L	grab	Semi-annual
1,2-dichloroethane	µg/L	grab	Semi-annual
1,1,1-trichloroethane	µg/L	grab	Semi-annual
Trichloroethylene	µg/L	grab	Semi-annual
Tetrachloroethylene	µg/L	grab	Semi-annual
Vinyl chloride	µg/L	grab	Semi-annual
Freon 113	µg/L	grab	Semi-annual
Total dissolved solids	mg/L	grab	Semi-annual
Sulfate	mg/L	grab	Semi-annual
Chloride	mg/L	grab	Semi-annual
Boron	mg/L	grab	Semi-annual
Hexavalent chromium	µg/L	grab	Annual
Total Chromium	µg/L	grab	Annual
Priority pollutant*	µg/L	grab	one-time

* A complete list of priority pollutants (Attachment A) is attached, but the Discharger is required to test only for metals and volatile organic compounds (VOCs) on the priority pollutant list.

B. Effluent Monitoring

A sampling station shall be established at the point of discharge (the end point of the groundwater treatment system or at the passive infiltration point) and shall be located where representative samples of the effluent can be obtained. This sampling station shall not be changed and any proposed change of sampling location shall be identified and approved by the Executive Officer prior to its use.

The following shall constitute the effluent monitoring program for the treated groundwater prior to discharge to the injection wells:

<u>Constituents</u>	<u>Units</u>	<u>Type of Sample</u>	<u>Minimum Frequency of Analysis</u>
pH	pH units	grab	quarterly
Temperature	°F	grab	quarterly
Benzene	µg/L	grab	quarterly
Toluene	µg/L	grab	quarterly
Ethylbenzene	µg/L	grab	quarterly
Total Xylenes	µg/L	grab	quarterly
Methyl Tertiary Butyl Ether	µg/L	grab	quarterly
Carbon tetrachloride	µg/L	grab	quarterly
1,1-dichloroethylene	µg/L	grab	quarterly
1,4-Dioxane	µg/L	grab	quarterly
1,1-dichloroethane	µg/L	grab	quarterly
1,2-dichloroethane	µg/L	grab	quarterly
1,1,1-trichloroethane	µg/L	grab	quarterly
Trichloroethylene	µg/L	grab	quarterly
Tetrachloroethylene	µg/L	grab	quarterly
Vinyl chloride	µg/L	grab	quarterly
Freon 113	µg/L	grab	quarterly
Total dissolved solids	mg/L	grab	quarterly
Sulfate	mg/L	grab	quarterly
Chloride	mg/L	grab	quarterly
Boron	mg/L	grab	quarterly
Hexavalent chromium	µg/L	grab	Semi-annual
Total Chromium	µg/L	grab	Semi-annual
<u>Priority pollutant*</u>	<u>µg/L</u>	<u>grab</u>	<u>one-time</u>

* A complete list of priority pollutants (Attachment A) is attached, but the Discharger is required to test only for metals and volatile organic compounds (VOCs) on the priority pollutant list.

C. Groundwater Monitoring

Representative samples of groundwater shall be obtained from groundwater monitoring wells S-10, S-2, S-12, and S-13. A sampling station shall be established for each groundwater monitoring well and shall be located where representative samples can be obtained. These sampling stations shall not be changed and any proposed change of monitoring locations shall be identified and approved by the Executive Officer prior to their use. The following shall constitute the groundwater monitoring program:

<u>Constituents</u>	<u>Units</u>	<u>Type of Sample</u>	<u>Minimum Frequency of Analysis</u>
pH	pH units	grab	Annual
Temperature	°F	grab	Annual
Benzene	µg/L	grab	Annual
Toluene	µg/L	grab	Annual
Ethylbenzene	µg/L	grab	Annual
Total Xylenes	µg/L	grab	Annual
Methyl Tertiary Butyl Ether	µg/L	grab	Annual
Carbon tetrachloride	µg/L	grab	Annual
1,1-dichloroethylene	µg/L	grab	Annual
1,4-Dioxane	µg/L	grab	Annual
1,1-dichloroethane	µg/L	grab	Annual
1,2-dichloroethane	µg/L	grab	Annual
1,1,1-trichloroethane	µg/L	grab	Annual
Trichloroethylene	µg/L	grab	Annual
Tetrachloroethylene	µg/L	grab	Annual
Vinyl chloride	µg/L	grab	Annual
Freon 113	µg/L	grab	Annual
Hexavalent chromium	µg/L	grab	Annual
Total Chromium	µg/L	grab	Annual
Total dissolved solids	mg/L	grab	Annual
Sulfate	mg/L	grab	Annual
Chloride	mg/L	grab	Annual
Boron	mg/L	grab	Annual

All groundwater monitoring reports must include, at minimum, the following:

- a. Well identification, date and time of sampling;
- b. Sampler identification, and laboratory identification; and
- c. Quarterly observation of groundwater levels, recorded to 0.01 feet mean sea level and groundwater flow direction.

III. WASTE HAULING REPORT

In the event that wastes are hauled for further treatment or to a disposal site, the name and address of the hauler of the waste shall be reported in each quarterly monitoring report, along with quantities hauled during the quarter, and the location of the final point of disposal. If no wastes are hauled during the reporting period, a statement to that effect shall be submitted in the quarterly monitoring report.

IV. OPERATION AND MAINTENANCE REPORT

The Discharger shall file a technical report with this Regional Board, no later than 30 days after receipt of these Waste Discharge Requirements, relative to the operation and maintenance program for the groundwater treatment system. The information to be contained in that report shall include, at a minimum, the following:

1. The name, address, and telephone number of the person or company responsible for operation and maintenance of the groundwater treatment system;
2. Type of maintenance (preventive or corrective); and
3. Frequency of maintenance, if preventive.

V. MONITORING FREQUENCIES

Specifications in this monitoring program are subject to periodic revisions. Monitoring requirements may be modified or revised by the Executive Officer based on review of monitoring data submitted pursuant to this Order. Monitoring frequencies may be adjusted to a less frequent basis or parameters and locations dropped by the Executive Officer if the Discharger makes a request and the request is backed by statistical trends of monitoring data submitted.

VI. CERTIFICATION STATEMENT

Each report shall contain the following completed declaration:

"I certify under penalty of law that this document, including all attachments and supplemental information, was prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true,

