

0 5,000 10,000
Feet



Map Grid Index

LEGEND:

- Groundwater Monitoring Well
- Agricultural Supply Well
- ⊕ Domestic Supply Well
- Other Supply Well
- Groundwater Extraction Well (Active) Multiuse Test Well, or Inactive Extraction/Injection Well
- ▲ Inactive In Situ Reactive Zone Injection Well
- ◆ Freshwater Injection Well
- PG&E-Owned Property
- PG&E Compressor Station
- County Parcel
- Transmission Line
- Approximate Limit of Saturated Alluvium Upper Aquifer (Dashed Where Inferred)
- ● ● Approximate Location of Lockhart Fault; Fault Trace is Inferred, and There is No Surface Expression (Stamos et al. 2001)
- Bedrock Exposed at Ground Surface
- See Footnote 3.
- Approximate Outline of Cr(VI) or Cr(T) in Upper Aquifer Exceeding Values of 3.1 and 3.2 µg/L, Respectively, Second Quarter 2017
- Approximate 10 µg/L Outline of Cr(VI) or Cr(T)
- Concentrations in Upper Aquifer, Second Quarter 2017
- Approximate 50 µg/L Outline of Cr(T)
- Concentrations in Upper Aquifer, Second Quarter 2017
- Approximate 1,000 µg/L Outline of Cr(VI) or Cr(T)
- Concentrations in Upper Aquifer, Second Quarter 2017

MW-177D Well ID

1.5/1.7 Cr(VI)/Cr(T) concentrations in µg/L; maximum of primary and duplicate samples during Second Quarter 2017 sampling.

(0.73/1.2) Data in parentheses are from previous reporting period.
See Table E-1 for sample dates.

Groundwater Cr(VI) Concentrations in Monitoring Wells:

- More than 1,000 µg/L
- 10 to 50 µg/L
- 100 to 1,000 µg/L
- 3.1 to 10 µg/L
- 50 to 100 µg/L
- Less than 3.1 µg/L or ND

ABBREVIATIONS:

µg/L	Micrograms per Liter
Cr(VI)	Hexavalent Chromium
Cr(T)	Total Dissolved Chromium
J	Estimated Result
ND	Not Detected

NOTES:


1. Chromium results are shown for Site-wide Groundwater Monitoring Program and domestic wells sampled in the Second Quarter (April through June) 2017 monitoring period. For wells sampled multiple times during the reporting period, the most recent results are shown.
2. The concentration contours are based on Second Quarter 2017 chromium results for the groundwater monitoring and extraction wells that are completed in the shallow zone and deep zone of the Upper Aquifer as noted on Figures 5-1 and 5-2. Results for domestic wells (brown-colored labels) were not used for chromium plume contouring, except for those in the northern disputed plume areas, pursuant to the Lahonton Regional Water Quality Control Board's Cleanup and Abatement Order dated November 4, 2015 (Water Board 2015).
3. Pursuant to the Lahonton Regional Water Quality Control Board's Cleanup and Abatement Order dated November 4, 2015 (Water Board 2015), groundwater monitoring wells are not used for chromium contouring if they are located in the areas southwest of the Lockhart Fault and on or east of Dixie Road. Monitoring wells sampled southwest of Lockhart Fault and east of Dixie Road were sampled in support of United States Geological Survey background chromium investigations.
4. Chromium plume contours in the general area south of Highway 58, were developed using a larger set of monitoring data which is presented in the July 28, 2017 Second Quarter 2017 Monitoring Report for the In Situ Reactive Zone and Northwest Freshwater Injection Projects (Arcadis 2017). Select wells from that program are shown here for reference.
5. Chromium contours were changed on the eastern side of the plume during the Third Quarter of 2016. These changes were made based on discussions with the Water Board, requirements in the Order and professional judgement. These changes to the plume contours on the eastern side of the plume reflect a revised interpretation of monitoring data and do not indicate plume expansion.

WORKS CITED:

Arcadis. 2017. Second Quarter 2017 Monitoring Report for the In Situ Reactive Zone and Northwest Freshwater Injection Projects, Pacific Gas and Electric Company, Hinkley Compressor Station, Hinkley, California, California Regional Water Quality Control Board, Lahonton Region Order No. R6V-2008-0014 (Waste Discharge Requirements Identification No. 6B369107001). July 28.

Stamos, C.L., P. Martin, T. Nishikawa, and B.F. Cox. 2001. *Simulation of Ground-Water Flow in the Mojave River Basin, California*. U.S. Geological Survey Water-Resources Investigations Report 01-4002, Version 3. Prepared in cooperation with the Mojave Water Agency.

Water Board. 2015. Cleanup and Abatement Order No. R6V-2015-0068 Requiring Pacific Gas and Electric Company to Clean up and Abate Waste Discharges of Total and Hexavalent Chromium to the Groundwaters of the Mojave Hydrologic Unit. November 4.




**See Legend Figure for
Feature Descriptions**

0 500 1,000
Feet



MAP 01




**See Legend Figure for
Feature Descriptions**

0 500 1,000
Feet



MAP 02




**See Legend Figure for
Feature Descriptions**

0 500 1,000
Feet



MAP 03




**See Legend Figure for
Feature Descriptions**

0 500 1,000
Feet



MAP 04




**See Legend Figure for
Feature Descriptions**

0 500 1,000
Feet



MAP 05





**See Legend Figure for
Feature Descriptions**


0 500 1,000
Feet



MAP 06








See Legend Figure for Feature Descriptions

0 500 1,000
Feet



MAP 09




See Legend Figure for
Feature Descriptions


0 500 1,000
Feet



MAP 10



MAP 11




**See Legend Figure for
Feature Descriptions**

0 500 1,000
Feet



MAP 12




**See Legend Figure for
Feature Descriptions**

0 500 1,000
Feet




MAP 13



0 500 1,000
Feet




MAP 14



0 500 1,000
Feet



MAP 15



See Legend Figure for
Feature Descriptions

0 500 1,000 Feet



MAP 16