## CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD SAN DIEGO REGION

ORDER NO. 93-125

# WASTE DISCHARGE REQUIREMENTS FOR POOLE PROPERTIES, INC. MOUNT PALOMAR WINERY RIVERSIDE COUNTY

The California Regional Water Quality Control Board, San Diego Region (hereinafter Regional Board), finds that:

- On April 10, 1978 this Regional Board adopted Order No. 78-10, "Waste Discharge Requirements for Mount Palomar Winery Near Temecula, California." Addendum No. 1 established requirements for the disposal of up to 50,000 gallons per month of winery wastewater.
- 2. Mr. Peter A. Poole is currently the Vice President and General Manager of Mount Palomar Winery (hereinafter discharger), a public corporation.
- 3. Mr. Poole reported that the waste water is generated from the washing of wine production equipment and winery floors. Chemicals used in these processes are soda ash, citric acid and a chlorine disinfectant. The waste water is discharged to three evaporation ponds that are lined with Permaline X-210 Containment Liners. Domestic waste water is treated and discharged via a septic/subsurface disposal system.
- 4. The evaporation ponds are 110 feet long x 30 feet wide x 4 feet deep each. Each pond has a separate underdrain system for monitoring any seepage from the ponds. The ponds have separate shut-off valves so that pond usage can be alternated.
- 5. Ray Forkey Construction certified that the ponds and monitor drains were constructed in compliance with the plans and specifications.
- 6. Mount Palomar Winery is located on 173 acres of land approximately 5.5 miles east of Temecula in the center of Section 29 (projected), T7S, R2W, SBB&M, in the Gertrudis Hydrographic Subarea (2.42) of the Auld Hydrographic Area of the Santa Margarita Hydrographic Unit.
- 7. As a part of the 1993-1994 Waste Discharge Order Update Program, Order No. 78-10 and Addendum No. 1 to Order No. 78-10, were reviewed by Regional Board staff. As a result of this review, modifications have been incorporated into this Order. This Order makes changes to the Findings, Discharge Specifications, Reporting Requirements and Monitoring and Reporting Program of Order No. 78-10.

- 8. The Rancho California Water District supplies water to the winery.
- 9. As prescribed in Order 78-10, the discharger submitted selfmonitoring reports that contained effluent analyses. The average values and ranges for the sampled constituents for 1983 through 1987 are as follows;

Constituents	Unit	Average	Range
Total Dissolved			
Solids	mg/l	451	335 - 580
Chlorides	mg/l	46	0 - 118
Sodium	mg/l	88	40 - 116
Sulfate	mg/l	77	16 - 145
Boron	mg/l	0.17	<0.1 - 0.2

Note: mg/l = milligrams per liter

- 10. The discharge of wastewater to the evaporation ponds at Mount Palomar Winery is exempt from the provisions of California Code of Regulations, Title 23, Division 3, Chapter 15, Discharges of Waste to Land, pursuant to Section 2511 (b) of that chapter.
- 11. The Comprehensive Water Quality Control Plan Report, San Diego Basin (9) (Basin Plan) was adopted by this Regional Board on March 17, 1975; and subsequently approved by the State Water Resources Control Board (State Board). Subsequent revisions to the Basin Plan have also been adopted by the Regional Board and approved by the State Board.
- 12. The Basin Plan established the following beneficial uses for surface waters of the Auld Hydrologic Area:
  - (a) Municipal and domestic supply
  - (b) Agricultural supply
  - (c) Industrial service supply
  - (d) Industrial process supply
  - (e) Ground water recharge (potential)
  - (f) Water contact recreation
  - (g) Non-contact water recreation
  - (h) Warm freshwater habitat
  - (i) Cold freshwater habitat
  - (j) Wildlife habitat
- 13. The Basin Plan established the following beneficial uses for ground waters of the Auld Hydrologic Area:
  - (a) Municipal and domestic supply
  - (b) Agricultural irrigation

## (c) Industrial service supply

14. The Basin Plan establishes the following water quality objectives for the Auld Hydrologic Area:

Total Dissolved Solids 500 mg/l 500 mg/l 250 mg/l 250 mg/l Percent Sodium 60 % 60 % 60 % Sulfate 250 mg/l 250 mg/l 250 mg/l Nitrate (as NO <sub>3</sub> ) 10 mg/l Nitrogen and Phosphorus	Constituent	Concentration not more than 10 perceduring any one year Surface Water	nt of the time r period
Methylene Blue Active 0.5 mg/l 0.5 mg/l Substance Boron 0.5 mg/l 0.5 mg/l Dissolved Oxygen ** Odor None None Turbidity 20 NTU 5 NTU	Chloride Percent Sodium Sulfate Nitrate (as NO <sub>3</sub> ) Nitrogen and Phosphorus Iron Manganese Methylene Blue Active Substance Boron Dissolved Oxygen Odor Turbidity Color	250 mg/l 60 % 250 mg/l  * 0.3 mg/l 0.05 mg/l 0.5 mg/l  ** None 20 NTU 20 Units	250 mg/l 60 % 250 mg/l 10 mg/l 0.3 mg/l 0.05 mg/l 0.5 mg/l 0.5 mg/l None 5 NTU 15 Units

Note: mg/l = milligrams per liter
NTU = Nephelometric Turbidity Units

- Concentrations of nitrogen and phosphorus, by themselves or in combination with other nutrients, shall be maintained at levels below those which stimulate algae and emergent plant growth. Threshold total Phosphorus (P) concentrations shall not exceed 0.05 mg/l in any stream at the point where it enters any standing body of water, nor 0.025 mg/l in any standing body of water. A desired goal in order to prevent plant nuisances in streams and other flowing waters appears to be 0.1 mg/l total P. These values are not to be exceeded more than 10 percent of the time unless studies of the specific water body in question clearly show that water quality objective changes are permissible and changes are approved by the Regional Board. Analogous threshold values have not been set for nitrogen compounds; however, natural ratios of nitrogen to phosphorus are to be determined by surveillance and monitoring and upheld. If data are lacking, a ratio of N:P = 10:1 shall be used.
- \*\* Ninety percent or more of natural seasonal minimum oxygen concentration and more than 5.0 mg/l maintained at least 90 percent of the time.

15. The Basin Plan also contains the following prohibitions:

"Discharge of treated or untreated sewage or industrial wastewater, exclusive of cooling water or other waters which are chemically unchanged, to a watercourse, is prohibited except in cases where the quality of said discharge complies with the receiving body's water quality objectives." Allowance for dilution would be made on a case-by-case basis by the water Regional Board. Consideration would include streamflow data, the degree of treatment provided and safety measures to ensure reliability of facility performance. As an example, discharge of secondary effluent would probably be permitted if streamflow provided 100:1 dilution capability.

"Discharging of treated or untreated sewage or industrial wastes in such manner or volume as to cause sustained surface flow or pending on lands not owned or under the control of the discharger is prohibited except in cases defined in the previous paragraph and in cases in which the responsibility for all downstream adverse effects is accepted by the discharger."

"The dumping or deposition of oil, garbage, trash or other solid municipal, industrial or agricultural waste directly into inland waters or watercourses or adjacent to the watercourses in any manner which may permit its being washed into the watercourse is prohibited."

- 16. The Mount Palomar Winery facility is an existing facility and as such is exempt from the provisions of the California Environmental Quality Act, in accordance with Title 14, California Code of Regulations, Chapter 3, Article 18, Section 15261.
- 17. The Regional Board, in establishing the requirements contained herein, considered factors including, but not limited to, the following:
  - a. Beneficial uses to be protected and the water quality objectives reasonably required for that purpose;
  - b. Other waste discharges;
  - c. The need to prevent nuisance;
  - d. Past, present, and probable future beneficial uses of water;
  - e. Environmental characteristics of the hydrographic unit under consideration, including the quality of water available thereto;
  - f. Water quality conditions that could reasonably be achieved through the coordinated control of all factors which affect water quality in the area;
  - g. Economic considerations; and
  - h. The need for developing housing within the region.

- 18. The Regional Board has considered all water resource related environmental factors associated with the proposed discharge of waste.
- 19. The Regional Board has notified the discharger and all known interested parties of the intent to prescribe waste discharge requirements for the proposed discharge.
- 20. The Regional Board in a public meeting heard and considered all comments pertaining to its proposed action.

IT IS HEREBY ORDERED, that Mount Palomar Winery, in order to meet provisions contained in Division 7 of the California Water Code and regulations adopted thereunder, shall comply with the following:

#### A. PROHIBITIONS

- 1. Discharges of wastes which have not been specifically described in the report of waste discharge and for which valid waste discharge requirements are not in force are prohibited.
- 2. The discharge of any radiological, chemical or biological warfare agent, or high-level radiological waste is prohibited.
- 3. Storage, use and/or disposal of wastes in a manner that would result in ponding or surfacing of wastes on lands beyond the disposal area, as described in the findings of this Order, is prohibited.
- 4. Bypassing or direct discharge of treated or untreated liquid or solid wastes to Gertrudis Creek or tributaries thereto, or beyond the limits of lands specifically designated for waste handling or disposal is prohibited.
- 5. Discharges of wastes to runoff impounding facilities are prohibited.
- 6. Discharges of domestic wastes into the evaporation ponds are prohibited. All domestic wastes shall be discharged to a subsurface disposal system for disposal in accordance with all applicable ordinances of the Riverside County Department of Public Health.
- 7. The discharge of waste water shall not:
  - a. Cause the occurrence of coliform or pathogenic organisms in waters pumped from the basin;
  - b. Cause the occurrence of objectionable tastes and odors in

waters pumped from the basin;

- c. Cause waters pumped from the basin to foam;
- d. Cause the presence of toxic materials in waters pumped from the basin;
- e. Cause the pH of waters pumped from the basin to fall below 6.0 or rise above 9.0;
- f. Cause this Regional Board's objectives for the ground and surface waters of the Auld Hydrologic Area as established in the Basin Plan to be exceeded;
- g. Cause odors, septic conditions, mosquitoes or other vectors, weed growth or other nuisance conditions in any inland watercourse;
- h. Cause a surface flow recognizable as sewage in any inland watercourse;
- i. Cause pollution, contamination or nuisance or adversely affect beneficial uses of the Auld Hydrographic Area as established in the Basin Plan.
- 8. The discharge of a waste flow volume in excess of 50,000 gallons per month is prohibited unless the discharger obtains revised waste discharge requirements for the proposed increased flow.

## B. DISCHARGE SPECIFICATIONS

- 1. The bottoms and sides of all ponds that contain wastewater shall be maintained in an impervious state.
- 2. Each pond that contains wastewater shall be provided with an underdrain system adequate to monitor any leakage through the pond bottom and sides. The underdrain system shall terminate on the outside of the pond dike and shall be maintained at all times so that samples of any leakage that occurs may be collected.
- 3. All waste treatment, containment and disposal facilities (including evaporation ponds) shall be protected against 100-year peak stream flows as defined by the Riverside County flood control agency.
- 4. All waste treatment, containment and disposal facilities (including evaporation ponds) shall be protected against erosion, overland runoff, and other impacts resulting from a 100-year frequency 24-hour storm.

#### C. PROVISIONS

- 1. Neither the treatment nor the discharge of waste shall create pollution, contamination or nuisance, as defined by Section 13050 of the California Water Code.
- 2. The discharger must comply with all conditions of this Order. Any noncompliance with this Order constitutes a violation of the California Water Code and is grounds for (a) enforcement action; (b) termination, revocation and reissuance, or modification of this Order; or (c) denial of a report of waste discharge in application for new or revised waste discharge requirements.
- 3. In an enforcement action, it shall not be a defense for the discharger that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with this Order. Upon reduction, loss, or failure of the treatment facility, the discharger shall, to the extent necessary to maintain compliance with this Order, control production or all discharges, or both, until the facility is restored or an alternative method of treatment is provided. The provision applies for example, when the primary source of power of the treatment facility fails, is reduced, or is lost.
- 4. The discharger shall take all reasonable steps to minimize or correct any adverse impact on the environment resulting from noncompliance with this Order, including such accelerated or additional monitoring as may be necessary to determine the nature and impact of the noncompliance.
- 5. The discharger shall, at all times, properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the discharger to achieve compliance with conditions of this Order. Proper operation and maintenance include effective performance, adequate funding, adequate operator staffing and training, and adequate laboratory and process controls including appropriate quality assurance procedures. This provision requires the operation of backup or auxiliary facilities or similar systems only when necessary to achieve compliance with the conditions of this Order.
- 6. This Order may be modified, revoked and reissued, or terminated for cause including, but not limited to, the following:
  - a. Violation of any terms or conditions of this Order;
  - b. Obtaining this Order by misrepresentation or failure to disclose fully all relevant facts;

- c. A change in any condition that requires either a temporary or permanent reduction or elimination of the authorized discharge.
- 7. The filing of a request by the discharger for the modification, revocation and reissuance, or termination of this Order, or notification of planned changes or anticipated noncompliance does not stay any condition of this Order.
- 8. This Order is not transferable to any person except after notice to the Executive Officer. The Regional Board may require modification or revocation and reissuance of this Order to change the name of the discharger and incorporate such other requirements as may be necessary under the California Water Code. The discharger shall submit notice of any proposed transfer of this Order's responsibility and coverage to a new discharger as described under Reporting Requirement D.3.
- 9. This Order does not convey any property rights of any sort or any exclusive privileges. The requirements prescribed herein do not authorize the commission of any act causing injury to persons or property, nor protect the discharger from liability under federal, state or local laws, nor create a vested right for the discharger to continue the waste discharge.
- 10. The discharger shall allow the Regional Board, or an authorized representative upon the presentation of credentials and other documents as may be required by law, to:
  - a. Enter upon the discharger's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this Order;
  - b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this Order;
  - c. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this Order;
  - d. Sample or monitor at reasonable times, for the purposes of assuring compliance with this Order or as otherwise authorized by the California Water Code, any substances or parameters at any location.
- 11. A copy of this Order shall be maintained at Mount Palomar Winery and shall be available to operating personnel at all times.
- 12. The provisions of this Order are severable, and if any provision of this Order, or the application of any provision

of this Order to any circumstance, is held invalid, the application of such provision to other circumstances, and the remainder of this Order, shall not be affected thereby.

- 13. The discharger shall comply with the Monitoring and Reporting Program No. 93-125 as specified by the Executive officer.
- 14. The wastewater disposal facilities shall have adequate capacity for the full design flow of 50,000 gallons per month.
- 15. Waste discharge requirements shall remain applicable regardless of changes in ownership or lessee. A change in ownership shall be reported promptly to this Regional Board by letter.
- 16. The above prescribed waste discharge requirements are established only for (a) a discharge to lands owned by the discharger and specifically reserved for the purpose of effluent disposal; (b) a waste disposal operation as described in the Report of Waste Discharge; and (c) a waste discharge volume not in excess of 50,000 gallons per month.
- 17. Prior to initiating discharges of wastes from Mount Palomar Winery at locations other than those provided for by this Order or prior to initiating any material change in characteristics or volume of discharge, the discharger shall (a) submit a supplementary Report of Waste Discharge describing the proposed changes, and (b) obtain waste discharge requirements for the proposed changes.
- 18. The discharger shall implement an operation and maintenance program to maintain the pond liners and pond berms and embankments. This program shall include a schedule of routine inspections of the pond linings and berms, control of weeds, insects, and burrowing animals, and periodic removal of solid materials that accumulate on the bottom of the evaporation ponds.

## D. REPORTING REQUIREMENTS

- 1. The discharger shall file a new Report of Waste Discharge at least 120 days prior to the following:
  - a. The addition of a new process or product by the discharger that results in a change in the character of the wastes;
  - b. Significant change in the treatment or disposal method (e.g., change in the method of treatment which would

significantly alter the nature of the waste);

- c. Change in the disposal area from that described in the findings of this Order;
- d. Increase in flow beyond that specified in this Order;
- e. Other circumstances which result in a material change in character, amount, or location of the waste discharge;
- f. Any planned change in the regulated facility or activity which may result in noncompliance with this Order.
- 2. The discharger shall furnish, to the Executive Officer of this Regional Board, within a reasonable time, any information which the Executive Officer may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this Order. The discharger shall also furnish, to the Executive Officer, upon request, copies of records required to be kept by this Order.
- 3. The discharger must notify the Executive Officer, in writing at least 30 days in advance of any proposed transfer of this Order's responsibility and coverage to a new discharger. The notice must include a written agreement between the existing and new discharger containing a specific date for the transfer of this Orders responsibility and coverage between the current discharger and the new discharger. This agreement shall include an acknowledgement that the existing discharger is liable for violations up to the transfer date and that the new discharger is liable from the transfer date on.
- 4. The discharger shall comply with the attached Monitoring and Reporting Program No. 93-125, and further revisions thereto as specified by the Executive Officer. Monitoring results shall be reported at the intervals specified in Monitoring and Reporting Program No. 93-125.
- 5. Where the discharger becomes aware that it failed to submit any relevant facts in a Report of Waste Discharge or submitted incorrect information in a Report of Waste Discharge or in any report to the Regional Board, it shall promptly submit such facts or information.
- 6. If a need for a discharge bypass is known in advance, the discharger shall submit prior notice and, if at all possible, such notice shall be submitted at least 10 days prior to the date of the bypass.
- 7. The discharger shall report any noncompliance which may endanger health or the environment. Any such information shall be provided orally to the Executive Officer within 24

hours from the time the discharger becomes aware of the circumstances. A written submission shall also be provided within five days of the time the discharger becomes aware of the circumstances. The written noncompliance and its cause; the period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected; the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance. The Executive Officer, or an authorized representative, may waive the written report on a case-by-case basis if the oral report has been received within 24 hours. The following occurrence(s) must be reported to the Executive Officer within 24 hours:

- a. Any bypass from any portion of the treatment facility;
- b. Any discharge of treated or untreated wastewater resulting from pipeline breaks, obstruction, surcharge or any other circumstances.
- 8. All applications, reports or information submitted to the Executive Officer shall be signed and certified as follows:
  - a. The Report of Waste Discharge shall be signed as follows:
  - (1) For a corporation by a principal executive officer of at least the level of vice-president;
  - (2) For a partnership or sole proprietorship by a general partner or the proprietor, respectively;
  - (3) For a municipality, state, federal or other public agency by either a principal executive officer or ranking elected official.
  - b. All other reports required by this Order and other information required by the Executive Officer shall be signed by a person designated in paragraph (a) of this provision, or by a duly authorized representative of that person. An individual is a duly authorized representative only if:
  - The authorization is made in writing by a person described in paragraph (a) of this provision;
  - (2) The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity; and
  - (3) The written authorization is submitted to the Executive Officer.

c. Any person signing a document under this Section shall make the following certification:

"I certify the under penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment."

9. The discharger shall submit reports required under this Order, or other information required by the Executive Officer, to:

Executive Officer
California Regional Water Quality Control Board
San Diego Region
9771 Clairemont Mesa Blvd., Suite B
San Diego, CA 92124-1331

### E. NOTIFICATION

1. California Water Code Section 13263(g) states:

"No discharge of waste into waters of the state, whether or not such discharge is made pursuant to waste discharge requirements shall create a vested right to continue such discharge. All discharges of waste into waters of the state are privileges, not rights."

- 2. These requirements have not been officially reviewed by the United States Environmental Protection Agency and are not issued pursuant to Section 402 of the Clean Water Act.
- 3. The California Water Code provides that any person who intentionally or negligently violates any waste discharge requirements issued, reissued, or amended by this Regional Board is subject to a civil monetary remedy of up to 20 dollars per gallon of waste discharged or, if a cleanup and abatement order is issued, up to 15,000 dollars per day of violation or some combination thereof.
- 4. The California Water Code provides that any person failing or refusing to furnish technical or monitoring program reports, as required under this Order, or falsifying any information provided in the monitoring reports is guilty of a misdemeanor.
- 5. This Order becomes effective on the date of adoption by the Regional Board.

6. The requirements prescribed by this Order supersede the requirements prescribed by Order No. 78-10.

I, Arthur L. Coe, Executive Officer, do hereby certify the foregoing is a full, true, and correct copy of an Order adopted by the California Regional Water Quality Control Board, San Diego Region, on December 20, 1993.

Arthur L. Coe Executive Officer

## CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD SAN DIEGO REGION

## MONITORING AND REPORTING PROGRAM NO. 93-125 FOR MOUNT PALOMAR WINERY RIVERSIDE COUNTY

## A. MONITORING PROVISIONS

- 1. Samples and measurements taken as required herein shall be representative of the volume and nature of the monitored discharge. All samples shall be taken at the monitoring points specified in this Order and, unless otherwise specified, before the effluent joins or is diluted by any other waste stream, body of water, or substance. Monitoring points shall not be changed without notification to and the approval of the Executive Officer.
- 2. Appropriate flow measurement devices and methods consistent with accepted scientific practices shall be selected and used to ensure the accuracy and reliability of measurements of the volume of monitored discharges. The devices shall be installed, calibrated and maintained to ensure that the accuracy of the measurements is consistent with the accepted capability of that type of device. Devices selected shall be capable of measuring flows with a maximum deviation of less than ±5 percent from true discharge rates throughout the range of expected discharge volumes. Guidance in selection, installation, calibration and operation of acceptable flow measurement devices can be obtained from the following references:
  - a. "A Guide to Methods and Standards for the Measurement of Water Flow," U.S. Department of Commerce, National Bureau of Standards, NBS Special Publication 421, May 1975, 97 pp. (Available from the U.S. Government Printing Office, Washington, D.C. 20402. Order by SD Catalog No. C13.10:421.)
  - b. "Water Measurement Manual," U.S. Department of Interior, Bureau of Reclamation, Second Edition, Revised Reprint, 1974, 327 pp. (Available from the U.S. Government Printing Office, Washington, D.C. 20402. Order by Catalog No. 127,19/2:W29/2, Stock No. S/N 24003-0027.)
  - C. "Flow Measurement in Open Channels and Closed Conduits," U.S. Department of Commerce, National Bureau of Standards, NBS Special Publication 484, October 1977, 982 pp. (Available in paper copy or microfiche from National Technical Information Services (NTIS) Springfield, VA 22151. Order by NTIS No. PB-273-5ST.)

- d. "NPDES Compliance Sampling Manual," U.S. Environmental Protection Agency, Office of Water Enforcement. Publication MCD-51, 1977, 140 pp. (Available from the General Services Administration (8FFS), Centralized Mailing Lists Services, Building 41, Denver Federal Center, Denver, CO 80225.)
- 3. Monitoring must be conducted according to United States Environmental Protection Agency test procedures approved under Title 40, Code of Federal Regulations (CFR), Part 136, "Guidelines Establishing Test Procedures for Analysis of Pollutants Under the Clean Water Act" as amended, unless other test procedures have been specified in this Order.
- 4. All analyses shall be performed in a laboratory certified to perform such analyses by the California Department of Health Services or a laboratory approved by the Executive Officer.
- 5. Monitoring results must be reported on discharge monitoring report forms approved by the Executive Officer.
- 6. If the discharger monitors any pollutants more frequently than required by this Order, using test procedures approved under 40 CFR, Part 136, or as specified in this Order, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the discharger's monitoring report. The increased frequency of monitoring shall also be reported.
- 7. The discharger shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this Order, and records of all data used to complete the application for this Order. Records shall be maintained for a minimum of five years from the date of the sample, measurements, report or application. This period may be extended during the course of any unresolved litigation regarding this discharge or when requested by the Regional Board Executive Officer.
- 8. Records of monitoring information shall include:
  - a. The date, exact place, and time of sampling or measurements;
  - b. The individual(s) who performed the sampling or measurements;
  - c. The date(s) analyses were performed;
  - d. The individual(s) who performed the analyses;
  - e. The analytical techniques or method used; and

- f. The results of such analyses.
- 9. All monitoring instruments and devices which are used by the discharger to fulfill the prescribed monitoring program shall be properly maintained and calibrated as necessary to ensure their continued accuracy.
- 10. The discharger shall report all instances of noncompliance not reported under Reporting Requirement D.7 of this Order at the time monitoring reports are submitted. The reports shall contain the information listed in Reporting Requirement D.7.
- 11. The monitoring reports shall be signed by an authorized person as required by Reporting Requirement D.8.
- 12. A composite sample is defined as a combination of at least eight sample aliquots of at least 100 milliliters, collected at periodic intervals during the operating hours of a facility over a 24 hour period. For volatile pollutants, aliquots must be combined in the laboratory immediately before analysis. The composite must be flow proportional; either the time interval between each aliquot or the volume of each aliquot must be proportional to either the stream flow at the time of sampling or the total stream flow since the collection of the previous aliquot. Aliquots may be collected manually or automatically.
- 13. A grab sample is an individual sample of at least 100 milliliters collected at a randomly selected time over a period not exceeding 15 minutes.

## B. EFFLUENT MONITORING

- 1. The monthly volume of wastewater discharged to the evaporation ponds shall be reported semiannually.
- 2. A grab sample of the discharge shall be taken during the processing season and analyzed for the following constituents with the results reported annually:

Constituent	Unit	
Total Dissolved Solids Chloride Boron pH	mg/l mg/l mg/l	

Note: mg/l = milligrams per liter

## C. UNDERDRAIN MONITORING

1. If there is a discharge from the underdrain system, a grab sample shall be taken and analyzed for the following constituents with the results reported semiannually:

Constituent	Unit
Total Flow Volume Total Dissolved Solids Chloride Percent Sodium Sulfate Nitrate (as NO <sub>3</sub> ) Potassium Boron pH	gallons mg/l mg/l % mg/l mg/l mg/l mg/l mg/l

Note: mg/l = milligrams per liter

## D. OPERATION AND MAINTENANCE PROGRAM IMPLEMENTATION

By January 30 of each year the discharger shall submit a statement certifying that the operation and maintenance program developed pursuant to Provision C. 18 of Order No. 93-125 was implemented by the operating personnel throughout the previous year.

## E. SOLIDS DISPOSAL

 A log of the quantity and type of solid wastes hauled for disposal and the point of disposal shall be submitted annually.

## F. REPORT SCHEDULE

Report Frequency	Report Period	Report Due
Semiannually	January-June July-December	July 30 January 30
Annually	January-December	January 30

I, Arthur L. Coe, Executive Officer, do hereby certify the foregoing is a full true, and correct copy of an Addendum adopted by the California Regional Water Quality Centrol Foard, San Diego Region, on December 20, 1993.

Arthur L. Coe Executive Officer