



California Regional Water Quality Control Board San Diego Region



Linda S. Adams
Secretary for
Environmental Protection

Over 50 Years Serving San Diego, Orange, and Riverside Counties
Recipient of the 2004 Environmental Award for Outstanding Achievement from USEPA

Arnold Schwarzenegger
Governor

9174 Sky Park Court, Suite 100, San Diego, California 92123-4340
(858) 467-2952 • Fax (858) 571-6972
[http:// www.waterboards.ca.gov/sandiego](http://www.waterboards.ca.gov/sandiego)

June 16, 2006

Mr. Ogdon Watson
General Manager
Pauma Valley Community Services District
33129 Cole Grade Road
P.O. Box 434
Pauma Valley, CA 92061

In reply refer to:
**NCRU:01-
0145.02:Ebecker**

Dear Mr. Watson:

**ADOPTION OF ORDER NO. R9-2006-0049, WASTE DISCHARGE REQUIREMENTS FOR
PAUMA VALLEY COMMUNITY SERVICES DISTRICT, PAUMA VALLEY TREATMENT PLANT,
SAN DIEGO COUNTY**

Enclosed is a copy of Order No. R9-2006-0049 which was adopted by the Regional Board at their June 14, 2006 meeting. Order No. R9-2006-0049 updates waste discharge requirements for the discharge of treated wastewater effluent from the Pauma Valley Community Services District's treatment plant to on-site percolation ponds. Order No. R9-2006-0049 supersedes Order No. R9-1993-0046 and updates the monitoring and reporting requirements.

An electronic copy of Order No. R9-2006-0049 will be made available at our website at <http://www.waterboards.ca.gov/sandiego/orders/orders-06.html>.


Although not required in the Order, we would appreciate receiving periodic reports and updates of the schedule for the treatment plant upgrade. These reports can be included in the quarterly submittals of the District's self-monitoring reports. Please take the time to fill out our electronic customer service survey located at <http://www.calepa.ca.gov/customer/>.

The heading portion of this letter includes a Regional Board code number noted after "In reply refer to:" In order to assist us in the processing of your correspondence please include this code number in the heading or subject line portion of all correspondence and reports to the Regional Board pertaining to this matter.

California Environmental Protection Agency

If you have any questions regarding the above, please contact Mr. Eric Becker at (858) 492-1785 or via e-mail at Ebecker@waterboards.ca.gov.

Respectfully,



JOHN H. ROBERTUS
Executive Officer

Enclosure: 1. Order No. R9-2006-0049
2. Monitoring and Reporting Program No. R9-2006-0049

CC:

John Richards
Staff Counsel
Office of Chief Counsel (OCC)
State Water Resources Control Board
1001 "I" Street, 22nd Floor
Sacramento, CA 95814

Jolene Northrop
Kennedy/Jenks Consultants
16855 W. Bernardo Drive, # 360
San Diego, CA 92127

Matt Tebbetts
Principal Engineer
Kennedy/Jenks Consultants
16855 W. Bernardo Drive, # 360
San Diego, CA 92127

Brian Bernados
State Department of Health Services
1350 Front Street, Rm 2050
San Diego, CA 92101

Laura L. Peters
Water Resources Control Engineer
State Water Resources Control Board
1001 I Street, 16-53E
Sacramento, CA 95814

Mark Mc Pherson
County Department of Environmental
Health
5201 Ruffin Road, Suite C
San Diego, CA 92123

**CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
SAN DIEGO REGION**

TENTATIVE ORDER NO. R9-2006-0049

**WASTE DISCHARGE REQUIREMENTS
FOR THE
PAUMA VALLEY COMMUNITY SERVICES DISTRICT
PAUMA VALLEY TREATMENT PLANT
SAN DIEGO COUNTY**

Table of Contents

	Findings	2
A.	Prohibitions	5
B.	Discharge Specifications	5
C.	Facility Design and Operation Specifications	6
D.	Biosolids Specifications	7
E.	Standard Provisions	8
F.	Special Provisions	14
G.	Notifications	15
	Monitoring and Reporting Program No. R9-2006-0049	16
A.	Monitoring Provisions	16
B.	Discharge Monitoring	18
C.	Sewage Solids and Biosolids	19
D.	Monitoring Wells	20
E.	Operator Staffing	20
F.	Annual Report	20
G.	Report Schedule	20

**CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
SAN DIEGO REGION**

TENTATIVE ORDER NO. R9-2006-0049

**WASTE DISCHARGE REQUIREMENTS
FOR THE
PAUMA VALLEY COMMUNITY SERVICES DISTRICT
PAUMA VALLEY TREATMENT PLANT
SAN DIEGO COUNTY**

The California Regional Water Quality Control Board, San Diego Region (hereinafter Regional Board), finds that:

1. The Pauma Valley Community Services District (hereafter Discharger) owns and operates the Pauma Valley Treatment Plant (PVTP) that discharges up to 0.115 million gallons per day (MGD) of secondary treated effluent under Order No. R9-1993-0046.
2. On November 15, 2005, the Discharger submitted to this Regional Board an incomplete Report of Waste Discharge prepared by Kennedy/Jenks Consultants proposing to upgrade the PVTP and to increase its capacity to 0.150 MGD. On March 8, 2006, the Discharger, submitted a complete Report of Waste Discharge including documentation of compliance with the California Environmental Quality Act (CEQA).
3. The PVTP is at 33129 Cole Grade Road in Pauma Valley, an unincorporated area of San Diego County, within section 17 of Township 10 South, Range 1 West, San Bernardino Base Meridian.
4. The existing PVTP will be replaced with a packaged treatment plant that consists of conventional treatment processes such as flow equalization, aeration, anoxic zone, clarifiers, sludge holding tank, and disinfection or similar treatment processes. New and expanded percolation ponds will be designed and constructed for the disposal of up to 0.150 MGD of effluent from the plant.
5. In accordance with Section 2200, Title 23 of the California Code of Regulation, the threat to water quality and complexity of the treated wastewater discharge from the PVTP is determined to be category 2B.
6. The Discharger reported that the upgraded PVTP will produce an effluent with the following characteristics:

Projected Effluent Water Quality

Constituent	Units	Projected Effluent Water Quality
Biochemical Oxygen Demand ₅	mg/L	30
Total Suspended Solids	mg/L	30
Total Nitrogen (as N)	mg/L	10
Total Dissolved Solids	mg/L	800
Chloride	mg/L	200
Sulfate	mg/L	300
Fluoride	mg/L	1.0

7. This Regional Board, acting in accordance with Section 13244 of the California Water Code, adopted the Water Quality Control Plan for the San Diego Basin (9), (hereinafter Basin Plan) on September 8, 1994. The Basin Plan was subsequently approved by the State Water Resources Control Board (SWRCB) on December 13, 1994. Subsequent revisions to the Basin Plan have also been adopted by the Board and approved by the SWRCB. The Basin Plan contains beneficial uses and water quality objectives.
8. All wastewater discharges from the proposed wastewater treatment facilities are located within the Pauma Hydrologic Sub-Area (HSA 903.22) of the Monserate Hydrologic Area (HA 903.20) of the San Luis Rey Hydrologic Unit (HU 903.00). The Basin Plan established municipal, domestic supply, and agricultural supply as existing beneficial uses of ground water in HSA 903.22.
9. The Basin Plan states that waters designated for use as domestic or municipal supply shall not contain concentrations of chemical constituents in excess of the maximum contaminant levels specified in the California Code of Regulations, Title 22, Table 64449-A of Section 64449 (Secondary Maximum Contaminant Levels, Consumer Acceptance Limits), incorporated by reference, including future changes to the incorporated provisions as the changes take effect. Additionally the Basin Plan establishes the following ground water quality objectives for HA 903.22:

BASIN PLAN GROUNDWATER WATER QUALITY OBJECTIVES													(mg/L or as noted)	
(Concentrations not to be exceeded more than 10% of the time during any one year period)														
HYDROLOGIC AREA	TDS	Cl	SO ₄	%Na	NO ₃	Fe	Mn	M B A S	B	O D O R	TURB (NTU)	COLOR (UNITS)	F	
903.22 Pauma	800	300	400	60	10	0.3	0.05	0.5	0.75	None	5	15	1	

10. A discharge in compliance with this Order will be consistent with the standards, policies, and regulations established in the Basin Plan for the achievement of water quality objectives.
11. In establishing the effluent limits contained herein the Regional Board considered water quality data supplied in the RWD and the assimilative capacity of the soil and groundwater to ensure that groundwater would not exceed Basin Plan water quality objectives beyond the limits of the disposal area property.
12. In establishing the requirements contained herein the Regional Board considered factors including, but not limited to, the following:
 - a. Beneficial uses to be protected and the water quality objectives reasonably required for that purpose,
 - b. Other waste discharges,
 - c. The need to prevent nuisance,
 - d. Past, present, and probable future beneficial uses of the hydrologic subunits under consideration,
 - e. Environmental characteristics of the hydrologic subunits under consideration,
 - f. Water quality conditions that could reasonably be achieved through the coordinated control of all factors that affect water quality in the area,
 - g. Economic considerations,
 - h. The need for additional housing within the region.
13. The Discharger adopted a Mitigated Negative Declaration on March 12, 2001 prepared for the upgrade/expansion project pursuant to the provisions of the CEQA.
14. This Regional Board has considered all water resource related environmental factors associated with the proposed discharge of waste from the proposed PVTP.
15. This Regional Board has notified the discharger and all known interested parties of the intent to prescribe waste discharge requirements for the proposed discharge.
16. This Regional Board in a public meeting has heard and considered all comments pertaining to the proposed discharge of waste from the PVTP.

IT IS HEREBY ORDERED THAT, the Pauma Valley Community Services District (hereafter Discharger), in order to meet the provisions contained in Division 7 of the California Water Code and Regulations adopted thereunder, shall comply with the

following requirements, which supersede the requirements prescribed by Order No. R9-1993-0046, for the discharge from the Pauma Valley Treatment Plant to the Pauma Hydrologic Area (HA 903.22).

A. PROHIBITIONS

1. Discharge of wastes and sewage sludge and solids to lands that have not been specifically described in the RWD and for which valid waste discharge requirements are not in force are prohibited.
2. Discharges of treated or untreated solid or liquid waste to a navigable water or tributary of a navigable water are prohibited unless as authorized by an NPDES permit issued by this Regional Board.
3. Neither the treatment, storage nor disposal of waste shall create a pollution, contamination or nuisance, as defined by Section 13050 of the California Water Code.
4. The discharge of treated wastewater shall not cause a violation of the prohibitions contained in the Basin Plan.

B. DISCHARGE SPECIFICATIONS

1. Prior to the Discharger receiving authorization to discharge pursuant to section C.2 of this Order, effluent from the existing PVTP shall not contain constituents in excess of the following limitations:

Biochemical Oxygen Demand (BOD ₅ @ 20°C)	mg/L	45	30	--
Total Suspended Solids	mg/L	45	30	--
Total Dissolved Solids	mg/L	850	--	750
Chloride	mg/L	200	--	150
Sulfate	mg/L	300	--	260
Nitrate	mg/L		--	60
Fluoride	mg/L	1.5		1.0

¹The daily maximum effluent limitation shall apply to the results of a single composite or grab sample.

²The monthly average effluent limitation shall apply to the arithmetic mean of the results of all samples collected during any 30 consecutive calendar day period.

³The 12-month average effluent limitation shall apply to the arithmetic mean of the results of all samples collected during any 12 consecutive calendar month period.

2. After the Discharger receives authorization to discharge pursuant to section C.2 of this Order, effluent from the new PVTP shall not contain

constituents in excess of the following limitations:

CONSTITUENT	UNIT	DAILY MAXIMUM EFFLUENT LIMITATION	MONTHLY AVERAGE EFFLUENT LIMITATION	12-MONTH AVERAGE EFFLUENT LIMITATION
Biochemical Oxygen Demand (BOD ₅ @ 20°C)	mg/L	45	30	--
Total Suspended Solids	mg/L	45	30	--
PH	within the limits of 6.0 to 9.0 at all times			
Total Dissolved Solids	mg/L		--	800
Chloride	mg/L		--	200
Sulfate	mg/L		--	300
Total Nitrogen (as N)	mg/L		--	10
Fluoride	mg/L		--	1.0

¹The daily maximum effluent limitation shall apply to the results of a single composite or grab sample.

²The monthly average effluent limitation shall apply to the arithmetic mean of the results of all samples collected during any 30 consecutive calendar day period.

³The 12-month average effluent limitation shall apply to the arithmetic mean of the results of all samples collected during any 12 consecutive calendar month period.

3. The average daily effluent flow rate from the existing PVTP shall not exceed 0.115 MGD. After the Discharger receives authorization to discharge pursuant to section C.2 of this Order, the average daily effluent flow rate from the new PVTP shall not exceed 0.150 MGD.
4. All wastewater treatment and disposal facilities shall be maintained to remain effective in treating wastewater.

C. FACILITY DESIGN AND OPERATION SPECIFICATIONS

1. PROPER OPERATION

The discharger shall, at all times, properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the discharger to achieve compliance with conditions of this Order. Proper operation and maintenance includes effective performance, adequate funding, adequate operator staffing and training, and adequate laboratory and process controls including appropriate quality assurance procedures. This provision requires the operation of backup or auxiliary facilities or similar systems only when necessary to achieve compliance with the conditions of this Order.

2. CERTIFICATION REPORT

The new wastewater treatment and disposal facilities shall be completely constructed and operable prior to the initiation of the discharge. The completed facilities shall have adequate capacity for the new full design flow of 0.150 MGD. A report from the design engineer certifying the adequacy of each component of the treatment, storage, and disposal facilities shall be submitted by the discharger prior to commencement of the discharge. The certification report shall contain a requirement-by-requirement analysis based on acceptable engineering practices, of how the process and physical designs of the facilities will ensure compliance with the waste discharge requirements. The certification report shall also contain an operation and maintenance manual for the wastewater treatment facilities. The design engineer shall affix their signature and engineering license number to the certification report and should submit it prior to construction of the facilities. Prior to the initiation of the discharge, the following requirements shall be met:

- a. The certification report is received and approved by the Regional Board,
- b. The Regional Board has been notified of the completion of facilities by the discharger,
- c. An inspection of the facilities has been made by staff of the Regional Board, and
- d. The Regional Board notifies the discharger by letter that discharge can be initiated.

4. OPERATION MANUAL

A copy of the facility operations manual shall be maintained at the discharger's facility and shall be available to operation personnel and Regional Board staff at all times.

5. FLOOD PROTECTION

All waste treatment, storage and disposal facilities shall be protected against 100-year peak stream flows as defined by the San Diego County flood control agency.

6. RUNOFF PROTECTION

All wastewater storage facilities shall be protected against erosion, overland runoff, and other impacts resulting from a 100-year, 24-hour frequency storm.

7. MONITORING AND REPORTING

The discharger shall comply with the attached Monitoring and Reporting Program No. R9-2006-0049, and future revisions thereto as specified by the Executive Officer. Monitoring results shall be reported at the intervals specified in Monitoring and Reporting Program No. R9-2006-0049.

D. BIOSOLIDS SPECIFICATIONS

1. Management of all solids and sludge must comply with all applicable requirements of 40 CFR Parts 257, 258, 501 and 503; CWA Part 405(d), and Title 27, CCR, including all monitoring, record keeping and reporting requirements. Since the State of California, hence the State and Regional Boards, has not been delegated the authority by the USEPA to implement the sludge program, enforcement of sludge requirements of CFR Part 503 is under USEPA's jurisdiction. Once sludge leaves a facility, it is subject to all applicable local, state and federal laws and regulations.
2. All collected screenings, sludges, and other solids removed from liquid wastes must be disposed of in a municipal solid waste landfill, reused by land application, or disposed of in a sludge-only landfill accordance with 40 CFR Parts 503 and 258, and Title 27 CCR. If the discharger desires to dispose of solids or sludge by a different method, a request for permit modification must be submitted to the USEPA and this Regional Board 180 days prior to the initiation of the alternative disposal.
3. Solids and sludge storage shall not create a nuisance, such as objectionable odors or flies, and shall not result in groundwater contamination.
4. The discharger shall submit a copy of each of the annual reports required by 40 CFR 503 to this Regional Board Executive Officer at the same time those reports are submitted to USEPA. The discharger shall also submit an annual report of the quantity and disposition of sludge generated in the previous calendar year.

E. STANDARD PROVISIONS

1. DUTY TO COMPLY

The discharger must comply with all conditions of this Order. Any noncompliance with this Order constitutes a violation of the California Water Code and is grounds for (a) enforcement action; (b) termination, revocation and reissuance, or modification of this Order; or (c) denial of a report of waste discharge in application for new or revised waste

discharge requirements.

2. ENTRY AND INSPECTION

The discharger shall allow the Regional Board, or an authorized representative, upon the presentation of credentials and other documents as may be required by law to do the following:

- a. Enter upon the discharger's premises where a regulated facility or activity is located or conducted or where records must be kept under the conditions of this Order,
- b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this Order,
- c. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices or operations regulated or required under this Order, and
- d. Sample or monitor, at reasonable times for the purposes of assuring compliance with this Order or as otherwise authorized by the California Water Code, any substances or parameters at any location.

3. CIVIL MONETARY REMEDIES

The California Water Code provides that any person who intentionally or negligently violates any waste discharge requirements issued, reissued, or amended by this Regional Board shall be liable civilly in accordance with California Water Code section 13350 (d), (e), or (f).

4. PENALTIES FOR INVESTIGATION, MONITORING OR INSPECTION VIOLATIONS

The California Water Code provides that any person failing or refusing to furnish technical or monitoring program reports, as required under this Order, or falsifying any information provided in the monitoring reports is guilty of a misdemeanor and is subject to a civil liability in accordance with CWC Section 13268.

5. ENDANGERMENT OF HEALTH AND ENVIRONMENT

The discharger shall report any noncompliance that may endanger health or the environment. Any such information shall be provided orally to the Executive Officer within 24 hours from the time the discharger becomes aware of the circumstances. A written submission shall also be provided within 5 days of the time the discharger becomes aware of the circumstances. The written submission shall contain a description of the

noncompliance and its cause; the period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected; the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance. The Executive Officer, or an authorized representative, may waive the written report on a case-by-case basis if the oral report has been received within 24 hours. The following occurrence(s) must be reported to the Executive Officer within 24 hours:

- a. Any bypass from any portion of the treatment facility. "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility to other than a sewer system.
- b. Any treatment facility upset that causes the performance requirements of this Order to be exceeded. These incidents shall also be reported orally to the State DHS and County DEH within 24-hours of the incident.

6. CORRECTIVE ACTION

The discharger shall take all reasonable steps to minimize or correct any adverse impact on the environment resulting from noncompliance with this Order, including such accelerated or additional monitoring as may be necessary to determine the nature and impact of the noncompliance.

7. TREATMENT FAILURE

In an enforcement action, it shall not be a defense for the discharger that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with this Order. Upon reduction, loss, or failure of the treatment facility, the discharger shall, to the extent necessary to maintain compliance with this Order, control production or all discharges, or both, until the facility is restored or an alternative method of treatment is provided. This provision applies for example, when the primary source of power of the treatment facility is failed, reduced, or lost.

8. HAZARDOUS RELEASES

Except for a discharge which is in compliance with these waste discharge requirements, any person who, without regard to intent or negligence, causes or permits any hazardous substance or sewage to be discharged in or on any waters of the State, shall as soon as (a) that person has knowledge of the discharge, (b) notification is possible, and (c) notification can be provided without substantially impeding cleanup or other emergency measures, immediately notify the Director of Environmental Health Services, County of San Diego in accordance with California Health and Safety Code section 5411.5 and the Office of Emergency

Services of the discharge in accordance with the spill reporting provision of the State toxic disaster contingency plan adopted pursuant to Article 3.7 (commencing with section 8574.7) of Chapter 7 of Division 1 of Title 2 of the Government Code, and immediately notify the State Board or the appropriate Regional Board of the discharge. This provision does not require reporting of any discharge of less than a reportable quantity as provided for under subdivisions (f) and (g) of section 13271 of the Water Code unless the discharger is in violation of a prohibition in the applicable Water Quality Control Plan.

9. PETROLEUM RELEASES

Except for a discharge which is in compliance with these waste discharge requirements, any person who without regard to intent or negligence, causes or permits any oil or petroleum product to be discharged in or on any waters of the State, or discharged or deposited where it is, or probably will be, discharged in or on any waters of the State, shall, as soon as (a) such person has knowledge of the discharge, (b) notification is possible, and (c) notification can be provided without substantially impeding cleanup or other emergency measures, immediately notify the Office of Emergency Services of the discharge in accordance with the spill reporting provision of the State oil spill contingency plan adopted pursuant to Article 3.5 (commencing with section 8574.1) of Chapter 7 of Division 1 of Title 2 of the Government Code. This requirement does not require reporting of any discharge of less than 42 gallons unless the discharge is also required to be reported pursuant to Section 311 of the Clean Water Act or the discharge is in violation of a prohibition in the applicable Water Quality Control Plan.

10. PERMIT REPOSITORY

A copy of this Order shall be maintained at the discharger's facility and shall be available to operating personnel at all times.

11. RETENTION OF RECORDS

The discharger shall retain records of all monitoring information, including all calibration and maintenance records, copies of all reports required by this Order, and records of all data used to complete the application for this Order. Records shall be maintained for a minimum of five years from the date of the sample, measurement, report, or application. This period may be extended during the course of any unresolved litigation regarding this discharge or when requested by the Regional Board Executive Officer.

12. GENERAL REPORTING REQUIREMENT

The discharger shall furnish to the Executive Officer of this Regional Board, within a reasonable time, any information which the Executive Officer may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this Order. The discharger shall also furnish to the Executive Officer, upon request, copies of records required to be kept by this Order.

13. PERMIT REVISION

This Order may be modified, revoked and reissued, or terminated for cause including, but not limited to, the following:

- a. Violation of any terms or conditions of this Order.
- b. Obtaining this Order by misrepresentation or failure to disclose fully all relevant facts.
- c. A change in any condition that requires either a temporary or permanent reduction or elimination of the authorized discharge.

The filing of a request by the discharger for the modification, revocation and reissuance, or termination of this Order, or notification of planned changes or anticipated noncompliance does not stay any condition of this Order.

14. CHANGE IN DISCHARGE

The discharger shall file a new Report of Waste Discharge at least 120 days prior to the following:

- a. Addition of a major industrial waste discharge to a discharge of essentially domestic sewage, or the addition of a new process or product by an industrial facility resulting in a change in the character of the wastes.
- b. Significant change in the treatment or disposal method (e.g., change in the method of treatment which would significantly alter the nature of the waste).
- c. Change in the disposal area from that described in the findings of this Order.
- d. Increase in flow beyond that specified in this Order.
- e. Other circumstances that result in a material change in character, amount, or location of the waste discharge.
- f. Any planned change in the regulated facility or activity that may result in noncompliance with this Order.

15. CHANGE IN OWNERSHIP

This Order is not transferable to any person except after notice to the Executive Officer. The discharger shall submit this notice in writing at least 30 days in advance of any proposed transfer. The notice must include a written agreement between the existing and new discharger containing a specific date for the transfer of this Order's responsibility and coverage between the current discharger and the new discharger. This agreement shall include an acknowledgement that the existing discharger is liable for violations up to the transfer date and that the new Recycled Water Agency is liable from the transfer date on. The Regional Board may require modification or revocation and reissuance of this Order to change the name of the discharger and incorporate such other requirements as may be necessary under the California Water Code.

16. INCOMPLETE REPORTS

Where the discharger becomes aware that it failed to submit any relevant facts in a Report of Waste Discharge or submitted incorrect information in a Report of Waste Discharge or in any report to the Regional Board, it shall promptly submit such facts or information.

17. REPORT DECLARATION

All applications, reports, or information submitted to the Executive Officer shall be signed and certified as follows:

- a. The Report of Waste Discharge shall be signed as follows:
 - (1) For a corporation - by a principal Executive Officer of at least the level of Vice-President.
 - (2) For a partnership or sole proprietorship - by a general partner or the proprietor, respectively.
 - (3) For a municipality, state, federal or other public agency - by either a principal Executive Officer or ranking elected official.
- b. All other reports required by this Order and other information required by the Executive Officer shall be signed by a person designated in paragraph (a) of this provision, or by a duly authorized representative of that person. An individual is a duly authorized representative only if all of the following are true:
 - (1) The authorization is made in writing by a person described in paragraph (a) of this provision,
 - (2) The authorization specifies either an individual or a position having responsibility for the overall operation of the

regulated facility or activity, and

- (3) The written authorization is submitted to the Executive Officer.
- c. Any person signing a document under this section shall make the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

18. REGIONAL BOARD ADDRESS

The discharger shall submit reports required under this Order or other information required by the Executive Officer to the following address:

Northern Core Regulatory Unit
California Regional Water Quality Control Board
San Diego Region
9174 Sky Park Court, Suite 100
San Diego, California 92123

F. **SPECIAL PROVISIONS**

1. Adequate measures shall be taken to assure that unauthorized persons are effectively excluded from contact with the wastewater.
2. Adequate measures shall be taken to assure that flood or surface drainage waters do not erode or otherwise render portions of the discharge facilities inoperable.

G. NOTIFICATIONS1. VESTED RIGHTS

This Order does not convey any property rights of any sort or any exclusive privileges. The requirements prescribed herein do not authorize the commission of any act causing injury to persons or property, nor protect the discharger from liability under federal, state or local laws, nor create a vested right for the discharger to continue the waste discharge.

2. U.S. EPA REVIEW

These requirements have been reviewed by the United States Environmental Protection Agency, Ground Water Office. However, these requirements are not issued pursuant to section 402 of the Clean Water Act.

3. SEVERABILITY

The provisions of this Order are severable, and if any provision of this Order, or the application of any provision of this Order to any circumstance, is held invalid, the application of such provision to other circumstances, and the remainder of this Order, shall not be affected thereby.

4. EFFECTIVE DATE

This Order becomes effective on the date of adoption by the San Diego Regional Board.

I, John H. Robertus, Executive Officer, do hereby certify the foregoing is a full, true and correct copy of an Order adopted by the California Regional Water Quality Control Board, San Diego Region, on June 14, 2006.



JOHN H. ROBERTUS
Executive Officer

**CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
SAN DIEGO REGION**

**MONITORING AND REPORTING PROGRAM NO. R9-2006-0049
FOR THE
PAUMA VALLEY COMMUNITY SERVICES DISTRICT
PAUMA VALLEY TREATMENT PLANT
SAN DIEGO COUNTY**

A. MONITORING PROVISIONS

1. Samples and measurements taken as required herein shall be representative of the volume and nature of the monitored discharge. All samples shall be taken at the monitoring points specified in this Monitoring and Reporting Program (M&RP) and, unless otherwise specified, before the effluent joins or is diluted by any other waste stream, body of water or substance. Monitoring points shall not be changed without notification to and the approval of the Executive Officer.
2. Appropriate flow measurement devices and methods consistent with accepted scientific practices shall be selected and used to ensure the accuracy and reliability of measurements of the volume of monitored discharges. The devices shall be installed, calibrated and maintained to ensure that the accuracy of the measurements is consistent with the accepted capability of that type of device. Devices selected shall be capable of measuring flows with a maximum deviation of less than +10 percent from true discharge rates throughout the range of expected discharge volumes.
3. Monitoring must be conducted according to United States Environmental Protection Agency (USEPA) test procedures approved under Title 40, Code of Federal Regulations (CFR), Part 136, "Guidelines Establishing Test Procedures for Analysis of Pollutants Under the Clean Water Act" as amended, unless other test procedures have been specified in this M&RP.
4. All analyses shall be performed in a laboratory certified to perform such analyses by the California Department of Health Services or a laboratory approved by the Executive Officer.
5. Monitoring results must be reported on discharge monitoring report forms approved by the Executive Officer.
6. If the Pauma Valley Community Services District (hereafter Discharger) monitors any pollutants more frequently than required by this M&RP, using test procedures approved under 40 CFR, Part 136, or as specified in this

M&RP, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the discharger's monitoring report. The increased frequency of monitoring shall also be reported.

7. The discharger shall retain records of all monitoring information, including all calibration and maintenance records and copies of all reports required by this M&RP, and records of all data used to complete the application for this M&RP. Records shall be maintained for a minimum of five years from the date of the sample, measurement, report or application. This period may be extended during the course of any unresolved litigation regarding this discharge or when requested by the Regional Board Executive Officer.
8. Records of monitoring information shall include the following:
 - a. The date, exact place, and time of sampling or measurements,
 - b. The individual(s) who performed the sampling or measurements,
 - c. The date(s) analyses were performed,
 - d. The individual(s) who performed the analyses,
 - e. The analytical techniques or method used, and
 - f. The results of such analyses.
9. All monitoring instruments and devices that are used by the discharger to fulfill the prescribed monitoring program shall be properly maintained and calibrated as necessary to ensure their continued accuracy.
10. The discharger shall report all instances of noncompliance not reported under Standard Provision E.5 of Order No. R9-2006-0049 at the time monitoring reports are submitted. The reports shall contain the information described in Provision E.5.
11. The monitoring reports shall be signed by an authorized person as required by Standard Provision E.21.
12. A grab sample is an individual sample of at least 100 milliliters collected at a randomly selected time over a period not exceeding 15 minutes.

B. DISCHARGE MONITORING

1. Samples of the effluent discharged from the Pauma Valley Treatment Plant (PVTP) shall be collected at a point at or nearest to the effluent pump station, downstream of the disinfection process and prior to any dilution.

2. The Discharger is responsible for monitoring and reporting in accordance with the following criteria:

CONSTITUENT	UNIT	TYPE OF SAMPLE	SAMPLING FREQUENCY ¹	REPORTING FREQUENCY
Flowrate ²	Gallons/Day	Measurement	Daily	Quarterly
Biochemical Oxygen Demand (BOD ₅ @ 20°C)	mg/L	Grab	Weekly	Quarterly
Total Suspended Solids	mg/L	Grab	Weekly	Quarterly
pH	Units	Grab	Weekly	Quarterly
Nitrate (as NO ₃)	Mg/L	Grab	Quarterly	Quarterly
Total Dissolved Solids	mg/L	Grab	Quarterly	Quarterly
Chloride	mg/L	Grab	Quarterly	Quarterly
Sulfate	mg/L	Grab	Quarterly	Quarterly
Nitrite (as NO ₂)	mg/L	Grab	Quarterly	Quarterly
Kjeldahl Nitrogen (as N)	mg/L	Grab	Quarterly	Quarterly
Total Nitrogen (as N)	mg/L	Grab	Quarterly	Quarterly

Notes: mg/L = milligrams per liter

- 1 The discharger shall increase the sampling frequency from quarterly to monthly, from semiannually to quarterly, and from annually to semiannually for any noted constituent that exceeds the limit specified by Discharge Specifications Requirements of Order No. R9-2006-0049. The increased frequency of monitoring shall continue until the discharger achieves compliance with the limitations for three consecutive periods. After compliance is achieved, the discharger shall resume sampling at the specified frequency. Monthly is defined as a calendar month. Quarterly is defined as three consecutive calendar months beginning at the first of the year. Semiannually is defined as six consecutive calendar months beginning at the first of the year. Annual is defined as a calendar year.
- 2 Report both the average daily and total flowrate for the reporting period for the discharge of effluent to the percolation ponds.
3. Groundwater samples shall be collected from monitoring wells MW-1, MW-3, & MW-7.
4. The discharger is responsible for the monitoring and reporting of the groundwater from monitoring wells in accordance with the following criteria:

CONSTITUENT	UNIT	TYPE OF SAMPLE	SAMPLING FREQUENCY ¹	REPORTING FREQUENCY
Water Depth	Feet		Quarterly	Quarterly
Nitrate (as NO ₃)	mg/L	Grab	Quarterly	Quarterly
Nitrite (as NO ₂)	mg/L	Grab	Quarterly	Quarterly
Kjeldahl Nitrogen (as N)	mg/L	Grab	Quarterly	Quarterly
Total Nitrogen (as N)	mg/L	Grab	Quarterly	Quarterly
Total Dissolved Solids	mg/L	Grab	Quarterly	Quarterly

Notes: mg/L = milligrams per liter

- 1 The discharger shall increase the sampling frequency from quarterly to monthly, from semiannually to quarterly, and from annually to semiannually for any noted constituent that exceeds the limit specified by Discharge Specifications of Order No. R9-20060049. The increased frequency of monitoring shall continue until the discharger achieves compliance with the limitations for three consecutive periods. After compliance is achieved, the discharger shall resume sampling at the specified frequency. Monthly is defined as a calendar month. Quarterly is defined as three consecutive calendar months beginning at the first of the year. Semiannually is defined as six consecutive calendar months beginning at the first of the year. Annual is defined as a calendar year.

5. The discharger shall review the monitoring results for compliance with Order No. R9-2006-0049 and submit a statement of compliance as part of the Monitoring and Reporting Program No. R9-2006-0049. The statement of compliance shall identify and report all violations of Discharge Specifications of Order No. R9-2006-0049.

C. SEWAGE SOLIDS AND BIOSOLIDS

A record of the type, quantity, manner, and location of disposal of all solids removed in the course of sewage treatment shall be maintained by the discharger and be submitted to the Regional Board annually.

A biosolids certification, certifying that the disposal of biosolids complies with existing Federal and State laws and regulations, including permitting requirements and technical standards included in 40 CFR 503 shall be submitted annually.

D. MONITORING WELLS

The Discharger shall monitor wells MW-1, MW-3, and MW-7 to verify the conclusions in Findings 10 and 11. Monitoring wells shall be sampled quarterly for the constituents above in Section B.4, *Discharge Monitoring*. Monitoring wells that that are dry or do not yield adequate water for sampling shall be replaced.

E. OPERATOR STAFFING

The discharger shall include with the quarterly monitoring report a list of all wastewater treatment operator(s) employed or contracted by the District who performed operation and maintenance on the system during the quarter along with their qualifications and training.

F. ANNUAL REPORT

The Discharger submits an annual report that contains both tabular and graphical summaries of monitoring data obtained during the previous year.


G. REPORT SCHEDULE

Monitoring reports shall be submitted to the Executive Officer in accordance with the following schedule:

<u>Reporting Frequency</u>	<u>Report Period</u>	<u>Report Due</u>
Quarterly	January - March	May 1 st
	April - June	August 1 st ,
	July - September	November 1 st
	October - December	February 1 st
Annual	January – December	March 1

Monitoring reports shall be submitted to:

ATTN: Northern Core Regulatory Unit
 California Regional Water Quality Control Board
 San Diego Region
 9174 Sky Park Court, Suite 100
 San Diego, CA 92123

Ordered by: 
 JOHN H. ROBERTUS
 Executive Officer
 June 14, 2006