

(b) Redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface (collectively over the entire project site on an existing site of 10,000 square feet or more of impervious surfaces). This includes commercial, industrial, residential, mixed-use, and public development projects on public or private land.

~~(b)~~

(c) New or redevelopment projects that create 5,000 square feet or more of impervious surface (collectively over the entire project site), and support one or more of the following uses:

2) Provision E.3.c.(1)

(a) Each Priority Development Project must be required to implement LID BMPs that are designed to retain (i.e. intercept, store, infiltrate, evaporate, and evapotranspire) onsite ~~100 percent of~~ the pollutants contained in the volume of storm water runoff produced from a 24-hour 85th percentile storm event (design capture volume);

~~(b) (i) If a Copermittee determines that implementing BMPs to retain the full design capture volume onsite for a Priority Development Project is not technically feasible, then the Copermittee may allow the Priority Development Project to utilize ~~flow-thru treatment control~~ biofiltration BMPs. Biofiltration BMPs must be sized and designed to achieve the equivalent pollutant load removal described in Provision E.3.c.(1)(a). ~~Biofiltration LID BMPs must be considered as a first option before other types of flow-thru treatment control BMPs may be considered.~~~~

[a] Treat 1.5 times the design capture volume not reliably retained onsite;
OR

[b] Treat the design capture volume not reliably retained onsite with a flow-thru design that has a total volume, including pore spaces and pre-filter detention volume, sized to hold at least 0.75 times the portion of the design capture volume not reliably retained onsite.

[c] Have an appropriate loading rate to prevent erosion, scour, and channeling within the BMP.

(ii) If a Copermittee determines that biofiltration is not technically feasible, then the Copermittee may allow the Priority Development Project to utilize flow-thru treatment control BMPs to treat runoff leaving the site, AND mitigate for the design capture volume not reliably retained onsite pursuant to Provision E.3.c.(1)(b). Flow thru treatment control BMPs must be sized and designed to:

[a] Remove pollutants from storm water to the MEP;

[b] Filter or treat either: 1) the maximum flow rate of runoff produced from a rainfall intensity of 0.2 inch of rainfall per hour, for each hour of a storm

event, or 2) the maximum flow rate of runoff produced by the 85th percentile hourly rainfall intensity (for each hour of a storm event), as determined from the local historical rainfall record, multiplied by a factor of two;

[c] Be ranked with high or medium pollutant removal efficiency for the Priority Development Project's most significant pollutants of concern. Flow-thru treatment control BMPs with a low removal efficiency ranking must only be approved by a Copermittee when a feasibility analysis has been conducted which exhibits that implementation of flow-thru treatment control BMPs with high or medium removal efficiency rankings are infeasible for a Priority Development Project or portion of a Priority Development Project.

~~(e)~~

(b) A Priority Development Project may be allowed to utilize alternative compliance under Provision E.3.c.(3) in lieu of complying with the storm water pollutant control BMP performance requirements of Provision E.3.c.(1)(a). The Priority Development Project must mitigate for the portion of the pollutant load in the design capture volume not retained onsite if Provision E.3.c.(3) is utilized. If a Priority Development Project is allowed to utilize alternative compliance, flow-thru treatment control BMPs must be implemented to treat the portion of the design capture volume that is not reliably retained onsite. Flow-thru treatment control BMPs must be sized and designed in accordance with Provision E.3.c.(1)(a)(ii)[a]-[c].

~~(d) If a Priority Development project is allowed to utilize alternative compliance, flow-thru treatment control BMPs must be implemented to treat the portion of the design capture volume that is not retained onsite. Flow-thru treatment control BMPs must be sized and designed to:~~

~~(i) Remove pollutants from storm water to the MEP;~~

~~(ii) Filter or treat either: 1) the maximum flow rate of runoff produced from a rainfall intensity of 0.2 inch of rainfall per hour, for each hour of a storm event, or 2) the maximum flow rate of runoff produced by the 85th percentile hourly rainfall intensity (for each hour of a storm event), as determined from the local historical rainfall record, multiplied by a factor of two;~~

~~(iii) Be ranked with high or medium pollutant removal efficiency for the Priority Development Project's most significant pollutants of concern. Flow-thru treatment control BMPs with a low removal efficiency ranking must only be approved by a Copermittee when a feasibility analysis has been conducted which exhibits that implementation of flow thru treatment control BMPs with high or medium removal efficiency rankings are infeasible for a Priority Development Project or portion of a Priority Development Project.~~

Tentative Order No. R9-2013-0001
Errata Sheet (OPTION 1)

April 11, 2013

3) Provision E.3.c.(2)(b)

- (b) Each Priority Development Project must avoid ~~known~~ critical sediment yield areas known to the Copermittee or identified by the Watershed Management Area Analysis pursuant to Provision B.3.b.(4), or implement measures that allow critical coarse sediment to be discharged to receiving waters, such that there is no net impact to the receiving water ~~sediment supply is unaffected by the project.~~

4) Provision E.3.c.(3)(a)(ix)

- ~~(ix) Receiving waters must not be utilized to convey untreated storm water runoff from the Priority Development Project to the candidate project;~~

5) Provision E.3.c.(3)(b)

- (b) Retrofitting or redevelopment of existing paved alleys, streets or roads that are designed and constructed in accordance with the USEPA Green Streets guidance.

6) Provision E.3.e.(1)(a)

- (a) Each Copermittee must require and confirm that for all Priority Development Project applications that have not received prior lawful approval by the Copermittee by the time the BMP Design Manual is updated pursuant to Provision E.3.d ~~18 months after the commencement of coverage under this Order~~, the requirements of Provision E.3 are implemented. For project applications that have received prior lawful approval ~~by 18 months after~~ before the BMP Design Manual is updated pursuant to Provision E.3.d ~~commencement of coverage under this Order~~, the Copermittee may allow previous land development requirements to apply.

PROVISION F Errata

1) Provisions F.1 and F.2

Delete the terms "~~certification~~" and "~~notification of concurrence~~" and replace with "notification of acceptance" throughout Provisions F.1 and F.2.

2) Provision F.1.a.(1)(c)

- (c) The Copermittees must coordinate the schedules for the public participation process among the Watershed Management Areas to provide the public ~~as much~~ time and opportunity ~~as possible~~ to participate during the development of the Water Quality Improvement Plans.

Tentative Order No. R9-2013-0001
Errata Sheet (OPTION 1)

April 11, 2013

3) Provision F.1.b.(7)

- (7) During implementation of the Water Quality Improvement Plan ~~after implementation~~ the Copermittees must correct any deficiencies in the Plan identified by the San Diego Water Board ~~no later than 90 days in the updates submitted with the Water Quality Improvement Plan Annual Report~~ following a request by the Board to do so.

4) Provision F.2.a.(2)

- (2) Each Copermittee must update its jurisdictional runoff management program document to incorporate the requirements of Provision E ~~no later than 3 months after San Diego Water Board notification of concurrence with~~ concurrent with the submittal of the Water Quality Improvement Plan. Each Copermittee must correct any deficiencies in the jurisdictional runoff management program document based on comments received from the San Diego Water Board in the updates submitted with the Water Quality Improvement Plan Annual Report.

5) Provision F.2.b.(1)

- (1) Each Copermittee must update its BMP Design Manual to incorporate the requirements of Provisions E.3.a-d ~~no later than 3 months after San Diego Water Board notification of concurrence with~~ concurrent with the submittal of the Water Quality Improvement Plan ~~by the San Diego Water Board Executive Officer.~~ Each Copermittee must correct any deficiencies in the BMP Design Manual based on comments received from the San Diego Water Board in the updates submitted with the Water Quality Improvement Plan Annual Report.

6) Provision F.3.b.(2)

- (2) Transitional Monitoring and Assessment Program Annual Reports

The Copermittees for each Watershed Management Area must submit a Transitional Monitoring and Assessment Program Annual Report no later than January 31 for each complete transitional monitoring and assessment program reporting period (i.e. October 1 to September 30) during the transitional period, until the first Water Quality Improvement Plan Annual Reports are required to be submitted under this Order. The Transitional Monitoring and Assessment Program Annual Reports must include:

ATTACHMENT E Errata

1) Attachment E, Specific Provision 1.b.(3)(a)-(c)

Delete "~~Copermittees~~" and replace with "Copermittee's"

Tentative Order No. R9-2013-0001
Errata Sheet (OPTION 1)

April 11, 2013

2) Attachment E, Specific Provision 1.d

Add the following after Specific Provision 1.d.(2):

(3) For assessing and determining compliance with the concentration-based effluent limitations under Specific Provision 1.b.(2)(b), dry and wet weather discharge concentrations may be calculated based on a flow-weighted average across all major MS4 outfalls along a water body segment or within a jurisdiction if samples are collected within a similar time period.

3) Attachment E, Specific Provision 2.b.(2)(b), Table 2.2

Table 2.2

Final Effluent Limitations as Expressed as Annual Loads in MS4 Discharges to Shelter Island Yacht Basin

Constituent	Effluent Limitation
Dissolved Copper	30 g/yr*

* If the water quality objectives for dissolved copper in Shelter Island Yacht Basin are changed in the future, then the margin of safety (MOS), TMDL and allocations will be recalculated using the [Method for Recalculation of the Total Maximum Daily Load for Dissolved Copper in the Shelter Island Yacht Basin, San Diego Bay in the Basin Plan \(p. 7-14\)](#).

4) Attachment E, Specific Provision 3.d

Add the following after Specific Provision 3.d.(2):

(3) For assessing and determining compliance with the concentration-based effluent limitations under Specific Provision 3.b.(2)(b)(i), dry and wet weather discharge concentrations may be calculated based on a flow-weighted average across all major MS4 outfalls along a water body segment or within a jurisdiction if samples are collected within a similar time period.

5) Attachment E, Specific Provision 4.b.(3)(a)-(c)

Delete “~~Copermittees~~” and replace with “Copermittee’s”

6) Attachment E, Specific Provision 4.c.(2)(a)-(d)

Delete “~~Copermittees~~” and replace with “Copermittee’s”

7) Attachment E, Specific Provision 4.d

Add the following after Specific Provision 4.d.(2):

(3) For assessing and determining compliance with the concentration-based effluent limitations under Specific Provision 4.b.(2)(b), dry and wet weather discharge

Tentative Order No. R9-2013-0001
 Errata Sheet (OPTION 1)

April 11, 2013

concentrations may be calculated based on a flow-weighted average across all major MS4 outfalls along a water body segment or within a jurisdiction if samples are collected within a similar time period.

8) Attachment E, Specific Provision 5.b.(3)(a)-(c)

Delete “~~Copermittees~~” and replace with “Copermittee's”

9) Attachment E, Specific Provision 5.c.(1)(b)(i)-(iii)

Delete “~~Copermittees~~” and replace with “Copermittee's”

10) Attachment E, Specific Provision 5.d.(3)

Add the following after Specific Provision 5.d.(3)(a) and renumber subsequent provisions appropriately:

(b) For assessing and determining compliance with the concentration-based effluent limitations under Specific Provision 5.b.(2)(b)(i), dry and wet weather discharge bacteria densities may be calculated based on a flow-weighted average across all major MS4 outfalls along a water body segment or within a jurisdiction if samples are collected within a similar time period.

11) Attachment E, Specific Provision 6.b.(2)(a), Table 6.2a

Table 6.2a

Final Receiving Water Limitations Expressed as Bacteria Densities and Allowable Exceedance Frequencies for Beaches

Constituent	Wet Weather Days		Dry Weather Days	
	Single Sample Maximum ^{a,b} (MPN/100mL)	Single Sample Maximum Allowable Exceedance Frequency ^c	30-Day Geometric Mean ^b (MPN/100mL)	30-Day Geometric Mean Allowable Exceedance Frequency
Total Coliform	10,000	22% 10%	1,000	0%
Fecal Coliform	400	22% 10%	200	0%
<i>Enterococcus</i>	104	22% 10%	35	0%

Notes:

- a. During wet weather days, only the single sample maximum receiving water limitations are required to be achieved.
- b. During dry weather days, the single sample maximum and 30-day geometric mean receiving water limitations are required to be achieved.
- c. The 22% single sample maximum allowable exceedance frequency only applies to wet weather days. ~~The 0% single sample maximum allowable exceedance frequency applies to dry weather days. For dry weather days the single sample allowable exceedance frequency must be consistent with the single sample maximum REC-1 water quality objectives in the Ocean Plan.~~

12) Attachment E, Specific Provision 6.b.(2)(a), Table 6.2b

Table 6.2b

Final Receiving Water Limitations Expressed as Bacteria Densities and Allowable Exceedance Frequencies for Creeks

Constituent	Wet Weather Days		Dry Weather Days	
	Single Sample Maximum ^{a,b} (MPN/100mL)	Single Sample Maximum Allowable Exceedance Frequency ^c	30-Day Geometric Mean ^b (MPN/100mL)	30-Day Geometric Mean Allowable Exceedance Frequency
Fecal Coliform	400	22% 10%	200	0%
Enterococcus	61 (104)	22% 10%	33	0%

Notes:

- During wet weather days, only the single sample maximum receiving water limitations are required to be achieved.
- During dry weather days, the single sample maximum and 30-day geometric mean receiving water limitations are required to be achieved.
- The 22% single sample maximum allowable exceedance frequency only applies to wet weather days. ~~The 0% single sample maximum allowable exceedance frequency applies to dry weather days.~~ For dry weather days the single sample allowable exceedance frequency must be consistent with the single sample maximum REC-1 water quality objectives in the Basin Plan.
- A single sample maximum of 104 MPN/100ml for *Enterococcus* may be applied as a receiving water limitation for creeks, instead of 61 MPN/100mL, if one or more of the creeks addressed by these TMDLs (San Juan Creek, Aliso Creek, Tecolote Creek, Forrester Creek, San Diego River, and/or Chollas Creek) is designated with a "moderately to lightly used area" or less frequent usage frequency in the Basin Plan. Otherwise, the single sample maximum of 61 MPN/100mL for *Enterococcus* must be used to assess compliance with the allowable exceedance frequency.

13) Attachment E, Specific Provision 6.b.(2)(b), Table 6.2

Table 6.2c

Final Effluent Limitations Expressed as Bacteria Densities and Allowable Exceedance Frequencies in MS4 Discharges to the Water Body

Constituent	Concentration-Based Effluent Limitations			
	Single Sample Maximum ^{a,b} (MPN/100mL)	Single Sample Maximum Allowable Exceedance Frequency ^c	30-Day Geometric Mean ^b (MPN/100mL)	30-Day Geometric Mean Allowable Exceedance Frequency
Total Coliform ^d	10,000	22% 10%	1,000	0%
Fecal Coliform	400	22% 10%	200	0%
Enterococcus	104 ^e / 61 ^f	22% 10%	35 ^e / 33 ^f	0%

Notes:

- During wet weather days, only the single sample maximum effluent limitations are required to be achieved.
- During dry weather days, the single sample maximum and 30-day geometric mean effluent limitations are required to be achieved.
- The 22% single sample maximum allowable exceedance frequency only applies to wet weather days. ~~The 0% single sample maximum allowable exceedance frequency applies to dry weather days.~~ For dry weather days the single sample allowable exceedance frequency must be consistent with the single sample maximum REC-1 water quality objectives in the Ocean Plan for discharges to beaches, and the Basin Plan for discharges to creeks and creek mouths.
- Total coliform effluent limitations only apply to MS4 outfalls that discharge to the Pacific Ocean Shorelines and creek mouths listed in Table 6.0.
- This *Enterococcus* effluent limitation applies to MS4 discharges to segments of areas of Pacific Ocean Shoreline listed in Table 6.0.
- This *Enterococcus* effluent limitation applies to MS4 discharges to segments or areas of creeks or creek mouths listed in Table 6.0.

Tentative Order No. R9-2013-0001
Errata Sheet **(OPTION 1)**

April 11, 2013

14) Attachment E, Specific Provision 6.b.(3)(a)-(c)

Delete “~~Copermittees~~” and replace with “Copermittee’s”

15) Attachment E, Specific Provision 6.c.(3)(a)-(c)

Delete “~~Copermittees~~” and replace with “Copermittee’s”

16) Attachment E, Specific Provision 6.d.(1)(b)

Add the following after Specific Provision 6.d.(1)(b)(iii):

(iv) For Pacific Ocean Shoreline segments or areas listed in Table 6.0 that have been de-listed from the Clean Water Act Section 303(d) List, the Responsible Copermittees may propose alternative monitoring procedures to demonstrate that the water bodies continue to remain in compliance with water quality standards under wet weather and dry weather conditions. The alternative monitoring procedures must be submitted as a part of the Water Quality Improvement Plans or any updates required under Provisions F.1 and F.2.c of the Order.

17) Attachment E, Specific Provision 6.d.(1)(c)

Add the following after Specific Provision 6.d.(1)(c)(iii) and renumber subsequent provisions appropriately:

(iv) For assessing and determining compliance with the concentration-based effluent limitations under Specific Provision 6.b.(2)(b)(i), dry and wet weather discharge bacteria densities may be calculated based on a flow-weighted average across all major MS4 outfalls along a water body segment or within a jurisdiction if samples are collected within a similar time period.

18) Attachment E, Specific Provision 6.d.(1)(c)(iii)[c]

[c] If there are any storm events not sampled, the bacteria density for every wet weather day of those storm events must be assumed to be equal to the average of the highest bacteria densities result reported from ~~wet weather samples collected~~ each of the storm events sampled; and

19) Attachment E, Specific Provision 6.d.(2)(b)

Add the following after Specific Provision 6.d.(2)(b)(iii):

(iv) For creeks or creek mouths listed in Table 6.0 that have been de-listed from the Clean Water Act Section 303(d) List, the Responsible Copermittees may propose alternative monitoring procedures to demonstrate that the water bodies

Tentative Order No. R9-2013-0001
Errata Sheet (OPTION 1)

April 11, 2013

continue to remain in compliance with water quality standards under wet weather and dry weather conditions. The alternative monitoring procedures must be submitted as a part of the Water Quality Improvement Plans or any updates required under Provisions F.1 and F.2.c of the Order.

20) Attachment E, Specific Provision 6.d.(2)(c)

Add the following after Specific Provision 6.d.(2)(c)(iv) and renumber subsequent provisions appropriately:

(v) For assessing and determining compliance with the concentration-based effluent limitations under Specific Provision 6.b.(2)(b)(i), dry and wet weather discharge bacteria densities may be calculated based on a flow-weighted average across all major MS4 outfalls along a water body segment or within a jurisdiction if samples are collected within a similar time period.

21) Attachment E, Specific Provision 6.d.(2)(c)(iii)[c]

[c] If there are any storm events not sampled, the bacteria density for every wet weather day of those storm events must be assumed to be equal to the average of the highest bacteria densities ~~result~~ reported from ~~wet weather samples collected~~ each of the storm events sampled; and

ATTACHMENT F Errata

1) Attachment F, Under the Fact Sheet discussion of Provision B

Purpose: Since 1990, the Copermittees have been developing and implementing programs and BMPs intended to effectively prohibit non-storm water discharges to the MS4s and control pollutants in storm water discharges from the MS4s to receiving waters. As a result, several water body / pollutant combinations have been de-listed from the CWA Section 303(d) List, beach closures have been significantly reduced, and public awareness of water quality issues has increased. The Copermittees have been able to achieve improvements in water quality in some respects, but significant improvements to the quality of receiving waters and discharges from the MS4s are still necessary to meet the requirements and objectives of the Clean Water Act.

Provision B includes requirements for the Copermittees to develop and implement Water Quality Improvement Plans to ultimately comply with the prohibitions and limitations under Provision A. The Water Quality Improvement Plans will provide the Copermittees a comprehensive program that can achieve the requirements and further the objectives of the CWA. Implementation of the Water Quality Improvement Plans will also improve the quality of the receiving waters in the San Diego Region.

2) Attachment F, Under the Fact Sheet discussion of Provision B.3

~~Finally, Provision B.3.c has been included to provide the Copermittees an option to demonstrate and be in compliance with the requirements of Provisions A.1.a, A.1.c and A.2.a. One or more Copermittees within a Watershed Management Area can choose to implement this option. This option is only expected to be utilized by the Copermittees that wish to clearly demonstrate and be in compliance with the requirements of Provisions A.1.a, A.1.c and A.2.a.~~

~~In order for a Copermittee to utilize this option, the Copermittee is required to include three components in the Water Quality Improvement Plan. The first component is a comprehensive set of numeric goals that will demonstrate the requirements of Provisions A.1.a, A.1.c and A.2.a will be achieved. The criteria provided in the Order will require the Copermittee to demonstrate that the discharges from its MS4s will not cause or contribute to exceedances of water quality objectives in the receiving waters, and the receiving waters will be protected from the Copermittee's MS4 discharges.~~

~~The second component is an analysis utilizing a watershed model or other watershed analytical tools. The analysis must demonstrate that the implementation of the water quality improvement strategies required under Provision B.3.b will achieve the numeric goals within the established schedules required under Provision B.3.a. Because the development of the analysis may require significant resources, the Order allows the Copermittees in each Watershed Management Area that choose to implement this option to perform the analysis individually, or pool their resources for the analysis collectively.~~

~~The San Diego Water Board does not expect the analysis to be a "guarantee" that the water quality improvement strategies will achieve the numeric goals within the established schedules. The analysis, however, must "reasonably" and "quantitatively" demonstrate that the implementation of the water quality improvement strategies can achieve the numeric goals within the established schedules. However, as more data and information are collected to demonstrate progress toward achieving the numeric goals, the numeric goals, water quality improvement strategies and schedules may need to be updated. When these updates occur, the Copermittees that choose to utilize this option must also update the analysis.~~

~~Thus, the third component is the key component that will allow a Copermittee to demonstrate the implementation of the water quality improvement strategies within its jurisdiction is making progress toward achieving the numeric goals. Each Copermittee must specify the monitoring and assessments that will be performed to confirm the implementation of the water quality improvement strategies are making progress toward achieving the numeric goals within the established schedules.~~

~~These three components must then be reviewed by the Water Quality Improvement~~

~~Consultation Panel. The Water Quality Improvement Consultation Panel is required to be formed as part of the public participation process for the development of the Water Quality Improvement Plans. The Water Quality Improvement Consultation Panel is described under Provision F.1.a.(1)(b). Review by the Water Quality Improvement Consultation Panel has been included to provide an additional layer of input, support, and accountability for the implementation of this option.~~

~~Compliance with the requirements of Provisions A.1.a, A.1.c and A.2.a begins when the Water Quality Improvement Plan, incorporating the requirements of Provision B.3.c.(1), is accepted by the San Diego Water Board. Each Copermittee that chooses to implement and continues to implement this option will be in compliance with the requirements of Provisions A.1.a, A.1.c and A.2.a as long as the San Diego Water Board continues to accept the analysis, and subsequent updates, and the Copermittee continues to implement the strategies, monitoring and assessments as incorporated in the Water Quality Improvement Plan in accordance with Provision B.3.c.(1).~~

3) Attachment F, Under the Fact Sheet discussion of Provision D.2

Until the wet weather MS4 outfall discharge monitoring requirements of Provision D.2.c are incorporated into a Water Quality Improvement Plan that is accepted by the San Diego Water Board, the Copermittees must comply with the requirements of transitional wet weather MS4 outfall monitoring requirements pursuant to Provision D.2.a.(3). Provision D.2.a.(3) requires each Copermittee to sample, at least five of the major MS4 outfalls inventoried pursuant to Provision D.2.a.(1) ~~twice~~ once per wet season for the monitoring data required to be collected pursuant to Provision D.2.a.(3)(c)-(e).

4) Attachment F, Under the Fact Sheet discussion of Provision E.3

The 85th percentile storm event is the event that has a precipitation total greater than or equal to 85 percent of all storm events over a given period of record in a specific area or location. For example, to determine what the 85th percentile storm event is in a specific location, all 24 hour storms that have recorded values over a 30 year period would be tabulated and a 85th percentile storm would be determined from this record (i.e., 15 percent of the storms would be greater than the number determined to be the 85th percentile storm). Most jurisdictions in the San Diego Region have already developed isopluvial maps that can provide this type of information. The 85th percentile storm might be determined to be a number such as 1.0 inch, and this would be multiplied by the total area of the project footprint producing runoff to calculate the design capture volume. The Priority Development Project designer would then select a system of BMPs that would retain (i.e. intercept, store, infiltrate, evaporate, or evapotranspire) ~~100 percent of~~ the pollutants contained in the design capture volume onsite.

Retention BMPs are necessary to capture and retain pollutants generated from a Priority Development Project. In a recent study performed by SCCWRP in the Los Angeles Region, they found “*that the magnitude of constituent load associated with storm water runoff depends, at least in part, on the amount of time available for pollutant build-up on land surfaces. The extended dry period that typically occurs in arid climates such as southern California maximizes the time for constituents to build-up on land surfaces, resulting in proportionally higher concentrations and loads during initial storms of the season.*”² This implies that the “first flush” of a rainy season and the first storm events after long antecedent dry periods tend to have the highest pollutant loads. Capturing and retaining the pollutant loads of the “first flush” of a rainy season and the first storm events after long antecedent dry periods will reduce a significant portion of the pollutants in storm water discharged to and from the MS4.

The San Diego Water Board, however, acknowledges that in some situations retention of the full design capture volume onsite may not be technically feasible. In this event, the Copermittee may allow the Priority Development Project to utilize [biofiltration BMPs to treat 1.5 times the design capture volume not reliably retained onsite, or biofiltration BMPs with a flow-thru design that has a total volume, including pore spaces and pre-filter detention volume, sized to hold at least 0.75 times the portion of the design capture volume not reliably retained onsite](#) ~~flow-thru treatment control BMPs to achieve the equivalent pollutant load removal that would have been achieved if the design capture volume were fully retained onsite, pursuant to Provision E.3.c.(1)(b). Biofiltration LID BMPs must be considered as a first option before other types of flow-thru treatment control BMPs may be considered because of the ancillary benefits they provide, such as reduction in flow rates and creation of habitat. In any event, no matter what types of BMPs (or combination of BMPs) are chosen, 100 percent of the pollutants contained in the design capture volume must not be allowed to be discharged from the Priority Development Project.~~

[The 1.5 multiplier is based on the finding in the Ventura County Technical Guidance Manual that biofiltration of 1.5 times the design capture volume not retained onsite will provide approximately the same pollutant removal as retention of the design capture volume on an annual basis.](#)³ This standard is consistent with the [Los Angeles Water Board’s Los Angeles and Ventura County municipal storm water permits \(Order Nos. R4-2012-0175 and R4-2010-0108, respectively\)](#). The [flow-thru design of 0.75 times the portion of the design capture volume not reliably retained onsite is consistent with the San Diego Water Board’s Orange County and Riverside County municipal storm water permits \(Order Nos. R9-2009-0002 and R9-2010-0016, respectively\)](#).

² Stein, E.D., Tiefenthaler, L.L., and Schiff, K.C., 2007. Technical Report 510, Sources, Patterns and Mechanisms of Storm Water Pollutant Loading from Watershed and Land Uses of the Greater Los Angeles Area, California, USA. March 20, 2007.

³ [Ventura Countywide Stormwater Management Program. 2011. Ventura Technical Guidance Manual, Manual Update, 2011.](#)

The San Diego Water Board further recognizes that, in addition to not being technically feasible, retention of the full design capture storm onsite may be cost prohibitive, or may not provide as much water quality benefit to the Watershed Management Area as would implementing BMPs elsewhere in the watershed. Thus, Provision ~~E.3.c.(1)(e)~~ E.3.c.(1)(b) allows for the use of a combination of onsite retention BMPs, and the implementation of an Alternative Compliance Program described in Provision E.3.c.(3). Provision E.3.c.(3) is discussed in more detail below.

If the full design capture volume is not retained onsite either because biofiltration is not technically feasible, or a Copermittee grants a Priority Development Project permission to utilize the Alternative Compliance Program, then the pollutants in the portion of the design capture volume that are not reliably retained onsite must still be reduced to the MEP. Thus, flow-thru treatment control BMPs are required to be implemented on Priority Development Projects in addition to the retention BMPs. The requirements of Provisions ~~E.3.c.(1)(d)~~ E.3.c.(1)(a)(i)[a]-[c] include the performance standards for flow-thru treatment control BMPs, consistent with the Fourth Term Permits in the San Diego Region.

5) Attachment F, Under the Fact Sheet discussion of Provision F.1

The San Diego Water Board recognizes that the development of multiple Water Quality Improvement Plans concurrently may limit the ability of the public to review and provide comments to the Copermittees. Thus, Provision F.1.a.(1)(c) requires the Copermittees to coordinate the schedules for the public participation process among the Watershed Management Areas to provide the public ~~as much~~ time and opportunity ~~as possible~~ to participate during the development of the Water Quality Improvement Plans.

6) Attachment F, Under the Fact Sheet discussion of Provision F.3

Provision F.3.b.(2) includes the transitional annual reporting requirements for the transitional monitoring and assessment program for each Watershed Management Area. The Copermittees in the Watershed Management Area are required to submit a Transitional Monitoring and Assessment Program Annual Report no later than January 31 for each complete transitional monitoring and assessment program reporting period (i.e. October 1 to September 30) during the transitional period, until the first Water Quality Improvement Plan Annual Reports are required to be submitted. The Transitional Monitoring and Assessment Program Annual Report is required to include the transitional period monitoring data collected pursuant to Provisions D.1.a and D.2.a, and the findings from the transitional period findings from the assessments required pursuant to Provisions D.4.a.(1)(a), D.4.b.(1)(a)(i), D.4.b.(2)(a)(i).