State Water Resources Control Board



Division of Water Quality

1001 I Street • Sacramento, California 95814 • (916) 341-5455 Mailing Address: P.O. Box 100 • Sacramento, California • 95812-0100 Fax (916) 341-5584 • http://www.swrcb.ca.gov



DRAFT

PROPOSED MITIGATED NEGATIVE DECLARATION

Pursuant to Section 21080(c) Public Resources Code

Office of Planning & Research From: State Water Resources Control Board To:

State Clearinghouse Division of Water Quality 1400 Tenth Street 1001 I Street

Sacramento, CA 95814

Sacramento, CA 95814

Exception to the California Ocean Plan for the University of California, Davis Bodega **Project Title:**

Marine Laboratory Discharge into the Bodega Area of Special Biological Significance

University of California, Davis **Bodega Marine Laboratory**

PO Box 247

Bodega Bay, CA 94923

Project Description: University of California, Davis (UCD) Bodega Marine Laboratory (BML) seeks an exception from the California Ocean Plan's prohibition on discharges into Areas of Special Biological Significance (ASBS). The exception with conditions, if approved, would allow their continued waste seawater and storm water discharges into the Bodega ASBS.


Determination: The State Water Resources Control Board has determined that the above-proposed project will have a less-than-significant effect on the environment for the reasons specified in the attached Initial Study.

Terms and Conditions:

Applicant:

- 1. The discharge must comply with all other applicable provisions, including water quality standards, of the Ocean Plan. Natural water quality conditions in the receiving water, seaward of the surf zone, must not be altered as a result of the discharge. The surf zone is defined as the area between the breaking waves and the shoreline at any one time. Natural water quality will be defined, based on a review of the monitoring data, by Regional Water Quality Control Board (Regional Water Board) staff in consultation with the State Water Board's Division of Water Quality. For constituents other than indicator bacteria, natural water quality will be determined using the reference station in the ocean near Mussel Point. For indicator bacteria, the Ocean Plan bacteria objectives will be used.
- 2. UCD/BML shall not discharge any constituents at levels in excess of the objectives in Table B water quality objectives as required in Section III.C. of the Ocean Plan. Chemical additives, including but not limited to antibiotics, shall not be discharged in the seawater system effluent. UCD/BML must minimize its discharge of halomethanes and total residual chlorine (TRC).
- 3. UCD/BML shall continuously monitor TRC using an instrument capable of a minimum detection limit of 5 µg/L. The reporting limit shall be 50 µg/L. In addition, bench top TRC measurements shall be performed at least once monthly with a minimum method detection limit of 10 µg/L TRC and a reporting limit of 12 µg/L.

California Environmental Protection Agency



- **4.** For metals analysis, waste seawater effluent, storm water effluent, reference samples, and receiving water samples must be analyzed by the approved analytical method with the lowest minimum detection limits (currently Inductively Coupled Plasma/Mass Spectrometry) described in the Ocean Plan.
- 5. The seawater system will not flow at a rate greater than 1.5 mgd. Flows for the waste seawater effluent and storm water runoff (by storm event) must be reported at least quarterly to the Regional Water Board. The storm water runoff may be calculated, rather than measured directly, using a method approved by the Regional Water Board.
- **6.** Freshwater discharged from the Salmon Research Facility must be discharged to a groundwater recharge area in the sand dunes adjacent to the laboratory and not to the marsh or the ASBS.
- 7. UCD/BML must continue to prevent all discharges of non-storm water facility runoff (i.e., any discharge of facility runoff that reaches the ocean that is not composed entirely of storm water), except those associated with the waste seawater system and emergency fire fighting.
- 8. UCD/BML must specifically address the prohibition of non-storm water runoff and the reduction of pollutants in storm water discharges draining to the ASBS in a Storm Water Management Plan/Program (SWMP). UCD/BML is required to submit it's final SWMP to the Regional Water Board
- The SWMP must describe the measures by which non-storm water discharges have been eliminated, how these measures will be maintained over time, and how these measures are monitored and documented.
- 10. The SWMP must include a map of surface drainage of storm water runoff, including areas of sheet runoff, and any structural Best Management Practices (BMPs) employed. The map must also show the storm water conveyances in relation to other facility features such as the laboratory seawater system and discharges, service areas, sewage treatment, and waste and hazardous materials storage areas. The SWMP must also include a procedure for updating the map and plan when other changes are made to the facilities.
- 11. The SWMP must also address storm water discharges, and how pollutants have been and will be reduced in storm water runoff into the ASBS through the implementation of BMPs. The SWMP must describe the BMPs currently employed and BMPs planned (including those for construction activities) and an implementation schedule. The BMPs and implementation schedule must be designed to ensure natural water quality conditions in the receiving water due to either a restriction of flows from impervious surfaces, or reduction in pollutants, or some combination thereof. The BMPs must include the measures taken to prevent the runoff of herbicides or pesticides, from BML and the Reserve, into the ASBS. The implementation schedule must be developed to ensure that the BMPs are implemented within one year of the approval date of the SWMP by the Regional Water Board.
- 12. At least once every permit cycle (every five years), a quantitative survey of intertidal benthic marine life must be performed near the discharge and at a reference site. The Regional Water Board, in consultation with the State Water Board's Division of Water Quality, must approve the survey design. The results of the survey must be completed and submitted to the Regional Water Board within six months before the end of the permit cycle. Furthermore, any data from other intertidal and subtidal surveys performed by researchers in the ASBS must be reported to the State and Regional Water Boards.

- 13. Once during the upcoming permit cycle, a bioaccumulation study using resident California mussels (*Mytilus californianus*) must be conducted to determine the concentrations of metals near field (outfall station) and far field (Mussel Point). The Regional Water Board, in consultation with the State Water Board's Division of Water Quality, only must approve the study design. The results of the survey must be completed and submitted to the Regional Water Board at least six months prior to the end of the permit cycle (permit expiration). Based on the study results, the Regional Water Board, in consultation with the State Water Board's Division of Water Quality, may adjust the study design in subsequent permits, or add additional test organisms.
- 14. During the first year of each permit cycle, at least two effluent samples must be collected from the waste seawater discharge (with at least one collected during dry weather and one collected during wet weather, i.e., a storm event). In addition, reference samples must also be collected along with the effluent samples. Reference samples will be collected in the ocean at a station near Mussel Point. Samples collected at the reference station will represent natural water quality for all Ocean Plan constituents. Wet weather samples at the reference station may be collected immediately following a storm event, but in no case more than 24 hours after, if sampling conditions are unsafe during the storm. All of these samples must be analyzed for all Ocean Plan Table B constituents, pH, salinity, and temperature. Based on the results from the first year, the Regional Water Board will determine the frequency of sampling (at a minimum, once annually during wet weather) and the constituents to be tested during the remainder of the permit cycle, except that halomethanes, residual chlorine, ammonia nitrogen, pH, salinity, and temperature must be tested at least monthly, and Ocean Plan metals and chronic toxicity (three species initially and thereafter the most sensitive species) must be tested at least annually for the waste seawater effluent.
- 15. At least once annually, during wet weather (i.e. storm event), the runoff from the outfall draining the marsh, and the receiving water adjacent to the storm water marsh outfall, in Horseshoe Cove, must be sampled and analyzed for Ocean Plan Table B constituents. The storm water runoff and the Horseshoe Cove receiving water must also be monitored for Ocean Plan indicator bacteria water quality objectives. The sample location for the receiving water will be immediately seaward of the surf zone in Horseshoe Cove adjacent to the outfall location. Storm water runoff and Horseshoe Cove receiving water must be sampled at the same time as the wet weather seawater effluent and reference sampling effort described in condition 14 above. Based on the first year sample results the Regional Water Board will determine specific constituents in the storm water runoff and receiving water (that were at or above Table B objectives) to be tested during the remainder of the permit cycle, except that chronic toxicity (three species initially and thereafter the most sensitive species) for receiving water must be tested annually during a storm event.
- 16. Once annually, the subtidal sediment in Horseshoe Cove must be sampled and analyzed for Ocean Plan Table B constituents. For sediment toxicity testing, an acute toxicity test using the amphipod *Eohaustorius estuarius* must be performed during the first year of the permit cycle. Based on the first year sample results, the Regional Water Board will determine specific constituents in the sediment to be tested during the remainder of each permit cycle, except that acute toxicity for sediment must be tested annually.
- 17. If the results of Horseshoe Cove receiving water monitoring indicate that the storm water runoff is causing or contributing to an alteration of natural water quality in the ASBS, as measured at the reference station at Mussel Point, UCD/BML is required to submit a report to the Regional Water Board within 30 days of receiving the results. Those constituents in storm water that alter natural water quality or receiving water objectives must be identified in that report. The report must describe BMPs that are currently being implemented, BMPs that are planned for in the SWMP, and additional BMPs that may be added to the SWMP. The report shall include a new or modified implementation schedule. The Regional Water Board may require modifications to the report. Within 30 days following approval of the report by the Regional Water Board, UCD/BML must revise its SWMP to

incorporate any new or modified BMPs that have been and will be implemented, the implementation schedule, and any additional monitoring required. As long as UCD/BML has complied with the procedures described above and is implementing the revised SWMP, then UCD/BML does not have to repeat the same procedure for continuing or recurring exceedances of the same constituent.

- **18.** UCD/BML must pursue and implement a program for prevention of Biological Pollutants (non-native invasive species) in consultation with the California Department of Fish and Game Marine Resources Division. This program must be submitted to the State and Regional Water Board no later than two years following the approval of this Exception. Any non-native species found in the ASBS must be reported to the State and Regional Water Board and the California Department of Fish and Game.
- 19. UCD/BML shall prepare a waterfront and marine operations non-point source management plan containing appropriate management practices to address non-point source pollutant discharges. The Plan must address the current prohibition on launching motorized vessels, restrictions on motor vehicles, and other appropriate management measures including those described in the State's Non-point Source Program Implementation Plan for marinas and recreational boating, as applicable. The Regional Water Board, in consultation with the State Water Board's Division of Water Quality, will review the plan. Non-point source discharges will be appropriately regulated by the Regional Water Board in accordance with the State Water Board's Policy for Implementation and Enforcement of the Non-point Source Pollution Control Program. The waterfront plan must be implemented within six months of its approval.
- 20. UCD/BML will notify the Regional Water Board within 180 days prior to any construction activity that could result in any discharge or habitat modification in the ASBS. Furthermore, UCD/BML must receive approval and appropriate conditions from the Regional Water Board prior to performing any significant modification, re-building or renovation of the water front facilities, including the boat launch, according to the requirements of Section III.E.2 of the Ocean Plan.
- 21. The Regional Water Board will include all the above listed mitigating conditions in one National Pollutant Discharge Elimination System permit that regulates both the seawater effluent and storm water. Alternatively, the Regional Water Board may regulate the storm water discharge in a storm water NPDES permit and, in that case would include those conditions relative to storm water in that storm water NPDES permit. In the latter case, all conditions would be included, in some combination, in the waste seawater effluent permit and the storm water permit, and through its SWMP.

Contact Person: Constance S. Anderson	Telephone: (916) 341-5280 email: csanderson@waterboards.ca.gov
Adopted by the State Water Resources Control Board on _	, 2007.
Song Her Clerk to the Board	Date