

MODELING



MODELING PRESENTATION OVERVIEW

- Overview of CWF Models and Tools
 - CalSim II
 - DSM2
- CWF Modeling Scenarios and Assumptions
- Water Supply Modeling Results
- Delta Salinity and Water Level Modeling Results
- Summary Findings




MODEL DEFINITIONS

Mathematical Model:

- A systematic description of an object or phenomenon that shares important characteristics with the object or phenomenon.
- A simplified representation used to explain the workings of a real world system or event.




AN INTENSELY INTEGRATED HYDROLOGIC SYSTEM





... AND AN INTERTIED WATER SYSTEM





MODELING APPROACH

Hydrology and System Operations (CalSim II)

(monthly time-step)

River flows, reservoir storage, diversions and deliveries

Delta Hydrodynamics (DSM2-Hydro)

(15 minute time-step)

Delta channel flows, velocities, stage

Delta Water Quality (DSM2-QUAL)

(15 minute time-step)

Salinity (EC and Cl)




CalSim II

- CalSim II simulates long-term operational scenarios of the SWP and CVP
 - Under a Coordinated Operations Agreement (COA)
 - On a monthly time-step
 - For various conditions (e.g. level of development, climate change, facilities, regulations)
 - Best available tool for long-term planning of the SWP/CVP system
- CalSim II is most appropriately used for comparative purposes and not for predictive purposes
- CalSim II is a planning tool, and should NOT be used to replicate historical conditions



CALSIM II MODEL SCHEMATIC




- Representing hydrology and operations
- Trinity and Shasta
 Reservoirs to terminal reservoirs of the SWP
- Complex network of nodes (junctions and storage) and arcs (flows)



DELTA SIMULATION MODEL 2 (DSM2)

- Simulates Delta Hydrodynamics and Water Quality
 - Tidal flows
 - Water levels (stage)
 - Water quality
- Uses a 15-minute time step
- Developed by DWR





CALSIM II MODEL FEATURES

- Input Hydrology and Demands
- System Representation
- SWP/CVP and Other Related Operations
- Simulated Parameters



DELTA CONSTRAINTS IN CalSim II

- Old and Middle River Flow (OMR)
- Minimum Required Delta Outflow (MRDO)
 - Including X2 Requirements
- Export/Inflow Ratio
- Delta Salinity Objectives
- San Joaquin Inflow/Export Ratio
- Cross Channel Gate Operation
- Rio Vista Flow
- Head of Old River Gate (HORG)



MEETING D-1641 WATER QUALITY OBJECTIVES

- Artificial Neural Networks (ANNs) are used to estimate EC at select locations in the Delta
- ANNs correlate Delta inflow, Delta diversions, Delta cross-channel position, and tidal energy to changes in EC
- ANNs were trained on DSM2 simulation results




D-1641 OBJECTIVES MODELED IN CalSim II

- Flow-salinity relationship comes from ANN
- Municipal and Industrial Use:
 - Old River at Rock Slough
 - Banks/Jones Pumping Plants
- Agricultural Beneficial Use:
 - Sacramento River at Emmaton
 - San Joaquin River at Jersey Point
- Fish and Wildlife Beneficial Uses:
 - Sacramento River at Collinsville



COMPARATIVE ANALYSIS REPRESENTATION



Base Case

Modeled Scenario

Comparative analysis to determine system response to structural and non-structural changes to that system



MODELING SCENARIOS (2015)

- No Action Alternative
- CWF Initial Operational Range Scenarios
 - Initial Operational Range H3
 - Initial Operational Range H4
- CWF Boundary Scenarios
 - Boundary 1 Lower outflow
 - Boundary 2 Higher outflow



SUMMARY OF MODELING ASSUMPTIONS DWR-5

~						
	9,000 cfs North Delta Diversion	Fall X2	Delta Outflow requirements	NMFS BiOp SJR i-e ratio	OMR Requirements	Head of Old River Barrier/Gate
No Action Alternative	No	Yes	Per D-1641	Yes	Yes; per BiOps	Temporary barrier installed in fall months
Boundary 1	Yes	No	Per D-1641	No	Yes; per BiOps	Permanent gate operating in fall months consistent with NAA
Н3	Yes	Yes	Per D-1641	No	Yes; more restrictive of either BiOps or	Permanent gate
H4	Yes	Yes	Per D-1641 and increased Delta Outflow requirements during March-May	No	new OMR requirements identified in the RDEIR/SDEIS for Alternative 4A	operating in fall, winter and spring months (partial closure)
Boundary 2	Yes	Yes	Per D-1641 and increased Delta Outflow goals in all months	No	Yes; more restrictive of either BiOps or new OMR requirements identified in the RDEIR/SDEIS Appendix C	Permanent gate operating in fall, winter and spring months (full closure)



NO ACTION ALTERNATIVE & CALIFORNIA WATERFIX



NO ACTION ALTERNATIVE

- Represents the continuation of policy and management direction
- Includes implementation of water operation components of the existing Reasonable and Prudent Alternative (RPA) actions specified in the 2008 U.S. Fish and Wildlife Service (USFWS) and 2009 National Marine Fisheries Service (NMFS) Biological Opinions (BiOps)



NO ACTION ALTERNATIVE (CONT'D)

- Includes future level of development
- Considers climate change and sea level rise effects
- No San Joaquin River Restoration (SJRRP) flows
- Modified Fremont Weir notch



COMMON FEATURES IN CWF SCENARIOS

Dual Conveyance

- Existing south delta pumps
- Proposed north delta diversion (NDD)

New Facilities include:

- Three new 3,000 cfs capacity NDD intakes
- Permanent operable Head of Old River Gate (HORG)



COMMON FEATURES IN CWF SCENARIOS

Additional Operational Requirements:

- NDD bypass flow and sweeping velocity requirements
- Additional Old and Middle River (OMR) flow requirements and CVP/SWP diversions restrictions
- January August Rio Vista minimum flow requirements



COMMON FEATURES IN CWF SCENARIOS

More restrictive South Delta operations

- New OMR restrictions in October-December
- More restrictive OMR in above normal and wet years
 October-June
- April June OMR based on Vernalis flows replaces NMFS
 BiOp Action, I-E ratio constraint in April and May
- Greater of OMR requirement under BiOps and the more restrictive CWF South Delta operations
- October June Head of Old River Gate (HORG) operations



NORTH DELTA DIVERSION INTAKE OPERATIONS


Bypass flow requirements

- Govern flow required to remain in the river downstream of intakes
- Initial pulse protection, and low level pumping at each intake during Sacramento River pulse flow period
- Following pulse protection, post-pulse operations through June
- Three levels of post-pulse protections (Level I, II and III)
- Transitioning between post-pulse levels subject to hydrologic and fishery conditions
- Approach and sweeping velocity requirements at the NDD fish screens






DWR-5






NDD BYPASS FLOW REQUIREMENTS EXAMPLE - DRY YEAR (1987)





NDD BYPASS FLOW REQUIREMENTS EXAMPLE - ABOVE NORMAL YEAR (1993)





DELTA OUTFLOW ASSUMPTIONS

NAA and H3 (D-1641 and BiOps)

	W	AN	BN	D	С
Oct	4000/Fall X2	4000/Fall X2	4000	4000	3000
Nov	4500/Fall X2	4500/Fall X2	4500	4500	3500
Dec	4500	4500	4500	4500	3500
Jan	4500	4500	4500	4500	4500
Feb	4000	4000	4000	4000	4000
Mar	4000	4000	4000	4000	4000
Apr	4000	4000	4000	4000	4000
May	4000	4000	4000	4000	4000
Jun	4000	4000	4000	4000	4000
Jul	8000	8000	6500	5000	4000
Aug	4000	4000	4000	3500	3000
Sep	3000/Fall X2	3000/Fall X2	3000	3000	3000

- D-1641 Feb Jun X2
- USFWS BiOp Fall X2 in W (74 km), AN (81 km) years

Boundary 2

	W	AN	BN	D	С
Oct	11400	11400	7100	7100	7100
Nov	11400	11400	7100	7100	7100
Dec	11400	11400	11400	11400	11400
Jan	35000	35000	35000	35000	35000
Feb	35000	35000	35000	35000	35000
Mar	44500	44500	44500	25000	25000
Apr	44500	44500	44500	25000	25000
May	44500	44500	44500	25000	25000
Jun	11400	11400	7100	7100	7100
Jul	7100	7100	7100	7100	7100
Aug	7100	7100	7100	7100	7100
Sep	11400	11400	7100	7100	7100

- Greater of D-1641/BiOps, or above
- Delta outflow goals above current regulatory requirements achieved through Delta export curtailments
- Upstream releases allowed in Jul Sep months in all water year types, except Critical.
- Boundary 1 Same as NAA, but no <u>Fall X2</u>
- Scenario H4 Same as NAA, but increased flows to maintain NAA spring delta outflow conditions



OMR SOUTH DELTA ASSUMPTIONS

Scenarios H3 and H4

Boundary 2

OMR Flows

OMR Flows

	_				_		
WY	W	AN	BN	D	С		
Oct ^a	-3500	-3500	-3500	-3500	-3500		
Nov	-5000	-5000	-5000	-5000	-5000		
Dec ^{b,c}	-5000	-5000	-5000	-5000	-5000		
Jan ^b	0	-3500	-5000	-5000	-5000		
Feb ^b	0	-3500	-5000	-5000	-5000		
Mar ^b	0	0	-3500	-3500	-3500		
Apr ^b	Qver	n, Qomr: (<	<5000,-2000	0), (6000,10	000),		
May ^b	(10000	, 2000), (19	5000, 3000)), (>=30000	,6000)		
Jun ^b	Qv, Qo: (<350	0,-3500), (>=	3500,0), (>=10	0000, 1000), (>15000, 2000		
Jul							
Aug							
Sep							
a Avg of 2000 of during CIP pulse period and 5000 of for non pulse							

_	_					_	, ,	_
	a				1 5000			-
Ш.	Ava ot 20	OOO ete duu	ina SJR bul	ise period s	and Soon a	fs for non-p	HISE V	a
	A V Q OI -21	uuu cia uui	mig John pur	iac period t	ANG -3000 (ла гот поптр	uloc ;	
							_	
	in the second se							

Or FWS RPA, whichever provides higher OMR

WY	W	AN	BN	D	С
Oct ^{a,d}	-3500	-3500	-5000	-5000	-5000
Nov ^{a,d}	-3500	-3500	-5000	-5000	-5000
Dec ^{c,d}	-3500	-3500	-5000	-5000	-5000
Jan	0	0	-2500	-2500	-2500
Feb	0	0	-2500	-2500	-2500
Mar ^b	Qv, Qo: (<35	00,-2500), (>=350	00,0), (>=10000, 1	000), (>15000, 20	00) or -2000
Apr		Qvern, Qom	r: (<5000,-2000), ((6000,1000),	
May	(1	10000, 2000), (150	000, 3000), (>=300	000,6000) or -200	0
Jun ^b	Qv, Qo: (<35	00,-2500), (>=350	00,0), (>=10000, 1	000), (>15000, 20	00) or -2000
Jul ^d	-5000	-5000	-5000	-5000	-5000
Aug ^d	-5000	-5000	-5000	-5000	-5000
Sep ^d	-5000	-5000	-5000	-5000	-5000

^a For before and after D-1641 fall pulse; No exports during D-1641 pulse (2 weeks)

Boundary 1 – Same as NAA fall operations

When ND pulse is triggered, -2000 when delta smelt RPA triggered

^b SJR based OMR per Scen 6 for Jun, with lowest OMR at -2500 cfs

c -2000 when Delta smelt RPA triggered

d -5,000 cfs for WET years and year following WET years



HORG SOUTH DELTA ASSUMPTIONS

DWR-5

Scenarios H3 and H4

Boundary 2

Head of Old River Gate Operations

Head of Old River Gate Operations

WY	W	AN	BN	D	O
Oct	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
Nov	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
Dec	OUT	OUT	OUT	OUT	OUT
Jan	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
Feb	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
March	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
April	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
May	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
Jun	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
Jul	OUT	OUT	OUT	OUT	OUT
Aug	OUT	OUT	OUT	OUT	OUT
Sep	OUT	OUT	OUT	OUT	OUT

WY	W	AN	BN	D	С
Oct	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
Nov	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
Dec	OUT	OUT	OUT	OUT	OUT
Jan	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
Feb	IN/OUT	IN/OUT	IN/OUT	IN/OUT	IN/OUT
March	IN	IN	IN	IN	IN
April	IN	Z	IN	IZ	IN
May	IN	IN	IN	IN	IN
Jun	IN	IZ	IN	IN	IN
Jul	OUT	OUT	OUT	OUT	OUT
Aug	OUT	OUT	OUT	OUT	OUT
Sep	OUT	OUT	OUT	OUT	OUT

Boundary 1 – Same as NAA fall operations



MODELING RESULTS



WATER SUPPLY ANALYSIS

- Deliveries North and South of the Delta
- SWP/CVP Delta Diversions
 - Existing and proposed intakes
- End of September Upstream SWP/CVP Reservoir Storage




NORTH OF DELTA DELIVERIES



ANNUAL CVP SETTLEMENT CONTRACTORS DELIVERIES

Early Long-Term (ELT) alternatives are simulated with 2025 climate change & sea level rise





ANNUAL CVP NOD REFUGE WATER SUPPLY DELIVERIES


Early Long-Term (ELT) alternatives are simulated with 2025 climate change & sea level rise






ANNUAL CVP EXCHANGE CONTRACTORS DELIVERIES

Early Long-Term (ELT) alternatives are simulated with 2025 climate change & sea level rise






ANNUAL CVP SOD REFUGE WATER SUPPLY (LEVEL 2) DELIVERIES






ANNUAL CVP NOD AGRICULTURAL WATER SERVICE CONTRACTORS DELIVERIES






ANNUAL CVP NOD MUNICIPAL & INDUSTRIAL WATER SERVICE CONTRACTORS DELIVERIES






ANNUAL SWP FEATHER RIVER SERVICE AREA CONTRACTOR DELIVERIES





ANNUAL COMBINED SWP AND CVP SOD WATER SERVICE CONTRACTOR DELIVERIES






CVP AND SWP DIVERSIONS




ANNUAL TOTAL DELTA CVP/SWP DIVERSIONS FROM JONES AND BANKS PUMPING PLANTS





LONG-TERM AVERAGE ANNUAL TOTAL DWR-5 NORTH AND SOUTH DELTA COMBINED CVP/SWP DIVERSIONS






END OF SEPTEMBER RESERVOIR STORAGE




SHASTA LAKE END OF SEPTEMBER STORAGE






LAKE OROVILLE END OF SEPTEMBER STORAGE






FOLSOM LAKE END OF SEPTEMBER STORAGE





TRINITY LAKE END OF SEPTEMBER STORAGE





SUMMARY OF WATER SUPPLY CHANGES UNDER CWF

CVP and SWP Water Contractor Deliveries

- No substantial differences to CVP Exchange and settlement contractors and refuges
- No substantial differences to SWP Feather River Settlement contractors
- Increased deliveries to CVP NOD in some scenarios, small decreases in dry and critical year types in Boundary 2 scenario (<5%)
- Significant changes to SWP/CVP water service contractor deliveries south of the Delta largely tied to assumed outflow and export restrictions (increase of 34% to reduction of 33%)



SUMMARY OF WATER SUPPLY CHANGES UNDER CWF

SWP and CVP Delta Diversions

- Boundary scenarios result in substantial changes in diversion (from +1,200,00 AFY to -1,100,000 AFY) depending on outflow and south delta assumptions
- SWP/CVP delta diversion under CWF Proposed Operational Range scenarios range from essentially no change to a 10% increase compared to NAA



SUMMARY OF WATER SUPPLY CHANGES UNDER CWF

- Carryover Storage in SWP and CVP Reservoirs
 - No substantial differences to reservoir storage
 - Small changes that do occur are at high storage levels



OVERVIEW

- Delta Water Quality
- Water Levels




WATER QUALITY ANALYSIS

- Monthly average EC at selected Delta locations
- Monthly average chloride at selected Delta locations
- D-1641 water quality SWP/CVP compliance




WATER QUALITY SACRAMENTO RIVER AT EMMATON






WATER QUALITY SAN JOAQUIN RIVER AT JERSEY POINT






WATER QUALITY SAN JOAQUIN RIVER AT SAN ANDREAS LANDING






WATER QUALITY SOUTH FORK MOKELUMNE (TERMINOUS)






WATER QUALITY OLD RIVER AT TRACY ROAD






WATER QUALITY SAN JOAQUIN RIVER AT BRANDT BRIDGE






CHLORIDE AT CONTRA COSTA CANAL






CHLORIDE AT OLD RIVER AT CLIFTON COURT FOREBAY





CHLORIDE AT BARKER SLOUGH/NORTH BAY AQUEDUCT





D-1641 WATER QUALITY OBJECTIVES MODELING APPROACH

CalSim II –


- Delta flows for regulatory and operational criteria assumed on a monthly time step
- Simulates compliance with Delta salinity objectives
- Relies on "Artificial Neural Network" for monthly averaged Delta flowsalinity relationships

DSM2 -

- Uses CalSim II results, and simulates Delta hydrodynamics and salinity on a 15-min time step
- Monthly CalSim II flows converted to daily flows using historical patterns
- DSM2 daily EC output was used to evaluate compliance with D-1641 water quality objectives




MODEL REPRESENTATION OF STANDARDS D-1641 WATER QUALITY OBJECTIVE AT EMMATON (EXAMPLE - 1987 DRY YEAR)






MODEL EVALUATION OF STANDARDS DSM2 SIMULATED EC AT EMMATON – EXAMPLE 1987 (DRY)






D-1641 EC OBJECTIVE AT EMMATON






D-1641 EC OBJECTIVE AT JERSEY POINT






D-1641 EC OBJECTIVE AT SOUTH FORK MOKELUMNE AT (TERMINOUS)






D-1641 EC OBJECTIVE AT SAN ANDREAS LANDING






D-1641 CHLORIDE OBJECTIVE (250 MG/L) AT CONTRA COSTA CANAL





D-1641 150 MG/L CHLORIDE OBJECTIVE AT CONTRA COSTA CANAL (REQUIRED NUMBER OF DAYS)





MOST OF THE D-1641 WATER QUALITY OBJECTIVE EXCEEDANCES SHOWN IN THE MODEL RESULTS ARE DUE TO THE DIFFERENCE IN THE MODEL ASSUMPTIONS




DELTA WATER LEVEL ANALYSIS

- Probability of exceedance daily minimum water levels
- Largest reductions are expected in and around the three proposed North Delta Diversions




WATER LEVEL RESULTS LOCATIONS






PROBABILITY OF EXCEEDANCE FOR DAILY MINIMUM STAGES SACRAMENTO RIVER DOWNSTREAM FROM THE THREE PROPOSED INTAKES.






PROBABILITY OF EXCEEDANCE FOR DAILY MINIMUM STAGE SACRAMENTO RIVER DOWNSTREAM OF GEORGIANA SLOUGH






PROBABILITY OF EXCEEDANCE FOR DAILY MINIMUM STAGE SACRAMENTO RIVER AT RIO VISTA






PROBABILITY OF EXCEEDANCE FOR DAILY MINIMUM STAGE OLD RIVER AT TRACY ROAD





PROBABILITY OF EXCEEDANCE FOR DAILY MINIMUM STAGE SOUTH FORK MOKELUMNE (TERMINOUS)





SUMMARY OF CHANGES

Water Quality (Ag and M&I)

- Model analysis of EC and Chloride
- Water quality results are mixed
- There are seasonal variations
- Small overall increase in EC at Emmaton
- DSM2 shows exceedances in D-1641 water quality objectives for all alternatives including the NAA
- Most exceedances are due to difference in the assumptions in the models (CalSim II and DSM2)



SUMMARY OF CHANGES (CONT'D)

Water Levels in the Delta

- Largest reduction in water levels near the proposed NDD
- Largest reduction in water levels during high flow events
- Maximum water level reduction of about 0.5 ft during low flow events near the NDD
 - Low water level occurs for only short period during tidal cycle
- Locations far from the NDD show negligible reduction in water level