



CALIFORNIA
WATER FIX
RELIABLE. CLEAN. WATER.

DWR-4




OPERATIONS



OPERATIONS SUMMARY

- **Overview of Water System Operations**
- **Real-Time Operations**
- **Success in meeting WQCP Objectives**
- **Modified Obligations in Recent Drought Years**
- **Increased Flexibility with CWF**
- **Conclusion**

California's Water Projects





OVERVIEW OF WATER SYSTEM OPERATIONS

- **Higher Priority Needs Must be met First**
 - In-Basin Requirements
 - Bay-Delta D-1641 water quality control plan objectives
 - Other legal users of water (including settlement contracts)
 - Other Regulatory Requirements
 - Endangered Species Act Requirements
 - Other State and Federal Permits
- **SWP/CVP developed supply is secondary**



OVERVIEW OF WATER SYSTEM OPERATIONS (CONT'D)

- **Excess Conditions**

- When SWP/CVP releases plus unregulated flow exceed In Basin Requirements

- **Balanced Conditions**

- When SWP/CVP releases and unregulated flow are equal to In Basin Requirements

- Unstored flow may be available for export
 - Supplemental SWP/CVP storage withdrawals may be needed to meet In-Basin requirements

- SWP/CVP actively manage the system



REAL-TIME OPERATIONS

- **Delta Hydrodynamics**

- Tides
 - Daily ebb and flood
 - Monthly spring and neap
- Delta Inflow
- In-Delta Diversions
- SWP/CVP Exports
- Net Delta Outflow



- **Real-time Monitoring**

- **SWP/CVP Operations**

- Upstream Release Changes
- Export Changes




SALT WATER / FRESH WATER INTERACTION






TYPICAL SEMI-DIURNAL FLOOD AND EBB FLOWS (CFS)






SEMI-MONTHLY SPRING AND NEAP TIDES (CFS)



Spring and Neap Tides at Martinez, CA August-September 2000




METEOROLOGICAL EVENTS CAN TURN A NEAP TIDE INTO A SPRING TIDE






KEY WATER QUALITY MONITORING STATIONS

- Water Quality Sampling Site
- ▲ Salinity Sampling Site
(Electrical Conductivity Measurement)
- ◐ Continuous Salinity Recording Site
(Electrical Conductivity Measurement)





Sacramento River

Other Delta Inflow

Net Delta
Outflow

Net Delta
Consumptive
Use

SWP
Exports

CVP
Exports

San Joaquin River




- **Net Delta Outflow Index =**
Delta Inflow – Net Delta Consumptive Use – Delta Exports
- **SWP/CVP Influence Delta Inflow**
- **SWP/CVP Control Delta Export**



EXISTING FACILITIES

- Two principal “knobs” for Net Delta Outflow Control
 - Releases
 - Exports





RECORD FOR MEETING BAY-DELTA D-1641 STANDARDS

- **What are the Bay-Delta D-1641 standards?**
 - Key compliance stations
- **Historical compliance record**
 - Responsive real-time operations
 - Simulation models simplify and approximate



Bay-Delta Standards

Contained in D-1641

DWR-4


CRITERIA	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
----------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

FLOW/OPERATIONAL

• Fish and Wildlife												
SWP/CVP Export Limits				1,500cfs [1]								
Export/Inflow Ratio [2]	65%	35% of Delta Inflow [3]					65% of Delta Inflow					
Minimum Delta Outflow	[4]						3,000 - 8,000 cfs [4]					
Habitat Protection Outflow		7,100 - 29,200 cfs [5]										
Salinity Starting Condition [6]		[6]										
River Flows:												
@ Rio Vista									3,000 - 4,500 cfs [7]			
@ Vernalis - Base		710 - 3,420 cfs [8]				[8]						
- Pulse				[9]					+28TAF			
Delta Cross Channel Gates	[10]	Closed				[11]					Conditional [10]	


WATER QUALITY STANDARDS

• Municipal and Industrial																											
	All Export Locations												≤ 250 mg/l Cl														
	Contra Costa Canal												150 mg/l Cl for the required number of days [12]														
• Agriculture																											
	Western/Interior Delta												Max. 14-day average EC mmhos/cm [13]														
	Southern Delta [14]												1.0 mS				30 day running avg EC 0.7 mS				1.0 mS						
• Fish and Wildlife																											
	San Joaquin River Salinity [15]												14-day avg: 0.44 EC														
	Suisun Marsh Salinity [16]				12.5 EC				8.0 EC				11.0 EC								19.0 EC				[17]		15.5 EC






SWP/CVP SUCCESS AT MEETING OPERATIVE BAY-DELTA OBJECTIVES (1978 – 2015)






SWP/CVP SUCCESS AT MEETING OBJECTIVES AT CCC ROCK SLOUGH DIVERSION (1984 – 2015)






SWP/CVP COMPLIANCE AT EMMATON (1984 – 2015)






SWP/CVP COMPLIANCE AT JERSEY POINT (1984 – 2015)






WITH CWF

- Same Delta water quality requirements
- No change to SWP/CVP water right permits
- Increased flexibility with two export control 'knobs' (North and South locations)






SOUTH DELTA STANDARDS STATIONS






SOUTH DELTA EXCEEDENCE AT OLD RIVER AT TRACY ROAD BRIDGE






SOUTH DELTA EXCEEDENCE AT OLD RIVER AT MIDDLE RIVER





SOUTH DELTA EXCEEDENCE AT SAN JOAQUIN RIVER AT BRANDT BRIDGE





- **South Delta water quality exceedances were beyond the reasonable control of the SWP/CVP operations**
- **South Delta water quality exceedances accounted for 89% of all D-1641 Standard exceedances**
- **If South Delta objections are removed from the calculation, comprehensive exceedances drop to 0.2%**




TEMPORARY URGENCY CHANGE PETITIONS

- **Past three years of exceptional drought**
 - Exceptionally warm and dry
- **Insufficient stored water available to meet standards**
 - SWRCB granted conditional approval



California Statewide 4-year Precipitation Sums




Lowest Totals

Year	4-year Sum
2015	62.2
1920	63.1
1926	63.3
1931	64.5
1934	65.1
1924	65.7
1925	65.9




SACRAMENTO VALLEY CALENDAR YEAR DATA (1895 – 2015)






SIERRA SNOWPACK VS WINTER TEMPERATURE (1950 – 2015)






EIGHT-RIVER 4-YEAR AVERAGE WATER YEAR RUNOFF (1909 – 2015)





EIGHT-RIVER 3-YEAR AVERAGE APRIL-JULY RUNOFF (1908 – 2015)





SOUTH DELTA OPERATIONAL CONSTRAINTS

- **Existing south Delta SWP/CVP facilities**
 - Restricted by regulations to protect listed species
 - Restricts diversion of unregulated flow during Excess Conditions
 - Restricts re-diversion of stored water during Balanced Conditions
- **Proposed CWF North Delta Diversions (NDD)**
 - Shift some of south Delta diversion to NDD
 - Increase opportunity to use existing water rights
 - Diversion of unregulated flow during Excess Conditions
 - Re-diversion of stored water during Balanced Conditions




EXAMPLE OF CWF OPERATION

- **Current water year's hydrology assumed**
- **Proposed CWF infrastructure assumed**
 - New NDD intakes and tunnels
 - Existing export pumping facilities (Banks and Jones)
- **Assumed CWF Alt 4a H3 Operating Criteria**
 - NDD Bypass Flow Criteria
 - New Rio Vista Flow Criteria
 - New South Delta Old and Middle River Flow Criteria
 - New Operable Head of Old River Gate




Conceptual CWF Operation (12/1/15 - 4/30/16) (Operational Criteria for Scenario H3)





Daily Average EC at Bacon Island (12/1/15 - 4/30/16) (Operational Criteria for Scenario H3)





CONCLUSION

- **Historical Compliance record**
 - Historically Standards only exceeded 1.1% of the time
 - Real-time adjustments cannot be captured by models
 - Increased operational flexibility supports continued success
- **Operations with proposed North Delta Diversion**
 - Continue to meet in-basin requirements
 - Increased flexibility provided with additional diversion point
 - Increased opportunity to capture water supply without significant impact to other legal users of water